LIN7076 – Foundations of Computational Linguistics

Naive Bayes

Adèle Hénot-Mortier

05/10/2026

Queen Mary University of London

Binary classification: some applications



- Positive? Negative?
- Neutral? Hateful?
- Neutral? Sarcastic?
- Real news? Fake news?
- Unbiased? Biased?

Binary classification: the task

- Given a piece of text, predict if it belongs to class 0 (e.g. **neutral**) or to class 1 (e.g. **hateful**). This is **binary classification**.
- **Supervised learning** *via* a set of (text, class) training examples.
- A few techniques used for binary classification: Naive Bayes, logistic regression, support vector machines, and of course, neural nets.[1]
- We'll cover on **Naive Bayes** (today) and **logistic regression** (in 2 weeks).
- We will focus on binary classification, but in fact **Naive Bayes extends to more than 2 classes!**

[1] There's also k-nearest neighbors, but it's unsupervised.

Binary classification: the task

- Given a piece of text, predict if it belongs to class 0 (e.g. **neutral**) or to class 1 (e.g. **hateful**). This is **binary classification**.
- **Supervised learning** *via* a set of (text, class) training examples.
- A few techniques used for binary classification: Naive Bayes, logistic regression, support vector machines, and of course, neural nets.[1]
- We'll cover on **Naive Bayes** (today) and **logistic regression** (in 2 weeks).
- We will focus on binary classification, but in fact **Naive Bayes extends to more than 2 classes!**

[1] There's also k-nearest neighbors, but it's unsupervised.

Binary classification: the task

- Given a piece of text, predict if it belongs to class 0 (e.g. **neutral**) or to class 1 (e.g. **hateful**). This is **binary classification**.
- **Supervised learning** *via* a set of (text, class) training examples.
- A few techniques used for binary classification: Naive Bayes, logistic regression, support vector machines, and of course, neural nets.[1]
- We'll cover on **Naive Bayes** (today) and **logistic regression** (in 2 weeks).
- We will focus on binary classification, but in fact **Naive Bayes extends to more than 2 classes!**

[1] There's also k-nearest neighbors, but it's unsupervised.

Binary classification: the task

- Given a piece of text, predict if it belongs to class 0 (e.g. **neutral**) or to class 1 (e.g. **hateful**). This is **binary classification**.
- **Supervised learning** *via* a set of (text, class) training examples.
- A few techniques used for binary classification: Naive Bayes, logistic regression, support vector machines, and of course, neural nets.[1]
- We'll cover on **Naive Bayes** (today) and **logistic regression** (in 2 weeks).
- We will focus on binary classification, but in fact **Naive Bayes extends to more than 2 classes!**

[1] There's also *k*-nearest neighbors, but it's unsupervised.

Binary classification: the task

- Given a piece of text, predict if it belongs to class 0 (e.g. **neutral**) or to class 1 (e.g. **hateful**). This is **binary classification**.
- **Supervised learning** *via* a set of (text, class) training examples.
- A few techniques used for binary classification: Naive Bayes, logistic regression, support vector machines, and of course, neural nets.[1]
- We'll cover on **Naive Bayes** (today) and **logistic regression** (in 2 weeks).
- We will focus on binary classification, but in fact **Naive Bayes extends to more than** 2 **classes!**

[1] There's also k-nearest neighbors, but it's unsupervised.

Setting up the model

Naive Bayes: core intuition

- Different pieces of text have **different characteristics**, for instance,

Naive Bayes: core intuition

- Different pieces of text have **different characteristics**, for instance, they vary in length, capitalization, use of punctuation, and of course, in the words they use.

Naive Bayes: core intuition

- Different pieces of text have **different characteristics**, for instance, they vary in length, capitalization, use of punctuation, and of course, in the words they use.
- Some of these features seem very relevant to certain classification tasks; for instance, a text in all caps with lots of strong punctuation and offensive words, is probably hateful. A text without these features is more likely to be neutral.

Naive Bayes: core intuition

- Different pieces of text have **different characteristics**, for instance, they vary in length, capitalization, use of punctuation, and of course, in the words they use.
- Some of these features seem very relevant to certain classification tasks; for instance, a text in all caps with lots of strong punctuation and offensive words, is probably hateful. A text without these features is more likely to be neutral.
- To determine which class a text belongs to, one can then think of how likely it is to display the features it has, were it from class 0, or from class 1.


A piece of text belongs to the class that makes the features it displays more likely!

Conditional probabilities, again!

- The **conditional probability** of an event A, given an event B, can be computed using the joint probability of A and B, and B's probability.
- Symmetrically, the conditional probability of B, given A, can be computed **using the same joint probability**, and A's probability.

$$P(A|B) = \frac{P(A,B)}{P(B)} = \frac{P(A \cap B)}{P(B)}$$

$$P(B|A) = \frac{P(A,B)}{P(A)} = \frac{P(A \cap B)}{P(A)}$$




Conditional probabilities, again!

- The **conditional probability** of an event A, given an event B, can be computed using the joint probability of A and B, and B's probability.
- Symmetrically, the conditional probability of B, given A, can be computed **using the same joint probability**, and A's probability.


$$P(A|B) = \frac{P(A,B)}{P(B)} = \frac{P(A \cap B)}{P(B)}$$

$$P(B|A) = \frac{P(A,B)}{P(A)} = \frac{P(A \cap B)}{P(A)}$$



Practice: weather forecast

- Suppose we want to get a sense of how rain influences wind and wind influences rain.[2] We have access to the following weather report.




- $P(wind|rain) =$

[2] I thank the MSc class of 2026-27 for suggesting this example, that I slightly adapted with the help of ChatGPT.

Practice: weather forecast

- Suppose we want to get a sense of how rain influences wind and wind influences rain.[2] We have access to the following weather report.




- $P(wind|rain) = \frac{P(wind \cap rain)}{P(rain)} = \frac{3}{4} = .75$
- $P(rain|wind) =$

[2] I thank the MSc class of 2026-27 for suggesting this example, that I slightly adapted with the help of ChatGPT.

Practice: weather forecast

- Suppose we want to get a sense of how rain influences wind and wind influences rain.[2] We have access to the following weather report.



- $P(wind|rain) = \frac{P(wind \cap rain)}{P(rain)} = \frac{3}{4} = .75$
- $P(rain|wind) = \frac{P(wind \cap rain)}{P(wind)} = \frac{3}{5} = .6$

[2] I thank the MSc class of 2026-27 for suggesting this example, that I slightly adapted with the help of ChatGPT.

Classification as conditional probability optimization

- Suppose we have a piece of text ("document") d, that we want to classify as neutral (c_0) or hateful (c_1).
- We want to figure out **which class is the most likely to represent** d, meaning, we want to compute $P(c_0|d)$ and $P(c_1|d)$, and assign d the class that is more likely.

$$\hat{c}(d) = \begin{cases} c_0 \text{ if } P(c_0|d) > P(c_1|d) \\ c_1 \text{ if } P(c_0|d) < P(c_1|d) \end{cases}$$

- We can "compress" and generalize this with the **argmax** notation: $\text{argmax}_x f(x)$ returns the element x that maximizes the function f; here, the class c that maximizes the function $P(c|d)$ for a fixed d.

$$\hat{c}(d) = \text{argmax}_{c \in \{c_0, c_1\}} P(c|d)$$

Classification as conditional probability optimization

- Suppose we have a piece of text ("document") d, that we want to classify as neutral (c_0) or hateful (c_1).
- We want to figure out **which class is the most likely to represent** d, meaning, we want to compute $P(c_0|d)$ and $P(c_1|d)$, and assign d the class that is more likely.

$$\hat{c}(d) = \begin{cases} c_0 \text{ if } P(c_0|d) > P(c_1|d) \\ c_1 \text{ if } P(c_0|d) < P(c_1|d) \end{cases}$$

- We can "compress" and generalize this with the **argmax** notation: $\text{argmax}_x f(x)$ returns the element x that maximizes the function f; here, the class c that maximizes the function $P(c|d)$ for a fixed d.

$$\hat{c}(d) = \text{argmax}_{c \in \{c_0, c_1\}} P(c|d)$$

Classification as conditional probability optimization

- Suppose we have a piece of text ("document") d, that we want to classify as neutral (c_0) or hateful (c_1).
- We want to figure out **which class is the most likely to represent** d, meaning, we want to compute $P(c_0|d)$ and $P(c_1|d)$, and assign d the class that is more likely.

$$\hat{c}(d) = \begin{cases} c_0 \text{ if } P(c_0|d) > P(c_1|d) \\ c_1 \text{ if } P(c_0|d) < P(c_1|d) \end{cases}$$

- We can "compress" and generalize this with the **argmax** notation: $\text{argmax}_x f(x)$ returns the element x that maximizes the function f; here, the class c that maximizes the function $P(c|d)$ for a fixed d.

$$\hat{c}(d) = \text{argmax}_{c \in \{c_0, c_1\}} P(c|d)$$


Argmax clarification

- To better understand the argmax, let's go back to the max operator. $max_{x \in D} f(x)$ returns the value(s) of f that are maximal within the domain D; called the maxima.
- The plot below for instance, shows that the max of f is 5 for $x = 2$, within the domain $D = \{1, 2, 3\}$: $max_{x \in \{1,2,3\}} f(x) = 5$.

- Now, $argmax_{x \in D} f(x)$ returns the **maximizer(s)** of f: the values of x within the domain D s.t. $f(x)$ is maximal.
- The plot above for instance, shows that the argmax of f is 2, because for $x = 2$, $f(x)$ is maximal: $argmax_{x \in \{1,2,3\}} f(x) = 2$.
- To find the argmax, find the function's maxima, and **return the values achieving these maxima**.

Argmax clarification


- To better understand the argmax, let's go back to the max operator. $max_{x \in D} f(x)$ returns the value(s) of f that are maximal within the domain D; called the maxima.
- The plot below for instance, shows that the max of f is 5 for $x = 2$, within the domain $D = \{1, 2, 3\}$: $max_{x \in \{1,2,3\}} f(x) = 5$.



- Now, $argmax_{x \in D} f(x)$ returns the **maximizer(s)** of f: the values of x within the domain D s.t. $f(x)$ is maximal.
- The plot above for instance, shows that the argmax of f is 2, because for $x = 2$, $f(x)$ is maximal: $argmax_{x \in \{1,2,3\}} f(x) = 2$.
- To find the argmax, find the function's maxima, and **return the values achieving these maxima**.

Argmax clarification

- To better understand the argmax, let's go back to the max operator. $max_{x \in D} f(x)$ returns the value(s) of f that are maximal within the domain D; called the maxima.
- The plot below for instance, shows that the max of f is 5 for $x = 2$, within the domain $D = \{1, 2, 3\}$: $max_{x \in \{1,2,3\}} f(x) = 5$.



- Now, $argmax_{x \in D} f(x)$ returns the **maximizer(s)** of f: the values of x within the domain D s.t. $f(x)$ is maximal.
- The plot above for instance, shows that the argmax of f is 2, because for $x = 2$, $f(x)$ is maximal: $argmax_{x \in \{1,2,3\}} f(x) = 2$.
- To find the argmax, find the function's maxima, and **return the values achieving these maxima**.

Deriving the Bayes formula for document classification

- To compare $P(c_0|d)$ and $P(c_1|d)$, we need to **approximate** them!
- Here is the trick: **rewrite the joint** $P(c \cap d)$ using $P(d|c)$ (the probability of a document, *given a class*) and $P(c)$, using the conditional probability formula:

$$P(d|c) = \frac{P(d \cap c)}{P(c)}$$

$$P(d \cap c) = P(d|c)P(c) \qquad (\star)$$

- Then express the target probability $P(c|d)$ as a function of $P(d|c)$, $P(d)$, and $P(c)$!

$$P(c|d) = \frac{P(d \cap c)}{P(d)} \overset{\star}{=} \frac{P(d|c)P(c)}{P(d)} \qquad \textbf{Bayes' Theorem}$$

- $P(d|c)P(c)$ will prove **easier to approximate** than the joint $P(c \cap d)$.

Deriving the Bayes formula for document classification

- To compare $P(c_0|d)$ and $P(c_1|d)$, we need to **approximate** them!
- Here is the trick: **rewrite the joint** $P(c \cap d)$ using $P(d|c)$ (the probability of a document, *given a class*) and $P(c)$, using the conditional probability formula:

$$P(d|c) = \frac{P(d \cap c)}{P(c)}$$

$$P(d \cap c) = P(d|c)P(c) \qquad (\bigstar)$$

- Then express the target probability $P(c|d)$ as a function of $P(d|c)$, $P(d)$, and $P(c)$!

$$P(c|d) = \frac{P(d \cap c)}{P(d)} \overset{\bigstar}{=} \frac{P(d|c)P(c)}{P(d)} \qquad \text{Bayes' Theorem}$$

- $P(d|c)P(c)$ will prove **easier to approximate** than the joint $P(c \cap d)$.

Deriving the Bayes formula for document classification

- To compare $P(c_0|d)$ and $P(c_1|d)$, we need to **approximate** them!
- Here is the trick: **rewrite the joint** $P(c \cap d)$ using $P(d|c)$ (the probability of a document, *given a class*) and $P(c)$, using the conditional probability formula:

$$P(d|c) = \frac{P(d \cap c)}{P(c)}$$

$$P(d \cap c) = P(d|c)P(c) \qquad (\bigstar)$$

- Then express the target probability $P(c|d)$ as a function of $P(d|c)$, $P(d)$, and $P(c)$!

$$P(c|d) = \frac{P(d \cap c)}{P(d)} \overset{\bigstar}{=} \frac{P(d|c)P(c)}{P(d)} \qquad \textbf{Bayes' Theorem}$$

- $P(d|c)P(c)$ will prove **easier to approximate** than the joint $P(c \cap d)$.

Deriving the Bayes formula for document classification

- To compare $P(c_0|d)$ and $P(c_1|d)$, we need to **approximate** them!
- Here is the trick: **rewrite the joint** $P(c \cap d)$ using $P(d|c)$ (the probability of a document, *given a class*) and $P(c)$, using the conditional probability formula:

$$P(d|c) = \frac{P(d \cap c)}{P(c)}$$

$$P(d \cap c) = P(d|c)P(c) \qquad (\bigstar)$$

- Then express the target probability $P(c|d)$ as a function of $P(d|c)$, $P(d)$, and $P(c)$!

$$P(c|d) = \frac{P(d \cap c)}{P(d)} \overset{\bigstar}{=} \frac{P(d|c)P(c)}{P(d)} \qquad \textbf{Bayes' Theorem}$$

- $P(d|c)P(c)$ will prove **easier to approximate** than the joint $P(c \cap d)$.

Analyzing Bayes' Theorem

$$P(c_0|d) = \frac{P(d|c_0)P(c_0)}{P(d)} \qquad P(c_1|d) = \frac{P(d|c_1)P(c_1)}{P(d)}$$

- To compare the above conditional probabilities, **we can conveniently ignore the denominators** $P(d)$.

$$\underbrace{P(c|d)}_{posterior} \propto \overbrace{P(d|c)}^{likelihood} \underbrace{P(c)}_{prior}$$

- The above equation says that the probability of a class, after observing a document (**posterior** $P(c|d)$), is proportional to:
  - how likely the document is, given that class (**likelihood** $P(d|c)$);
  - and to how probable the class is before observing the document (**prior** $P(c)$).

Analyzing Bayes' Theorem

$$P(c_0|d) = \frac{P(d|c_0)P(c_0)}{P(d)} \qquad P(c_1|d) = \frac{P(d|c_1)P(c_1)}{P(d)}$$

- To compare the above conditional probabilities, **we can conveniently ignore the denominators** $P(d)$.

$$\underbrace{P(c|d)}_{posterior} \propto \overbrace{P(d|c)}^{likelihood} \underbrace{P(c)}_{prior}$$

- The above equation says that the probability of a class, after observing a document (**posterior** $P(c|d)$), is proportional to:
  - how likely the document is, given that class (**likelihood** $P(d|c)$);
  - and to how probable the class is before observing the document (**prior** $P(c)$).

Analyzing Bayes' Theorem

$$P(c_0|d) = \frac{P(d|c_0)P(c_0)}{P(d)} \qquad P(c_1|d) = \frac{P(d|c_1)P(c_1)}{P(d)}$$

- To compare the above conditional probabilities, **we can conveniently ignore the denominators** $P(d)$.

$$\underbrace{P(c|d)}_{posterior} \propto \overbrace{P(d|c)}^{likelihood} \underbrace{P(c)}_{prior}$$

- The above equation says that the probability of a class, after observing a document (**posterior** $P(c|d)$), is proportional to:
  - how likely the document is, given that class (**likelihood** $P(d|c)$);
  - and to how probable the class is before observing the document (**prior** $P(c)$).

Analyzing Bayes' Theorem

$$P(c_0|d) = \frac{P(d|c_0)P(c_0)}{P(d)} \qquad P(c_1|d) = \frac{P(d|c_1)P(c_1)}{P(d)}$$

- To compare the above conditional probabilities, **we can conveniently ignore the denominators** $P(d)$.

$$\underbrace{P(c|d)}_{posterior} \propto \overbrace{P(d|c)}^{likelihood} \underbrace{P(c)}_{prior}$$

- The above equation says that the probability of a class, after observing a document (**posterior** $P(c|d)$), is proportional to:
  - how likely the document is, given that class (**likelihood** $P(d|c)$);
  - and to how probable the class is before observing the document (**prior** $P(c)$).

Analyzing Bayes' Theorem

$$P(c_0|d) = \frac{P(d|c_0)P(c_0)}{P(d)} \qquad P(c_1|d) = \frac{P(d|c_1)P(c_1)}{P(d)}$$

- To compare the above conditional probabilities, **we can conveniently ignore the denominators** $P(d)$.

$$\underbrace{P(c|d)}_{posterior} \propto \overbrace{P(d|c)}^{likelihood} \underbrace{P(c)}_{prior}$$

- The above equation says that the probability of a class, after observing a document (**posterior** $P(c|d)$), is proportional to:
  - how likely the document is, given that class (**likelihood** $P(d|c)$);
  - and to how probable the class is before observing the document (**prior** $P(c)$).

Analyzing Bayes' Theorem

$$P(c_0|d) = \frac{P(d|c_0)P(c_0)}{P(d)} \qquad P(c_1|d) = \frac{P(d|c_1)P(c_1)}{P(d)}$$

- To compare the above conditional probabilities, **we can conveniently ignore the denominators** $P(d)$.

$$\underbrace{P(c|d)}_{posterior} \propto \overbrace{P(d|c)}^{likelihood} \underbrace{P(c)}_{prior}$$

- The above equation says that the probability of a class, after observing a document (**posterior** $P(c|d)$), is proportional to:
  - how likely the document is, given that class (**likelihood** $P(d|c)$);
  - and to how probable the class is before observing the document (**prior** $P(c)$).

Illustrating the interplay between prior and likelihood

- Suppose harmful (c_1) documents represent .01% of all documents. $P(c_1) = .0001$, $P(c_0) = .9999$.

Illustrating the interplay between prior and likelihood

- Suppose harmful (c_1) documents represent .01% of all documents. $P(c_1) = .0001$, $P(c_0) = .9999$.
- Suppose we have a document d, whose features make it **very likely to be harmful**, say $P(d|c_1) = .99$. Still it's not completely impossible d is neutral, say $P(d|c_0) = .05$.

Illustrating the interplay between prior and likelihood

- Suppose harmful (c_1) documents represent .01% of all documents. $P(c_1) = .0001$, $P(c_0) = .9999$.
- Suppose we have a document d, whose features make it **very likely to be harmful**, say $P(d|c_1) = .99$. Still it's not completely impossible d is neutral, say $P(d|c_0) = .05$.
- Which class should we assign d?

Illustrating the interplay between prior and likelihood

- Suppose harmful (c_1) documents represent .01% of all documents. $P(c_1) = .0001$, $P(c_0) = .9999$.
- Suppose we have a document d, whose features make it **very likely to be harmful**, say $P(d|c_1) = .99$. Still it's not completely impossible d is neutral, say $P(d|c_0) = .05$.
- Which class should we assign d?

$$P(c_0|d) \propto .05 * .9999 \simeq .05 \qquad P(c_1|d) \propto .99 * .0001 \simeq .0001$$

Illustrating the interplay between prior and likelihood

- Suppose harmful (c_1) documents represent .01% of all documents. $P(c_1) = .0001$, $P(c_0) = .9999$.
- Suppose we have a document d, whose features make it **very likely to be harmful**, say $P(d|c_1) = .99$. Still it's not completely impossible d is neutral, say $P(d|c_0) = .05$.
- Which class should we assign d?

$$P(c_0|d) \propto .05 * .9999 \simeq .05 \qquad P(c_1|d) \propto .99 * .0001 \simeq .0001$$

- Counterintuitively, we should predict d to be **neutral** according to Naive Bayes!

Illustrating the interplay between prior and likelihood

- Suppose harmful (c_1) documents represent .01% of all documents. $P(c_1) = .0001$, $P(c_0) = .9999$.
- Suppose we have a document d, whose features make it **very likely to be harmful**, say $P(d|c_1) = .99$. Still it's not completely impossible d is neutral, say $P(d|c_0) = .05$.
- Which class should we assign d?

$$P(c_0|d) \propto .05 * .9999 \simeq .05 \qquad P(c_1|d) \propto .99 * .0001 \simeq .0001$$

- Counterintuitively, we should predict d to be **neutral** according to Naive Bayes!
- This illustrates how priors influence "rational" decision making, sometimes against what likelihood suggests. **Humans are notoriously bad at taking priors into account!**

Introducing features

$$
\begin{aligned}
P(c|d) &\propto P(d|c)P(c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\
&= \text{argmax}_{c \in \{c_0, c_1\}} P(d|c)P(c)
\end{aligned}
$$

- Our predicted class is the one for which d is the most likely, weighted by how probable the class is independently of d.
- How to measure how likely a document is given a class? Documents with certain **features**, tend to belong to certain **classes**...

  $P(d|c) = P(F(d)|c)$ with $F(d) = (f_1, ..., f_k)$ d's relevant features

- For instance, harmful documents contain harmful words... so the f_i can be words. This may sound idle, but dealing with individual words will help us further break down $P(d|c)$.

Introducing features

$$
\begin{aligned}
P(c|d) &\propto P(d|c)P(c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\
&= \text{argmax}_{c \in \{c_0, c_1\}} P(d|c)P(c)
\end{aligned}
$$

- Our predicted class is the one for which d is the most likely, weighted by how probable the class is independently of d.
- How to measure how likely a document is given a class? Documents with certain **features**, tend to belong to certain **classes**...

  $P(d|c) = P(F(d)|c)$ with $F(d) = (f_1, ..., f_k)$ d's relevant features

- For instance, harmful documents contain harmful words... so the f_i can be words. This may sound idle, but dealing with individual words will help us further break down $P(d|c)$.

Introducing features

$$
\begin{aligned}
P(c|d) &\propto P(d|c)P(c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\
&= \text{argmax}_{c \in \{c_0, c_1\}} P(d|c)P(c)
\end{aligned}
$$

- Our predicted class is the one for which d is the most likely, weighted by how probable the class is independently of d.
- How to measure how likely a document is given a class? Documents with certain **features**, tend to belong to certain **classes**...

$P(d|c) = P(F(d)|c)$ with $F(d) = (f_1, ..., f_k)$ d's relevant features

- For instance, harmful documents contain harmful words... so the f_i can be words. This may sound idle, but dealing with individual words will help us further break down $P(d|c)$.

Introducing features

$$\begin{aligned} P(c|d) &\propto P(d|c)P(c) \\ \hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\ &= \text{argmax}_{c \in \{c_0, c_1\}} P(d|c)P(c) \end{aligned}$$

- Our predicted class is the one for which d is the most likely, weighted by how probable the class is independently of d.
- How to measure how likely a document is given a class? Documents with certain **features**, tend to belong to certain **classes**...

$P(d|c) = P(F(d)|c)$ with $F(d) = (f_1, ..., f_k)$ d's relevant features

- For instance, harmful documents contain harmful words... so the f_i can be words. This may sound idle, but dealing with individual words will help us further break down $P(d|c)$.

The Bag of Word assumption

- Documents are “featurized” as **the multiset of their words**. A “multiset” is unordered like a set, but keeps track of multiple occurrences.
- It’s like writing each individual word of your document on separate pieces of paper, and tossing them all into a bag. For any document d, we call $BoW(d)$ its corresponding **Bag of Words**.

$$
\begin{aligned}
P(d|c) &\simeq P(BoW(d)|c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(BoW(d)|c) P(c)
\end{aligned}
$$

- Can you think of a classification task and a specific document (=sentence) for which losing positional information would likely affect classification?

The Bag of Word assumption

- Documents are “featurized” as **the multiset of their words**. A “multiset” is unordered like a set, but keeps track of multiple occurrences.
- It’s like writing each individual word of your document on separate pieces of paper, and tossing them all into a bag. For any document d, we call $BoW(d)$ its corresponding **Bag of Words**.

$$
\begin{aligned}
P(d|c) &\simeq P(BoW(d)|c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(BoW(d)|c) P(c)
\end{aligned}
$$

- Can you think of a classification task and a specific document (=sentence) for which losing positional information would likely affect classification?

The Bag of Word assumption

- Documents are “featurized” as **the multiset of their words**. A “multiset” is unordered like a set, but keeps track of multiple occurrences.
- It’s like writing each individual word of your document on separate pieces of paper, and tossing them all into a bag. For any document d, we call $BoW(d)$ its corresponding **Bag of Words**.

$$
\begin{aligned}
P(d|c) &\simeq P(BoW(d)|c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(BoW(d)|c)P(c)
\end{aligned}
$$



- Can you think of a classification task and a specific document (=sentence) for which losing positional information would likely affect classification?

The Bag of Word assumption

- Documents are “featurized” as **the multiset of their words**. A “multiset” is unordered like a set, but keeps track of multiple occurrences.
- It’s like writing each individual word of your document on separate pieces of paper, and tossing them all into a bag. For any document d, we call $BoW(d)$ its corresponding **Bag of Words**.

$$
\begin{aligned}
P(d|c) &\simeq P(BoW(d)|c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(BoW(d)|c) P(c)
\end{aligned}
$$

- Can you think of a classification task and a specific document (=sentence) for which losing positional information would likely affect classification?

Bag of Words practice

- What's the BoW corresponding to the sentence *This is really really cool*?

[3] In fact, to automatically check if two multisets or words are equal, one can first sort them each alphabetically, and them compare them element-wise, left-to-right.

Bag of Words practice

- What's the BoW corresponding to the sentence *This is really really cool*? The multiset {this, is, really, really, cool}. Note that this differs from {this, is, really, cool}, because the number of "copies" matter in multisets (e.g. words with 2 occurrences should "count twice").

[3] In fact, to automatically check if two multisets or words are equal, one can first sort them each alphabetically, and them compare them element-wise, left-to-right.

Bag of Words practice

- What's the BoW corresponding to the sentence *This is really really cool*? The multiset {this, is, really, really, cool}. Note that this differs from {this, is, really, cool}, because the number of "copies" matter in multisets (e.g. words with 2 occurrences should "count twice").
- Is it true to say that $BoW(\textit{This is really really cool}) = \{\text{cool, is, really, really, this}\}$?

[3] In fact, to automatically check if two multisets or words are equal, one can first sort them each alphabetically, and them compare them element-wise, left-to-right.

Bag of Words practice

- What's the BoW corresponding to the sentence *This is really really cool*? The multiset {this, is, really, really, cool}. Note that this differs from {this, is, really, cool}, because the number of "copies" matter in multisets (e.g. words with 2 occurrences should "count twice").
- Is it true to say that *BoW*(*This is really really cool*) = {cool, is, really, really, this}? Yes! Because multisets are unordered, {cool, is, really, really, this} = {this, is, really, really, cool} = *BoW*(*This is really really cool*).[3]

[3] In fact, to automatically check if two multisets or words are equal, one can first sort them each alphabetically, and them compare them element-wise, left-to-right.

The independence assumption

$$
\begin{aligned}
P(d|c) &\simeq P(BoW(d)|c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(BoW(d)|c)P(c)
\end{aligned}
$$

- To further decompose $P(BoW(d)|c)$, we take that the words in our document are **produced independently from each other**.
- This means that knowing a word is in the bag does not inform us about how likely other words are to be in the bag.
- So our likelihood becomes a convenient product of conditional probabilities, one per feature, i.e. one per word in the bag.
- Assuming $BoW(d)$ is the multiset $\{w_0, w_1, ..., w_n\}$:

$$
\begin{aligned}
P(d|c) \simeq P(BoW(d)|c) &= P(\{w_0, w_1, ..., w_n\}|c) \\
&= P(w_0|c) \times P(w_1|c) \times ... \times P(w_n|c) \\
&= \prod_{w \in BoW(d)} P(w|c)
\end{aligned}
$$

The independence assumption

$$
\begin{aligned}
P(d|c) &\simeq P(BoW(d)|c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(BoW(d)|c)P(c)
\end{aligned}
$$

- To further decompose $P(BoW(d)|c)$, we take that the words in our document are **produced independently from each other**.
- This means that knowing a word is in the bag does not inform us about how likely other words are to be in the bag.
- So our likelihood becomes a convenient product of conditional probabilities, one per feature, i.e. one per word in the bag.
- Assuming $BoW(d)$ is the multiset $\{w_0, w_1, ..., w_n\}$:

$$
\begin{aligned}
P(d|c) \simeq P(BoW(d)|c) &= P(\{w_0, w_1, ..., w_n\}|c) \\
&= P(w_0|c) \times P(w_1|c) \times ... \times P(w_n|c) \\
&= \prod_{w \in BoW(d)} P(w|c)
\end{aligned}
$$

The independence assumption

$$
\begin{aligned}
P(d|c) &\simeq P(BoW(d)|c) \\
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(BoW(d)|c)P(c)
\end{aligned}
$$

- To further decompose $P(BoW(d)|c)$, we take that the words in our document are **produced independently from each other**.
- This means that knowing a word is in the bag does not inform us about how likely other words are to be in the bag.
- So our likelihood becomes a convenient product of conditional probabilities, one per feature, i.e. one per word in the bag.
- Assuming $BoW(d)$ is the multiset $\{w_0, w_1, ..., w_n\}$:

$$
\begin{aligned}
P(d|c) \simeq P(BoW(d)|c) &= P(\{w_0, w_1, ..., w_n\}|c) \\
&= P(w_0|c) \times P(w_1|c) \times ... \times P(w_n|c) \\
&= \prod_{w \in BoW(d)} P(w|c)
\end{aligned}
$$

Challenging the independence assumption

- Can you give arguments from syntax or semantics showing why the independence assumption is “**naive**”?

Challenging the independence assumption

- Can you give arguments from syntax or semantics showing why the independence assumption is "**naive**"?
  - Some words "need" to be in a question or under negation. They are called negative polarity items (NPIs).

(4) Have you heard **anything**$_{NPI}$**?** I have**n't** heard **anything**$_{NPI}$/I have heard **something**!

  - Words with similar meanings tend to occur together.

(5) The **sailor steered** the **boat** through the **waves**, tightened the **sails**, and guided the **vessel** safely into the **harbour**. ©ChatGPT

  - Verbs assign fixed roles to their arguments (Agent, Patient, Experiencer, Goal)...leading them to "prefer" certain nominals (agentive vs. passive, animate vs. inanimate...).
  - English questions are often formed via *do*-support, along with a fronted *wh*-word. Also, subjects and verbs agree in number...

(6) **What did** you eat? I ate an apple.

Summary of the model

$$\begin{aligned}\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\ &= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)\end{aligned}$$

- A word w occurring multiple times in $BoW(d)$ will be associated with multiple terms $P(w|c)$ in the above product.
- A document belongs to the class that maximizes the likelihood of its constitutive words ($P(w|c)$), weighted by the class' prior ($P(c)$).
- Next question: how to estimate $P(c)$ and $P(w|c)$ for any class c and word w?

Summary of the model

$$\begin{aligned}\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\ &= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)\end{aligned}$$

- A word w occurring multiple times in $BoW(d)$ will be associated with multiple terms $P(w|c)$ in the above product.
- A document belongs to the class that maximizes the likelihood of its constitutive words ($P(w|c)$), weighted by the class' prior ($P(c)$).
- Next question: how to estimate $P(c)$ and $P(w|c)$ for any class c and word w?

Summary of the model

$$\begin{aligned}\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\ &= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)\end{aligned}$$

- A word w occurring multiple times in $BoW(d)$ will be associated with multiple terms $P(w|c)$ in the above product.
- A document belongs to the class that maximizes the likelihood of its constitutive words ($P(w|c)$), weighted by the class' prior ($P(c)$).
- Next question: how to estimate $P(c)$ and $P(w|c)$ for any class c and word w?

Practice: computing a class posterior

- Suppose we want to determine if the review *d=It was not amazing. But not horrible either.* is negative (class $c_\ominus$). We know negative reviews have a prevalence (prior) of 30%. And we have $P(it|c_\ominus) = .5$, $P(was|c_\ominus) = .5$, $P(not|c_\ominus) = .8$, $P(amazing|c_\ominus) = .1$, $P(but|c_\ominus) = .6$, $P(horrible|c_\ominus) = .9$, $P(either|c_\ominus) = .4$ (do these probabilities seem sensible?).

$$\begin{aligned} P(c_\ominus|d) &\propto P(c_\ominus) \times P(it|c_\ominus) \times P(was|c_\ominus) \times P(not|c_\ominus) \times P(amazing|c_\ominus) \\ &\quad \times P(but|c_\ominus) \times P(not|c_\ominus) \times P(horrible|c_\ominus) \times P(either|c_\ominus) \\ &\propto .3 \times .5 \times .5 \times .8 \times .1 \times .6 \times .8 \times .9 \times .4 \\ &\propto 0.0010368 \end{aligned}$$

- Notice how *not* counts twice for .8 in the equation, which comes from the fact BoWs are multisets.
- The final number seems very low, but remember it is only *proportional* to a probability. We might expect $P(c_\oplus|d)$ to be $\propto$ an even lower value. Only the comparison between the two values matters to determine the best class.

Estimating priors and likelihoods

A supervised learning task

$$
\begin{aligned}
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\
&= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \times P(w_1|c) \times P(w_2|c) \times \ldots \times P(w_n|c) \\
&\quad \text{(with } BoW(d) = \{w_1, \ldots, w_n\}\text{), a multiset)} \\
&= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)
\end{aligned}
$$

- To estimate our **priors** $P(c)$ and **likelihoods** $P(w|c)$ for each class c and word w, we'll use **statistics computed from a training dataset** $\mathcal{T}$.
- We'll assume the dataset is a set of labeled documents. $\mathcal{T} = \{(d_1, c(d_1)), (d_2, c(d_2)), \ldots, (d_k, c(d_k))\}$.
- For instance, $\mathcal{T}$ can be a set of tweets, labeled as harmful or neutral.

A supervised learning task

$$
\begin{aligned}
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\
&= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \times P(w_1|c) \times P(w_2|c) \times ... \times P(w_n|c) \\
&\quad \text{(with } BoW(d) = \{w_1, ..., w_n\}\text{), a multiset)} \\
&= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)
\end{aligned}
$$

- To estimate our **priors** $P(c)$ and **likelihoods** $P(w|c)$ for each class c and word w, we'll use **statistics computed from a training dataset** $\mathcal{T}$.
- We'll assume the dataset is a set of labeled documents. $\mathcal{T} = \{(d_1, c(d_1)), (d_2, c(d_2)), ..., (d_k, c(d_k))\}$.
- For instance, $\mathcal{T}$ can be a set of tweets, labeled as harmful or neutral.

A supervised learning task

$$
\begin{aligned}
\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\
&= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \times P(w_1|c) \times P(w_2|c) \times ... \times P(w_n|c) \\
&\quad \text{(with } BoW(d) = \{w_1, ..., w_n\}\text{), a multiset)} \\
&= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)
\end{aligned}
$$

- To estimate our **priors** $P(c)$ and **likelihoods** $P(w|c)$ for each class c and word w, we'll use **statistics computed from a training dataset** $\mathcal{T}$.
- We'll assume the dataset is a set of labeled documents. $\mathcal{T} = \{(d_1, c(d_1)), (d_2, c(d_2)), ..., (d_k, c(d_k))\}$.
- For instance, $\mathcal{T}$ can be a set of tweets, labeled as harmful or neutral.

Priors

- We need to estimate our prior $P(c)$ for each class c, e.g. the probability for a document to be harmful/neutral **given no extra evidence**.
- To do this, we can look at which **proportion** of the documents of the dataset $\mathcal{T}$ are of class c_i, with $i = 0$ (neutral) or $i = 1$ (harmful). $|.|$ is the set cardinality function–not the absolute value function.

$$\begin{aligned} P(c_i) &\simeq \frac{|\{(d, c(d)) \in \mathcal{T} \mid c(d) = c_i\}|}{|\mathcal{T}|} \\ &\simeq \frac{\text{number of docs of class } c_i \text{ in } \mathcal{T}}{\text{number of docs in } \mathcal{T}} \end{aligned}$$

- So, if $\mathcal{T}$ contains 87 harmful tweets and 1254 neutral ones:

$$\begin{aligned} P(c_0) &\simeq P(\text{neutral}) \\ &\simeq \frac{1254}{1254 + 87} \\ &\simeq 93.5\% \end{aligned} \qquad \begin{aligned} P(c_1) &\simeq P(\text{harmful}) \\ &\simeq \frac{87}{1254 + 87} \\ &\simeq 6.5\% \end{aligned}$$

Priors

- We need to estimate our prior $P(c)$ for each class c, e.g. the probability for a document to be harmful/neutral **given no extra evidence**.
- To do this, we can look at which **proportion** of the documents of the dataset $\mathcal{T}$ are of class c_i, with $i = 0$ (neutral) or $i = 1$ (harmful). $|.|$ is the set cardinality function–not the absolute value function.

$$\begin{aligned} P(c_i) &\simeq \frac{|\{(d, c(d)) \in \mathcal{T} \mid c(d) = c_i\}|}{|\mathcal{T}|} \\ &\simeq \frac{\text{number of docs of class } c_i \text{ in } \mathcal{T}}{\text{number of docs in } \mathcal{T}} \end{aligned}$$

- So, if $\mathcal{T}$ contains 87 harmful tweets and 1254 neutral ones:

$$\begin{aligned} P(c_0) &\simeq P(\text{neutral}) \\ &\simeq \frac{1254}{1254 + 87} \\ &\simeq 93.5\% \end{aligned} \qquad \begin{aligned} P(c_1) &\simeq P(\text{harmful}) \\ &\simeq \frac{87}{1254 + 87} \\ &\simeq 6.5\% \end{aligned}$$

Priors

- We need to estimate our prior $P(c)$ for each class c, e.g. the probability for a document to be harmful/neutral **given no extra evidence**.
- To do this, we can look at which **proportion** of the documents of the dataset $\mathcal{T}$ are of class c_i, with $i = 0$ (neutral) or $i = 1$ (harmful). $|.|$ is the set cardinality function–not the absolute value function.

$$\begin{aligned} P(c_i) &\simeq \frac{|\{(d, c(d)) \in \mathcal{T} \mid c(d) = c_i\}|}{|\mathcal{T}|} \\ &\simeq \frac{\text{number of docs of class } c_i \text{ in } \mathcal{T}}{\text{number of docs in } \mathcal{T}} \end{aligned}$$

- So, if $\mathcal{T}$ contains 87 harmful tweets and 1254 neutral ones:

$$\begin{aligned} P(c_0) &\simeq P(\text{neutral}) \\ &\simeq \frac{1254}{1254 + 87} \\ &\simeq 93.5\% \end{aligned} \qquad \begin{aligned} P(c_1) &\simeq P(\text{harmful}) \\ &\simeq \frac{87}{1254 + 87} \\ &\simeq 6.5\% \end{aligned}$$

Feature likelihoods step 1: mega-docs

- We need to estimate how likely any feature (=word) is, **given a class**: $P(w|c)$.
- For example, we need to estimate how likely we are to see the word *nice* in a harmful vs. a neutral document.
- For any class c, we define d_c as the "mega-document" resulting from the concatenation of all documents of class c in $\mathcal{T}$.
- d_c is a multiset: it may contain several copies of the same word.

$$\begin{aligned} d_{c_i} &= \bigsqcup \{BoW(d) \mid (d, c(d)) \in \mathcal{T} \text{ and } c(d) = c_i\} \\ &\simeq \text{the big compilation of all datapoints of class } c_i \end{aligned}$$

- Intuition: a word like *nice* will be **more frequent** ($\simeq$**more likely**) in the mega-doc d_{c_0} associated with the **neutral** class, as opposed to the mega-doc d_{c_1} associated with the harmful class!

Feature likelihoods step 1: mega-docs

- We need to estimate how likely any feature (=word) is, **given a class**: $P(w|c)$.
- For example, we need to estimate how likely we are to see the word *nice* in a harmful vs. a neutral document.
- For any class c, we define d_c as the "mega-document" resulting from the concatenation of all documents of class c in $\mathcal{T}$.
- d_c is a multiset: it may contain several copies of the same word.

$$\begin{aligned} d_{c_i} &= \bigsqcup \{BoW(d) \mid (d, c(d)) \in \mathcal{T} \text{ and } c(d) = c_i\} \\ &\simeq \text{the big compilation of all datapoints of class } c_i \end{aligned}$$

- Intuition: a word like *nice* will be **more frequent** ($\simeq$**more likely**) in the mega-doc d_{c_0} associated with the **neutral** class, as opposed to the mega-doc d_{c_1} associated with the harmful class!

Feature likelihoods step 1: mega-docs

- We need to estimate how likely any feature (=word) is, **given a class**: $P(w|c)$.
- For example, we need to estimate how likely we are to see the word *nice* in a harmful vs. a neutral document.
- For any class c, we define d_c as the "mega-document" resulting from the concatenation of all documents of class c in $\mathcal{T}$.
- d_c is a multiset: it may contain several copies of the same word.

$$\begin{aligned} d_{c_i} &= \bigsqcup \{BoW(d) \mid (d, c(d)) \in \mathcal{T} \text{ and } c(d) = c_i\} \\ &\simeq \text{the big compilation of all datapoints of class } c_i \end{aligned}$$

- Intuition: a word like *nice* will be **more frequent** ($\simeq$**more likely**) in the mega-doc d_{c_0} associated with the **neutral** class, as opposed to the mega-doc d_{c_1} associated with the harmful class!

Feature likelihoods step 1: mega-docs

- We need to estimate how likely any feature (=word) is, **given a class**: $P(w|c)$.
- For example, we need to estimate how likely we are to see the word *nice* in a harmful vs. a neutral document.
- For any class c, we define d_c as the "mega-document" resulting from the concatenation of all documents of class c in $\mathcal{T}$.
- d_c is a multiset: it may contain several copies of the same word.

$$\begin{aligned} d_{c_i} &= \bigsqcup \{BoW(d) \mid (d, c(d)) \in \mathcal{T} \text{ and } c(d) = c_i\} \\ &\simeq \text{the big compilation of all datapoints of class } c_i \end{aligned}$$

- Intuition: a word like *nice* will be **more frequent** ($\simeq$**more likely**) in the mega-doc d_{c_0} associated with the **neutral** class, as opposed to the mega-doc d_{c_1} associated with the harmful class!

Feature likelihoods step 2: frequencies in mega-docs

- We can then estimate $P(w|c)$ using the frequency of w, within the mega-document d_c.

$$\begin{aligned} P(w|c_i) &\simeq \frac{C(w, d_{c_i})}{|d_{c_i}|} \qquad \text{with } C \text{ the count function} \\ &\simeq \frac{\text{Number of occurrences of } w \text{ in the mega-doc } d_{c_i}}{\text{Total size of } d_{c_i}} \end{aligned}$$

- Suppose that together, all the harmful tweets in $\mathcal{T}$ add up to 2610 words, with 3 occurrences of *nice*. All the neutral tweets add up to 37625 words, with 455 occurrences of *nice*.

$$\begin{aligned} P(nice|c_0) &\simeq P(nice|\text{neutral}) \\ &\simeq \frac{455}{37625} \\ &\simeq 12.1‰ \end{aligned} \qquad \begin{aligned} P(nice|c_1) &\simeq P(nice|\text{harmful}) \\ &\simeq \frac{3}{2610} \\ &\simeq 1.15‰ \end{aligned}$$

Feature likelihoods step 2: frequencies in mega-docs

- We can then estimate $P(w|c)$ using the frequency of w, within the mega-document d_c.

$$\begin{aligned} P(w|c_i) &\simeq \frac{C(w, d_{c_i})}{|d_{c_i}|} \qquad \text{with } C \text{ the count function} \\ &\simeq \frac{\text{Number of occurrences of } w \text{ in the mega-doc } d_{c_i}}{\text{Total size of } d_{c_i}} \end{aligned}$$

- Suppose that together, all the harmful tweets in $\mathcal{T}$ add up to 2610 words, with 3 occurrences of *nice*. All the neutral tweets add up to 37625 words, with 455 occurrences of *nice*.

$$\begin{aligned} P(\textit{nice}|c_0) &\simeq P(\textit{nice}|\text{neutral}) \\ &\simeq \frac{455}{37625} \\ &\simeq 12.1‰ \end{aligned}$$

$$\begin{aligned} P(\textit{nice}|c_1) &\simeq P(\textit{nice}|\text{harmful}) \\ &\simeq \frac{3}{2610} \\ &\simeq 1.15‰ \end{aligned}$$

Summary of the naive Bayes approach

$$\begin{aligned}\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\ &= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)\end{aligned}$$

- The class we assign to a document is the "most likely", **given some relevant features of the document**–typically the words it contains.
- What counts as "most likely" depends on **how likely each feature of the document is**, given the class ($P(w|c)$), but also on **how probable the class is** overall (the prior $P(c)$).
- Both $P(c)$ and $P(w|c)$ can be estimated by extracting document/word **frequencies** from a training dataset.

Summary of the naive Bayes approach

$$\begin{aligned}\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\ &= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)\end{aligned}$$

- The class we assign to a document is the "most likely", **given some relevant features of the document**–typically the words it contains.
- What counts as "most likely" depends on **how likely each feature of the document is**, given the class ($P(w|c)$), but also on **how probable the class is** overall (the prior $P(c)$).
- Both $P(c)$ and $P(w|c)$ can be estimated by extracting document/word **frequencies** from a training dataset.

Summary of the naive Bayes approach

$$\begin{aligned}\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\ &= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)\end{aligned}$$

- The class we assign to a document is the "most likely", **given some relevant features of the document**–typically the words it contains.
- What counts as "most likely" depends on **how likely each feature of the document is**, given the class ($P(w|c)$), but also on **how probable the class is** overall (the prior $P(c)$).
- Both $P(c)$ and $P(w|c)$ can be estimated by extracting document/word **frequencies** from a training dataset.

Summary of the naive Bayes approach

$$\begin{aligned}\hat{c}(d) &= \text{argmax}_{c \in \{c_0, c_1\}} P(c|d) \\ &= \text{argmax}_{c \in \{c_0, c_1\}} P(c) \prod_{w \in BoW(d)} P(w|c)\end{aligned}$$

- The class we assign to a document is the "most likely", **given some relevant features of the document**–typically the words it contains.
- What counts as "most likely" depends on **how likely each feature of the document is**, given the class ($P(w|c)$), but also on **how probable the class is** overall (the prior $P(c)$).
- Both $P(c)$ and $P(w|c)$ can be estimated by extracting document/word **frequencies** from a training dataset.

Evaluating a Naive Bayes model

Defining a test set

- To evaluate a Naive Bayes model, we'll need fresh, annotated data, in the form of a **test set** $\mathcal{T}'$.
- This set will have **same structure** as the training set: a set of document-class pairs.
- $\mathcal{T}'$ must be similar-enough to the training set to enable **meaningful comparisons** between competing models/sets of relevant features.
- But $\mathcal{T}'$ must also contain fresh unseen data, in order to estimate how well the model **generalized** beyond the training data.
- **The metrics we'll see in this section are extremely general, and apply beyond Naive Bayes! In fact they extend to any binary classifier!**

Defining a test set

- To evaluate a Naive Bayes model, we'll need fresh, annotated data, in the form of a **test set** $\mathcal{T}'$.
- This set will have **same structure** as the training set: a set of document-class pairs.
- $\mathcal{T}'$ must be similar-enough to the training set to enable **meaningful comparisons** between competing models/sets of relevant features.
- But $\mathcal{T}'$ must also contain fresh unseen data, in order to estimate how well the model **generalized** beyond the training data.
- **The metrics we'll see in this section are extremely general, and apply beyond Naive Bayes! In fact they extend to any binary classifier!**

Defining a test set

- To evaluate a Naive Bayes model, we'll need fresh, annotated data, in the form of a **test set** $\mathcal{T}'$.
- This set will have **same structure** as the training set: a set of document-class pairs.
- $\mathcal{T}'$ must be similar-enough to the training set to enable **meaningful comparisons** between competing models/sets of relevant features.
- But $\mathcal{T}'$ must also contain fresh unseen data, in order to estimate how well the model **generalized** beyond the training data.
- The metrics we'll see in this section are extremely general, and apply beyond Naive Bayes! In fact they extend to any binary classifier!

Defining a test set

- To evaluate a Naive Bayes model, we'll need fresh, annotated data, in the form of a **test set** $\mathcal{T}'$.
- This set will have **same structure** as the training set: a set of document-class pairs.
- $\mathcal{T}'$ must be similar-enough to the training set to enable **meaningful comparisons** between competing models/sets of relevant features.
- But $\mathcal{T}'$ must also contain fresh unseen data, in order to estimate how well the model **generalized** beyond the training data.
- The metrics we'll see in this section are extremely general, and apply beyond Naive Bayes! In fact they extend to any binary classifier!

Defining a test set

- To evaluate a Naive Bayes model, we'll need fresh, annotated data, in the form of a **test set** $\mathcal{T}'$.
- This set will have **same structure** as the training set: a set of document-class pairs.
- $\mathcal{T}'$ must be similar-enough to the training set to enable **meaningful comparisons** between competing models/sets of relevant features.
- But $\mathcal{T}'$ must also contain fresh unseen data, in order to estimate how well the model **generalized** beyond the training data.
- **The metrics we'll see in this section are extremely general, and apply beyond Naive Bayes! In fact they extend to any binary classifier!**

An intuitive measure of success: accuracy

- We have $\mathcal{T}' = \{(d'_1, c(d'_1)), (d'_2, c(d'_2)), ..., (d'_k, c(d'_k))\}$.
- Intuitive idea: for each pair $((d'_i, c(d'_i)))$, predict $\hat{c}(d'_i)$ using the Naive Bayes model, and compare $\hat{c}(d'_i)$ to the ground truth $c(d'_i)$:
  - If they match yay! We increment our success score by 1;
  - If they don't match shoot! We move on to the next pair.
- We can then compute our probability of success: our success score divided by the number of pairs scanned (k).
- More formally, the **accuracy** of a Naive Bayes model (i.e. a classification function $\hat{c}$) on a test set $\mathcal{T}'$ is:

$$\begin{aligned} \textsc{Accuracy}(\mathcal{T}', \hat{c}) &= \frac{|\{(d', c') \in \mathcal{T}' \mid c' = \hat{c}(d')\}|}{|\mathcal{T}'|} \\ &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}} \end{aligned}$$

An intuitive measure of success: accuracy

- We have $\mathcal{T}' = \{(d'_1, c(d'_1)), (d'_2, c(d'_2)), ..., (d'_k, c(d'_k))\}$.
- Intuitive idea: for each pair $((d'_i, c(d'_i)))$, predict $\hat{c}(d'_i)$ using the Naive Bayes model, and compare $\hat{c}(d'_i)$ to the ground truth $c(d'_i)$:
  - If they match yay! We increment our success score by 1;
  - If they don't match shoot! We move on to the next pair.
- We can then compute our probability of success: our success score divided by the number of pairs scanned (k).
- More formally, the **accuracy** of a Naive Bayes model (i.e. a classification function $\hat{c}$) on a test set $\mathcal{T}'$ is:

$$\begin{aligned} \textsc{Accuracy}(\mathcal{T}', \hat{c}) &= \frac{|\{(d', c') \in \mathcal{T}' \mid c' = \hat{c}(d')\}|}{|\mathcal{T}'|} \\ &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}} \end{aligned}$$

An intuitive measure of success: accuracy

- We have $\mathcal{T}' = \{(d'_1, c(d'_1)), (d'_2, c(d'_2)), ..., (d'_k, c(d'_k))\}$.
- Intuitive idea: for each pair $((d'_i, c(d'_i)))$, predict $\hat{c}(d'_i)$ using the Naive Bayes model, and compare $\hat{c}(d'_i)$ to the ground truth $c(d'_i)$:
  - If they match yay! We increment our success score by 1;
  - If they don't match shoot! We move on to the next pair.
- We can then compute our probability of success: our success score divided by the number of pairs scanned (k).
- More formally, the **accuracy** of a Naive Bayes model (i.e. a classification function $\hat{c}$) on a test set $\mathcal{T}'$ is:

$$\begin{aligned} \textsc{Accuracy}(\mathcal{T}', \hat{c}) &= \frac{|\{(d', c') \in \mathcal{T}' \mid c' = \hat{c}(d')\}|}{|\mathcal{T}'|} \\ &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}} \end{aligned}$$

An intuitive measure of success: accuracy

- We have $\mathcal{T}' = \{(d'_1, c(d'_1)), (d'_2, c(d'_2)), ..., (d'_k, c(d'_k))\}$.
- Intuitive idea: for each pair $((d'_i, c(d'_i)))$, predict $\hat{c}(d'_i)$ using the Naive Bayes model, and compare $\hat{c}(d'_i)$ to the ground truth $c(d'_i)$:
  - If they match yay! We increment our success score by 1;
  - If they don't match shoot! We move on to the next pair.
- We can then compute our probability of success: our success score divided by the number of pairs scanned (k).
- More formally, the **accuracy** of a Naive Bayes model (i.e. a classification function $\hat{c}$) on a test set $\mathcal{T}'$ is:

$$\begin{aligned}\textsc{Accuracy}(\mathcal{T}', \hat{c}) &= \frac{|\{(d', c') \in \mathcal{T}' \mid c' = \hat{c}(d')\}|}{|\mathcal{T}'|} \\ &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}}\end{aligned}$$

An intuitive measure of success: accuracy

- We have $\mathcal{T}' = \{(d'_1, c(d'_1)), (d'_2, c(d'_2)), ..., (d'_k, c(d'_k))\}$.
- Intuitive idea: for each pair $((d'_i, c(d'_i)))$, predict $\hat{c}(d'_i)$ using the Naive Bayes model, and compare $\hat{c}(d'_i)$ to the ground truth $c(d'_i)$:
  - If they match yay! We increment our success score by 1;
  - If they don't match shoot! We move on to the next pair.
- We can then compute our probability of success: our success score divided by the number of pairs scanned (k).
- More formally, the **accuracy** of a Naive Bayes model (i.e. a classification function $\hat{c}$) on a test set $\mathcal{T}'$ is:

$$\begin{aligned} \textsc{Accuracy}(\mathcal{T}', \hat{c}) &= \frac{|\{(d', c') \in \mathcal{T}' \mid c' = \hat{c}(d')\}|}{|\mathcal{T}'|} \\ &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}} \end{aligned}$$

Accuracy practice

- Suppose we are classifying reviews as positive ($\oplus$) or negative ($\ominus$). Below is our test dataset, including the human-derived labels ("ground-truth") along with those predicted by Naive Bayes (or another binary classifier).

Review	Ground-truth	Predicted	Ground-truth=Predicted?
d_1	$\oplus$	$\oplus$	1
d_2	$\ominus$	$\oplus$	0
d_3	$\ominus$	$\ominus$	1
d_4	$\oplus$	$\oplus$	1
d_5	$\oplus$	$\ominus$	0
d_6	$\ominus$	$\oplus$	0
		Total matches	3

- Accuracy is $\frac{\text{Total matches}}{\text{Number of rows}}$ i.e. $\frac{3}{6}$ = 50%.

Shortcomings of accuracy: the stupid classifier

- Suppose our two classes are **very imbalanced**, as is often the case: the more critical/problematic class is much rarer.

Shortcomings of accuracy: the stupid classifier

- Suppose our two classes are **very imbalanced**, as is often the case: the more critical/problematic class is much rarer.
- For instance, assume $\mathcal{T}'$ contains 90% of neutral tweets, and 10% of harmful tweets.

Shortcomings of accuracy: the stupid classifier

- Suppose our two classes are **very imbalanced**, as is often the case: the more critical/problematic class is much rarer.
- For instance, assume $\mathcal{T}'$ contains 90% of neutral tweets, and 10% of harmful tweets.
- Take a very **stupid classifier**, predicting a tweet to be neutral 100% of the time. What will be its accuracy?

Shortcomings of accuracy: the stupid classifier

- Suppose our two classes are **very imbalanced**, as is often the case: the more critical/problematic class is much rarer.
- For instance, assume $\mathcal{T}'$ contains 90% of neutral tweets, and 10% of harmful tweets.
- Take a very **stupid classifier**, predicting a tweet to be neutral 100% of the time. What will be its accuracy?

$$\begin{aligned}
\textsc{Accuracy}(\mathcal{T}', \hat{c}_{stupid}) &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}} \\
&= \frac{\text{Number of neutral datapoints}}{\text{Number of datapoints}} \\
&= 90\%
\end{aligned}$$

Shortcomings of accuracy: the stupid classifier

- Suppose our two classes are **very imbalanced**, as is often the case: the more critical/problematic class is much rarer.
- For instance, assume $\mathcal{T}'$ contains 90% of neutral tweets, and 10% of harmful tweets.
- Take a very **stupid classifier**, predicting a tweet to be neutral 100% of the time. What will be its accuracy?

$$\begin{aligned}
\textsc{Accuracy}(\mathcal{T}', \hat{c}_{stupid}) &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}} \\
&= \frac{\text{Number of neutral datapoints}}{\text{Number of datapoints}} \\
&= 90\%
\end{aligned}$$

- Pretty high! But what's the point if harmful tweets are never identified?

Shortcomings of accuracy: the zealous classifier

- Now consider $\hat{c}$, a classifier which at least tries to identify harmful tweets–causing it to mispredict some neutral ones.

Shortcomings of accuracy: the zealous classifier

- Now consider $\hat{c}$, a classifier which at least tries to identify harmful tweets–causing it to mispredict some neutral ones.
- Let's assume 5/10 harmful tweets, and 80/90 neutral tweets from $\mathcal{T}'$ are correctly classified by $\hat{c}$. What will be its accuracy?

Shortcomings of accuracy: the zealous classifier

- Now consider $\hat{c}$, a classifier which at least tries to identify harmful tweets–causing it to mispredict some neutral ones.
- Let's assume 5/10 harmful tweets, and 80/90 neutral tweets from $\mathcal{T}'$ are correctly classified by $\hat{c}$. What will be its accuracy?

$$\begin{aligned}
\textsc{Accuracy}(\mathcal{T}', \hat{c}) &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}} \\
&= \frac{5 + 80}{100} \\
&= 85\%
\end{aligned}$$

Shortcomings of accuracy: the zealous classifier

- Now consider $\hat{c}$, a classifier which at least tries to identify harmful tweets–causing it to mispredict some neutral ones.
- Let's assume 5/10 harmful tweets, and 80/90 neutral tweets from $\mathcal{T}'$ are correctly classified by $\hat{c}$. What will be its accuracy?

$$\begin{aligned}
\textsc{Accuracy}(\mathcal{T}', \hat{c}) &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}} \\
&= \frac{5 + 80}{100} \\
&= 85\%
\end{aligned}$$

- That's lower than the stupid classifier :((

Shortcomings of accuracy: the zealous classifier

- Now consider $\hat{c}$, a classifier which at least tries to identify harmful tweets–causing it to mispredict some neutral ones.
- Let's assume 5/10 harmful tweets, and 80/90 neutral tweets from $\mathcal{T}'$ are correctly classified by $\hat{c}$. What will be its accuracy?

$$\begin{aligned}
\textsc{Accuracy}(\mathcal{T}', \hat{c}) &= \frac{\text{Number of datapoints whose class was correctly predicted}}{\text{Number of datapoints}} \\
&= \frac{5 + 80}{100} \\
&= 85\%
\end{aligned}$$

- That's lower than the stupid classifier :((
- Intuition: **had we focused on the harmful tweets**, we'd have noticed that the stupid classifier was doing a poor job (none of them were identified), and the zealous classifier a better job (5 were identified).

Recall

- We want a measure that tracks some proportion of correctly predicted harmful tweets.
- One idea is to look at the **proportion of correctly predicted harmful tweets, over all *actually* harmful tweets.**
- This is known as **recall**.
- The stupid classifier predicted 0 tweets to be harmful, so its recall is 0!
- The zealous classifier correctly predicted 5 tweets to be harmful, out of the 10 actually harmful tweets, so its recall is 50%! Better!

Recall

- We want a measure that tracks some proportion of correctly predicted harmful tweets.
- One idea is to look at the **proportion of correctly predicted harmful tweets, over all *actually* harmful tweets.**
- This is known as **recall**.
- The stupid classifier predicted 0 tweets to be harmful, so its recall is 0!
- The zealous classifier correctly predicted 5 tweets to be harmful, out of the 10 actually harmful tweets, so its recall is 50%! Better!

Recall

- We want a measure that tracks some proportion of correctly predicted harmful tweets.
- One idea is to look at the **proportion of correctly predicted harmful tweets, over all *actually* harmful tweets.**
- This is known as **recall**.
- The stupid classifier predicted 0 tweets to be harmful, so its recall is 0!
- The zealous classifier correctly predicted 5 tweets to be harmful, out of the 10 actually harmful tweets, so its recall is 50%! Better!

Recall

- We want a measure that tracks some proportion of correctly predicted harmful tweets.
- One idea is to look at the **proportion of correctly predicted harmful tweets, over all *actually* harmful tweets.**
- This is known as **recall**.
- The stupid classifier predicted 0 tweets to be harmful, so its recall is 0!
- The zealous classifier correctly predicted 5 tweets to be harmful, out of the 10 actually harmful tweets, so its recall is 50%! Better!

Recall practice

- Suppose we are classifying reviews as positive ($\oplus$) or negative ($\ominus$). Below is our test dataset, including the human-derived labels ("ground-truth") along with those predicted by Naive Bayes (or another binary classifier).

Review	Ground-truth	Predicted	Correctly predicted $\ominus$?	Actually $\ominus$?
d_1	$\oplus$	$\oplus$	0	0
d_2	$\ominus$	$\oplus$	0	1
d_3	$\ominus$	$\ominus$	1	1
d_4	$\oplus$	$\oplus$	0	0
d_5	$\oplus$	$\ominus$	0	0
d_6	$\ominus$	$\oplus$	0	1
		Total	1	3

- Recall is $\frac{1}{3}$ = 33.3%.

Precision

- Another way to track the proportion of correctly predicted harmful tweets, is to look at the **proportion of correctly predicted harmful tweets, over all tweets that were *predicted* to be harmful–correctly or not.**
- This is known as **precision**.
- The stupid classifier predicted 0 tweets to be harmful, so its precision is undefined (null numerator and denominator).
- The zealous classifier correctly predicted 5 tweets to be harmful, and incorrectly predicted 10 tweets to be harmful, so its precision is $5/(5+10) = 33\%$! Better!

Precision

- Another way to track the proportion of correctly predicted harmful tweets, is to look at the **proportion of correctly predicted harmful tweets, over all tweets that were *predicted* to be harmful–correctly or not.**
- This is known as **precision**.
- The stupid classifier predicted 0 tweets to be harmful, so its precision is undefined (null numerator and denominator).
- The zealous classifier correctly predicted 5 tweets to be harmful, and incorrectly predicted 10 tweets to be harmful, so its precision is $5/(5+10) = 33\%$! Better!

Precision

- Another way to track the proportion of correctly predicted harmful tweets, is to look at the **proportion of correctly predicted harmful tweets, over all tweets that were *predicted* to be harmful–correctly or not.**
- This is known as **precision**.
- The stupid classifier predicted 0 tweets to be harmful, so its precision is undefined (null numerator and denominator).
- The zealous classifier correctly predicted 5 tweets to be harmful, and incorrectly predicted 10 tweets to be harmful, so its precision is $5/(5+10) = 33\%$! Better!

Precision

- Another way to track the proportion of correctly predicted harmful tweets, is to look at the **proportion of correctly predicted harmful tweets, over all tweets that were *predicted* to be harmful–correctly or not.**
- This is known as **precision**.
- The stupid classifier predicted 0 tweets to be harmful, so its precision is undefined (null numerator and denominator).
- The zealous classifier correctly predicted 5 tweets to be harmful, and incorrectly predicted 10 tweets to be harmful, so its precision is $5/(5+10) = 33\%$! Better!

Precision practice


- Suppose we are classifying reviews as positive ($\oplus$) or negative ($\ominus$). Below is our test dataset, including the human-derived labels ("ground-truth") along with those predicted by Naive Bayes (or another binary classifier).

Review	Ground-truth	Predicted	Correctly predicted $\ominus$?	Predicted $\ominus$?
d_1	$\oplus$	$\oplus$	0	0
d_2	$\ominus$	$\oplus$	0	0
d_3	$\ominus$	$\ominus$	1	1
d_4	$\oplus$	$\oplus$	0	0
d_5	$\oplus$	$\ominus$	0	1
d_6	$\ominus$	$\oplus$	0	0
		Total	1	3

- Recall is $\frac{1}{2}$ = 50%.

Precision and recall summary

- Imo the definitions of precision and recall are hard to remember. Memorable examples/graphical representations can help.[4]



[4] Note that "positive" here refers the comparatively rare/critical class that must be reliably detected (here pregnancy). In many cases this class comes with more *negative* connotations (i.e. fake news, hateful speech, illness etc.)

The F-score

- Lastly, there's a way to combine precision and recall into one score balancing the two. This is known as the F-score.

$$F = \frac{2 \times \textsc{Precision} \times \textsc{Recall}}{\textsc{Precision} + \textsc{Recall}}$$

Lab

https://colab.research.google.com/drive/1N0FJU0q_bYh-LAMEo6qFzcbfZ2Abut8b6?usp=sharing