



Incident report analysis

The organization recently experienced a DoS attack, which compromised the internal network for two hours until it was resolved.

During the attack, your organization's network services suddenly stopped responding due to an incoming flood of ICMP packets. Normal internal network traffic could not access any network resources. The incident management team responded by blocking incoming ICMP packets, stopping all non-critical network services offline, and restoring critical network services.

The company's cybersecurity team then investigated the security event. They found that a malicious actor had sent a flood of ICMP pings into the company's network through an unconfigured firewall. This vulnerability allowed the malicious attacker to overwhelm the company's network through a denial of service (DoS) attack.

Summary	The company experienced a security event when all network services suddenly stopped responding. The cybersecurity team found the disruption was caused by a distributed denial of services (DDoS) attack through a flood of incoming ICMP packets. The team responded by blocking the attack and stopping all non-critical network services, so that critical network services could be restored.
Identify	A malicious actor or actors targeted the company with an ICMP flood attack. The entire internal network was affected. All critical network resources needed to be secured and restored to a functioning state.
Protect	The cybersecurity team implemented a new firewall rule to limit the rate of

	incoming ICMP packets and an IDS/IPS system to filter out some ICMP traffic based on suspicious characteristics.
Detect	The cybersecurity team configured source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets and implemented network monitoring software to detect abnormal traffic patterns.
Respond	For future security events, the cybersecurity team will isolate affected systems to prevent further disruption to the network. They will attempt to restore any critical systems and services that were disrupted by the event. Then, the team will analyze network logs to check for suspicious and abnormal activity. The team will also report all incidents to upper management and appropriate legal authorities, if applicable.
Recover	To recover from a DDoS attack by ICMP flooding, access to network services need to be restored to a normal functioning state. In the future, external ICMP flood attacks can be blocked at the firewall. Then, all non-critical network services should be stopped to reduce internal network traffic. Next, critical network services should be restored first. Finally, once the flood of ICMP packets have timed out, all non-critical network systems and services can be brought back online.

Reflections/Notes: