

# Integrating Logical Dependencies in Software Clustering: A case of study on Apache Ant

1<sup>st</sup> Adelina Stana

Computer Science and Engineering Department  
"Politehnica" University of Timisoara  
Timișoara, România  
stana.adelina.diana@gmail.com

2<sup>nd</sup> Ioana Sora

Computer Science and Engineering Department  
"Politehnica" University of Timisoara  
Timișoara, România  
ioana.sora@cs.upt.ro

**Abstract**—Extracted code co-changes from versioning systems have multiple applications across numerous fields, including fault detection, software reconstruction, key class identification, among others. This paper will focus on the influence of code co-changes on software clustering. Specifically, we will analyze their impact on the clustering solution of Apache Ant in order to assess whether co-changes usage enhances the quality of the obtained solution.

**Index Terms**—logical dependencies, logical coupling, mining software repositories, code co-change; co-changing entities, software evolution, clustering

## I. INTRODUCTION

The software architecture helps developers in gaining a better understanding of the system and its expected behavior. Additionally, it is also of great help in change management. By knowing the existing system architecture, project managers can assess whether a requested change can be easily implemented or not.

Architecture reconstruction appears in contexts where a software system lacks documentation entirely, or where the documentation hasn't been updated to reflect changes in the system.

Previous research has revealed that dependencies extracted from versioning systems are distinct from those extracted from code, implying that using them could enhance our understanding of the system [1], [2], [3].

We intend to use dependencies obtained from the versioning system to enhance the results of clustering methods that previously relied solely on connections extracted from code.

To evaluate the results, we will initially create a clustering solution based on structural dependencies alone. Next, we will incorporate dependencies extracted from the versioning system with the structural dependencies to produce a second clustering solution. Lastly, we will construct a clustering solution that relies entirely on logical dependencies, and we will compare all three solutions obtained.

## II. LOGICAL DEPENDENCIES

During development processes, numerous software entities are changed. It has been observed that entities changing together are not only those with structural relationships but also include entities that are functionally dependent on one another.




Fig. 1. Overview on updates of different entities

This functional dependency, however, cannot be observed by examining the code.

This type of entities, that consistently change together throughout development activities, are called logical dependencies or coupling. This concept was initially introduced by Gall et al. [4] and has numerous fields of application.

A problem with dependencies extracted from the versioning system is their potential to become excessively numerous. This often results from commits that contain numerous files, thereby generating thousands of dependencies from a single commit. Additionally, the reliability of co-changes is another problem; certain entities may only change together once throughout the entire versioning history, making them less reliable than entities that change together hundreds of times, for instance. Figure 1 illustrates this scenario.

Previous research uses two known metrics in order to solve this problems: *support* and *confidence*. Given a dependency where  $A \rightarrow B$ , the support metric measures the frequency of updates that two entities share within the versioning system. The confidence metric calculates the proportion of updates between two entities relative to the total updates of the antecedent (A) or consequent (B) entity [1], [2], [5].

In our previous research, we focused on identifying metrics that enhance the reliability of dependencies extracted from the versioning system [6], [7]. One of the metrics is the *commit size metric*, which involves extracting dependencies from commits that do not exceed a specific commit size limit, thereby reducing the possibility of extracting an overly large number of dependencies. Additionally, we developed the

strength metric, which serves as a refinement of the more known *confidence metric* [8].

The strength metric was developed to obtain a better reflection of the system and its values. For instance, when using the confidence metric, two entities that update together only once will have the highest possible score on the confidence metric, a result that is not desirable. On the other hand, entities that undergo hundreds of updates together, and even more updates with other entities, will receive a lower confidence metric score. Thus, the confidence metric will favor entities that update less and always together.

The strength metric is calculated by multiplying the confidence metric value with a system factor, which is determined by the average number of updates for all entities in the system. In this way, a very high confidence score resulting from only a few updates will be adjusted downwards, while a low confidence score that is based on a big number of updates will be increased.

The confidence metric score ranges from 0 to 1, with 1 representing the best value. On the other hand, the strength metric ranges from 0 to 100, where 100 represents the best possible score.

Co-changes that meet both the commit size metric threshold and the strength metric threshold are referred to as *logical dependencies*.

### III. RELATED WORK

There are numerous applications of co-changes extracted from version control systems. Prajapati et al. used structural dependencies, co-changes, and lexical dependencies to enhance system modularization. Benkoczi et al. analyze how a system's modularity evolves over time using only co-change history [9], by utilizing two metrics based on a weighted design structure matrix.

Anshu et al. analyze how co-changes impact the packaging restructuring [10], Silva et al. generated co-change clusters based on the versioning system information [11].

The Modularization Quality (MQ) metric, as defined by Mitchell and Mancoridis [12], [13], is extensively utilized to assess the results of clustering techniques. While it is primarily applied to clusters formed from structural dependencies [14], [15], [16], it also for evaluating clusters derived from other types of dependencies [17].

### IV. METHOD

To obtain the logical dependencies for further use, we will use the same Python tool developed in our previous research [8]. This tool retrieves all necessary data from GitHub [18] using git commands and then processes it. The initial phase involves applying a commit size filter to exclude all commits that involve changes to more than 10 files. Following, the tool creates dependencies based on these commits, establishing a dependency link between each entity in a modified file and all entities in other files modified by the same commit.

Next, the tool calculates the strength metric as described in chapter II. It then filters out any dependencies falling below the




Fig. 2. Logical dependencies extraction workflow

set strength metric threshold. For our experiments, we initiated with a strength metric threshold of 10, incrementing in steps of 10 up to 100 (the maximum value for the metric). Finally, we exported the results in comma separated values format file (.csv). The above described workflow is illustrated in figure 2.

Following the generation of logical dependencies, we integrate them into software clustering techniques. For this, a Python script was developed to extract both structural and logical dependencies from their respective files, forming a dependency matrix. This matrix is used as the input for the Minimum Spanning Tree (MST) and Louvain Clustering algorithms. The resulting clustering solution is then evaluated using the Modularity Quality (MQ) metric [12].

#### A. Clustering algorithms: MST Clustering


Minimum Spanning Tree Clustering is a hierarchical clustering method based on the construction of a minimum spanning tree from the weighted graph formed by the data connections of the system [19].

#### B. Clustering algorithms: Louvain Clustering

Louvain Clustering is a community detection algorithm designed for finding clusters or communities in complex networks. The Louvain method involves a greedy algorithm that moves nodes between clusters to obtain clusters that are highly interconnected [20].

In order to compare the clustering solutions and their associated MQ metric, we generated clustering solutions in three scenarios: the first one by using only structural dependencies, the second one by using only logical dependencies and the third one by using logical and structural dependencies to populate the dependency matrix that is further used in the cluster generation. The third scenario workflow is illustrated in the figure 3.

To generate and compare the clustering solutions and their corresponding Modularity Quality (MQ) metric, we created



## V. RESULTS

TABLE I

Dataset	Entities Count	Cluster count		MQ metric	
		Louvain	MST	Louvain	MST
SD only	517	14	228	0.085	0.084
LD strength 10%	517	272	353	0.047	0.031
LD strength 20%	517	355	360	0.04	0.037
LD strength 30%	517	387	404	0.036	0.033
LD strength 40%	517	405	413	0.034	0.033
LD strength 50%	517	414	422	0.03	0.029
LD strength 60%	517	431	439	0.029	0.027
LD strength 70%	517	443	444	0.027	0.026
LD strength 80%	517	454	460	0.024	0.022
LD strength 90%	517	462	463	0.021	0.021
LD strength 100%	517	472	480	0.019	0.016

TABLE II

Dataset	Entities Count	Cluster count		MQ metric	
		Louvain	MST	Louvain	MST
SD only	517	14	228	0.085	0.084
SD LD strength 10%	517	15	74	0.087	<u>0.054</u>
SD LD strength 20%	517	13	8	0.071	<u>0.059</u>
SD LD strength 30%	517	13	14	0.071	<u>0.083</u>
SD LD strength 40%	517	13	8	0.071	0.109
SD LD strength 50%	517	13	8	0.071	0.109
SD LD strength 60%	517	13	8	0.071	0.109
SD LD strength 70%	517	13	10	0.071	0.155
SD LD strength 80%	517	13	6	0.071	0.177
SD LD strength 90%	517	13	2	0.071	0.129
SD LD strength 100%	517	13	8	0.072	0.166



## VI. DISCUSSION

The placement of the `Concat` class and its inner classes (`Concat$1`, `Concat$MultiReader`, `Concat$TextElement`) in a different cluster might be based on its usage and purpose; according to the documentation : "This class contains the 'concat' task, used to concatenate a series of files into a single stream." [21]. 4

## VII. CONCLUSION AND FUTURE WORK

Based on the outcomes detailed in Chapter V and the analysis in Chapter VI, it is clear that incorporating logical dependencies improves the quality of clustering solutions. For our forthcoming work, we intend to conduct further experiments across various projects to validate these findings. Additionally, we will try to create a reference clustering solution for these projects, based on their code and documentation. We will then evaluate the clustering results against the reference solution by utilizing the MOJO metric for comparison [22].

## REFERENCES

- [1] G. A. Oliva and M. A. Gerosa, "Experience report: How do structural dependencies influence change propagation? an empirical study," in *26th IEEE International Symposium on Software Reliability Engineering, ISSRE 2015, Gaithersburg, MD, USA, November 2-5, 2015*, 2015, pp. 250–260. [Online]. Available: <https://doi.org/10.1109/ISSRE.2015.7381818>

- [2] N. Aijenka and A. Capiluppi, "Understanding the interplay between the logical and structural coupling of software classes," *Journal of Systems and Software*, vol. 134, pp. 120–137, 2017. [Online]. Available: <https://doi.org/10.1016/j.jss.2017.08.042>
- [3] G. A. Oliva and M. A. Gerosa, "On the interplay between structural and logical dependencies in open-source software," in *Proceedings of the 2011 25th Brazilian Symposium on Software Engineering*, ser. SBES '11. Washington, DC, USA: IEEE Computer Society, 2011, pp. 144–153. [Online]. Available: <https://doi.org/10.1109/SBES.2011.39>
- [4] H. Gall, K. Hajek, and M. Jazayeri, "Detection of logical coupling based on product release history," in *Proceedings of the International Conference on Software Maintenance*, ser. ICSM '98. Washington, DC, USA: IEEE Computer Society, 1998, pp. 190–. [Online]. Available: <http://dl.acm.org/citation.cfm?id=850947.853338>
- [5] T. Zimmermann, P. Weisgerber, S. Diehl, and A. Zeller, "Mining version histories to guide software changes," in *Proceedings of the 26th International Conference on Software Engineering*, ser. ICSE '04. Washington, DC, USA: IEEE Computer Society, 2004, pp. 563–572. [Online]. Available: <http://dl.acm.org/citation.cfm?id=998675.999460>
- [6] A. D. Stana and I. Şora, "Analyzing information from versioning systems to detect logical dependencies in software systems," in *2019 IEEE 13th International Symposium on Applied Computational Intelligence and Informatics (SACI)*, 2019, pp. 000 015–000 020.
- [7] A. D. Stana. and I. Şora., "Identifying logical dependencies from co-changing classes," in *Proceedings of the 14th International Conference on Evaluation of Novel Approaches to Software Engineering - Volume 1: ENASE, INSTICC. SciTePress*, 2019, pp. 486–493.
- [8] A.-D. Stana and I. Şora, "Logical dependencies: Extraction from the versioning system and usage in key classes detection," *Computer Science and Information Systems*, vol. 20, pp. 25–25, 01 2023.
- [9] R. Benkoczi, D. Gaur, S. Hossain, and M. A. Khan, "A design structure matrix approach for measuring co-change-modularity of software products," in *Proceedings of the 15th International Conference on Mining Software Repositories*, ser. MSR '18. New York, NY, USA: Association for Computing Machinery, 2018, p. 331–335. [Online]. Available: <https://doi.org/10.1145/3196398.3196409>
- [10] A. Parashar and J. Chhabra, "Package-restructuring based on software change history," *National Academy Science Letters*, vol. 40, 04 2016.
- [11] L. Silva, M. Valente, and M. Maia, "Co-change clusters: Extraction and application on assessing software modularity," *Transactions on Aspect-Oriented Software Development*, 03 2015.
- [12] S. Mancoridis, B. Mitchell, C. Rorres, Y. Chen, and E. Gansner, "Using automatic clustering to produce high-level system organizations of source code," in *Proceedings. 6th International Workshop on Program Comprehension. IWPC'98 (Cat. No.98TB100242)*, 1998, pp. 45–52.
- [13] B. Mitchell and S. Mancoridis, "Comparing the decompositions produced by software clustering algorithms using similarity measurements," in *Proceedings IEEE International Conference on Software Maintenance. ICSM 2001*, 2001, pp. 744–753.
- [14] S. Mancoridis, B. Mitchell, Y.-F. Chen, and E. Gansner, "Bunch: A clustering tool for the recovery and maintenance of software system structures," 04 1999.
- [15] B. Mitchell and S. Mancoridis, "On the evaluation of the bunch search-based software modularization algorithm," *Soft Comput.*, vol. 12, pp. 77–93, 01 2008.
- [16] —, "Demonstration proposal: Clustering module dependency graphs of software systems using the bunch tool," 04 1999.
- [17] A. Prajapati, A. Parashar, and A. Rathee, "Multi-dimensional information-driven many-objective software remodularization approach," *Frontiers of Computer Science*, vol. 17, 11 2022.
- [18] A. S. Foundation, "Apache ant," <https://github.com/apache/ant>, 2024, GitHub repository.
- [19] M. Yu, A. Hillebrand, P. Tewarie, J. Meier, B. Dijk, P. Mieghem, and C. Stam, "Hierarchical clustering in minimum spanning trees," *Chaos (Woodbury, N.Y.)*, vol. 25, p. 023107, 02 2015.
- [20] S. Harenberg, G. Bello, L. Gjeltrema, S. Ranshous, J. Harlalka, R. Seay, K. Padmanabhan, and N. Samatova, "Community detection in large-scale networks: A survey and empirical evaluation," *Wiley Interdisciplinary Reviews: Computational Statistics*, vol. 6, 11 2014.
- [21] Apache Ant Project, "Apache Ant Concat Task Documentation," <https://ant.apache.org/manual/api/org/apache/tools/ant/taskdefs/Concat.html>, accessed on February 14, 2024.
- [22] V. Tzerpos and R. Holt, "Mojo: a distance metric for software clusterings," in *Sixth Working Conference on Reverse Engineering (Cat. No.PR00303)*, 1999, pp. 187–193.