


Loops, events og closure

Objekter, Arrays og DOM-manipulation

Agenda

- Objekter og arrays
- Fetch og JSON
- Loops
- Events og closure
- DOM-manipulation
- Specialisering af output

```
main.js
1 "use strict";
2
3 fetch("http://headlesscms.cederdorff.com/wp-json/wp/v2/posts?_embed")
4   .then(function(response) {
5     return response.json();
6   })
7   .then(function(json) {
8     appendPosts(json);
9   });
10
11 function appendPosts(posts) {
12   for (let post of posts) {
13     console.log(post);
14     document.querySelector("#grid-posts").innerHTML += `
15       <article>
16         <h3>${post.title.rendered}</h3>
17         <p>Email: <a href="mailto:${post.acf.email}">${post.acf.email}</a></p>
18         <p>Phone: ${post.acf.phone}</p>
19       </article>
20     `;
21   }
22 }
```



Men, hold det op imod,
hvad du kunne for 1
uge siden, 14 dage
eller 2 måneder...

Computer science student




Senior developer, 10+ years experience



<https://www.instagram.com/p/BxWAgatgSmn/>

Data

JavaScript, lister,
objekter, JSON, fetch,
DOM-manipulation og
meget mere...




The screenshot shows a browser window displaying a JSON array of three characters from Harry Potter. The array contains objects for Harry Potter, Hermione Granger, and Ron Weasley, each with various properties like name, species, gender, house, date of birth, year of birth, ancestry, eye colour, hair colour, wand, patronus, Hogwarts status, actor, and image URL.

```
[{"name": "Harry Potter", "species": "human", "gender": "male", "house": "Gryffindor", "dateOfBirth": "31-07-1980", "yearOfBirth": 1980, "ancestry": "half-blood", "eyeColour": "green", "hairColour": "black", "wand": "holly,phoenix feather,11", "patronus": "stag", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Daniel Radcliffe", "alive": true, "image": "http://hp-api.herokuapp.com/images/harry.jpg"}, {"name": "Hermione Granger", "species": "human", "gender": "female", "house": "Gryffindor", "dateOfBirth": "19-09-1979", "yearOfBirth": 1979, "ancestry": "muggleborn", "eyeColour": "brown", "hairColour": "brown", "wand": "vine,dragon heartstring", "patronus": "otter", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Emma Watson", "alive": true, "image": "http://hp-api.herokuapp.com/images/hermione.jpeg"}, {"name": "Ron Weasley", "species": "human", "gender": "male", "house": "Gryffindor", "dateOfBirth": "11-08-1980", "yearOfBirth": 1980, "ancestry": "pure-blood", "eyeColour": "brown", "hairColour": "red", "wand": "willow,mongoose hair,12", "patronus": "ewe", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Rupert Grint", "alive": true, "image": "http://hp-api.herokuapp.com/images/ron.jpg"}]
```

Hvordan viser vi denne JSON-data, så det giver mening for brugerne?

- Denne rette visualisering
- Generere HTML
- DOM-manipulation



The screenshot shows a browser window displaying JSON data for three characters: Harry Potter, Hermione Granger, and Ron Weasley. The data is presented in a hierarchical tree view, where each character is represented by a brace {}, and each character's properties are listed inside. The properties include name, species, gender, house, date of birth, year of birth, ancestry, eye colour, hair colour, wand material, patronus, Hogwarts status, staff status, actor, alive status, and image URL. The JSON is color-coded for readability, with green for strings and blue for booleans.

```
[{"name": "Harry Potter", "species": "human", "gender": "male", "house": "Gryffindor", "dateOfBirth": "31-07-1980", "yearOfBirth": 1980, "ancestry": "half-blood", "eyeColour": "green", "hairColour": "black", "wand": "holly,phoenix feather,11", "patronus": "stag", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Daniel Radcliffe", "alive": true, "image": "http://hp-api.herokuapp.com/images/harry.jpg"}, {"name": "Hermione Granger", "species": "human", "gender": "female", "house": "Gryffindor", "dateOfBirth": "19-09-1979", "yearOfBirth": 1979, "ancestry": "muggleborn", "eyeColour": "brown", "hairColour": "brown", "wand": "vine,dragon heartstring", "patronus": "otter", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Emma Watson", "alive": true, "image": "http://hp-api.herokuapp.com/images/hermione.jpeg"}, {"name": "Ron Weasley", "species": "human", "gender": "male", "house": "Gryffindor", "dateOfBirth": "11-12-1980", "yearOfBirth": 1980, "ancestry": "pureblood", "eyeColour": "brown", "hairColour": "red", "wand": "willow,mongoose hair,12", "patronus": "ewe", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Rupert Grint", "alive": true, "image": "http://hp-api.herokuapp.com/images/ron.jpg"}]
```

Fetch Persons

127.0.0.1:5503/fetch-persons-grid/index.html

Apps KEA DAT DAT.js IT Arkitektur EAAA BOOKS

Fetch Persons


 <p>Birgitte Kirk Iversen Senior Lecturer hki@mail.dk</p>	 <p>Martin Aagaard Nøhr Lecturer mnr@mail.dk</p>	 <p>Rasmus Cederdorff Senior Lecturer rnc@mail.dk</p>
 <p>Dan Okkels Brendstrup Lecturer dob@mail.dk</p>	 <p>Line Skjødt Senior Lecturer & Internship Coordinator lskj@mail.dk</p>	 <p>Kasper Fischer Topp Lecturer keto@mail.dk</p>
 <p>Anne Kirketerp Head of Department anki@mail.dk</p>	 <p>Maria Louise Bendixen Senior Lecturer mlbe@basa.dk</p>	 <p>Marlene Ahlgreen Jensen Senior Lecturer maj@basa.dk</p>

Forståelse for objekter og arrays

Programming knowledge

Backend & Frontend

Frontend (client)



<https://cederdorff.github.io/potter-app/>

JSON Data Source (Server)

A screenshot of a browser developer tools JSON viewer. It shows two tabs: "Raw" and "Parsed". The "Raw" tab displays the raw JSON data, and the "Parsed" tab displays the data as a hierarchical object. The JSON data represents the characters from the Harry Potter series, including their names, species, gender, house, birth dates, ancestry, eye and hair colors, wands, patronuses, Hogwarts status, actors, and images.

```
Raw Parsed  
[{"name": "Harry Potter", "species": "human", "gender": "male", "house": "Gryffindor", "dateOfBirth": "31-07-1980", "yearOfBirth": 1980, "ancestry": "half-blood", "eyeColour": "green", "hairColour": "black", "wand": "holly,phoenix feather,11", "patronus": "stag", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Daniel Radcliffe", "alive": true, "image": "http://hp-api.herokuapp.com/images/harry.jpg"}, {"name": "Hermione Granger", "species": "human", "gender": "female", "house": "Gryffindor", "dateOfBirth": "19-09-1979", "yearOfBirth": 1979, "ancestry": "muggleborn", "eyeColour": "brown", "hairColour": "brown", "wand": "vine,dragon heartstring", "patronus": "otter", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Emma Watson", "alive": true, "image": "http://hp-api.herokuapp.com/images/hermione.jpeg"}, {"name": "Ron Weasley", "species": "human", "gender": "male", "house": "Gryffindor", "dateOfBirth": "01-03-1980", "yearOfBirth": 1980, "ancestry": "pure-blood", "eyeColour": "blue", "hairColour": "red", "wand": "willow,unicorn tail-hair,14", "patronus": "Jack Russell terrier", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Rupert Grint", "alive": true, "image": "http://hp-api.herokuapp.com/images/ron.jpg"}]
```

<https://raw.githubusercontent.com/cederdorff/dat-js/main/data/potter.json>

Objects

A set of named values

Objects are used to store keyed
collections of various data



Containers for named values
called properties. A property
is a “key: value” pair


Objects

A set of named values

```
const user = {  
    name: "Alicia",  
    age: 6  
};
```

```
console.log(`${user.name} is ${user.age} years old.`);
```

user →



Alicia is 6 years old.

main.js:11

Hvad ser du?

The screenshot shows the KEA website's search interface. At the top, there's a navigation bar with links for 'For studerende', 'For ansatte', 'For alumner', 'Blog', 'Bibliotek', 'Job', and 'Kontakt'. Below the navigation is a red header bar with the KEA logo and links for 'UDDANNELSER', 'EFTERUDDANNELSER', 'FORSKNING OG UDVIKLING', 'SAMARBEJDE OG VIRKSOMHEDER', and 'OM KEA'. A language switcher 'EN' and a search icon are also in the header. The main content area has a breadcrumb trail 'FORSIDEN / FIND EN MEDARBEJDER'. A search form at the top has fields for 'DEL AF NAVN, E-MAIL ELLER TELEFON' containing 'RACE' and 'AFDELING' set to 'Alle'. Below the form is a placeholder image of a person. To its right, a card displays the profile of 'RASMUS CEDERDORFF' as a 'Lektor' at KEA Digital, with contact info: E: RACE@kea.dk, address: Guldbergsgade 29N, 2200 Copenhagen N, and a 'LÆS MERE' link.

This screenshot shows a detailed view of the search result for 'RASMUS CEDERDORFF'. The page title is 'FIND EN MEDARBEJDER'. The search form at the top is identical to the one in the first screenshot. Below it, a card displays the profile of 'RASMUS CEDERDORFF' as a 'Lektor' at KEA Digital. The card includes his photo, name, title, email (RACE@kea.dk), address (Guldbergsgade 29N, 2200 Copenhagen N), and a LinkedIn link (https://linkedin.com/in/cederdorff). A close button 'X' is visible in the top right corner of the card.


Hvad ser du?

The screenshot shows a web browser window with the URL kea.dk/find-medarbejder#qx-kea-phonebook-7910. The page title is "Find en medarbejder - Københavns Erhvervsakademi". The navigation bar includes links for "For studerende", "For ansatte", "For alumner", "Blog", "Bibliotek", "Job", and "Kontakt". A language switcher shows "EN" and a search icon. The main content area has a breadcrumb trail "FORSIDEN / FIND EN MEDARBEJDER" and a large heading "FIND EN MEDARBEJDER". Below this is a search form with fields for "DEL AF NAVN, E-MAIL ELLER TELEFON" (containing "RACE") and "AFDELING" (containing "Alle"). A search button labeled "Søg..." is present. To the right, there is a profile card for "RASMUS CEDERDORFF", showing a circular photo of a man with short hair and a beard, his name, title "Lektor", email "RACE@kea.dk", department "KEA Digital", address "Guldbergsgade 29N, 2200 København N", and a "LÆS MERE" link. At the bottom, there are footer sections for "KEA - KØBENHAVNS ERHVERVSAKADEMI", "OM OS", "FOR STUDERENDE", and "PRAKTISK INFO".

```
const race = {  
    name: "Rasmus Cederdorff",  
    position: "Lektor",  
    mail: "race@kea.dk",  
    department: "KEA Digital",  
    address: "Guldbergsgade 29N, 2200 København N",  
    image: "https://kea.dk/slir/w180-c1x1/images/us";  
};
```

NETFLIX


Hvem ser?



Personen der
rent faktisk
betaler for
profilen



Nasser 1



Nasser 2



Nasser 3



Nasser 4 Khader

[Administrer profiler](#)

● ○ ● | □ | < > ⌂ +

netflix.com

NETFLIX Start Serier Film Nyt og populært Min liste

N SERIE

TOO HOT TO HANDLE

TOP 10 Nr. 4 i Danmark i dag

På paradisets kyst mødes de lækkere singler og mingler. Men der er et tvist. For at vinde den attraktive pengepræmie, må de give afkald på at have sex.

Afspil Mere info

13+

Kun på Netflix

TOO HOT TO HANDLE NYE EPISODER

EMILY IN PARIS

QUEER EYE more than a makeover

The Woman in the House Across the Street From the Girl in the Window

BRIDGERTON NYE EPISODER

Se videre med profilen Nasser 1

the office

TIGER KING

Don't Look UP

JEFFREY EPSTEIN: FILTHY RICH

THE MIND explained

Frost II (2019) - IMDb

imdb.com/title/tt4520988/

IMDb Menu All Search IMDb

Frost II

Original title: Frozen II
2019 · 7 · 1h 43m

IMDb RATING YOUR RATING POPULARITY

★ 6.8/10 160K ★ Rate 896 ▲ 102

Cast & crew · User reviews · Trivia · IMDbPro 🔍 All topics | [Share](#)

+ Play trailer 0:16

55 VIDEOS

99+ PHOTOS

Animation Adventure Comedy

+ Add to Watchlist

Anna, Elsa, Kristoff, Olaf and Sven leave Arendelle to travel to an ancient, autumn-bound forest of an enchanted land. They set out to find the origin of Elsa's powers in order to save their kingdom.

1.4K User reviews 289 Critic reviews 64 Metascore

Directors Chris Buck · Jennifer Lee


Writers

```
let movie = {  
  title: "Frozen 2",  
  description: "Elsa the Snow Queen has a",  
  trailer: "https://www.youtube.com/embed",  
  length: "1h 43m",  
  year: "2019"  
}
```

Arrays

Collections

Ordered collection of values or
objects



An array is a way to hold more than one value at a time we have a 1st, a 2nd, a 3rd, a 4th element and so on.

Hvad ser du?

The screenshot shows a web browser window for the KEA website. The URL is kea.dk/find-medarbejder#qx-kea-phonebook-7910. The page title is "Find en medarbejder". The header includes the KEA logo and navigation links for students, staff, alumni, blog, library, jobs, and contact. A search bar at the top has fields for "DEL AF NAVN, E-MAIL ELLER TELEFON" and "AFDELING" (set to "KEA Digital"), with a "Søg..." button. Below the search bar, there are five circular profile pictures. The first three profiles have associated data:

Name	Position	Mail	Department	Address	Image
LARS BOGETOFT	Uddannelseschef	T: 51850497 M: 51850497 E: larb@kea.dk	KEA Digital	Guldbergsgade 29N 2200 København N	https://share.cederdorff.com/images/lars-bogetoft.jpg
MAGDALENA MARIA OTAP	Adjunktvikar	E: mago@kea.dk	KEA Digital	Guldbergsgade 29N 2200 København N	https://share.cederdorff.com/images/magdalena-maria-otap.jpg
OSKAR TUSKA	Adjunkt	E: ostu@kea.dk	KEA Digital	Guldbergsgade 29N 2200 København N	https://share.cederdorff.com/images/oskar-tuska.jpg

The last two profiles are placeholder icons.

```
const lecturers = [
  {
    name: "Peter Lind",
    position: "Lektor",
    mail: "petl@kea.dk",
    department: "KEA Digital",
    address: "Guldbergsgade 29N, 2200 København N",
    image: "https://share.cederdorff.com/images/peter-lind.jpg"
  },
  {
    name: "Rasmus Cederdorff",
    position: "Lektor",
    mail: "race@kea.dk",
    department: "KEA Digital",
    address: "Guldbergsgade 29N, 2200 København N",
    image: "https://kea.dk/slir/w180-c1x1/images/rasmus-cederdorff.jpg"
  }
];
```

Hvad ser du?

CRUD App



Lars Bogetoft
Head of Education
lrb@kea.dk

UPDATE **DELETE**



Peter Lind
Senior Lecturer
petl@kea.dk

UPDATE **DELETE**



Magdalena "Lenka" Otap
Lecturer
mago@kea.dk

UPDATE **DELETE**



Rasmus Cederdorff
Senior Lecturer
race@kea.dk




UPDATE **DELETE**


Create a new User

CREATE USER

Update User

<https://cederdorff.github.io/dat-js-crud-intro/>





Name	Headers	Payload	Preview	Response	Initiator	Timing	Cookies
□ ?modules=PolarisBD...							
□ ?content_type=PROF...							
□ ?username=keacph							
□ reels_tray/							
□ timeline/							
□ ig_sso_users/							
□ logging_client_events							
□ bz?__d=dis							
□ falco							
□ bz?__a=1&__ccg=G...							
□ batch_fetch_web/							
□ get_encrypted_crede...							
□ highlights_tray/							
□ ?target_user_id=140...							
□ badge/							
□ story/							
□ bulk-route-definitions/							
□ bulk-route-definitions/							
□ ?query_hash=69cba4...							
□ bz?__a=1&__ccg=G...							
□ bz?__a=1&__ccg=G...							
□ bulk-route-definitions/							
□ bz?__a=1&__ccg=G...							
□ logging_client_events							
□ bz?__d=dis							

Objects? Arrays?

The screenshot shows the homepage of DR Nyheder. At the top, there are navigation links for NYHEDER, DRTV, and DR LYD. Below the navigation, there are six thumbnail cards for TV shows: DR1: Løvens Hule, DR3: Nationens stærkeste, P1: LSD kælderen, DR LYD: Annas Margrethe, DR3: Du fucker med de forkerte, and A Very British Scandal. Under these, a section titled "Seneste nyt" (Latest news) displays three news items: "EU klager over Kinas hårde kurs over for Litauen" (5 MIN. SIDEN), "Børn og skoleelever opfordres stadig til to ugentlige coronatest" (13 MIN. SIDEN), and "England skrætter størstedelen af coronarestriktionerne fra i dag" (25 MIN. SIDEN). The main content area features a large image of medical supplies (a mask, a thermometer, a syringe, and a bottle of hand sanitizer) against a blue background, with the text "15 lande bakker Danmark op: Danske soldater skal blive i Mali" overlaid. At the bottom, a red banner reads "Regeringen har meldt genåbning - men ikke".

The screenshot shows the "ALLE ERHVERVSAKADEMI-UDDANNELSER" (All Business Academy Programs) page. At the top, there are two navigation links: "ALLE UDDANNELSER" and "UDDANNELSER UD FRA INTERESSE". Below this, a grid of 12 program cards, each featuring a student's face and the program name. The programs are: AUTOMATIONSTEKNOLOG (Automation Technologist), BYGGEKOORDINATOR (Construction Coordinator), BYGGETEKNIKER (Building Technician), DATAMATIKER (Computer Science), DESIGNTEKNOLOG (Design Technologist), ENTREPRENØRSKAB OG DESIGN (Entrepreneurship and Design), EL-INSTALLATOR (Electrical Installer), ENERGITEKNOLOG (Energy Technologist), IT-TEKNOLOG (IT Technologist), KORT- OG LANDMÅLING (Surveying and Land Measurement), MULTIMEDIEDESIGNER (Multimedia Designer), and PRODUKTIONSTEKNOLOG (Production Technologist). Each card has a small arrow icon pointing to the right.

It's all objects &
arrays!

Data Types & Data Structures

Objects & Arrays

fetch(...)

HTTP Requests in
JavaScript.

A way to get and post data
from and to data sources.

```
// fetch with callbacks
fetch("https://cederdorff.github.io/web-frontend/callback.js")
  .then(function (response) {
    return response.json();
  })
  .then(function (data) {
    console.log(data);
  });
// or with promises
const response = fetch("https://cederdorff.github.io/web-frontend/promise.js");
const data = response.json();
console.log(data);
```

fetch(...)

HTTP Requests in
JavaScript.


A way to get and post data
from and to data sources.

getCharacters fetches a list of characters
from a JSON data source, parses the JSON
to JS and returns the data.


```
async function getCharacters() {  
  const response = await fetch(url);  
  const data = await response.json();  
  console.log(data);  
  return data;  
}
```

Client-Server Model


Communication between web **clients** and web **servers**.



Fetch, HTTP Request & Response



Fetch, HTTP Request & Response




fetch(...)

Og Potter App

Løsning

Kode



fetch(...) og “call stack”

1) initApp kaldes på load.

2) initApp kalder getCharacters og gemmer hvad der returneres i const'en characters. initApp er async, da den venter på getCharacters' returneret data fra et fetch-kald.

3) getCharacters er en async funktion, da der anvendes await inde i funktionen. Funktionen fetcher data fra en given url. Data parses fra JSON til JavaScript-array, der gemmes i data-variablen. data returneres, så det kan læses hvor funktionen kaldes.

4) initApp kalder nu showCharacters med characters som argument (parameter). characters holder den data, som returneres fra getCharacters i 3).

5) showCharacters har characterList som parameter. characterList holder den data som blev sendt med fra initApp, dvs at det er samme data som lå i characters i initApp og tidligere i data i getCharacters.

showCharacters loop'er igennem characterList. For hver character (objekt) i characterList (array) kaldes showCharacter.

6) showCharacter tager en character (et objekt) som parameter og genererer HTML med værdier fra character-objektets properties. HTML'en tilføjes med insertAdjacentHTML.

```
JS app.js    x JS app.js > ...
4
5 window.addEventListener("load", initApp); 1)
6
7 async function initApp() {
8     const characters = await getCharacters(); 2)
9     showCharacters(characters); 4)
10 }
11
12 // ===== READ ===== //
13 // Read (GET) characters from json file located on GitHub
14 async function getCharacters() {
15     const response = await fetch("https://raw.githubusercontent.com/cederdorff/characters.json");
16     const data = await response.json(); 3)
17     console.log(data);
18     return data;
19 }
20
21 // Create HTML and display all users from given list
22 function showCharacters(characterList) {
23     //loop through all users and create an article with content for each
24     for (const character of characterList) {
25         showCharacter(character); 5)
26     }
27 }
28
29 function showCharacter(character) {
30     document.querySelector("#characters").insertAdjacentHTML( 6)
31         "beforeend",
32         /*html*/
33         <article class="grid-item">
34             
35             <h2>${character.name}</h2>
36             <p>${character.house}</p>
37         </article>
Ln 1, Col 14  Spaces: 4  UTF-8  LF  {}  JavaScript  ⚡ Port : 5500  ✓ Prettier  ⌂  ⌂
```

fetch(...) og “call stack”

7) showCharacter tilføjer click-event til senest tilføjede article. Derfor article:last-child. Dette matcher med, at der i 6) anvendes “beforeend” som position til at indsætte.

8) Click-eventet er characterClicked, der er en nested function i showCharacter. Det er en nested function, da vi har brug for at kunne læse character og sende det med som argument (parameter) til showCharacterModal. På denne måde svarer character altid til den karakter, der bliver klikket på.

9) showCharacterModal tager character som parameter. character er netop den, vi klikker på. showCharacterModal bruger værdierne i character-objektet til at foretage DOM-manipulationen og opdatere de eksisterende HTML-elementer.

10) I showCharacterModal kaldes generateDescription, der er en hjælpefunktion.

11) generateDescription genererer en beskrivelse på baggrund af character objektets properties hogwartsStaff, hogwartsStudent, alive og name. Beskrivelsen returneres tilbage til showCharacterModal og vises.

12) Når alle informationer i dialog er sat med DOM-manipulation og .textContent, vises dialog'en med metoden .showModal().

The screenshot shows a code editor window with the file 'app.js' open. The code is a JavaScript application for displaying character information from the Harry Potter series. The code includes functions for showing characters, handling clicks, generating descriptions, and displaying modals. Numbered annotations (6 through 12) are placed next to specific lines of code to explain certain parts of the logic:

- Annotation 6 points to the 'beforeend' position in the DOM insertion code.
- Annotation 7 points to the event listener registration on the 'characters' element.
- Annotation 8 points to the nested function 'characterClicked'.
- Annotation 9 points to the 'showCharacterModal' function call.
- Annotation 10 points to the 'generateDescription' function call.
- Annotation 11 points to the 'generateDescription' function definition.
- Annotation 12 points to the 'showModal' method call on the modal element.

```
JS app.js x
JS app.js > ...
29  function showCharacter(character) {
30      document.querySelector("#characters").insertAdjacentHTML(
31          "beforeend",
32          /*html*/
33          <article class="grid-item">
34              
35              <h2>${character.name}</h2>
36              <p>${character.house}</p>
37          </article>
38      );
39  }
40
41  document.querySelector("#characters article:last-child").addEventListener("click", characterClicked);
42
43  function characterClicked() {
44      showCharacterModal(character);
45  }
46
47
48  function showCharacterModal(character) { 9)
49      console.log(character);
50      document.querySelector("#dialog-image").src = character.image;
51      document.querySelector("#dialog-title").textContent = character.name;
52      document.querySelector("#dialog-house").textContent = character.house;
53
54      // description
55      let description = generateDescription(character); 10)
56      document.querySelector("#dialog-character-description").textContent = description;
57
58      document.querySelector("#dialog-gender").textContent = character.gender;
59      document.querySelector("#dialog-birth-date").textContent = character.dateOfBirth;
60      document.querySelector("#dialog-eye-color").textContent = character.eyeColour;
61      document.querySelector("#dialog-hair-color").textContent = character.hairColour;
62      document.querySelector("#dialog-ancestry").textContent = character.ancestry;
63      document.querySelector("#dialog-species").textContent = character.species;
64
65      document.querySelector("#dialog-name").textContent = character.name;
66      document.querySelector("#dialog-actor-name").textContent = character.actor;
67
68      // show dialog
69      document.querySelector("#dialog-character").showModal(); 12
70  }
71
72  function generateDescription(character) { 11)
73      let description = "";
74      if (character.hogwartsStaff && character.alive) {
75          description = `${character.name} is employed at Hogwarts.`;
76      } else if (character.hogwartsStaff && !character.alive) {
77          description = `${character.name} was employed at Hogwarts but is no longer alive.`;
78      } else if (character.hogwartsStudent && character.alive) {
79          description = `${character.name} is a student at Hogwarts.`;
80      } else if (character.hogwartsStudent && !character.alive) {
81          description = `${character.name} was a student at Hogwarts but is no longer alive.`;
82      }
83  }
```

JSON

... a syntax for storing and exchanging data over the web


```
{  
  "name": "Alicia",  
  "age": 6  
}
```

JSON OBJECT

```
[{  
  "name": "Alicia",  
  "age": 6  
, {  
  "name": "Peter",  
  "age": 22  
}]
```

LIST OF JSON OBJECTS

JSON




A screenshot of a web browser window displaying a single JSON object. The URL is <https://raw.githubusercontent.com/cederdorff/dat-js/master/data/harry.json>. The JSON structure is as follows:

```
{  
  "name": "Harry Potter",  
  "species": "human",  
  "gender": "male",  
  "house": "Gryffindor",  
  "dateOfBirth": "31-07-1980",  
  "yearOfBirth": 1980,  
  "ancestry": "half-blood",  
  "eyeColour": "green",  
  "hairColour": "black",  
  "wand": "holly,phoenix feather,11",  
  "patronus": "stag",  
  "hogwartsStudent": true,  
  "hogwartsStaff": false,  
  "actor": "Daniel Radcliffe",  
  "alive": true,  
  "image": "http://hp-api.herokuapp.com/images/harry.jpg"  
}
```

The JSON is displayed in two tabs: "Raw" and "Parsed". The "Parsed" tab shows the JSON structure with color-coded keywords (e.g., "name", "species", "gender") and values.

JSON OBJECT



A screenshot of a web browser window displaying a list of three JSON objects. The URL is <https://raw.githubusercontent.com/cederdorff/dat-js/master/data/characters.json>. The JSON structure is as follows:

```
[  
  {  
    "name": "Harry Potter",  
    "species": "human",  
    "gender": "male",  
    "house": "Gryffindor",  
    "dateOfBirth": "31-07-1980",  
    "yearOfBirth": 1980,  
    "ancestry": "half-blood",  
    "eyeColour": "green",  
    "hairColour": "black",  
    "wand": "holly,phoenix feather,11",  
    "patronus": "stag",  
    "hogwartsStudent": true,  
    "hogwartsStaff": false,  
    "actor": "Daniel Radcliffe",  
    "alive": true,  
    "image": "http://hp-api.herokuapp.com/images/harry.jpg"  
  },  
  {  
    "name": "Hermione Granger",  
    "species": "human",  
    "gender": "female",  
    "house": "Gryffindor",  
    "dateOfBirth": "19-09-1979",  
    "yearOfBirth": 1979,  
    "ancestry": "muggleborn",  
    "eyeColour": "brown",  
    "hairColour": "brown",  
    "wand": "vine,dragon heartstring",  
    "patronus": "otter",  
    "hogwartsStudent": true,  
    "hogwartsStaff": false,  
    "actor": "Emma Watson",  
    "alive": true,  
    "image": "http://hp-api.herokuapp.com/images/hermione.jpeg"  
  },  
  {  
    "name": "Ron Weasley",  
    "species": "human",  
    "gender": "male",  
    "house": "Gryffindor",  
    "dateOfBirth": "01-03-1980",  
    "yearOfBirth": 1980,  
    "ancestry": "pure-blood",  
    "eyeColour": "blue",  
    "hairColour": "red",  
    "wand": "willow,unicorn tail-hair,14",  
  }  
]
```

The JSON is displayed in two tabs: "Raw" and "Parsed". The "Parsed" tab shows the JSON structure with color-coded keywords (e.g., "name", "species", "gender") and values.

LIST OF JSON OBJECTS



<https://www.instagram.com/p/CVqbCzgsZUF/>

JSON

The diagram illustrates the relationship between a piece of JavaScript code and its corresponding JSON data. On the left, a screenshot of a code editor shows a file named `app.js` with the following code:

```
28
29  function showCharacter(character) {
30      document.querySelector("#characters").insertAdjacentHTML(
31          "beforeend",
32          /*html*/
33          `

34              
35              <h2>${character.name}</h2>
36              <p>${character.house}</p>
37          </article>
38      `);
39  }
40 }


```

On the right, a screenshot of a web browser window displays a JSON object at the URL `https://raw.githubusercontent.com`. The JSON data is as follows:

```
[{"name": "Harry Potter", "species": "human", "gender": "male", "house": "Gryffindor", "dateOfBirth": "31-07-1980", "yearOfBirth": 1980, "ancestry": "half-blood", "eyeColour": "green", "hairColour": "black", "wand": "holly,phoenix feather,11", "patronus": "stag", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Daniel Radcliffe", "alive": true, "image": "http://hp-api.herokuapp.com/images/harry.jpg"}, {"name": "Hermione Granger", "species": "human", "gender": "female", "house": "Gryffindor", "dateOfBirth": "19-09-1979", "yearOfBirth": 1979, "ancestry": "muggleborn", "eyeColour": "brown", "hairColour": "brown", "wand": "vine,dragon heartstring", "patronus": "otter", "hogwartsStudent": true}]
```

Red arrows point from the `character` variable in the `showCharacter` function to the `name`, `image`, and `house` fields of the first character object in the JSON array.

Review JSON-objekt

Det er vigtigt at vores properties matcher med det forventede! Det skal matche med den datamodel vi er blevne enige om: <https://cederdorff.github.io/dat-js/05-data/>

- Kontroller:

 - Values - er der værdier i properties? Se hvilke [her](#).
 - Navngivning af properties - ja også store og små bogstaver  Se navngivning [her](#).
 - Er det den rigtige datatype? Brug dem vi er blevet enige om - se [her](#). Det må fx ikke være et array, hvis vi er blevet enige om en kommasepareret tekststreng.
 - Dobbeltjek properties og values matcher med: <https://cederdorff.github.io/dat-js/05-data/>
 - Din billed url. Er det et billede? Kontroller i browser. Du skal højeklikke på billede og vælge “Copy Image Address” eller “Copy Image Link” - ikke bare “Copy Link”.
 - Valider din JSON. Se mere [her](#): [Validering af JSON](#)
 - Foretag tilpasninger af dit JSON-objekt (fra sidste uge), ikke noget med et array. Commit og push, så vi kan få de tilrettede objekter med.

Raw Parsed

```
[{"name": "Harry Potter", "species": "human", "gender": "male", "house": "Gryffindor", "dateOfBirth": "31-07-1980", "yearOfBirth": 1980, "ancestry": "half-blood", "eyeColour": "green", "hairColour": "black", "wand": "holly,phoenix feather,11", "patronus": "stag", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Daniel Radcliffe", "alive": true, "image": "http://hp-api.herokuapp.com/images/harry.jpg"}, {"name": "Hermione Granger", "species": "human", "gender": "female", "house": "Gryffindor", "dateOfBirth": "19-09-1979", "yearOfBirth": 1979, "ancestry": "muggleborn", "eyeColour": "brown", "hairColour": "brown", "wand": "vine,dragon heartstring", "patronus": "otter", "hogwartsStudent": true, "hogwartsStaff": false}], [{"name": "Ronald Weasley", "species": "human", "gender": "male", "house": "Gryffindor", "dateOfBirth": "11-07-1980", "yearOfBirth": 1980, "ancestry": "pureblood", "eyeColour": "blue", "hairColour": "red", "wand": "willow,dragon heartstring,12", "patronus": "ewe", "hogwartsStudent": true, "hogwartsStaff": false, "actor": "Rupert Grint"}]
```

Loops

Iterate over arrays or other iterable objects.

Ex loop through an array of objects.

```
// .forEach
characterList.forEach(showCharacter);

// for of loop
for (const character of characterList) {
    showCharacter(character);
}

// for loop
for (let index = 0; index < characterList.length; index++) {
    const character = characterList[index];
    showCharacter(character);
}
```

.forEach

an array method

```
const names = ["Peter", "Lenka", "Oskar", "Rasmus"];
names.forEach(showNames);

function showNames(name) {
  console.log(name);
}
```

You can use it on an array to do *something* for each element in the array.

forEach will call a function for each element in an array.

For of Loop

```
const names = ["Peter", "Lenka", "Oskar", "Rasmus"];
for (const name of names) {
  console.log(name);
}
```

You can use it to loop over an array to do *something* for every element.

for of loops through the values of an iterable object (an array is an iterable object).

For of loop

Iterates over arrays or other iterable objects

<https://scrimba.com/learn/introductiontojavascript/for-loops-cMMM8U9>

<https://scrimba.com/learn/introductiontojavascript/challenge-for-loops-cPkpJrcv>

For Loop

```
const names = ["Peter", "Lenka", "Oskar", "Rasmus"];

for (let index = 0; index < names.length; index++) {
  const name = names[index];
  console.log(name);
}
```

You can use it to loop over an array.

A for loop repeats until a specified condition is false.

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Guide/Loops_and_iteration#for_statement


<https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Statements/for>

https://www.w3schools.com/js/js_loop_for.asp

Loops

Even more options 🎉


But use `forEach` or
`for of` for now.



JavaScript supports different kinds of loops:

- `for` - loops through a block of code a number of times
- `for/in` - loops through the properties of an object
- `for/of` - loops through the values of an iterable object
- `while` - loops through a block of code while a specified condition is true
- `do/while` - also loops through a block of code while a specified condition is true


https://www.w3schools.com/js/js_loop_for.asp



Events
and
closure

EventListener

The eventListener attaches an event handler to the specified element




```
document.querySelector("#characters article:last-child")  
.addEventListener("click", characterClicked);
```

```
function characterClicked() {  
    // do something  
}
```

EventListener

Vi tilføjer event for hver article som vi indsætter i DOM'en




```
function showCharacter(character) {  
    document.querySelector("#characters").insertAdjacentHTML(  
        "beforeend",  
        /*html*/ `'  
            <article class="grid-item">  
                  
                <h2>${character.name}</h2>  
                <p>${character.house}</p>  
            </article>  
        );  
  
    document.querySelector("#characters article:last-child").addEventListener("click", characterClicked);  
}
```

https://www.w3schools.com/js/js_htmldom_events.asp

https://www.w3schools.com/js/js_eventlistener.asp

Nested functions & closure

Men vi skal kende character, for at kunne vise
lige præcis den character vi klikker på.




```
function showCharacter(character) {
  document.querySelector("#characters").insertAdjacentHTML(
    "beforeend",
    /*html*/
    `<article class="grid-item">
      
      <h2>${character.name}</h2>
      <p>${character.house}</p>
    </article>
  );
}

document.querySelector("#characters article:last-child").addEventListener("click", characterClicked);

function characterClicked() {
  showCharacterModal(character);
}
```

Nested functions & closure

Derfor har vi en funktion i en funktion. Så vil characterClicked (nested function) have adgang til showCharacter's scope, og der ved kan vi læse character



```
function showCharacter(character) {
  document.querySelector("#characters").insertAdjacentHTML(
    "beforeend",
    /*html*/
    <article class="grid-item">
      
      <h2>${character.name}</h2>
      <p>${character.house}</p>
    </article>
  );
}

document.querySelector("#characters article:last-child").addEventListener("click", characterClicked);

function characterClicked() {
  showCharacterModal(character);
}

}
```

Nested function

A function inside a function.

All functions have access to the global scope.

Nested functions have access to the scope "above" them.

Closure

A closure is a function that have access to the parent scope - also after the parent function has closed / has been executed.

```
function showCharacter(character) {  
    document.querySelector("#characters").insertAdjacentHTML(  
        "beforeend",  
        /*html*/ `'  
            <article class="grid-item">  
                  
                <h2>${character.name}</h2>  
                <p>${character.house}</p>  
            </article>  
        );  
  
    document.querySelector("#characters article:last-child").addE  
};  
  
function characterClicked() {  
    showCharacterModal(character);  
}  
}
```

DOM Manipulation

“

When you use JavaScript to
add, remove, and modify
elements of a website

”

- document.querySelector(selector)
- document.querySelectorAll(name)
- document.createElement(name)
- parentNode.appendChild(node)
- element.append(node, node, ...)
- element.insertAdjacentHTML(position, html)
- element.innerHTML
- element.textContent
- element.style.xxx
- element.setAttribute()
- element.getAttribute()
- element.addEventListener()
- element.classList
- window.content
- Window.onload
- window.scrollTo()

Methods for DOM Manipulation

Common Methods

Vi har anvendt to metoder

```
// .createElement and .appendChild  
const title = document.createElement("h1");  
title.textContent = "Hi!";  
document.querySelector("body").appendChild(title);  
  
// backticks and .insertAdjacentHTML  
const html = /*html*/ `<h1>Hi, again!</h1>`;  
document.querySelector("body").insertAdjacentHTML("beforeend", html);
```

```
// .textContent - you must have a h1 element in your html  
document.querySelector("h1").textContent = "Hi, again, again!";
```

1. Byg ny HTML og tilføj til DOM/ eksisterende HTML-element.
2. Ændr indhold på eksisterende HTML-elementer.

DOM Manipulation

```
let fullName = "Peter Lind";
console.log(fullName);
document.querySelector("#fullName_container").textContent = fullName;
```

.textContent

Get or set the text content of a given (HTML) element

.textContent

Get or set the text content of a given (HTML) element. The element **must** be in the DOM.


```
let fullName = "Peter Lind";
console.log(fullName);
document.querySelector("#fullName_container").textContent = fullName;
```

```
<body>
  <header>
    <h1 id="fullName_container"></h1>
  </header>
  <script src="app.js"></script>
</body>
```



.textContent

Get or set the text content of a given (HTML) element. The element **must** be in the DOM.



The diagram illustrates the data flow between the `app.js` file and the `index.html` file. Red arrows connect the code snippets in `app.js` to the corresponding HTML elements in `index.html`.

app.js:

```
function showCharacterModal(character) {
    console.log(character);
    document.querySelector("#dialog-image").src = character.image;
    document.querySelector("#dialog-title").textContent = character.name;
    document.querySelector("#dialog-house").textContent = character.house;

    // description
    let description = generateDescription(character);
    document.querySelector("#dialog-character-description").textContent = description;

    document.querySelector("#dialog-gender").textContent = character.gender;
    document.querySelector("#dialog-birth-date").textContent = character.dateOfBirth;
    document.querySelector("#dialog-eye-color").textContent = character.eyeColour;
    document.querySelector("#dialog-hair-color").textContent = character.hairColour;
    document.querySelector("#dialog-ancestry").textContent = character.ancestry;
    document.querySelector("#dialog-species").textContent = character.species;

    document.querySelector("#dialog-name").textContent = character.name;
    document.querySelector("#dialog-actor-name").textContent = character.actor;

    // show dialog
    document.querySelector("#dialog-character").showModal();
}
```

index.html:

```
<dialog id="dialog-character">
    <section class="dialog-grid">
        <figure></h2>
            <h3 id="dialog-house"></h3>
            <p id="dialog-character-description"></p>
            <section>
                <h4>Personal Info</h4>
                <ul>
                    <li>Gender: <span id="dialog-gender"></span></li>
                    <li>Birth Date: <span id="dialog-birth-date"></span></li>
                    <li>Eye Color: <span id="dialog-eye-color"></span></li>
                    <li>Hair Color: <span id="dialog-hair-color"></span></li>
                    <li>Ancestry: <span id="dialog-ancestry"></span></li>
                    <li>Species: <span id="dialog-species"></span></li>
                </ul>
            </section>
            <section>
                <h4>Actor</h4>
                <p><span id="dialog-name">Character</span> is played by <span id=
                    <span id="dialog-name"></span></p>
            </section>
        </article>
    </section>
</dialog>
```

document.createElement()

```
// create a new h1 element
const newTitle = document.createElement("h1");

// and give it some content
newTitle.textContent = "Hi there and greetings!";

// add the newly created element into the DOM
document.querySelector("body").appendChild(newTitle);
```

.createElement

Creates an HTML element specified by tagName.

.appendChild

Appends an element as last child of an element.

insertAdjacentHTML(position, html)

```
// 1

// create a new h1 with content using a backtick
const newTitle = /*html*/ `<h1>Hi there and greetings!</h1>`;

// add the newly created element into the DOM
document.querySelector("body").insertAdjacentHTML("beforeend", newTitle);

// 2

// variable holding username
const username = "RACE";

// create a new p with content using a backtick and username variable
const newParagraph = /*html*/ `<p>Welcome, ${username}!</p>`;

// add the newly created element into the DOM
document.querySelector("body").insertAdjacentHTML("beforeend", newParagraph);
```

Backtick string

Create multiline strings (templates) with embedded expressions and tags.

.insertAdjacentHTML

Inserts HTML into a specified position.

showCharacter(character)

```
function showCharacter(character) {  
    document.querySelector("#characters").insertAdjacentHTML(  
        "beforeend",  
        /*html*/ `   
            <article class="grid-item">  
                  
                <h2>${character.name}</h2>  
                <p>${character.house}</p>  
            </article>  
        ` );  
}
```

Backtick string

Create multiline strings (templates) with embedded expressions and tags.

.insertAdjacentHTML

Inserts HTML into a specified position.

Hvorfor ikke .innerHTML?

```
function showCharacter(character) {  
  document.querySelector("#characters").innerHTML = /*html*/`  
    <article class="grid-item">  
        
      <h2>${character.name}</h2>  
      <p>${character.house}</p>  
    </article>  
`;  
}
```

Backtick string

Create multiline strings (templates) with embedded expressions and tags.

.innerHTML

... sets or returns the HTML content (inner HTML) of an element.

“To insert the HTML into the document rather than replace the contents of an element, use the method `insertAdjacentHTML()`.”

.innerHTML & events

```
function showCharacter(character) {  
  document.querySelector("#characters").innerHTML = /*html*/ `   
    <article class="grid-item">  
        
      <h2>${character.name}</h2>  
      <p>${character.house}</p>  
    </article>  
  `;  
  
  document.querySelector("#characters article:last-child").addEventListener("click", characterClicked);  
  
  function characterClicked() {  
    showCharacterModal(character);  
  }  
}
```

Backtick string

Create multiline strings (templates) with embedded expressions and tags.

.innerHTML

“Please note that using innerHTML to append HTML elements [...] will result in the removal of any previously set event listeners. That is, after you append any HTML element that way you won't be able to listen to the previously set event listeners.”

https://www.w3schools.com/jsref/prop_html_innerhtml.asp

<https://developer.mozilla.org/en-US/docs/Web/API/Element/innerHTML>

Which one?

```
// backticks and .insertAdjacentHTML
const html = /*html*/ `<h1>Hi, again!</h1>`;
document.querySelector("body").insertAdjacentHTML("beforeend", html);

// .textContent – you must have a h1 element in your html
const title = "Hi, again, again!";
document.querySelector("h1").textContent = title;
```

.insertAdjacentHTML

Inserts HTML into a specified position.

.textContent

Get or set the text content of a given (HTML) element

Which one?

.insertAdjacentHTML

```
function showCharacter(character) {
  document.querySelector("#characters").insertAdjacentHTML(
    "beforeend",
    /*html*/
    `<article class="grid-item">
      
      <h2>${character.name}</h2>
      <p>${character.house}</p>
    </article>
  `;
}
//...
```

.textContent

```
function showCharacterModal(character) {
  console.log(character);
  document.querySelector("#dialog-image").src = character.image;
  document.querySelector("#dialog-title").textContent = character.name;
  document.querySelector("#dialog-house").textContent = character.house;

  // description
  let description = generateDescription(character);
  document.querySelector("#dialog-character-description").textContent = description;

  document.querySelector("#dialog-gender").textContent = character.gender;
  document.querySelector("#dialog-birth-date").textContent = character.dateOfBirth;
  document.querySelector("#dialog-eye-color").textContent = character.eyeColour;
  document.querySelector("#dialog-hair-color").textContent = character.hairColour;
  document.querySelector("#dialog-ancestry").textContent = character.ancestry;
  document.querySelector("#dialog-species").textContent = character.species;

  document.querySelector("#dialog-name").textContent = character.name;
  document.querySelector("#dialog-actor-name").textContent = character.actor;

  // show dialog
  document.querySelector("#dialog-character").showModal();
}
```

Specialisering af output

“

Hmm, det handler vel om at vise
det “rigtige”, og det der giver
bedst mening for brugeren.

”

Hvis du ikke kendte til programmering?

A screenshot of a web browser window titled "Harry Potter Characters". The URL in the address bar is "127.0.0.1:5500/index.html". The main content area displays a character card for Hermione Granger. The card features a portrait of Emma Watson as Hermione Granger. The title "Hermione Granger" is displayed above her name, which is bolded. Below the title is the house "Gryffindor". A descriptive text states: "Hermione Granger is a student at Hogwarts." Under the heading "Personal Info", there is a bulleted list of her characteristics: Gender: female, Birth Date: 19-09-1979, Eye Color: brown, Hair Color: brown, Ancestry: muggleborn, Species: human. Below this section is the heading "Actor" followed by the text: "Hermione Granger is played by Emma Watson." At the bottom of the card is a "CLOSE" button.

A screenshot of a web browser window titled "Harry Potter Characters". The URL in the address bar is "127.0.0.1:5500/index.html". The main content area displays a character card for Hermione Granger. The card features a portrait of Emma Watson as Hermione Granger. The title "Hermione Granger" is displayed above her name, which is bolded. Below the title is the house "Gryffindor". To the right of the title, there is a JSON object containing her details: { "Hogwarts Student": true, "Hogwarts Staff": false, "Is alive": true }. Below this is the heading "Personal Info" followed by a bulleted list of her characteristics: Gender: female, Birth Date: 19-09-1979, Eye Color: brown, Hair Color: brown, Ancestry: muggleborn, Species: human. Below this section is the heading "Actor" followed by the text: "Hermione Granger is played by Emma Watson." At the bottom of the card is a "CLOSE" button.


```
function showCharacterModal(character) {  
    console.log(character);  
    //...  
  
    // description  
    let description = generateDescription(character);  
    document.querySelector("#dialog-character-description").textContent = description;  
  
    //...  
  
    // show dialog  
    document.querySelector("#dialog-character").showModal();  
}
```

Returns the right description,
based on conditions

Calls helper function

```
function generateDescription(character) {  
    let description = "";  
  
    if (character.hogwartsStaff && character.alive) {  
        description = `${character.name} is employed at Hogwarts.`;  
    } else if (character.hogwartsStaff && !character.alive) {  
        description = `${character.name} was employed at Hogwarts but is no longer alive.`;  
    } else if (character.hogwartsStudent && character.alive) {  
        description = `${character.name} is a student at Hogwarts.`;  
    } else if (character.hogwartsStudent && !character.alive) {  
        description = `${character.name} was a student at Hogwarts but is no longer alive.`;  
    }  
  
    return description;  
}
```

Forbedringer



- Er der informationer, vi gerne vil vise på en anden måde, illustrere, tilpasse osv?

Specialisering af styling

Hvad nu, hvis du vil differentiere stylingen af dine grid-elementer og/eller dialog?


Specialisering af output og styling

The image displays seven screenshots of a Harry Potter-themed application interface, illustrating various levels of output specialization and styling:

- Character List View:** Shows a grid of 12 characters with their names and house affiliations. The background color of each row corresponds to a house: Gryffindor (red), Slytherin (green), Hufflepuff (yellow), and Ravenclaw (blue).
- Cho Chang Profile:** A detailed profile for Cho Chang, a Ravenclaw student. It includes a portrait, her house crest, and descriptive text: "a student at Hogwarts", "human | female |", and "type: hawthorn, core: unicorn tail-hair, length: 10\". It also notes her birthday (approx. 2023) and her actor (Katie Leung).
- Minerva McGonagall Profile:** A detailed profile for Minerva McGonagall, a Gryffindor teacher. It includes a portrait, her house crest, and descriptive text: "a teacher at Hogwarts", "human | female |", and "type: ash, core: unicorn hair, length: 12.25\". It also notes her birthday (04-10-1925) and her actor (Dame Maggie Smith).
- Cedric Diggory Profile:** A detailed profile for Cedric Diggory, a Hufflepuff student. It includes a portrait, his house crest, and descriptive text: "a student at Hogwarts", "human | male |", and "type: hawthorn, core: unicorn tail-hair, length: 10\". It also notes his birthday (approx. 1977) and his actor (Robert Pattinson).
- Draco Malfoy Profile:** A detailed profile for Draco Malfoy, a Slytherin student. It includes a portrait, his house crest, and descriptive text: "a student at Hogwarts", "human | male | pure-blood", and "type: hawthorn, core: unicorn tail-hair, length: 10\". It also notes his birthday (05-06-1980) and his actor (Tom Felton).
- Character Card View:** A view showing character cards for Harry Potter, Hermione Granger, Ron Weasley, and Luna Lovegood. Each card includes a small portrait and the text "Gryffindor".
- Character Card View:** A view showing character cards for Harry Potter, Hermione Granger, Ron Weasley, and Neville Longbottom. Each card includes a small portrait and the text "Gryffindor".

class på grid-element



```
function showCharacter(character) {
  document.querySelector("#characters").insertAdjacentHTML(
    "beforeend",
    /*html*/
    <article class="grid-item ${character.house.toLowerCase()}">
      
      <h2>${character.name}</h2>
      <p>${character.house}</p>
    </article>
  );
}
```



```
<!DOCTYPE html>
<html lang="en">
  <head> ... </head>
  <body>
    <header> ... </header>
    <main>
      <section id="characters" class="grid-container" style="grid = $0">
        <article class="grid-item gryffindor"> ... </article>
        <article class="grid-item gryffindor"> ... </article>
        <article class="grid-item gryffindor"> ... </article>
        <article class="grid-item slytherin"> ... </article>
        <article class="grid-item gryffindor"> ... </article>
        <article class="grid-item hufflepuff"> ... </article>
        <article class="grid-item ravenclaw"> ... </article>
        <article class="grid-item slytherin"> ... </article>
        <article class="grid-item gryffindor"> ... </article>
        <article class="grid-item gryffindor"> ... </article>
        <article class="grid-item ravenclaw"> ... </article>
        <article class="grid-item gryffindor"> ... </article>
        <article class="grid-item slytherin"> ... </article>
        <article class="grid-item slytherin"> ... </article>
        <article class="grid-item slytherin"> ... </article>
        <article class="grid-item "> ... </article>
        <article class="grid-item slytherin"> ... </article>
        <article class="grid-item "> ... </article>
```

class på grid-element

```
.grid-item.gryffindor {  
    background-color: #ae0001;  
    color: #eeba30;  
}
```




Elements Console Sources Network Performance Memory

```
<!DOCTYPE html>  
<html lang="en">  
  <head>...</head>  
  <body>  
    <header>...</header>  
    <main>  
      <section id="characters" class="grid-container"> grid == $0  
        <article class="grid-item Gryffindor">...</article>  
        <article class="grid-item Gryffindor">...</article>  
        <article class="grid-item Gryffindor">...</article>  
        <article class="grid-item Slytherin">...</article>  
        <article class="grid-item Gryffindor">...</article>  
        <article class="grid-item Hufflepuff">...</article>  
        <article class="grid-item Ravenclaw">...</article>  
        <article class="grid-item Slytherin">...</article>  
        <article class="grid-item Gryffindor">...</article>
```

data-theme attribute på dialog

```
function showCharacterModal(character) {  
    // ...  
  
    const dialog = document.querySelector("dialog");  
    // set theme  
    dialog.setAttribute("data-theme", character.house.toLowerCase());  
    // show dialog  
    dialog.showModal();  
}
```





```
<!DOCTYPE html>  
<html lang="en">  
  <head>...</head>  
  <body>  
    <header>...</header>  
    <main>...</main>  
    ... <dialog id="dialog-character" data-theme="gryffindor" open>  
      <section class="dialog-grid">...</section>  
      <form method="dialog">...</form>  
      ::backdrop  
    </dialog>  
    <footer>...</footer>  
    <script src="app.js"></script>  
    <!-- Code injected by live-server -->  
    <script>...</script>  
  </body>  
</html>
```

data-theme attribute på dialog

```
dialog[data-theme="gryffindor"] {  
    background-color: #740001;  
    color: #eeba30;  
}
```

```
dialog[data-theme="gryffindor"] button {  
    background-color: #d3a625;  
}
```



```
<!DOCTYPE html>  
<html lang="en">  
  ><head>...</head>  
  ><body>  
    ><header>...</header>  
    ><main>...</main>  
    ><dialog id="dialog-character" data-theme="gryffindor" open>  
      ><section class="dialog-grid">...</section> grid  
      ><form method="dialog">  
        ><button id="btn-cancel">Close</button>  
      </form>  
      >::backdrop
```



Code
Every
Day

And have fun 