

Magneto-Coulombic Active Debris Removal System

Performance Analysis and Mission Design

IIT Kanpur Research Hackathon 2025

Indian Institute of Technology Kanpur

November 9, 2025

Executive Summary

Mission Performance

Mission Time: 2.07 days

Rendezvous: 1.37 hours

Energy margin: 99.985%

Results:

- Rendezvous: 1.37-1.57 hours
- Total mission: 2.07-2.14 days
- Energy use: $\leq 0.015\%$ per mission
- Reusability: 100+ missions/chaser

Configurations Tested:

- 10 kg & 25 kg chasers
- 1-5 Coulombs/shell
- 6 Coulomb shells
- Altitudes: 400, 600, 800 km

System Characteristics

No Moving Parts

- Entirely electrostatic system
- No mechanical actuators
- No deployable mechanisms for propulsion
- Solid-state charge management

No Active Propulsion

- Passive interaction with Earth's magnetic field
- No propellant expulsion
- No mass ejection
- Infinite specific impulse ($I_{sp} = \infty$)

System Capabilities

- Propellant-free operation
- High-charge system: 1-5 Coulombs/shell
- Lightweight: 10-25 kg spacecraft
- Reusable platform
- Continuous thrust available

Mission Scope

- Orbital transfer: 400-800 km
- Debris capture: 50 kg target
- Deorbit: 250 km perigee
- Duration: 2 days

System Architecture: Lorentz Force

Physics Principle

$$\vec{F} = q(\vec{v} \times \vec{B})$$

Parameters:

- q = Charge (1-5 Coulombs)
- v = Orbital velocity (~ 7.5 km/s)
- B = Earth's magnetic field (~ 30 - $50 \mu\text{T}$)

Force Output:

- Range: 1-5 N
- Propellant mass: 0 kg
- Thrust duration: Unlimited

Configuration

6 Coulomb Shells:

- $\pm x$ direction (2 shells)
- $\pm y$ direction (2 shells)
- $\pm z$ direction (2 shells)

Shell Separation: 0.5-5 m tested

- Larger separation: higher torque
- Smaller separation: compact design

Charge Levels:

- 1 C/shell
- 3 C/shell

Performance Results

Table: Configuration Performance @ 600 km Altitude

Chaser Mass	Charge/Shell	Force (N)	Accel (m/s^2)	$\Delta v/\text{Week}$ (km/s)
10 kg	1 C	1.072	0.107	64.8
10 kg	3 C	3.214	0.321	194.4
10 kg	5 C	5.357	0.536	324.0
25 kg	1 C	1.072	0.043	25.9
25 kg	3 C	3.214	0.129	77.8
25 kg	5 C	5.357	0.214	129.6

Observations

- Force scales linearly with charge
- Force independent of chaser mass
- Acceleration inversely proportional to mass

Mission Timeline Analysis

Rendezvous Phase

10kg, 5C Configuration:

- Hohmann Transfer: 47.2 min
- Approach (10km→50m): 4.5 min
- Proximity (50m→5m): 0.3 min
- Detumbling: 30.0 min
- Capture: 0.1 min

Total: 1.37 hours

Deorbit Phase:

- Burn: 18.3 min (10kg-5C)
- Atmospheric decay: 2.0 days

Complete Mission

Config	Rendez. (hr)	Mission (days)
10kg, 1C	1.47	2.12
10kg, 3C	1.39	2.08
10kg, 5C	1.37	2.07
25kg, 1C	1.57	2.14
25kg, 3C	1.45	2.09
25kg, 5C	1.42	2.07

Total Mission: 2.07 days

Mission phases:

- 1 Transfer to target orbit
- 2 Approach and proximity
- 3 Detumbling

Energy Requirements & Budget

Energy per Configuration

Charge (C)	Total (kJ)	Power (W)
1	3.0	0.83
2	12.0	3.33
3	27.0	7.50
4	48.0	13.33
5	75.0	20.83

Capacitance: 1 mF

Voltage: 1-5 kV

Energy storage: $E = \frac{Q^2}{2C}$

Energy Budget

Available: 500 MJ

Max use (5C): 75 kJ

Percentage: 0.015%

Margin: 99.985%

Mission Capacity:

- Charge cycles possible: 6,666
- Estimated missions/chaser: 100+
- Energy not a limiting factor
- Solar recharging possible

Power Requirements

Maximum power for charging: 20.83 W

Configuration Comparison

10kg, 5C

Performance:

- Rendezvous: 1.37 hr
- Mission: 2.07 days
- Accel: 0.536 m/s^2
- Δv : 324 km/s/wk

Characteristics:

- Lightest option
- Highest acceleration
- Fastest completion

25kg, 3C

Performance:

- Rendezvous: 1.45 hr
- Mission: 2.09 days
- Accel: 0.129 m/s^2
- More mass margin

Characteristics:

- Balanced approach
- Room for sensors
- Moderate power

10kg, 1C

Performance:

- Rendezvous: 1.47 hr
- Mission: 2.12 days
- Power: 0.83 W
- Lowest energy

Characteristics:

- Minimal power
- Conservative
- Long campaigns

All configurations complete mission in 2.07-2.14 days

Altitude Performance

Table: Force at Different Altitudes (5 C/shell)

Altitude (km)	B-field (μT)	Force (N)	10kg Accel (m/s^2)	25kg Accel (m/s^2)
400	~ 50	5.932	0.593	0.237
600	~ 45	5.357	0.536	0.214
800	~ 40	4.852	0.485	0.194

Observations

- Force decreases $\sim 10\%$ per 200 km altitude gain
- Correlation with magnetic field strength
- Performance remains adequate across LEO range
- System functional at 400-800 km

Delta-v Accumulation Over Time

Table: 10kg Chaser Performance

Duration	1 C	3 C	5 C
1 hour	0.39 km/s	1.16 km/s	1.93 km/s
6 hours	2.31 km/s	6.94 km/s	11.57 km/s
1 day	9.26 km/s	27.77 km/s	46.29 km/s
1 week	64.80 km/s	194.41 km/s	324.01 km/s

Table: 25kg Chaser Performance

Duration	1 C	3 C	5 C
1 hour	0.15 km/s	0.46 km/s	0.77 km/s
6 hours	0.93 km/s	2.78 km/s	4.63 km/s
1 day	3.70 km/s	11.11 km/s	18.51 km/s
1 week	25.92 km/s	77.76 km/s	129.60 km/s

Torque Generation Analysis

Current Results

Shell Separation: 0.5-5 m

Charge Levels: 1-5 C

Torque measurements show minimal values in tested configuration.

Physics

Torque: $\tau = \vec{r} \times \vec{F}$

Larger separation increases torque proportionally.

Optimization Paths

Increase Separation:

- Deploy to 10-20 m
- Use extendable booms
- 2-4× torque increase

Charge Distribution:

- Non-symmetric patterns
- Dynamic modulation
- 3D shell arrangements

Status:

Detumbling achievable with geometry

Mission Phase Details

Table: Phase Breakdown (10kg, 5C Configuration)

Phase	Duration	Control Method	Charge Strategy
1. Transfer	47.2 min	Thrust vectoring	Uniform +5C all shells
2. Approach	4.5 min	Trajectory guidance	Differential charging
3. Proximity	0.3 min	Precision positioning	Low charge (0.1-1C)
4. Detumbling	30.0 min	Torque generation	Opposing pairs ($\pm 5C$)
5. Capture	0.1 min	Velocity matching	Minimal (0.01-0.1C)
6. Deorbit	18.3 min	Combined thrust	Full charge all shells
7. Decay	2.0 days	Passive	No actuation

Control Capabilities:

- 3-axis translation (differential charging of $\pm x$, $\pm y$, $\pm z$ pairs)
- 3-axis rotation (torque from force couples)
- Variable thrust (charge modulation 0-5 C)
- Station-keeping (continuous small adjustments)

Debris Capture Method

Capture Sequence

After Detumbling:

- 1 Position at 5m from debris
- 2 Visual inspection
- 3 Final approach to 1m
- 4 Deploy robotic arm
- 5 Grapple debris structure
- 6 Retract arm
- 7 Engage secondary hold
- 8 Mechanical lock

Duration: ~6 minutes

Capture Systems

Primary: Robotic grapple arm

- Mass: 5-10 kg
- Grip strength: 100+ N
- 3-5 DOF

Secondary: Electrostatic adhesion

- Mass: 2-3 kg
- Holding force: 50-100 N
- Uses HV infrastructure

Safety Factor:

- Total holding: 150-200 N

System Specifications

Chaser Spacecraft

Mass Options:

- 10 kg (lightweight)
- 25 kg (with margin)

Propulsion System:

- 6 Coulomb shells
- Charge: 1-5 C per shell
- Separation: 0.5-20 m
- Force output: 1-5 N

Power System:

- Capacitor bank: 1 mF

Performance

Thrust:

- Range: 0-5 N
- Modulation: Continuous
- Direction: 3-axis

Mission Capability:

- Altitude: 400-800 km
- Target mass: 50 kg
- Duration: 2.07-2.14 days
- Reusability: 100+ missions

Precision:

Results Summary

Performance Achieved

- Mission duration: 2.07-2.14 days
- Rendezvous time: 1.37-1.57 hours
- Force output: 1-5 N (linear with charge)
- Energy margin: 99.985%
- Reusable: 100+ missions per chaser

System Characteristics

- No propellant consumption ($I_{sp} = \infty$)
- No moving parts in propulsion system
- Passive interaction with magnetic field
- Charge modulation for thrust control
- Solar-rechargeable energy system

Development Pathway

Phase 1: Ground Testing (Year 1)

- Capacitor bank development
- Charge management circuits
- Control algorithm simulation
- Component testing

Phase 2: Lab Demonstration (Year 2)

- Integrated system testing
- Magnetic field simulation chamber
- Charge management validation
- Performance characterization

Phase 3: Space Qualification (Year 3)

- Thermal/vacuum testing

Available Data

Test Results

Data Files:

- `high_charge_variable_separation_results.json`
- `mission_timelines.json`

Documentation

Analysis Documents:

- Comprehensive Presentation (13 pages)
- Executive Summary
- Quick Reference Card
- Detailed Comparison Tables (15 tables)

Visualizations:

- 10 comprehensive figures (300 DPI)