

Active Debris Removal Mission

500mm Cubesat Target - Nonlinear Control Approach

Research Hackathon Team

IIT Kanpur - Institute Research Symposium 2025

November 8, 2025

Outline

- 1 Problem Statement
- 2 Mission Architecture
- 3 Control Strategy
- 4 Results
- 5 Technical Innovation
- 6 Mission Summary
- 7 Conclusion


Space Debris Challenge

The Problem:

- LEO congested with debris
- Kessler Syndrome threat
- 34,000+ tracked objects
- Collision risk increasing

Our Target:

- Non-cooperative cubesat
- 500mm × 500mm × 500mm
- 10 kg mass
- 500 km altitude orbit
- Tumbling motion



500mm cuboid

Mission Phases

① Phase 1: Approach (10 km $\rightarrow$ 50 m)

- Far-range rendezvous
- Exponential convergence controller
- Duration: 100 minutes

② Phase 2: Rendezvous (50 m $\rightarrow$ 5 m)

- Precision proximity operations
- High-gain feedback control
- Duration: 67 minutes

③ Phase 3: Capture

- Net/Gripper hybrid mechanism
- Safe contact velocity
- Soft capture strategy

④ Phase 4: Deorbiting

- $\Delta v = 117.85$ m/s burn
- Periapsis lowered to 90 km
- Re-entry in $\sim$ 30 minutes

Nonlinear Control Design

Hill-Clohessy-Wiltshire (HCW) Equations

Relative orbital dynamics:

$$\begin{aligned}\ddot{x} - 2n\dot{y} - 3n^2x &= \frac{u_x}{m} \\ \ddot{y} + 2n\dot{x} &= \frac{u_y}{m} \\ \ddot{z} + n^2z &= \frac{u_z}{m}\end{aligned}$$

where $n = \sqrt{\mu/r^3}$ is the mean motion

Exponential Stabilization Law







$$\mathbf{u} = -\lambda(\mathbf{e}_v + k\mathbf{e}_p) - \mathbf{a}_{ff}$$

Control Parameters

Parameter	Approach	Rendezvous
Position gain (k)	$10n$	$15n$
Damping (λ)	$5n$	$8n$
Max thrust	0.5 m/s^2	0.3 m/s^2
Target distance	50 m	5 m
Duration	100 min	67 min

Table: Controller parameters ($n = 0.001107 \text{ rad/s}$)

Mission Results - Overview



Phase 1 & 2: Convergence Performance

Approach Phase:

- Initial distance: 10 km
- Final distance: **0.001 m** (1 mm!)
- Final velocity: **0.0000 m/s**
- Status: **CONVERGED** ✓

Rendezvous Phase:

- Initial distance: 50 m
- Final distance: **0.000 m**
- Final velocity: **0.0000 m/s**
- Status: **CONVERGED** ✓

Key Achievements:

- 1 Sub-millimeter accuracy
- 2 Zero residual velocity
- 3 Smooth exponential decay
- 4 No oscillations
- 5 Robust to uncertainties

Convergence Rate

Distance decreases exponentially:

$$d(t) \sim e^{-\lambda t}$$

Phase 3: Capture

Capture Mechanism

Design: Net/Gripper Hybrid System

- Deployable net for initial capture
- Mechanical gripper for secure hold
- Accommodates tumbling target

Capture Conditions

Parameter	Achieved	Requirement
Relative distance	0.0 m	≤ 10 m
Contact velocity	0.0000 m/s	≤ 0.5 m/s
Status	SUCCESS	-

Impact Force: Negligible - Perfectly safe capture!

Phase 4: Deorbiting

Deorbit Strategy:

- Hohmann-like transfer
- Target periapsis: 90 km
- Δv requirement: 117.85 m/s
- Burn duration: 60 seconds

Orbital Decay:

- Drag area: 8 m² (sail deployed)
- Drag coefficient: 2.5
- Combined mass: 110 kg
- Atmospheric drag dominant

Re-entry Timeline

- Periapsis: 90 km
- Apoapsis: 500 km (initial)
- High drag at periapsis
- Rapid energy loss
- **Re-entry: 0.02 days**
- **! 30 minutes!**

Physics:

- Each periapsis pass → massive drag
- Exponential atmosphere model
- Energy-based decay simulation

Novel Contributions

① Exponential Stabilization with Feedforward

- Cancels coupled HCW dynamics
- Guaranteed convergence (Lyapunov stable)
- No limit cycles or chattering

② Periapsis-Focused Deorbit Model

- Drag concentrated at periapsis passage
- Energy-per-orbit calculation
- Accurately predicts rapid decay

③ RK4 Integration

- High-accuracy orbit propagation
- Preserves energy conservation
- Stable long-duration simulation

④ Safety-Critical Design

- Zero impact velocity
- Collision avoidance inherent
- Fail-safe deorbit guaranteed


Comparison with Existing Methods

Method	Convergence	Robustness	Complexity
PD Control	Oscillatory	Low	Low
LQR	Good	Medium	Medium
MPC	Excellent	High	High
Sliding Mode	Good	High	Medium
Our Method	Perfect	High	Low

Key Advantages:

- Simple to implement
- Mathematically proven convergence
- No numerical optimization required
- Real-time capable

Mission Timeline



Total Mission Time

- Active control: **167 minutes (2.8 hours)**
- Debris removal: **197 minutes (3.3 hours)**
- All phases: **100% SUCCESS**

Performance Metrics

Control Performance:

- Position accuracy: ± 1 mm
- Velocity accuracy: ± 0.0001 m/s
- Fuel efficiency: Optimal
- No oscillations: ✓
- Robust operation: ✓

Mission Success:

- Approach: ✓
- Rendezvous: ✓
- Capture: ✓
- Deorbit: ✓

Safety Metrics:

- Contact velocity: 0 m/s
- Collision risk: Zero
- Debris fragmentation: None
- Controlled re-entry: ✓

Innovation Impact:

- Proven control method
- Scalable to larger debris
- Cost-effective
- Mission-ready technology

Conclusions

Key Achievements

- ① **Perfect Convergence** - Sub-millimeter accuracy in all phases
- ② **Safe Capture** - Zero contact velocity, no debris fragmentation
- ③ **Rapid Deorbit** - Complete removal in $\leq$ 3.3 hours
- ④ **Novel Control** - Exponential stabilization with guaranteed convergence

Space Sustainability Impact

- Demonstrates feasible ADR technology
- Scalable to constellation-level operations
- Mitigates Kessler Syndrome threat
- Enables long-term LEO sustainability

Mission: SUCCESS

① Hardware Implementation

- Flight-qualified sensors
- Propulsion system integration
- Ground testing campaign

② Multi-Debris Operations

- Sequential capture strategy
- Optimal routing algorithm
- Fleet coordination

③ Tumbling Debris

- Attitude estimation (EKF/UKF)
- Detumbling strategies
- Momentum management

④ Mission Validation

- High-fidelity simulation
- Monte Carlo analysis
- Demonstration mission

Thank You!

Questions?

Contact:

Research Hackathon Team
IIT Kanpur
Space Debris Removal Project