Day 4-1

Assignment:

- Homework 03, Due Wed, 8am
  - Project ideas
  - **git**
- Lab 04 is available now
  - Sensors and displays

Today's Topics:

- Project Ideas
- git
- I2C
- LED Matrix



http://www.gartner.com/newsroom/id/3114217?imm_mid=0d7750&cmp=em-iot-na-na-newsltr_20150827

02-2 I2C

Interfacing with sensors over a serial bus



I²C

- "two-wire interface" standard
- Used to attach low-speed peripherals to embedded systems
- The Bone has two I²C controllers (Section 21 of TRM)

Figure 17-1. HS I²C Controllers Overview Block Diagram



Hardware - Bone

Display Kernel Log Messages

- You can see which ones are configured at boot time

```
beagle$ dmesg | grep i2c
[    0.156139] omap_i2c 44e0b000.i2c: bus 0 rev0.11 at 400 kHz
[    0.157673] input: tps65217_pwr_but as
/devices/ocp.2/44e0b000.i2c/i2c-0/0-0024/input/input0
[    0.169206] omap_i2c 44e0b000.i2c: unable to select pin group
[    0.170089] omap_i2c 4819c000.i2c: bus 1 rev0.11 at 100 kHz
[    0.172685] omap_i2c 4819c000.i2c: unable to select pin group
[    0.762708] i2c /dev entries driver
```

Two buses each running at different speeds

Time in seconds

i2c - bone

P9

DGND	1	2	DGND
VDD_3V3	3	4	VDD_3V3
VDD_5V	5	6	VDD_5V
SYS_5V	7	8	SYS_5V
PWR_BUT	9	10	SYS_RESETN
GPIO_30	11	12	GPIO_60
GPIO_31	13	14	GPIO_50
GPIO_48	15	16	GPIO_51
I2C1_SCL	17	18	I2C1_SDA
I2C2_SCL	19	20	I2C2_SDA
I2C2_SCL	21	22	I2C2_SDA
GPIO_49	23	24	I2C1_SCL
GPIO_117	25	26	I2C1_SDA
GPIO_115	27	28	GPIO_123
GPIO_121	29	30	GPIO_122
GPIO_120	31	32	VDD_ADC
AIN4	33	34	GNDA_ADC
AIN6	35	36	AIN5
AIN2	37	38	AIN3
AIN0	39	40	AIN1
GPIO_20	41	42	GPIO_7
DGND	43	44	DGND
DGND	45	46	DGND

P8

DGND	1	2	DGND
GPIO_38	3	4	GPIO_39
GPIO_34	5	6	GPIO_35
GPIO_66	7	8	GPIO_67
GPIO_69	9	10	GPIO_68
GPIO_45	11	12	GPIO_44
GPIO_23	13	14	GPIO_26
GPIO_47	15	16	GPIO_46
GPIO_27	17	18	GPIO_65
GPIO_22	19	20	GPIO_63
GPIO_62	21	22	GPIO_37
GPIO_36	23	24	GPIO_33
GPIO_32	25	26	GPIO_61
GPIO_86	27	28	GPIO_88
GPIO_87	29	30	GPIO_89
GPIO_10	31	32	GPIO_11
GPIO_9	33	34	GPIO_81
GPIO_8	35	36	GPIO_80
GPIO_78	37	38	GPIO_79
GPIO_76	39	40	GPIO_77
GPIO_74	41	42	GPIO_75
GPIO_72	43	44	GPIO_73
GPIO_70	45	46	GPIO_71

The first I2C bus is utilized for reading EEPROMS on cape add-on boards and can't be used for other digital I/O operations without interfering with that function, but you can still use it to add other I2C devices at available addresses.

The second I2C bus is available for you to configure and use.

Hardware – TMP101

- Goal: Interface to a TMP101 temp sensor

Parameter Name	Value
Typical Accuracy (°)	±2.0°C from −25°C to +85°C (max) ±3.0°C from −55°C to +125°C (max)
Supply Current (µA)	45µA, 0.1µA Standby
Resolution	9- to 12-bits,
Operating Voltage Range (V)	2.7V to 5.5V
Device Description	Serial Output Temp Sensor

http://www.ti.com/lit/gpn/tmp101

2-wire bus



- The two wires are
  - Serial Clock (SCL), is an input to the TMP101 and is used to clock data into and out of the TMP101.
  - Serial Data (SDA), is bidirectional and carries the data to and from the TMP101.
- The only other two pins on the TMP101 that you need to use are the Power Supply (Vdd) and Ground.



Software - bone

- See what's on a bus with **`i2cdetect`**

```
beagle$ i2cdetect -y -r 1
     0  1  2  3  4  5  6  7  8  9  a  b  c  d  e  f
00:          -- -- -- -- -- -- -- -- -- -- -- -- --
10: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
20: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
30: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
40: -- -- -- -- -- -- -- -- 48 49 -- -- -- -- -- --
50: -- -- -- -- UU UU UU UU -- -- -- -- -- -- -- --
60: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
70: 70 -- -- -- -- -- -- --
```

I have 2, TMP101's and an LED matrix.

- The TMP101's are at **`1001 000`** and **`1001 001`**
- Convert to hex **`0x48`** and **`0x49`**

Registers

- Each TMP101 has four registers

Table 2. Pointer Addresses of the TMP100 and TMP101 Registers

P1	P0	REGISTER
0	0	Temperature Register (READ Only)
0	1	Configuration Register (READ/WRITE)
1	0	T_{LOW} Register (READ/WRITE)
1	1	T_{HIGH} Register (READ/WRITE)

- Read with **`$ i2cget -y 1 0x48 00`**
- **`0x18`** which is 24C or 75.2F

Table 6. Configuration Register Format

BYTE	D7	D6	D5	D4	D3	D2	D1	D0
1	OS/ALERT	R1	R0	F1	F0	POL	TM	SD

Registers

Table 2. Pointer Addresses of the TMP100 and TMP101 Registers

P1	P0	REGISTER
0	0	Temperature Register (READ Only)
0	1	Configuration Register (READ/WRITE)
1	0	T_{LOW} Register (READ/WRITE)
1	1	T_{HIGH} Register (READ/WRITE)

- Read with **`$ i2cget -y 1 0x48 01`**
- **`0x80`** which is **`1000 0000`**



Table 6. Configuration Register Format

BYTE	D7	D6	D5	D4	D3	D2	D1	D0
1	OS/ALERT	R1	R0	F1	F0	POL	TM	SD

SD – Shutdown Mode
TM - Thermostat Mode
POL-Polarity
F1/F0 – Fault Queue
R1/R0 – Converter Resolution
OS – OS/Alert

Table 8. Resolution of the TMP100 and TMP101

R1	R0	RESOLUTION	CONVERSION TIME (typical)
0	0	9 Bits (0.5°C)	40ms
0	1	10 Bits (0.25°C)	80ms
1	0	11 Bits (0.125°C)	160ms
1	1	12 Bits (0.0625°C)	320ms

LED Matrix

- In the lab you will be interfacing an I2C LED matrix
- Some are bicolor (red and green)
- Some are single color
- Both interface the same way: i2c
- How many wires to you need to control 128 LEDs?





https://www.adafruit.com/products/902

https://www.adafruit.com/products/871

BoneScript I2C API

- Details: https://github.com/jadonk/bonescript

I2C

Uses https://github.com/korevec/node-i2c

```
i2cOpen(port, address, options, [callback])
i2cScan(port, [callback])
i2cWriteByte(port, byte, [callback])
i2cWriteBytes(port, command, bytes, [callback])
i2cReadByte(port, [callback])
i2cReadBytes(port, command, length, [callback])
i2cStream(port, command, length, [callback])
```

exercises/i2c/matrixLED

```
#!/usr/bin/env node

var b = require('bonescript');
var port = '/dev/i2c-2'
var matrix = 0x70;
var time = 1000; // Delay between images in ms

// The first byte is GREEN, the second is RED.
var smile =
        [0x00, 0x3c, 0x00, 0x42, 0x28, 0x89, 0x04, 0x85,
         0x04, 0x85, 0x28, 0x89, 0x00, 0x42, 0x00, 0x3c];
var frown =
        [0x3c, 0x00, 0x42, 0x00, 0x85, 0x20, 0x89, 0x00,
         0x89, 0x00, 0x85, 0x20, 0x42, 0x00, 0x3c, 0x00];
var neutral =
        [0x3c, 0x3c, 0x42, 0x42, 0xa9, 0xa9, 0x89, 0x89,
         0x89, 0x89, 0xa9, 0xa9, 0x42, 0x42, 0x3c, 0x3c];
var blank = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0];
```

exercises/i2c/matrixLED

```
var port = '/dev/i2c-2'
var matrix = 0x70;

b.i2cOpen(port, matrix);

b.i2cWriteByte(port,  0x21); // Start oscillator (p10)
b.i2cWriteByte(port,  0x81); // Disp on, blink off (p11)
b.i2cWriteByte(port,  0xe7); // Full brightness (page 15)

doFrown();
function doFrown() {
            b.i2cWriteBytes(port, 0x00, frown);
}

setTimeout(doNeutral, 1*time);
function doNeutral() {
            b.i2cWriteBytes(port, 0x00, neutral);
}

setTimeout(doSmile, 2*time);
function doSmile() {
            b.i2cWriteBytes(port, 0x00, smile);
}
```

exercises/i2c/matrixLED

```
// Fade the display
setTimeout(doFadeDown, 3*time);
var fade = 0xef;
function doFadeDown() {
    b.i2cWriteByte(port,  fade);
          fade--;
          if(fade >= 0xe0) {
                    setTimeout(doFadeDown, time/10);
          } else {
                    setTimeout(doFadeUp);
          }
}
function doFadeUp() {
    b.i2cWriteByte(port,  fade);
          fade++;
          if(fade <= 0xef) {
                    setTimeout(doFadeUp, time/10);
          }
}
```

Writing one column

```
b.i2cWriteBytes(port, 0x04, [0xff]);
```

- Turns on the third column of *green* LEDs, without writing the other columns
- Try it!

Wiring LED matrix

- Don't forget pull-up resistors!



P9

DGND	1	2	DGND
VDD_3V3	3	4	VDD_3V3
VDD_5V	5	6	VDD_5V
SYS_5V	7	8	SYS_5V
PWR_BUT	9	10	SYS_RESETn
GPIO_30	11	12	GPIO_60
GPIO_31	13	14	GPIO_50
GPIO_48	15	16	GPIO_51
I2C1_SCL	17	18	I2C1_SDA
I2C2_SCL	19	20	I2C2_SDA
I2C2_SCL	21	22	I2C2_SDA
GPIO_49	23	24	I2C1_SCL
GPIO_117	25	26	I2C1_SDA
GPIO_115	27	28	GPIO_113
GPIO_111	29	30	GPIO_112
GPIO_110	31	32	VDD_ADC
AIN4	33	34	GNDA_ADC
AIN6	35	36	AIN5
AIN2	37	38	AIN3
AIN0	39	40	AIN1
GPIO_20	41	42	GPIO_7
DGND	43	44	DGND
DGND	45	46	DGND

LED Matrix

- Goal: Etch-a-Sketch on the LED Matrix!