Programiz C Online Compiler

Programiz PRO >

main.c

Share Run

```c
#include <stdio.h>
int fibonacci(int n)
{
    if (n == 0)
        return 0;
    else if (n == 1)
        return 1;
    else
        return fibonacci(n-1) + fibonacci(n-2);
}
int main()
{
    int n, i;
    printf("Enter the number of terms: ");
    scanf("%d", &n);
    printf("Fibonacci Series:\n");
    for(i = 0; i < n; i++)
    {
        printf("%d ", fibonacci(i));
```

Output

Clear

```
Enter the number of terms: 6
Fibonacci Series:
0 1 1 2 3 5

=== Code Execution Successful ===
```

Programiz C Online Compiler

Programiz PRO ›

main.c

Share Run

```c
#include <stdio.h>
int main()
{
    int arr[100], n, i, pos, value, choice;
    printf("Enter number of elements: ");
    scanf("%d", &n);
    printf("Enter elements:\n");
    for(i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    printf("\n1.Insert\n2.Delete\n3.Display\n");
    printf("Enter your choice: ");
    scanf("%d", &choice);
    switch(choice)
    {
        case 1:
            printf("Enter position to insert: ");
            scanf("%d", &pos);
            printf("Enter value: ");
            scanf("%d", &value);
```

Output

Clear

```
Enter the number of terms: 6
Fibonacci Series:
0 1 1 2 3 5

=== Code Execution Successful ===
```

Programiz C Online Compiler

Programiz PRO ›

main.c

Share

Run

```c
#include <stdio.h>
int main()
{
    int arr[100], n, i, key, found = 0;

    printf("Enter number of elements: ");
    scanf("%d", &n);
    printf("Enter elements:\n");
    for(i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    printf("Enter number to search: ");
    scanf("%d", &key);
    for(i = 0; i < n; i++)
    {
        if(arr[i] == key)
        {
            printf("Element found at position %d", i + 1);
            found = 1;
            break;
```

Output

Clear

```
Enter number of elements: 5
Enter elements:
1 2 3 4 5
Enter number to search: 5
Element found at position 5

=== Code Execution Successful ===
```

Programiz C Online Compiler

Programiz PRO >

main.c

Share Run

```c
#include <stdio.h>
int main()
{
    int arr[100], n, i, key;
    int low = 0, high, mid;
    printf("Enter number of elements: ");
    scanf("%d", &n);
    printf("Enter sorted elements:\n");
    for(i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    printf("Enter number to search: ");
    scanf("%d", &key);
    high = n - 1;
    while(low <= high)
    {
        mid = (low + high) / 2;
        if(arr[mid] == key)
        {
            printf("Element found at position %d", mid + 1);
```

Output

Clear

```
Enter number of elements: 6
Enter sorted elements:
1 2 3 4 5 6
Enter number to search: 4
Element found at position 4

=== Code Execution Successful ===
```

Programiz C Online Compiler

Programiz PRO >

main.c

Share Run

```c
#include <stdio.h>
#include <stdlib.h>
struct node
{
    int data;
    struct node *next;
};
struct node *head = NULL;
void insert()
{
    struct node *newnode;
    newnode = (struct node*)malloc(sizeof(struct node));
    printf("Enter value: ");
    scanf("%d", &newnode->data);
    newnode->next = head;
    head = newnode;
}
void delete()
{
```

Output

Clear

```
1.Insert
2.Delete
3.Display
4.Exit
Enter choice: 1
Enter value: 10

1.Insert
2.Delete
3.Display
4.Exit
Enter choice: 3
10 -> NULL

1.Insert
2.Delete
3.Display
4.Exit
```