# predictive\_maintainance\_analysis

September 28, 2023

#### 1 Predictive Maintenance

- By Yash Mayur

## 2 Stages of Data Science

- 1) Data Collection
- 2) Exploratory Data Analysis (visual and Descriptive)
- 3) Feature Engineering (Data Preprocessing)
- 4) Model Creation and Evaluation

#### 5) Model Deployment

```
[1]: import os
     import numpy as np
     import pandas as pd
     import seaborn as sns
     import matplotlib.pyplot as plt
     import matplotlib
     import warnings
     from pandas_profiling import ProfileReport
     from sklearn.preprocessing import (LabelEncoder,OneHotEncoder,MaxAbsScaler)
     from sklearn.metrics import silhouette_score
     from sklearn.neighbors import NearestNeighbors
     from sklearn.model_selection import train_test_split
     from imblearn.over_sampling import SVMSMOTE
     from sklearn.metrics import f1_score, precision_score, recall_score,_
      →accuracy_score,roc_auc_score,confusion_matrix
     from sklearn.neighbors import KNeighborsClassifier
     from sklearn.ensemble import (
         GradientBoostingClassifier,
         RandomForestClassifier,
     )
```

```
from catboost import CatBoostClassifier
from sklearn.naive_bayes import GaussianNB
from sklearn.neural_network import MLPClassifier
from sklearn.tree import DecisionTreeClassifier
from sklearn.linear_model import LogisticRegression
```

C:\Users\Yash Mayur\AppData\Local\Temp\ipykernel\_12308\1597575372.py:8:
DeprecationWarning: `import pandas\_profiling` is going to be deprecated by April
1st. Please use `import ydata\_profiling` instead.
 from pandas profiling import ProfileReport

# 3 1) Data Collection

0

0

0

0

0

0

0

```
[40]: df = pd.read_csv('ai4i2020.csv')
      df.head(10)
[40]:
         UDI Product ID Type Air temperature [K] Process temperature [K] \
      0
            1
                  M14860
                                                298.1
                                                                            308.6
                             М
      1
            2
                  L47181
                             L
                                                298.2
                                                                            308.7
      2
            3
                  L47182
                                                298.1
                                                                            308.5
      3
            4
                                                298.2
                  L47183
                                                                            308.6
      4
            5
                  L47184
                                                298.2
                                                                            308.7
      5
            6
                  M14865
                                                298.1
                                                                            308.6
      6
            7
                  L47186
                                                298.1
                                                                            308.6
                             L
      7
                  L47187
            8
                             L
                                                298.1
                                                                            308.6
      8
            9
                  M14868
                             М
                                                298.3
                                                                            308.7
      9
           10
                  M14869
                             М
                                                298.5
                                                                            309.0
                                    Torque [Nm] Tool wear [min] Machine failure
         Rotational speed [rpm]
                                                                                        TWF
      0
                              1551
                                            42.8
                                                                  0
                                                                                          0
                                            46.3
                                                                  3
      1
                              1408
                                                                                     0
                                                                                          0
      2
                             1498
                                            49.4
                                                                  5
                                                                                     0
                                                                                          0
                                            39.5
                                                                  7
      3
                             1433
                                                                                     0
                                                                                          0
      4
                             1408
                                            40.0
                                                                  9
                                                                                          0
                                                                                     0
                                            41.9
      5
                             1425
                                                                 11
                                                                                     0
                                                                                          0
                                            42.4
      6
                                                                                          0
                             1558
                                                                 14
                                                                                     0
      7
                                            40.2
                                                                 16
                                                                                     0
                                                                                          0
                             1527
                                            28.6
      8
                              1667
                                                                 18
                                                                                     0
                                                                                          0
      9
                             1741
                                            28.0
                                                                 21
         HDF
               PWF
                    OSF
                          RNF
      0
            0
                 0
                       0
                            0
      1
            0
                 0
                       0
                            0
      2
                       0
            0
                 0
                            0
```

- 3.1 Feature Description
- 1)product ID: consisting of a letter L, M, or H for low (50% of all products), medium (30%) and high (20%) as product quality variants and a variant-specific serial number.
- 2) Type: just the product type L, M or H from column 2.
- 3) Air Temperature [K]: generated using a random walk process later normalized to a standard deviation of 2 K around 300 K.
- 4) Process Temperature [K]: generated using a random walk process normalized to a standard deviation of 1 K, added to the air temperature plus 10 K.
- 5) Rotational Speed [rpm]: calculated from a power of 2860 W, overlaid with a normally distributed noise.
- 6) Torque [Nm]: torque values are normally distributed around 40 Nm with a SD = 10 Nm and no negative values.
- 7) Tool Wear [min]: (breakdown and gradual failure of a cutting tool due to regular operation) The quality variants H/M/L add 5/3/2 minutes of tool wear to the used tool in the process.
- 8) A 'Machine failure' label that indicates, whether the machine has failed in this particular datapoint for any of the following failure modes are true. The machine failure consists of five independent failure modes as follows:
- a) Tool wear failure (TWF): the tool will be replaced of fail at a randomly selected tool wear time between 200 240 mins (120 times in our dataset). At this point in time, the tool is replaced 69 times, and fails 51 times (randomly assigned).
- b) Heat dissipation failure (HDF): heat dissipation causes a process failure, if the difference between air and process temperature is below 8.6 K and the tools rotational speed is below 1380 rpm. This is the case for 115 data points.
- c) Power failure (PWF): the product of torque and rotational speed (in rad/s) equals the power required for the process. If this power is below 3500 W or above 9000 W, the process fails, which is the case 95 times in our dataset.

- d) Overstrain failure (OSF): if the product of tool wear and torque exceeds 11,000 minNm for the L product variant (12,000 M, 13,000 H), the process fails due to overstrain. This is true for 98 datapoints.
- e) Random failures (RNF): each process has a chance of 0.1% to fail regardless of its process parameters. This is the case for only 5 datapoints, less than could be expected for 10,000 datapoints in our dataset.
- 3.1.1 Note: If at least one of the above failure modes is true, the process fails and the 'machine failure' label is set to 1. It is therefore not transparent to the machine learning method, which of the failure modes has caused the process to fail.

# 4 2) Exploratory Data Analysis

#### [41]: df.info()

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10000 entries, 0 to 9999
Data columns (total 14 columns):

#	Column	Non-Null Count	Dtype
0	UDI	10000 non-null	int64
1	Product ID	10000 non-null	object
2	Туре	10000 non-null	object
3	Air temperature [K]	10000 non-null	float64
4	Process temperature [K]	10000 non-null	float64
5	Rotational speed [rpm]	10000 non-null	int64
6	Torque [Nm]	10000 non-null	float64
7	Tool wear [min]	10000 non-null	int64
8	Machine failure	10000 non-null	int64
9	TWF	10000 non-null	int64
10	HDF	10000 non-null	int64
11	PWF	10000 non-null	int64
12	OSF	10000 non-null	int64
13	RNF	10000 non-null	int64
٠.	67 (01/0) (01/0)	1 (0)	

dtypes: float64(3), int64(9), object(2)

memory usage: 1.1+ MB

#### 4.0.1 Acronyms to be considered:

[K]: kelvin

[rpm]: revolutions per minute

[Nm]: newton-meter

# [min]: minutes

```
[42]: # let's find the null values
df.isnull().sum()
```

```
[42]: UDI
                                 0
     Product ID
                                  0
     Туре
                                 0
     Air temperature [K]
                                 0
     Process temperature [K]
                                 0
     Rotational speed [rpm]
                                  0
     Torque [Nm]
     Tool wear [min]
                                  0
     Machine failure
                                  0
     TWF
                                  0
     HDF
                                  0
     PWF
                                 0
     OSF
                                 0
     RNF
                                 0
      dtype: int64
```


## No null values present

```
[43]: # Let's get some description of data df.describe().T
```

[43]:		count	mean	std	min	25%	\
	UDI	10000.0	5000.50000	2886.895680	1.0	2500.75	
	Air temperature [K]	10000.0	300.00493	2.000259	295.3	298.30	
	Process temperature [K]	10000.0	310.00556	1.483734	305.7	308.80	
	Rotational speed [rpm]	10000.0	1538.77610	179.284096	1168.0	1423.00	
	Torque [Nm]	10000.0	39.98691	9.968934	3.8	33.20	
	Tool wear [min]	10000.0	107.95100	63.654147	0.0	53.00	
	Machine failure	10000.0	0.03390	0.180981	0.0	0.00	
	TWF	10000.0	0.00460	0.067671	0.0	0.00	
	HDF	10000.0	0.01150	0.106625	0.0	0.00	
	PWF	10000.0	0.00950	0.097009	0.0	0.00	
	OSF	10000.0	0.00980	0.098514	0.0	0.00	
	RNF	10000.0	0.00190	0.043550	0.0	0.00	
		50%	75%	max			
	UDI	5000.5	7500.25 100	0.00			
	Air temperature [K]	300.1	301.50	304.5			
	Process temperature [K]	310.1	311.10	313.8			
	Rotational speed [rpm]	1503.0	1612.00 28	386.0			
	Torque [Nm]	40.1	46.80	76.6			
	Tool wear [min]	108.0	162.00 2	253.0			
	Machine failure	0.0	0.00	1.0			

```
TWF
                                          0.00
                                                    1.0
                                  0.0
                                                     1.0
     HDF
                                  0.0
                                          0.00
     PWF
                                                    1.0
                                  0.0
                                          0.00
      OSF
                                  0.0
                                          0.00
                                                     1.0
     RNF
                                  0.0
                                          0.00
                                                     1.0
[44]: # Let's convert int datatype to float for preprocessing purposes
      for feature in df.columns:
          if df[feature].dtype != '0':
              df[feature] = df[feature].astype(float)
[45]: # Let's find the correlation of features with each other
      plt.figure(figsize=(10,10))
      sns.heatmap(df.corr(),
                  cmap='RdYlBu',
                  annot=True,
                  linewidths=0.2,
```

linecolor='lightgrey').set\_facecolor('white')



4.0.2 We can see that there are strongly correlated features namely process temperature and air temperature. Torque and rotational speed are also negatively correlated. We can drop one of the temperatures, but the torque to rotational speed difference might be a indication of a failure, so we'll keep both.

# 5 So now we will drop some columns which is not usefull

```
dropping the indices and product id
```

```
[46]: df.drop(['UDI','Product ID'],axis=1,inplace=True)
```

Drop the failure modes, as currently we are only interested whether something is failed or not.

```
[47]: df.drop(['TWF','HDF','PWF','OSF','RNF'],axis=1,inplace=True)
```

#### Let's check balanced relation of the independent features with the target feature

```
[48]: df_group = df.groupby(['Machine failure'])
df_group.count()
```

[48]:		Type Air	temperature [	K] Process t	emperature [K] \
	Machine failure				
	0.0	9661	96	61	9661
	1.0	339	3.	39	339
		Rotational	speed [rpm]	Torque [Nm]	Tool wear [min]
	Machine failure				
	0.0		9661	9661	9661
	1.0		339	339	339


#### 5.0.1 The above table clearly shows that the dataset is imbalanced

# 6 Let's derive a power attribute using this formula:

Power = Torque  $\times$  Rotational speed

```
[49]: df['Power'] = df[['Rotational speed [rpm]', 'Torque [Nm]']].product(axis=1) sns.histplot(df['Power'])
```


[49]: <AxesSubplot:xlabel='Power', ylabel='Count'>



#### We get gaussian normal distribution for the power feature

```
[50]: ## Boxplot

fig, ax = plt.subplots(2, 3, figsize=(20, 10))
i=0
for _, col in enumerate(df.columns):
    if col == "Machine failure":
        continue
    elif col == "Type":
        continue
    else:
        sns.boxplot(x="Machine failure", y=col, data=df, ax=ax[i//3][i%3])
        i += 1
```




# 7 3) Descriptive Analysis

#### 7.0.1 Clustering

```
[52]: plt.figure(figsize=(10, 8))

# create a pairplot of the data, colored by cluster label
sns.pairplot(df.sample(frac=0.05), hue="kmeans_cluster", vars=feature_list)
plt.show()
```

#### <Figure size 720x576 with 0 Axes>



### 7.1 From the above results we can clearly observe

Process Temperature and Air Temperature have Linear Relationship with each other and both the data has gaussian normal distribution

```
[53]: # calculate the silhouette coefficient
score = silhouette_score(X, kmeans.predict(X))
print(f"Silhouette Coefficient: {score}")
```

Silhouette Coefficient: 0.5191499897517547

7.1.1 We can say that the clusters are well apart from each other as the silhouette score is closer to 1.

```
[33]: ## Let's convert the dataframe which can be used further in our project

os.makedirs(os.getcwd(),exist_ok=True)

df.to_csv("data.csv",header=True,index=False)
```

# 8 4) Feature Engineering (Data Pre-processing) and Feature Selection

#### 8.0.1 Encoding of Categorical Feature i.e. Type

Use any one only

1) Label Encoding or 2) One Hot Encoding

```
[17]: ## Label Encoding

le = LabelEncoder()
df['Type'] = le.fit_transform(df['Type'])
df.head()
```

[17]:	Туре	Air temperature [K]	Process temperature [K]	Rotational speed [rpm] \
0	2	298.1	308.6	1551.0
1	1	298.2	308.7	1408.0
2	1	298.1	308.5	1498.0
3	1	298.2	308.6	1433.0
4	1	298.2	308.7	1408.0
	Т	o [Nm] Tool woon [mi	] Markina failum Da	vor Imoona aluator

	Torque [Nm]	Tool wear [min]	Machine failure	Power	${\tt kmeans\_cluster}$
0	42.8	0.0	0.0	66382.8	1
1	46.3	3.0	0.0	65190.4	1
2	49.4	5.0	0.0	74001.2	3
3	39.5	7.0	0.0	56603.5	0
4	40.0	9.0	0.0	56320.0	0

```
[54]: # One Hot Encoding
      frame = pd.get_dummies(data=df['Type'],drop_first=True)
      df.drop(columns='Type',axis=1,inplace=True)
      df['L'] = frame['L']
      df['M'] = frame['M']
      df.head()
[54]:
         Air temperature [K]
                               Process temperature [K]
                                                         Rotational speed [rpm]
                                                  308.6
                                                                          1551.0
                        298.1
                       298.2
                                                  308.7
                                                                          1408.0
      1
      2
                       298.1
                                                  308.5
                                                                          1498.0
      3
                        298.2
                                                  308.6
                                                                          1433.0
      4
                       298.2
                                                                          1408.0
                                                  308.7
         Torque [Nm]
                      Tool wear [min] Machine failure
                                                                   kmeans_cluster
                                                            Power
      0
                42.8
                                   0.0
                                                     0.0 66382.8
                                                                                 1
                46.3
                                                          65190.4
      1
                                   3.0
                                                     0.0
                                                                                 1
                                                                                    1
      2
                49.4
                                   5.0
                                                     0.0 74001.2
                                                                                 3
                                                                                    1
      3
                39.5
                                   7.0
                                                     0.0 56603.5
                                                                                 0 1
      4
                40.0
                                   9.0
                                                     0.0 56320.0
                                                                                 0
         Μ
         1
      0
      1
        0
      2 0
      3 0
      4
         0
[55]: X = df.drop(columns=['Machine failure', 'kmeans_cluster'],axis=1)
      y = df['Machine failure']
      Х
                                  Process temperature [K]
[55]:
            Air temperature [K]
                                                            Rotational speed [rpm]
                           298.1
                                                     308.6
                                                                             1551.0
      0
      1
                           298.2
                                                     308.7
                                                                             1408.0
      2
                           298.1
                                                     308.5
                                                                             1498.0
      3
                           298.2
                                                     308.6
                                                                             1433.0
      4
                           298.2
                                                     308.7
                                                                             1408.0
                                                     308.4
      9995
                           298.8
                                                                             1604.0
      9996
                           298.9
                                                     308.4
                                                                             1632.0
      9997
                           299.0
                                                     308.6
                                                                             1645.0
      9998
                           299.0
                                                     308.7
                                                                             1408.0
      9999
                           299.0
                                                     308.7
                                                                             1500.0
            Torque [Nm]
                        Tool wear [min]
                                             Power L M
```

```
0
            42.8
                            0.0 66382.8 0 1
            46.3
                             3.0 65190.4 1
1
2
            49.4
                             5.0 74001.2 1
            39.5
                             7.0 56603.5 1
3
4
            40.0
                             9.0 56320.0 1
            29.5
9995
                            14.0 47318.0 0
9996
            31.8
                            17.0 51897.6 0
                            22.0 54943.0 0 1
9997
            33.4
9998
            48.5
                            25.0 68288.0 0
9999
            40.2
                            30.0 60300.0 0 1
```

[10000 rows x 8 columns]

```
[59]: X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.25, with a random_state = 42)

X_test.shape
```

[59]: (2500, 8)

8.0.2 As analysed and Mentioned earlier that the dataset is imbalanced so we have to use SMOTE technique on training data inorder to make balance data

```
[60]: oversample = SVMSMOTE(random_state = 42)
    X_train, y_train = oversample.fit_resample(X_train, y_train)

[61]: scale = MaxAbsScaler()
    X_train = scale.fit_transform(X_train)
    X_test = scale.transform(X_test)
```

# 9 5) Model Creation and Evaluation

#### 9.0.1 a) Logistic Regression

```
[62]: # Logistic Regression

model_dict = dict()

model = LogisticRegression().fit(X_train,y_train)
y_pred = model.predict(X_test) # These are the predictions from the test data.
y_pred
```

[62]: array([0., 0., 0., ..., 0., 0., 0.])

```
[63]: accuracy = accuracy_score(y_test, y_pred)
      recall = recall_score(y_test, y_pred, average='weighted')
      precision = precision_score(y_test, y_pred, average='weighted')
      f1s = f1_score(y_test, y_pred, average='weighted')
      ROC_AUC = roc_auc_score(y_test, model.predict_proba(X_test)[:,1],_
       →average='weighted')
      confusion_mat = confusion_matrix(y_test,y_pred)
      model_dict.update({"Logistic Regression":accuracy})
      print("Accuracy: "+ "{:.2%}".format(accuracy))
      print("Recall: "+ "{:.2%}".format(recall))
      print("Precision: "+ "{:.2%}".format(precision))
      print("F1-Score: "+ "{:.2%}".format(f1s))
      print("ROC AUC score: "+ "{:.2%}".format(ROC_AUC))
      print("Confusion Matrix: \n")
      confusion_mat
     Accuracy: 88.24%
     Recall: 88.24%
     Precision: 96.59%
     F1-Score: 91.65%
     ROC AUC score: 86.40%
     Confusion Matrix:
[63]: array([[2156, 272],
             [ 22, 50]], dtype=int64)
     9.0.2 b) Decision Tree
[64]: # Decision Tree
      model = DecisionTreeClassifier().fit(X_train,y_train)
      y_pred = model.predict(X_test)
      y_pred
[64]: array([0., 0., 0., ..., 0., 0., 0.])
[65]: accuracy = accuracy_score(y_test, y_pred)
      recall = recall_score(y_test, y_pred, average='weighted')
      precision = precision_score(y_test, y_pred, average='weighted')
      f1s = f1_score(y_test, y_pred, average='weighted')
      ROC_AUC = roc_auc_score(y_test, model.predict_proba(X_test)[:,1],_u
       →average='weighted')
      confusion_mat = confusion_matrix(y_test,y_pred)
      model_dict.update({"Decision Tree":accuracy})
```

```
print("Accuracy: "+ "{:.2%}".format(accuracy))
      print("Recall: "+ "{:.2%}".format(recall))
      print("Precision: "+ "{:.2%}".format(precision))
      print("F1-Score: "+ "{:.2%}".format(f1s))
      print("ROC AUC score: "+ "{:.2%}".format(ROC_AUC))
      print("Confusion Matrix: \n")
      confusion mat
     Accuracy: 96.20%
     Recall: 96.20%
     Precision: 97.35%
     F1-Score: 96.66%
     ROC AUC score: 82.55%
     Confusion Matrix:
[65]: array([[2356,
                     72],
                     49]], dtype=int64)
             [ 23,
     9.0.3 c) Random Forest Classifier
[66]: # Random Forest Classifier
      model = RandomForestClassifier(n_estimators =_
      4100,n_jobs=-1,random_state=42,bootstrap=True,).fit(X_train,y_train)
      y_pred = model.predict(X_test)
      y_pred
[66]: array([0., 0., 0., ..., 0., 0., 0.])
[67]: accuracy = accuracy_score(y_test, y_pred)
      recall = recall_score(y_test, y_pred, average='weighted')
      precision = precision_score(y_test, y_pred, average='weighted')
      f1s = f1_score(y_test, y_pred, average='weighted')
      ROC_AUC = roc_auc_score(y_test, model.predict_proba(X_test)[:,1],_
       ⇔average='weighted')
      confusion_mat = confusion_matrix(y_test,y_pred)
      model_dict.update({"Random Forest Classifier":accuracy})
      print("Accuracy: "+ "{:.2%}".format(accuracy))
      print("Recall: "+ "{:.2%}".format(recall))
      print("Precision: "+ "{:.2%}".format(precision))
      print("F1-Score: "+ "{:.2%}".format(f1s))
      print("ROC AUC score: "+ "{:.2%}".format(ROC_AUC))
      print("Confusion Matrix: \n")
      confusion_mat
```

```
Accuracy: 97.64%
     Recall: 97.64%
     Precision: 98.07%
     F1-Score: 97.81%
     ROC AUC score: 96.88%
     Confusion Matrix:
[67]: array([[2386,
                      42],
                     55]], dtype=int64)
             [ 17,
     9.0.4 d) Gradient Boosting classifier
[68]: model = GradientBoostingClassifier().fit(X_train,y_train)
      y_pred = model.predict(X_test)
      y_pred
[68]: array([0., 0., 0., ..., 0., 0., 0.])
[69]: accuracy = accuracy_score(y_test, y_pred)
      recall = recall_score(y_test, y_pred, average='weighted')
      precision = precision_score(y_test, y_pred, average='weighted')
      f1s = f1_score(y_test, y_pred, average='weighted')
      ROC_AUC = roc_auc_score(y_test, model.predict_proba(X_test)[:,1],_
       →average='weighted')
      confusion_mat = confusion_matrix(y_test,y_pred)
      model_dict.update({"Gradient Boosting":accuracy})
      print("Accuracy: "+ "{:.2%}".format(accuracy))
      print("Recall: "+ "{:.2%}".format(recall))
      print("Precision: "+ "{:.2%}".format(precision))
      print("F1-Score: "+ "{:.2%}".format(f1s))
      print("ROC AUC score: "+ "{:.2%}".format(ROC AUC))
      print("Confusion Matrix: \n")
      confusion_mat
     Accuracy: 96.80%
     Recall: 96.80%
     Precision: 97.98%
     F1-Score: 97.23%
     ROC AUC score: 97.07%
     Confusion Matrix:
[69]: array([[2360,
                      68],
             [ 12,
                     60]], dtype=int64)
```

#### 9.0.5 e) K Neighbors Classifier

```
[70]: model = KNeighborsClassifier(n_neighbors=2).fit(X_train, y_train)
      y pred = model.predict(X test)
      y_pred
[70]: array([0., 0., 0., ..., 0., 0., 0.])
[71]: accuracy = accuracy_score(y_test, y_pred)
      recall = recall_score(y_test, y_pred, average='weighted')
      precision = precision_score(y_test, y_pred, average='weighted')
      f1s = f1_score(y_test, y_pred, average='weighted')
      ROC_AUC = roc_auc_score(y_test, model.predict_proba(X_test)[:,1],_
       ⇔average='weighted')
      confusion_mat = confusion_matrix(y_test,y_pred)
      model_dict.update({"KNN Classifier":accuracy})
      print("Accuracy: "+ "{:.2%}".format(accuracy))
      print("Recall: "+ "{:.2%}".format(recall))
      print("Precision: "+ "{:.2%}".format(precision))
      print("F1-Score: "+ "{:.2%}".format(f1s))
      print("ROC AUC score: "+ "{:.2%}".format(ROC_AUC))
      print("Confusion Matrix: \n")
      confusion mat
     Accuracy: 94.96%
     Recall: 94.96%
     Precision: 97.19%
     F1-Score: 95.84%
     ROC AUC score: 85.81%
     Confusion Matrix:
[71]: array([[2323, 105],
             [ 21, 51]], dtype=int64)
     9.0.6 f) Gaussian Naive Bayes Classifier
[72]: model = GaussianNB().fit(X_train, y_train)
      y_pred = model.predict(X_test)
      y_pred
[72]: array([0., 0., 0., ..., 0., 0., 0.])
[73]: accuracy = accuracy_score(y_test, y_pred)
      recall = recall_score(y_test, y_pred, average='weighted')
      precision = precision_score(y_test, y_pred, average='weighted')
```

```
f1s = f1_score(y_test, y_pred, average='weighted')
      ROC_AUC = roc_auc_score(y_test, model.predict_proba(X_test)[:,1],__
       ⇔average='weighted')
      confusion mat = confusion matrix(y test,y pred)
      model dict.update({"Gaussian Naive Bayes":accuracy})
      print("Accuracy: "+ "{:.2%}".format(accuracy))
      print("Recall: "+ "{:.2%}".format(recall))
      print("Precision: "+ "{:.2%}".format(precision))
      print("F1-Score: "+ "{:.2%}".format(f1s))
      print("ROC AUC score: "+ "{:.2%}".format(ROC_AUC))
      print("Confusion Matrix: \n")
      confusion_mat
     Accuracy: 88.56%
     Recall: 88.56%
     Precision: 96.60%
     F1-Score: 91.85%
     ROC AUC score: 88.84%
     Confusion Matrix:
[73]: array([[2164, 264],
             [ 22, 50]], dtype=int64)
     9.0.7 g) Cat Boost Classifier
[74]: | model = CatBoostClassifier(verbose = False).fit(X_train,y_train)
      y_pred = model.predict(X_test)
      y_pred
[74]: array([0., 0., 0., ..., 0., 0., 0.])
[75]: accuracy = accuracy_score(y_test, y_pred)
      recall = recall_score(y_test, y_pred, average='weighted')
      precision = precision_score(y_test, y_pred, average='weighted')
      f1s = f1_score(y_test, y_pred, average='weighted')
      ROC_AUC = roc_auc_score(y_test, model.predict_proba(X_test)[:,1],_
      ⇔average='weighted')
      confusion_mat = confusion_matrix(y_test,y_pred)
      model_dict.update({"Catboost Classifier":accuracy})
      print("Accuracy: "+ "{:.2%}".format(accuracy))
      print("Recall: "+ "{:.2%}".format(recall))
      print("Precision: "+ "{:.2%}".format(precision))
      print("F1-Score: "+ "{:.2%}".format(f1s))
      print("ROC AUC score: "+ "{:.2%}".format(ROC_AUC))
```

```
print("Confusion Matrix: \n")
      confusion mat
     Accuracy: 97.96%
     Recall: 97.96%
     Precision: 98.28%
     F1-Score: 98.09%
     ROC AUC score: 97.07%
     Confusion Matrix:
[75]: array([[2392,
                      361.
             [ 15, 57]], dtype=int64)
     9.0.8 h) Nueral Network MLP Classifier
[76]: model = MLPClassifier(hidden layer sizes = (100,100,), activation='relu',
      ⊖solver='adam', batch_size=2000,verbose=0).fit(X_train,y_train)
      y_pred = model.predict(X_test)
     C:\Users\Yash Mayur\anaconda3\lib\site-
     packages\sklearn\neural_network\_multilayer_perceptron.py:692:
     ConvergenceWarning: Stochastic Optimizer: Maximum iterations (200) reached and
     the optimization hasn't converged yet.
       warnings.warn(
[77]: accuracy = accuracy_score(y_test, y_pred)
      recall = recall_score(y_test, y_pred, average='weighted')
      precision = precision_score(y_test, y_pred, average='weighted')
      f1s = f1_score(y_test, y_pred, average='weighted')
      ROC_AUC = roc_auc_score(y_test, model.predict_proba(X_test)[:,1],__
       →average='weighted')
      confusion_mat = confusion_matrix(y_test,y_pred)
      model_dict.update({"Nueral Network Classifier":accuracy})
      print("Accuracy: "+ "{:.2%}".format(accuracy))
      print("Recall: "+ "{:.2%}".format(recall))
      print("Precision: "+ "{:.2%}".format(precision))
      print("F1-Score: "+ "{:.2%}".format(f1s))
      print("ROC AUC score: "+ "{:.2%}".format(ROC_AUC))
      print("Confusion Matrix: \n")
      confusion_mat
     Accuracy: 88.04%
     Recall: 88.04%
     Precision: 96.73%
```

F1-Score: 91.55%

# 10 6) Best Model to use

The Best Model is Catboost Classifier and its accuracy is 97.9600000000001

## 11 7) Quick Data Analysis Report

```
[]: dataframe = pd.read_csv('ai4i2020.csv')
Report = ProfileReport(dataframe,explorative=True)
Report
```

```
[ ]: Report.to_file("Data_Analysis_Report.pdf")
```