

JavaScript – 100 Questions with Detailed Explanations

1. `console.log("JavaScript".substring(4, 2));`

Answer: "va"

Explanation: substring swaps indices if start > end → substring(2,4).

2. `console.log("hello".charAt(10));`

Answer: ""

Explanation: Index out of range returns empty string.

3. `console.log("JS".repeat(2.5));`

Answer: "JSJS"

Explanation: repeat() floors decimal → 2.

4. `console.log("abc".padStart(5, "0"));`

Answer: "00abc"

Explanation: Adds padding at beginning until length 5.

5. `console.log("abc".padEnd(2, "0"));`

Answer: "abc"

Explanation: No padding because length already ≥ 2 .

6. `console.log("hello".includes(""));`

Answer: true

Explanation: Every string contains empty string.

7. `console.log("abc".indexOf("b", 2));`

Answer: -1

Explanation: Search starts at index 2 → no 'b' found.

8. `console.log("aaa".replace("a", "b"));`

Answer: "baa"

Explanation: Only first occurrence replaced.

9. `console.log("aaa".replaceAll("a", "b"));`

Answer: "bbb"

Explanation: All occurrences replaced.

10. `console.log(" hi ".trimStart().length);`

Answer: 3

Explanation: "hi " length is 3.

11. `console.log("abc".slice(-2));`

Answer: "bc"

Explanation: Negative index counts from end.

12. `console.log("abc".substr(1, 1));`

Answer: "b"

Explanation: substr(start, length).

13. `console.log("abc".substring(1, 1));`

Answer: ""

Explanation: Same start & end → empty string.

14. `console.log("5" + 1 + 2);`

Answer: "512"

Explanation: Left-to-right → string concatenation.

15. `console.log(1 + 2 + "5");`

Answer: "35"

Explanation: $1+2=3 \rightarrow "3"+"5"$.

16. `console.log("abc".charCodeAt(0));`

Answer: 97

Explanation: ASCII of 'a'.

17. `console.log(String.fromCharCode(97));`

Answer: "a"

Explanation: Converts ASCII to character.

18. `console.log("abc".toUpperCase().toLowerCase());`

Answer: "abc"

Explanation: Converts to upper then back to lower.

19. `console.log("abc".localeCompare("abd"));`

Answer: -1

Explanation: $abc < abd$.

20. `console.log("abc".startsWith("a", 1));`

Answer: false

Explanation: Starts check from index 1.

21. `console.log("abc".endsWith("b", 2));`

Answer: true

Explanation: First 2 chars = "ab".

22. `console.log("a,b,c".split(",", 2));`

Answer: ["a", "b"]

Explanation: Limit = 2 items.

23. `console.log(["a", "b", "c"].join());`

Answer: "a,b,c"

Explanation: Default separator is comma.

24. `console.log("abc".search("b"));`

Answer: 1

Explanation: Returns index of match.

25. `console.log("abc".match(/d/));`

Answer: null

Explanation: No match found.

26. `console.log([1,2,3].push(4));`

Answer: 4

Explanation: Returns new length.

27. `console.log([1,2,3].pop());`

Answer: 3

Explanation: Returns removed element.

28. `console.log([1,2,3].shift());`

Answer: 1

Explanation: Removes first element.

29. `console.log([1,2,3].unshift(0));`

Answer: 4

Explanation: Returns new length.

30. `console.log([1,2,3].slice(1));`

Answer: [2,3]

Explanation: Returns shallow copy from index 1.

31. `console.log([1,2,3].splice(1,1));`

Answer: [2]

Explanation: Removes 1 element at index 1.

32. `let a=[1,2,3]; a.splice(1,1); console.log(a);`

Answer: [1,3]

Explanation: splice modifies original array.

33. `console.log([1,2].concat([3,4]));`

Answer: [1,2,3,4]

Explanation: Merges arrays.

34. `console.log([1,2,3].indexOf(2));`

Answer: 1

35. `console.log([1,2,3].includes(4));`

Answer: false

36. `console.log([1,2,3].find(x=>x>1));`

Answer: 2

37. `console.log([1,2,3].findIndex(x=>x>2));`

Answer: 2

38. `console.log([1,2,3].map(x=>x*2));`

Answer: [2,4,6]

39. `console.log([1,2,3].filter(x=>x>1));`

Answer: [2,3]

40. `console.log([1,2,3].reduce((a,b)=>a+b));`

Answer: 6

41. `console.log([1,2,3].every(x=>x>0));`

Answer: true

42. `console.log([1,2,3].some(x=>x>2));`

Answer: true

43. `console.log([1,2,3].reverse());`

Answer: [3,2,1]

44. `console.log([3,1,2].sort());`

Answer: [1,2,3]

45. `console.log([10,2,1].sort());`

Answer: [1,10,2]

Explanation: Sorted as strings.

46. `console.log(Array.isArray([]));`

Answer: true

47. `console.log(Array.from("abc"));`

Answer: ["a","b","c"]

48. `console.log([1,2,3].toString());`

Answer: "1,2,3"

49. `console.log([1,[2,3]].flat());`

Answer: [1,2,3]

50. `console.log([1,2,3].at(-1));`

Answer: 3

51. `typeof NaN` → number

52. Block scoped → let & const

53. `5 + "5"` → "55"

54. Strict equality → ===

55. Falsy → 0

56. Runs at least once → do-while

57. `Boolean("")` → false

58. `2 ** 3` → 8

59. `typeof null` → object

60. Not primitive → object

61. var scope → function

62. `"5" - 2` → 3

63. switch uses → ===

64. Stops loop → break

65. `0 == false` → true

66. `0 === false` → false

67. `typeof []` → object

68. Infinite loop → for(;;)

69. `+"5"` → 5

70. Nullish → ??

71. `1 && 0` → 0

72. `1 || 0` → 1

73. `!1` → false

74. Iterates values → for...of

75. Iterates keys → for...in

76. `parseInt("10px")` → 10

77. `Math.floor(4.9)` → 4

78. `Math.ceil(4.1)` → 5

79. `isNaN("abc")` → true

80. `typeof undefined` → undefined

81. `5 % 2` → 1

82. `!!"hello"` → true

83. `1 < 2 < 3` → true (true=1 → 1<3)

84. `3 > 2 > 1` → false (true=1 → 1>1 false)

85. `true + true` → 2

86. `"5" * 2` → 10

87. `5 + null` → 5

88. `5 + undefined` → NaN

89. `null == undefined` → true
90. `null === undefined` → false
91. `typeof function(){} → function`
92. `1 ? "yes":"no" → yes`
93. `"" ? "yes":"no" → no`
94. `0 || "hello" → hello`
95. `0 && "hello" → 0`
96. `"5" == 5 → true`
97. `"5" === 5 → false`
98. `[1,2] + [3,4] → "1,23,4"`
Explanation: Arrays convert to strings before concatenation.
99. `typeof Infinity → number`
100. `0.1 + 0.2 == 0.3 → false` (floating precision issue)

End of Full Expanded Version.