

GE23131-Programming Using C-2024

Quiz navigation



Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Thursday, 12 December 2024, 9:35 PM
Duration	10 days 19 hours

Question 1

Correct

Marked out of 1.00

Flag question

Given an array of numbers and a window of size k. Print the maximum of numbers inside the window for each step as the window moves from the beginning of the array.

Input Format

Input contains the array size, no of elements and the window size

Output Format

Print the maximum of numbers

Constraints

1 <= size <= 1000

Sample Input 1

8
1 3 5 2 1 8 6 9
3

Sample Output 1

5 5 5 8 8 9

For example:

0	5 5 5 0 0 9
1 3 5 2 1 8 6 9	
3	
10	7 7 5 9 9 9 8 5
3 7 5 1 2 9 8 5 3 2	
3	

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int n,k;
4     scanf("%d",&n);
5     int arr[n];
6     for(int i=0;i<n;i++)
7     {
8         scanf("%d",&arr[i]);
9     }
10    scanf("%d",&k);
11    for(int a=0;a<=n-k;a++)
12    {
13        int max=arr[a];
14        for(int b=a;b<a+k;b++)
15        {
16            if(arr[b]>max)
17            {
18                max=arr[b];
19            }
20        }
21        printf("%d ",max);
22    }
23 }
```

	Input	Expected	Got	
--	-------	----------	-----	--

	3			
✓	10 3 7 5 1 2 9 8 5 3 2 3	7 7 5 9 9 9 8 5	7 7 5 9 9 9 8 5	✓

Passed all tests! ✓

Question **2**
Correct
Marked out of 1.00
[Flag question](#)

Given an array and a threshold value find the output.

Input: {5,8,10,13,6,2}

Threshold = 3

Output count = 17

Explanation:

Number	Parts	Counts
5	{3,2}	2
8	{3,3,2}	3
10	{3,3,3,1}	4
13	{3,3,3,3,1}	5
6	{3,3}	2
2	{2}	1

Input Format

N - no of elements in an array

Array of elements

Threshold value

Output Format

Display the count

5 8 10 13 6 2

3

Sample Output 1

17

For example:

Input	Result
6 5 8 10 13 6 2 3	17
7 20 35 57 30 56 87 30 10	33

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int n,t,count=0;
4     scanf("%d",&n);
5     int arr[n];
6     for(int i=0;i<n;i++)
7     {
8         scanf("%d",&arr[i]);
9     }
10    scanf("%d",&t);
11    for(int j=0;j<n;j++)
12    {
13        while(arr[j]>0)
14        {
15            arr[j]-=t;
16            count++;
17        }
18    }
```

```
21 | }
```

	Input	Expected	Got	
✓	6 5 8 10 13 6 2 3	17	17	✓
✓	7 20 35 57 30 56 87 30 10	33	33	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of 1.00

 [Flag question](#)

Output is a merged array without duplicates.

Input Format

N1 - no of elements in array 1

Array elements for array 1

N2 - no of elements in array 2

Array elements for array2

Output Format

Display the merged array

Sample Input 1

5

1 2 3 6 9

Sample Output 1

1 2 3 4 5 6 9 10

For example:

Input	Result
5	1 2 3 4 5 6 9 10
1 2 3 6 9	
4	
2 4 5 10	

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int a,b;
4     scanf("%d",&a);
5     int arr1[a];
6     for(int i=0;i<a;i++)
7         scanf("%d",&arr1[i]);
8     scanf("%d",&b);
9     int arr2[b];
10    for(int i=0;i<b;i++)
11        scanf("%d",&arr2[i]);
12    int p=0,q=0;
13    while((p<a)&&(q<b))
14    {
15        if(arr1[p]<arr2[q])
16        {
17            printf("%d ",arr1[p]);
18            p++;
19        }
20        else if(arr1[p]>arr2[q])
21        {
22            printf("%d ",arr2[q]);
23            q++;
24        }
```

```
27     {
28         printf("%d ",arr1[p]);
29         p++;
30         q++;
31     }
32 }
33
34 }
35 for(int j=p;j<a;j++)
36 {
37     printf("%d ",arr1[j]);
38 }
39
40 for(int j=q;j<b;j++)
41 {
42     printf("%d ",arr2[j]);
43 }
44 }
```

	Input	Expected	Got	
✓	5 1 2 3 6 9 4 2 4 5 10	1 2 3 4 5 6 9 10	1 2 3 4 5 6 9 10	✓

Passed all tests! ✓