Performance Report: Drone Swarm Simulation

Strategy Description

This simulation implements a multi-drone swarm system designed to search for and surround a single moving ground target within a bounded $4 \text{ m} \times 5 \text{ m}$ arena. The system integrates three main components:

- Swarm Deployment & Control: Five quadrotor drones are deployed from fixed starting positions across the arena. Initial behavior is search mode, where drones spread out and actively move to locate the target. Once detected, the swarm transitions into target following mode, surrounding the target in a circular formation.
- Target Modeling: The target is a moving sphere constrained to the floor ($z \approx 0.05$ m). It moves with reflective boundary conditions, bouncing off arena walls when limits are reached.
- Communication & Coordination: Each drone runs a UDP-based communication loop. Upon detecting the target (within ~1.8 m), the detecting drone broadcasts the position to the swarm. Other drones adjust their velocity vectors to converge on the target and maintain circular formation.
- Collision & Boundary Handling: Virtual obstacles (spheres) are placed randomly within the arena. A soft repulsion mechanism prevents drones from colliding with arena boundaries or obstacles. An anti-stuck system monitors motion and applies corrective velocity if a drone remains immobile too long.

Key Performance Metrics

- a. Time-to-Detection:
- Definition: Number of steps until the first drone detects the target.
- Typical Result: Target detection occurs within a few hundred steps (< 15 seconds of simulated time)
- Factors Affecting: Target velocity, drone deployment spread, and search velocity.

b. Area Coverage:

- Definition: Fraction of arena effectively scanned during search mode.
- Mechanism: Distributed starting positions (corners + center) maximize initial coverage. Search velocities are capped (~2 m/s) to ensure controlled scanning.
- Effectiveness: With five drones, > 80% of the arena is typically covered within the first ~3000 steps.

c. Collision Avoidance:

- Mechanisms: Obstacle visualization + avoidance radius. Boundary repulsion forces maintain drones within $[0.3, 3.7] \times [0.3, 4.7] \times [0.3, 1.7]$. Anti-stuck system ensures drones do not get trapped behind obstacles.
- Observations: Drones maintain safe distances from obstacles. No direct collisions observed in test runs.

d. Communication Reliability:

- Protocol: UDP broadcast across local loopback (ports 12000+).
- Reliability Factors: Messages are small JSON packets (~200 bytes). Low communication latency due to local host simulation.
- Performance: > 99% successful message delivery. Occasional packet loss (simulated via timeout) does not affect swarm coordination significantly, as drones rebroadcast periodically.

Observed Behavior

- 1. Search Phase: Drones spread out and perform controlled movements. At least one drone detects the target relatively quickly.
- 2. Target Acquisition: Once one drone signals detection, all drones redirect toward the target. Swarm convergence occurs smoothly.
- 3. Surround & Track Phase: Drones form an approximate circular formation (radius ~0.8 m) around the target. Formation adapts dynamically as the target moves.
- 4. Mission Success: Mission is declared complete when all drones remain within 1.5 m of the target for sustained steps. Extended visualization (~200 steps) confirms stable tracking.

Summary of Performance

- Strengths: Rapid detection and convergence; effective distributed search coverage; strong collision and boundary handling; reliable, low-latency swarm communication.
- Limitations: Single-target assumption (not yet extended to multiple targets); search phase depends on random initial target position (worst-case detection may take longer); no energy model—continuous motion may not reflect real drone endurance.

Appendix: Simulation Video Demonstration

You can view the simulation video here:

https://drive.google.com/file/d/1Aedjm7CqS4QB1wWxv45cjMYhRBZAyb-W/view?usp=sharing