```
#!/bin/bash
echo "Enter three numbers:"
read a b c
if [ $a -ge $b ] && [ $a -ge $c ]
then
    echo "$a is the biggest"
elif [ $b -ge $a ] && [ $b -ge $c ]
then
    echo "$b is the biggest"
else
    echo "$c is the biggest"
fichmod +x square.sh
./square.sh
```

```
Welcome to Cloud Shell! Type "help" to get started.
To set your Cloud Platform project in this session use `gcloud config set project [PROJECT_ID]`.
You can view your projects by running `gcloud projects list`.
thanveerthannu801@cloudshell:~$ nano square.sh
thanveerthannu801@cloudshell:~$ chmod +x square.sh
thanveerthannu801@cloudshell:~$ ./square.sh
Enter a number:
45
Square = 2025
thanveerthannu801@cloudshell:~$ nano biggest.sh
thanveerthannu801@cloudshell:~$ chmod +x square.sh
thanveerthannu801@cloudshell:~$ ./square.sh
Enter a number:
24
Square = 576
thanveerthannu801@cloudshell:~$
```

```
Setting up libnl-route-3-200:amd64 (3.7.0-0.3build1.1) ...
Setting up libblas3:amd64 (3.12.0-3build1.1) ...
update-alternatives: using /usr/lib/x86_64-linux-gnu/blas/libblas.so.3 to provide /usr/lib/x86_64-linux-gnu/libblas.so.3 (libblas.so.3-x86_64-linux-gnu) in auto mode
Setting up nmap-common (7.94+git20230807.3be01efb1+dfsg-3build2) ...
Setting up liblua5.4-0:amd64 (5.4.6-3build2) ...
Setting up libibverbs1:amd64 (50.0-2ubuntu0.2) ...
Setting up ibverbs-providers:amd64 (50.0-2ubuntu0.2) ...
Setting up liblinear4:amd64 (2.3.0+dfsg-5build1) ...
Setting up libpcap0.8t64:amd64 (1.10.4-4.1ubuntu3) ...
Setting up nmap (7.94+git20230807.3be01efb1+dfsg-3build2) ...
Processing triggers for man-db (2.12.0-4build2) ...
Processing triggers for libc-bin (2.39-0ubuntu8.8) ...
shaikadill283@cloudshell:~$ nmap --version
Nmap version 7.94SVN ( https://nmap.org )
Platform: x86_64-pc-linux-gnu
Compiled with: liblua-5.4.6 openssl-3.0.13 libssh2-1.11.0 libz-1.3 libpcre2-10.42 libpcap-1.10.4 nmap-libdnet-1.12 ipv6
Compiled without:
Available nsock engines: epoll poll select
shaikadill283@cloudshell:~$ ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
2: eth0@if7: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1460 qdisc noqueue state UP group default qlen 1000
    link/ether 7e:ad:bc:58:74:d5 brd ff:ff:ff:ff:ff:ff link-netnsid 0
    inet 10.88.0.3/16 brd 10.88.255.255 scope global eth0
       valid_lft forever preferred_lft forever
3: docker0: <NO-CARRIER,BROADCAST,MULTICAST,UP> mtu 1460 qdisc noqueue state DOWN group default
    link/ether 3a:2b:9c:83:4b:b4 brd ff:ff:ff:ff:ff:ff
    inet 172.17.0.1/16 brd 172.17.255.255 scope global docker0
       valid_lft forever preferred_lft forever
shaikadill283@cloudshell:~$ find ip address under (eth0@) -- Copy the IP address
-bash: syntax error near unexpected token `('
shaikadill283@cloudshell:~$ nmap paste_ip_address
Starting Nmap 7.94SVN ( https://nmap.org ) at 2026-08-27 03:18 UTC
Failed to resolve "paste_ip_address".
WARNING: No targets were specified, so 0 hosts scanned.
Nmap done: 0 IP addresses (0 hosts up) scanned in 0.12 seconds
shaikadill283@cloudshell:~$
```