```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">

    <link rel="stylesheet" type="text/css" href="css/bootstrap.min.css">
    <link rel="stylesheet" type="text/css" href="design.css">

    <script src="js/custom/ajaxcall.js"></script>
    <script src="js/custom/userOperations.js"></script>
    <script src="js/custom/cartOperations.js"></script>
    <script src="js/custom/controller.js"> </script>

    <title> GROCERYMart </title>
</head>

<body>
    <header>
        <h3> GROCERY MART </h3>
        <label class="notification" id="cartlabel"> 0 </label>
        <img src="images/cart.png" id="cart" data-toggle="modal" data-target="#exampleModalCenter">
    </header>

    <main>
        <div id="logindiv">
            <div>
                <br>
                <label for="username"> User Name </label><br>
                <input type="text" id="username" placeholder="Enter username" size="25"><br><br>
            </div>

            <div>
                <label for="pass"> Password </label><br>
                <input type="password" id="pass" placeholder="Enter password" size="25"><br>
                <h6 class="incorrect" id=incorrectpass> </h6>
            </div>
            <div>
                <button id="btnlogin" onclick="ajaxcall.ajax(checkuser,'http://localhost:3000/json/users.json','username')"> LOGIN </button><br>
                <h6 id="signup"> New User? SIGN UP </h6>
            </div>
        </div>

        <div id="registerdiv">
            <h6 class="incorrectregister" id="mandatory"></h6>
            <div>
                <label for="firstname"> First Name </label><br>
                <input type="text" id="firstname" placeholder="Enter firstname" size="25"><br>
                <h6 class="incorrectregister" id="wrongfirst">   </h6>
            </div>

            <div>
                <label for="lastname"> Last Name </label><br>
                <input type="text" id="lastname" placeholder="Enter lastname" size="25"><br>
                <h6 class="incorrectregister" id="wronglast"> </h6>
            </div>
```

```html
<div>
    <label for="rusername"> User Name </label><br>
    <input type="text" id="rusername" placeholder="Enter username" size="25"><br>
    <h6 class="incorrectregister" id="duplicateuser"> </h6>
</div>

<div>
    <label for="address"> Address </label><br>
    <textarea type="text" id="address" placeholder="Enter address" rows="5" cols="28"></textarea><br><br>
</div>
<div>
    <label for="rpass"> Password </label><br>
    <input type="password" id="rpass" placeholder="Enter password" size="25">
    <h6 id="hpass"> </h6>
</div>
<div>
    <button id="btnregister" onclick="ajaxcall.ajax(checkUser,'http://localhost:3000/json/users.json','username')"> REGISTER </button><br>
</div>
</div>

<div id="homediv">
  <div id="mainmenu">
    <div id="innerdiv"></div>
  </div>
  <div id="submenu"></div>
</div>

<div class="modal fade" id="exampleModalCenter" tabindex="-1" role="dialog" aria-labelledby="exampleModalCenterTitle" aria-hidden="true">
    <div class="modal-dialog" role="document">
      <div class="modal-content">
       <div class="modal-header">
        <h5 class="modal-title" id="exampleModalLongTitle"> Billing </h5>
        <button type="button" class="close" data-dismiss="modal" aria-label="Close">
         <span aria-hidden="true">&times;</span>
        </button>
       </div>
       <div class="modal-body">
        <table class="table table-bordered">
          <thead>
            <tr>
              <td> Item </td>
              <td> Price </td>
              <td> Quantity </td>
            </tr>
          </thead>
          <tbody id="itemtable"></tbody>
        </table>
        <div>
         <p> Total Price : <span id="pricevalue"> 0 </span></p>
         <p> Tax : <span> 10% </span></p>
         <p> Cart Subtotal : <span id="totalpricevalue"> 0 </span></p>
        </div>
       </div>
       <div class="modal-footer">
        <!-- <button type="button" class="btn btn-secondary" data-dismiss="modal">Close</button> -->
```

```html
            <button type="button" class="btn btn-primary" id="buy"> Buy Now </button>
          </div>
        </div>
      </div>
    </div>
  </main>

  <script src="js/jquery-3.2.1.min.js"></script>
  <script src="js/bootstrap.min.js"></script>
</body>

</html>
```