MerchantView API

November 2023

This document is strictly confidential and for the sole use of EverC and the recipient. The information herein may not be reproduced or circulated without EverC's prior written consent. If you are not the intended recipient, you are notified that disclosing, copying, distributing or taking any action in reliance on the contents of this documentation is strictly prohibited.

Introduction

Welcome to the EverC API documentation. This API allows you to integrate EverC's data services directly into your internal systems and workflows. This lets you take advantage of EverC's comprehensive intelligence infrastructure while preserving your existing workflows and software environment.

Overview

The EverC API is accessible over HTTPS and uses standard HTTP response codes to indicate request success or errors.

Read through the introduction section to get familiar with the API guidelines. Check out the Getting Started section to learn about common workflows and best practices. If you are looking for specific endpoint descriptions, structures or examples, see the relevant entry in the API reference.

Authentication

Every API call, except for login, requires providing a valid session access token.

To obtain a session access token you must perform a successful login to the API. Once you've obtained a session access token you're required to provide it in the Authorization header with the token in each subsequent API call you make.

Responses and Errors

The EverC API uses standard HTTP response codes and human-readable messages in JSON format to indicate success or failure of an API request. Codes in the 2xx range indicate success, codes in the 4xx range indicate an error due to a problematic request (e.g. not allowed method of the request, a bad parameter format, etc.), and codes in the 5xx range indicate an error with EverC's servers, although these shouldn't ever occur.

Detailed description of each code is under the HTTP Response Codes chapter below.

Backwards-Compatible Changes

EverC introduces periodical changes to its API in order to present new capabilities, improve user experience, etc. Changes that are backwards-compatible follow the same release policy as any other MerchantView feature. Any API integration should handle backwards compatible changes gracefully.

EverC considers the following changes to be backwards-compatible:

- Adding new API resources.
- Adding new optional request query parameters to existing API methods.
- Adding support for new media types (e.g. via the Content-Type Header)
- Adding new properties to existing API responses.

- Changing the order of properties in existing API responses.
- Modifying Name field for Enum types
- Adding new values to the following Enum types: Finding Type, Finding Category, Event Type, Dispute Status, Finding Status, Node Type, Edge Type, Callback Type, Card Type

Callbacks will follow the same rules as standard API responses. For more information about API changes, please see the release notes that are coupled with every MerchantView upgrade.

Support

Our technical support staff stands by ready to assist you with any API support requests or questions. For support requests and questions regarding this API please contact support@everc.com.

Getting Started

The Ongoing Workflow

This section explains the merchant entity life-cycle within the EverC system. Each step and object in the flow is later explained in this document.

1. **Log in** into the system
2. **Create** merchant within the EverC system using the **Quick Insights** scan type in the requestscantype field.
    a. The Quick Insights scan is EverC's Onboarding solution that provides insights about the merchant and aids in the assessment of its risk before adding it into the portfolio.
    b. It also can use the WebID mechanism to retrieve a URL for the merchant, if one was not provided.
    c. Once the scan is completed, API callbacks will be sent to your system.
    d. After the Quick Insights scan is completed, a merchant can be added into the monitored portfolio automatically or manually, per account configuration on EverC's side.
3. **Ongoing Monitoring** – After onboarding the merchant into the monitored portfolio the merchant will receive Monitoring scans on a regular basis according to the defined SLA, no API call necessary.

Quick Insights

After onboarding a merchant through Quick Insights, you will receive the following information about the merchant:

- Content findings by risk levels (Critical, High, Medium, Low, No risk per the account Risk Matrix setup)
- URL Detection (if no URL was entered and the account has WebID in its package)

- Availability findings (e.g. online, offline)
- Specialty MCC classification (And Global MCC detection and mismatch if included in package)
- Classification of redirect targets
- Rank from reputation websites
- Popularity rank
- URL Attributes
- Country of operation

Merchant Management

A merchant is the core entity in the EverC system. The merchant entity represents a client or a business in your company's portfolio. A merchant entity can have one or more reported websites. The information provided is used to assess the selected merchant's risk.

This guide will explain how to create and manage a merchant via the API.

Creating a Merchant

`POST /api/v4/merchants`

Create a new Merchant Object.

- To create a new merchant, use the create merchant endpoint and provide the relevant merchant information.
- The minimum required information for creating a merchant is the merchant Legal Name, its Unique ID in your system and at least one URL (If the account has WebID included for EverC to detect the URL, the mandatory fields are Legal name and Unique ID).
- Additional information may be provided in order to increase the coverage of merchant findings and the precision of the risk assessment. To learn more about the different types of information Any additional merchant information, such as the contact phone and email will enhance the scan results and it is highly recommended to include as many details as possible when creating a merchant. See the Merchant Object for a list of all merchant input fields.
- When trying to add a new merchant with an existing Unique ID, the new details will be added to the existing merchant, but no new merchant will be created.
- You can send up to 100 merchants for uploading in a single API call. If more than 100 merchants are entered in the call, an error is returned with the message: "Only 100 merchants can be uploaded in a single API call. Please reduce the number of merchants and try again"
- Add the scan parameter to scan the new merchant when it is created by filling in the requestScanType field with quick_insights. This sends the merchant to be scanned as soon as it is created and is best practice.
- It is possible to send the same merchant multiple times a day

- Existing merchants will be scanned in the regular Monitoring cycle.
- A successful request response will contain the newly-created Merchant Object.

```
curl "https://{{customer name}}.everc.com/api/v4/merchants"
  -H "Authorization: Bearer <TOKEN>"
  -H "Content-Type: application/json"
  -H "Accept: application/json"
  -X POST
  -d '{ \
    "requestScanType":"boarding",
    "legalName":"merchant_evoqq3wx",
    "uniqueId":"d67b2095-73f6-164b-979a-e64e351c6cad",
    "assignedOwner":"JohnJ",
    "urls":[{
      "url":"http://mywebsiteurl1.com/",
      "urlType":"website",
      "mid":"FD156DSD1",
      "dba":"merchant_r0fm7zpe DBA"
    }],
    "addresses":[{
        "country": "US",
        "infoType": "business",
        "city": "Springfield",
        "postalCode": "450211AZ",
        "state": "CA",
        "line1": "85 Broad St, 18th Floor",
        "line2": "Apt. 1805"
    }],
    "emails":[{
    "email":"my@mywebsiteurl1.com",
    "infoType":"business"
  }],
  "phones":[{
    "phone":"+1 (734) 555 1213",
    "infoType":"business"
  },{
    "phone":"+1 (734) 555 1217",
    "infoType":"owner"
  }],
  "aliases":[]

  }'
```

This returns the newly created Merchant object:


```
201 Created
{  "scanId": "32d9c285b6c70cf517f060b01f2a89ce",
  "legalName": "merchant_evoqq3wx",
  "uniqueId": "d67b2095-73f6-164b-979a-e64e351c6cad",
  "assignedOwner":"JohnJ",
  "note": null,
  "id": "78fd6a923fcd548ec17fadd516fe85c0",
  "href": "/api/v4/merchants/78fd6a923fcd548ec17fadd516fe85c0",
  "created": "2018-06-14T07:36:37Z",
  "merchantStatus": "monitoring",
  "active": true,
  "monitoring": true,
  "merchantRisk": null,
  "riskQuantifier": null,
  "lastScanned": null,
  "urls": [
      {
          "id": "556023763968107l6aaaba2416abdc09",
          "href":
"/api/v4/merchants/78fd6a923fcd548ec17fadd516fe85c0/urls/556023763968107l6aaaba2416abdc09",
          "created": "2018-06-14T07:36:37Z",
          "url": "http://mywebsiteurl1.com/",
          "urlType": "website",
          "mid": "FD156DSD1",
          "dba": "merchant_r0fm7zpe DBA",
          "active": true,
          "mcc": null
      }
  ],
  "phones": [
      {
          "id": "bb9a239eac638b8ba2edb91736c506d8",
          "href":
"/api/v4/merchants/78fd6a923fcd548ec17fadd516fe85c0/phones/bb9a239eac638b8ba2edb91736c506d8",
          "created": "2018-06-14T07:36:37Z",
          "phone": "+1 734-555-1213",
          "infoType": "owner"
      },
      {
```

```
            "id": "2bf4d87b44fbf66af178c2e7fde62258",
            "href":
"/api/v4/merchants/78fd6a923fcd548ec17fadd516fe85c0/phones/2bf4d87b44fbf66af178c2e7fde62258",
            "created": "2018-06-14T07:36:37Z",
            "phone": "+1 734-555-1217",
            "infoType": "business"
        }
    ],
    "emails": [
        {
            "id": "6474fcd809113884abdfa575baed6e46",
            "href":
"/api/v4/merchants/78fd6a923fcd548ec17fadd516fe85c0/emails/6474fcd809113884abdfa575baed6e46",
            "created": "2018-06-14T07:36:37Z",
            "email": "my@mywebsiteurl1.com",
            "infoType": "business"
        }
    ],
    "aliases": [],
    "addresses": [
        {
            "id": "03767201f1cce3f8573aabedd35d5342",
            "href":
"/api/v4/merchants/78fd6a923fcd548ec17fadd516fe85c0/addresses/03767201f1cce3f8573aabedd35d5342
",
            "created": "2018-06-14T07:36:37Z",
            "line1": "85 Broad St, 18th Floor",
            "line2": "Apt. 1805",
            "city": "Springfield",
            "state": "CA",
            "postalCode": "450211AZ",
            "country": "US",
            "infoType": "business"
        }
    ]
}
```


Retrieving a Merchant

`GET /api/v4/merchants/<MerchantID>`

Retrieve a Merchant Object by its ID.

`GET /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]`
Retrieve an array of multiple Merchant Objects by their IDs.

Search Merchants

Search for merchants in the portfolio. Returns merchant object with all searched fields, e.g. risk score, findings, etc.

`GET /api/v4/merchants`
Retrieve a Search Results Object containing all merchants.

`GET /api/v4/merchants?<parameters>`
Retrieve a Search Results Object containing merchants, according to filters, sorting, and pagination.

Without search parameters, all merchants (including merchants that were removed from the portfolio) will be returned.

Fields

`?fields=all|<Field>[,...]`

A specification of which Merchant Object Fields should be returned. If ?fields=all, all fields are returned.

The default fields scheme is `?fields=all`

Inclusion of Nested Objects

`?include=all|info|urls|scans|<NestedObject>[,...]`

A specification of which Merchant Object Nested Objects should be returned.
If `?include=info`, all contact information objects are returned.
If `?include=urls`, URLs are returned.
If `?include=scans`, all completed scans are returned.
If `?include=all`, all nested objects are returned.

By default, nested objects are not returned.

Filtering Parameters

`?<Filter>=<Value>[&...]`

Supported filter parameters are:

Filter	Accepted Values	Multiple Comma-Separated Values Accepted	Description
`legalName`	String	✓	

`uniqueId`	String	✓	
`url`	String	✓	
`merchantRisk`	String:Risk Level	✓	Returns merchants with the selected risk levels
`findingType`	String:Finding Type	✓	Returns merchants with the selected finding types
`findingCategory`	String:Finding Category	✓	Returns merchants with the selected finding categories
`active`	`true`, `false`	X	`true` returns merchants in the portfolio (both monitored and unmonitored), `false` returns pending merchants and merchants that were removed from the portfolio
`monitoring`	`true`, `false`	X	`true` returns monitored merchants, `false` returns unmonitored merchants
`lastScanned`	`<Date>`, `<Date>`	✓	Returns only merchants whose last completed scan occurred within the specified range, for example:

			`"lastScanned": ">2019-11-29,<2020-01-29"`
`onlyLatestScan`	`true, false`	X	Returns only the merchants whose latest completed scan satisfies all the criteria specified by the other filters (default = `true`)
`isMerchantUrl`	`true, false`	X	Returns only the merchants whose reported websites satisfy all the criteria specified by the other filters (default = `false`)

Sorting Parameters

`?sort=[+|-]<Field>[,...]`

Supported sorting parameters:

Field	Description
`created`	The date and time on which the merchant was created
`active`	Indicates whether a merchant is active
`monitoring`	Indicates whether a merchant is monitored
`merchantRisk`	The merchant's current risk level
`lastScanned`	The merchant's last scan date
`riskQuantifier`	The merchant's current risk quantifier

`legalName`	The name of the merchant
`uniqueId`	The ID of the merchant, set by the customer

The default sorting scheme is `?sort=-monitoring,-merchantRisk,-riskQuantifier`

Boolean fields are sorted with false first when ascending, and true first when descending.
Special value fields like `merchantRisk` are sorted according to the order of their appearance in the Field Values section.

Pagination Parameters `?limit=<Limit>&offset=<Offset>`

Pagination is supported using the following parameters:

Parameter	Default Value	Maximum Value	Description
`limit`	`20`	`1000`	Page size
`offset`	`0`		The starting position of the page

```
curl "https://{{customer
name}}.everc.com/api/v4/merchants?legalName=ABC%20Tech&include=urls&limit=10&sort=merchantRisk
"
  -H "Authorization: Bearer <TOKEN>"
  -H "Accept: application/json"
  -X GET
```

This returns the filtered list results:

```
200 OK
{
    "total": 1,
    "merchants": [
        {
          "id": "d422498a52ddb478082972902fe6a1c6",
          "href": "/api/v4/merchants/d422498a52ddb478082972902fe6a1c6",
          "created": "2016-11-29T15:35:21.307Z",
```

```
          "active": true,
          "monitoring": false,
          "legalName": "ABC LLC",
          "uniqueId": "mer_0000001",
          "merchantRisk": null,
          "riskQuantifier": null,
          "lastScanned": null,
          "aliases": [],
          "addresses": [],
          "emails": [],
          "phones": [],
          "urls": [
            {
              "id": "d422498a52ddb478082972902fe6aasd",
              "href":
"/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/urls/d422498a52ddb478082972902fe6aasd",
              "created": "2016-11-29T15:35:21.307Z",
              "url": "http://urlsrus.com/",
              "urlType": "website",
              "mid": "123424abc",
              "dba": "ABC HK OFfice",
              "active": true
            }
          ]
        }
    ],
    "offset": 0,
    "limit": 10
```


Retrieve Merchant Scans

`GET /api/v4/merchants/<MerchantID>/scans`
Retrieve all scans of a merchant.

`GET /api/v4/merchants/<MerchantID>/scans/latest`
Retrieve the latest scan of a merchant.

`GET /api/v4/merchants/<MerchantID>/scans/<ScanID>`
Retrieve a specific scan of a merchant.

`GET /api/v4/merchants/<MerchantID>/scans/<ScanID1>,<ScanID2>[,...]`
Retrieve multiple scans of a merchant.

`GET /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]/scans`
Retrieve all scans of multiple merchants.

`GET /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]/scans/latest`
Retrieve the latest scan of multiple merchants.

`GET /api/v4/merchants/<MerchantID>/scans/<ScanID>/network`
Retrieve the network (see Network Object) of a merchant as detected in the scan

```
curl "https://{{customer
name}}.everc.com/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/scans/d422498a52ddb47808297
2902fe6aasd"
  -H "Authorization: Bearer <TOKEN>"
  -H "Accept: application/json"
  -X GET
```

This will return the requested Scan Object:

```
200 OK
{
  "id": "d422498a52ddb478082972902fe6aasd",
  "href":
"/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/scans/d422498a52ddb478082972902fe6aasd",
  "created": "2016-11-29T15:35:21.307Z",
  "scanType": "monitoring",
  "scanRisk": "critical",
  "riskQuantifier": 1,
  "scanStatus": "completed",
  "total": 1,
  "scanItems": [
    {
    "id": "d422498a52dffc78082972902fe6aasd",
    "urlRisk": "critical",
    "riskQuantifier": 1,
    "isMerchantUrl": true,
    "url": "www.merchantwebsite.com",
    "link":
"/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/urls/d422498a52ddb478082972902fe6aaaa",
    "total": 1,
    "findings": [
        {
            "id": "4422498a52dffc78082972902fe6aasd",
```

```
            "findingRisk": "critical",
            "findingType": "pharmaceuticals",
            "findingName": "Pharmaceuticals",
            "findingCategory": "content",
            "findingCategoryName": "Content"
        }
        ]
    }
  ]
}
```


Updating a Merchant

A merchant ID is required to update merchant's information.

- To update a merchant's identifying information (Legal Name or Unique ID) use the update merchant request - `PUT /api/v4/merchants/<ID>` You can modify one or more fields of the Merchant Object.
    - The UniqueID, as it appears in your system, acts as a unique key. This means that you cannot change it to a parameter that already exists, or merge two merchants under the same UniqueID or Legal Name. It is a one-to-one relation; one Legal Name for one Unique ID.
    - To update a merchant's contact information (aliases, email addresses, etc.) use the relevant call from the Merchant contact information section.
    - To update the merchant URLs, see Merchant URLs section.
    - Sending unrecognized fields will result in a `400 Bad Request` error.

To update the URLs which are associated with a merchant, use the update URL call. Note that you can update the URL Type, MID and DBA fields, but you cannot update the URL string itself. To change the URL string, delete the relevant URL object and then add the new URL object with the current URL string.

Deboarding a Merchant

`DELETE /api/v4/merchants/<MerchantID>`
Delete a Merchant Object

`DELETE /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]`
Delete multiple Merchant Objects.

Deboarding a merchant removes the merchant from the portfolio and deletes all URLs added to it. When deboarding a merchant, the system performs a "soft-delete" - the merchant will still exist in the system but will be marked as inactive, sets the merchant's `active` field to `false` and `merchantStatus` to `deleted`.

Once a merchant is deboarded it won't be actively monitored anymore. However, you can always pull merchant information as well as past findings and risk assessment.

You can request to scan a deboarded merchant with a Quick Insights scan in order to return it to the portfolio.

Start and stop monitoring merchants

You can stop monitoring merchants at any stage. When you stop monitoring a merchant, its URLs, past findings and risk assessment will still remain available.

This action will result in the requested merchants' monitoring field to be set to false and merchantStatus to portfolio_not_monitored.

After you stop monitoring a merchant, you can start monitoring it again at any time:

`PUT /api/v4/merchants/<MerchantID>/monitoring`
Starts ongoing monitoring for a merchant.

`PUT /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]/monitoring`
Starts ongoing monitoring for multiple merchants.

This action results in the requested merchants' `monitoring` field to be set to true and `merchantStatus` to `monitoring`.

This action is allowed only for merchants whose monitoring was stopped. It is not allowed for merchants that have not yet been onboarded, merchants that are already in Monitoring status, deboarded merchants, or merchants that have no URLs. An attempt to start monitoring these merchants will result in `409 Conflict`.

Merchant URLs

Add a URL to a Merchant

`POST /api/v4/merchants/<MerchantID>/urls`
Creates a URL Object for the merchant.

When a new URL is added to an existing merchant, a new Quick Insights scan will be created.

```
curl "https://{{customer
name}}.everc.com/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/urls"
```

```
  -H "Authorization: Bearer <TOKEN>"
  -H "Content-Type: application/json"
  -H "Accept: application/json"
  -X POST
  -d '{ \
    "url": "http://urlsrus.com/", \
    "urlType": "website", \
    "mid": "123424abc", \
    "dba": "URLs R Us" \
  }'
```

This returns the newly-created URL object:

```
201 Created
{
  "id": "d422498a52ddb478082972902fe6aasd",
  "href":
"/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/urls/d422498a52ddb478082972902fe6aasd",
  "created": "2016-11-29T15:35:21.307Z",
  "url": "http://urlsrus.com/",
  "urlType": "website",
  "mid": "123424abc",
  "dba": "URLs R Us",
  "active": true
}
```

Retrieve Merchant URLs

`GET /api/v4/merchants/<MerchantID>/urls`
Retrieve all URLs of a merchant.

`GET /api/v4/merchants/<MerchantID>/urls/<URLID>`
Retrieve a specific URLs of a merchant.

`GET /api/v4/merchants/<MerchantID>/urls/<URLID2>,<URLID2>[,...]`
Retrieve multiple specific URLs of a merchant.

`GET /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]/urls`
Retrieve all URLs of a merchant.

```
curl "https://{{customer
name}}.everc.com/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/urls/d422498a52ddb478082972
```

```
902fe6aasd"
  -H "Authorization: Bearer <TOKEN>"
  -H "Accept: application/json"
  -X GET
```

This will return the URL Object:

```
200 OK
{
  "id": "d422498a52ddb478082972902fe6aasd",
  "href":
"/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/urls/d422498a52ddb478082972902fe6aasd",
  "created": "2016-11-29T15:35:21.307Z",
  "url": "http://urlsrus.com/",
  "urlType": "website",
  "mid": "222222abc",
  "dba": "URLs R Us NextGen",
  "active": true
}
```

Update Merchant URLs

```
PUT /api/v4/merchants/<MerchantID>/urls/<URLID>
```

Updates a URL Object for the merchant.

```
curl "https://{{customer
name}}.everc.com/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/urls/d422498a52ddb478082972
902fe6aasd"
  -H "Authorization: Bearer <TOKEN>"
  -H "Content-Type: application/json"
  -H "Accept: application/json"
  -X PUT
  -d '{ \
    "mid": "222222abc", \
    "dba": "URLs R Us NextGen" \
  }'
```

This returns the updated URL object:

```
200 OK
{
  "id": "d422498a52ddb478082972902fe6aasd",
  "href":
"/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/urls/d422498a52ddb478082972902fe6aasd",
  "created": "2016-11-29T15:35:21.307Z",
  "url": "http://urlsrus.com/",
  "urlType": "website",
  "mid": "222222abc",
  "dba": "URLs R Us NextGen",
  "active": true
}
```

Changing the url field is not allowed, and will result in a 400 Bad Request.

Delete Merchant URLs

`DELETE /api/v4/merchants/<MerchantID>/urls/<URLID>`
Deletes a merchant's URL Object.

`DELETE /api/v4/merchants/<MerchantID>/urls/<URLID1>,<URLID2>[,...]`
Deletes multiple URL Objects belonging to the merchant.

Perform a soft-delete of the URLs with a specified ID or IDs. This sets the URLs' active field to false. From that point on, the URLs won't be visible in listings. Deleting a URL changes the risk of the merchant that was associated with it. The next callback will return the new risk. You can always see the risk history in the MerchantView UI.

Deleting all of a merchant's URLs will remove the merchant from the portfolio.

```
curl "http://{{customer
name}}.everc.com/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/urls/d422498a52ddb478082972
902fe6a333"
  -H "Authorization: Bearer <TOKEN>"
  -X DELETE
```

This returns a confirmation of the action

```
204 No Content
```

Merchant Contact Information

Retrieve Merchant Contact Information

`GET /api/v4/merchants/<MerchantID>/addresses`
Retrieve all addresses of a merchant.

`GET /api/v4/merchants/<MerchantID>/aliases`
Retrieve all aliases of a merchant.

`GET /api/v4/merchants/<MerchantID>/emails`
Retrieve all emails of a merchant.

`GET /api/v4/merchants/<MerchantID>/phones`
Retrieve all phone numbers of a merchant.

`GET /api/v4/merchants/<MerchantID>/addresses/<AddressID>`
Retrieve a specific address of a merchant.

`GET /api/v4/merchants/<MerchantID>/aliases/<AliasID>`
Retrieve a specific alias of a merchant.

`GET /api/v4/merchants/<MerchantID>/emails/<EmailID>`
Retrieve a specific email of a merchant.

`GET /api/v4/merchants/<MerchantID>/phones/<PhonesID>`
Retrieve a specific phone number of a merchant.

`GET /api/v4/merchants/<MerchantID>/addresses/<AddressID1>,<AddressID2>[,...]`
Retrieve specific addresses of a merchant.

`GET /api/v4/merchants/<MerchantID>/aliases/<AliasID1>,<AliasID2>[,...]`
Retrieve specific aliases of a merchant.

`GET /api/v4/merchants/<MerchantID>/emails/<EmailID1>,<EmailID2>[,...]`
Retrieve specific emails of a merchant.

`GET /api/v4/merchants/<MerchantID>/phones/<PhonesID1>,<PhonesID2>[,...]`
Retrieve specific phone numbers of a merchant.

`GET /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]/addresses`
Retrieve all addresses of a merchant.

`GET /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]/aliases`
Retrieve all aliases of a merchant.

`GET /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]/emails`
Retrieve all emails of a merchant.

`GET /api/v4/merchants/<MerchantID1>,<MerchantID2>[,...]/phones`
Retrieve all phones of a merchant.

```
curl "https://{{customer
name}}.everc.com/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/aliases/d422498a52ddb478082
972902fe6aasd"
  -H "Authorization: Bearer <TOKEN>"
  -H "Accept: application/json"
  -X GET
```

This returns the Alias Object:

```
200 OK
{
  "id": "d422498a52ddb478082972902fe6aasd",
  "href":
"/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/aliases/d422498a52ddb478082972902fe6aasd",
  "created": "2016-11-29T15:35:21.307Z",
  "alias": "John Smith Enterprises Inc.",
  "infoType": "owner"
}
```

Add Contact Information

`POST /api/v4/merchants/<MerchantID>/addresses`
Creates an Address Object for the merchant.

`POST /api/v4/merchants/<MerchantID>/aliases`
Creates an Alias Object for the merchant.

`POST /api/v4/merchants/<MerchantID>/emails`
Creates an Email Object for the merchant.

`POST /api/v4/merchants/<MerchantID>/phones`
Creates a Phone Object for the merchant.

curl "https://{{customer
name}}.everc.com/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/aliases"

```
 -H "Authorization: Bearer <TOKEN>"
 -H "Content-Type: application/json"
 -H "Accept: application/json"
 -X POST
 -d '{ \
   "alias": "John Smith Holdings Inc.", \
   "infoType": "owner" \
 }'
```

This will return the newly-created Alias Object:

```
201 Created
{
  "id": "d422498a52ddb478082972902fe6aasd",
  "href":
"/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/aliases/d422498a52ddb478082972902fe6aasd",
  "created": "2016-11-29T15:35:21.307Z",
  "alias": "John Smith Holdings Inc.",
  "infoType": "owner"
}
```

Update Contact Information

`PUT /api/v4/merchants/<MerchantID>/addresses/<AddressID>`
Update an Address Object for the merchant.

`PUT /api/v4/merchants/<MerchantID>/aliases/<AliasID>`
Update an Alias Object for the merchant.

`PUT /api/v4/merchants/<MerchantID>/emails/<EmailID>`
Update an Email Object for the merchant.

`PUT /api/v4/merchants/<MerchantID>/phones/<PhoneID>`
Update a Phone Object for the merchant.

Delete Contact Information

`DELETE /api/v4/merchants/<MerchantID>/addresses/<AddressID>`
Delete an Address Object for the merchant.

`DELETE /api/v4/merchants/<MerchantID>/addresses/<AddressID1>,<AddressID2>[,...]`
Delete multiple Address Objects for the merchant.

`DELETE /api/v4/merchants/<MerchantID>/aliases/<AliasID>`
Delete an Alias Object for the merchant.

`DELETE /api/v4/merchants/<MerchantID>/aliases/<AliasID1>,<AliasID2>[,...]`
Delete multiple Alias Objects for the merchant.

`DELETE /api/v4/merchants/<MerchantID>/emails/<EmailID>`
Delete an Email Object for the merchant.

`DELETE /api/v4/merchants/<MerchantID>/emails/<EmailID1>,<EmailID2>[,...]`
Delete multiple Email Objects for the merchant.

`DELETE /api/v4/merchants/<MerchantID>/phones/<PhoneID>`
Delete a Phone Object for the merchant.

`DELETE /api/v4/merchants/<MerchantID>/phones/<PhoneID1>,<PhoneID2>[,...]`
Delete multiple Phone Objects for the merchant.

Delete the contact information with a specified ID or IDs. Once deleted, the contact information is no longer accessible.

```
curl "http://{{customer
name}}.everc.com/api/v4/merchants/d422498a52ddb478082972902fe6a1c6/alias/d422498a52ddb47808297
2902fe6a443"
  -H "Authorization: Bearer <TOKEN>"
  -X DELETE
```

This will return a confirmation on the action

```
204 No Content
```

Merchant Findings

Retrieve a Finding

`GET /api/v4/findings/<FindingID>`
Retrieve the Finding object.

```
curl "https://{{customer name}}.everc.com/api/v4/findings/d422498a52ddb478082972902fe6a1as"
  -H "Authorization: Bearer <TOKEN>"
```

```
  -H "Accept: application/json"
  -X GET
```

This returns the Finding object:

```
200 OK
{
  "id": "d422498a52ddb478082972902fe6aasd",
  "findingRisk": "high",
  "findingType": "pharmaceuticals",
  "findingName": "Pharmaceuticals",
  "findingCategory": "content",
  "findingCategoryName": "Content",
  "findingStatus": "not_checked"
}
```

Edit a Finding

To add notes to the finding for future reference you can add / edit the `reviewerNotes` field. The note will remain with the finding as long as it is relevant for the website, even if other findings are added / removed. The note can contain up to 1,000 characters.

To change the handling status for the finding, edit the `findingStatus` field to reflect the current work status.

The `disputed` finding status indicates that a dispute was opened for this finding. The `disputed` finding status will not be editable until the dispute is resolved.

```
curl "https://{{customer name}}.everc.com/api/v4/findings/d422498a52ddb478082972902fe6a1c6"
  -H "Authorization: Bearer <TOKEN>"
  -H "Content-Type: application/json"
  -H "Accept: application/json"
  -X PUT
  -d '{ \
    "reviewerNotes": "Talked to the merchants, issue is under ", \
    "uniqueId": "mer_0000001" \
  }'
```

This returns the updated object:

```
201 Created
{
  "id": "d422498a52ddb478082972902fe6a1c6",
  "href": "/api/v4/merchants/d422498a52ddb478082972902fe6a1c6",
  "created": "2016-11-29T15:35:21.307Z",
  "active": true,
  "monitoring": false,
  "legalName": "Merchant LLC",
  "uniqueId": "mer_0000001",
  "merchantRisk": null,
  "riskQuantifier": null,
  "lastScanned": null,
  "aliases": [],
  "addresses": [],
  "emails": [],
  "phones": [],
  "urls": []
}
```

Edit Finding Status and Reviewer Notes

Users can edit a merchant's finding status to the following values: `'not_checked', 'in_progress', 'allowed', 'remediated', 'review_completed'`, and `'rejected'` and add free text notes to the merchant (for example, to explain the reasons for the change).

```
PUT /api/v4/findings/<findingID>
```

Input parameters:
`reviewerNotes` *String*
Free text of the new reviewer note
`findingStatus` *Finding Status*
The new finding status.

Possible values for `findingStatus`:

- `not_checked`
- `in_progress`
- `allowed`
- `remediated`
- `review_completed`
- `rejected`

The finding status can be changed only if the current status is one of the possible values. Otherwise the system returns a 400 Bad Request error.

Retrieve Finding Evidence

`GET /api/v4/findings/<FindingID>/evidence`
All finding Evidence objects associated with the finding are retrieved.

If multiple evidence types exist for the requested finding, all evidence is returned in the JSON list in the HTTP response.

Evidence could be screenshots, text, links and more detailed under the Evidence object.

```
curl "https://{{customer
name}}.everc.com/api/v4/findings/d422498a52ddb478082972902fe6aasd/evidence"
  -H "Authorization: Bearer <TOKEN>"
  -H "Accept: application/json"
  -X GET
```

Retrieve Risk Matrix

`POST /api/v4/riskMatrix/`
Retrieve the risk severity levels of finding categories.

The Risk Matrix is the configuration mechanism that controls the risk level that is automatically assigned to each finding category.

A finding category can have a different risk level for reported vs. unreported domains. For example, the "Alcohol" finding type may have a "High" risk severity in reported domains, and a "Low" risk severity if found in an Unreported domain.

Possible Input Parameters

- Retrieve a single category by entering it in the call: categories: ["categoryName"]
- Retrieve multiple categories by separating them with commas: categories: ["categoryName1","categoryName2"]
- Retrieve all categories by leaving the 'categories' field empty: categories: [""]

The response will return the category object with details of the category's registered and unregistered severity levels.

Category Object

Field	Description	Possible Values
`categoryName`	The name of the category	
`categoryDescription`	The description of the category	
`registeredSeverity`	The risk severity of the category when detected on reported domains	no risk, low, medium, high, critical
`unregisteredSeverity`	The risk severity of the category when detected on unreported domains	no risk, low, medium, high, critical
`changeDate`	The date of the last change to the category's settings	

Edit Risk Matrix

By default, MerchantView uses a standard risk matrix recommended by EverC, which was designed considering federal law, market standards, and business policies to provide a unified and clear indication of the risk a finding poses. You can customize the default configuration to better accommodate your organization's rules and policies and the risk management guidelines in your organization.

Possible Input Parameters

`POST /api/v4/riskMatrix/edit/`
Enter the new severity value in the following fields:

Field	Editable	Description	Possible Values
`categoryName`	Read only	The name of the category	
`registeredSeverity`	Editable	The risk severity of the category when detected on reported domains	no risk, low, medium, high, critical
`unregisteredSeverity`	Editable	The risk severity of the category when detected on unreported domains	no risk, low, medium, high, critical

Response
Returns the category object with the updated category risk settings:

Field	Description
`categoryName`	The name of the category
`categoryDescription`	The description of the category
`registeredSeverity`	The risk severity of the category when detected on reported domains
`unregisteredSeverity`	The risk severity of the category when detected on unreported domains

API Reference

HTTP Headers

When accessing the API resources, set HTTP headers according to the method you are invoking.

`GET, DELETE`

Header	Value
Authorization	Bearer <TOKEN>
Accept	application/json

`POST, PUT`

Header	Value
Authorization	Bearer <TOKEN>
Content-Type	application/json

Accept	application/json

HTTP Response Codes

2xx Success

This class of status codes indicates the action requested by the client was received, understood and accepted.

Code

`200 OK`
The request was successful

`201 Created`
The requested object has been created

`204 No Content`
The 'Delete' operation was successful

4xx Client Errors

This class of status codes is intended for situations in which the error seems to have been caused by the client.

Code

`400 Bad Request`
One or more request parameters or field values is incorrect

`401 Unauthorized`
Unauthorized request

`404 Not Found`
One or more of the requested objects doesn't exist

`405 Method Not Allowed`
The method of the request isn't available for this resource

`408 Request Timeout`
The server timed out waiting for the request. The client may repeat the request without modifications at any later time

`409 Conflict`
The request is valid, however it creates a conflict, for instance attempting to create the same merchant twice

5xx Server Errors

The server failed to fulfil a request.

Code

`500 Internal Server Error`
The request has failed due to a failure on the API server

`502 Bad Gateway`
The server was acting as a gateway or proxy and received an invalid response from the upstream server

`503 Service Unavailable`
The API server is undergoing maintenance

Error Structure

Fields

`extendedMessage` *Array of errors*
extended information about the error, if available

`message` *String*
A short message describing the nature of the error

`status` *Integer*
The HTTP status code of the message

Errors

Fields

`errorValue`
The value of the error, e.g. illegalId. (can be null)

`Field`
The field containing the error

`Message`
A string describing the error, e.g. Unsupported field, ID(s) not found.

Specific Error Descriptions

A merchant was entered in the 'Update Merchant' API call with the wrong merchant ID

Fields

`Message`
Null

`Status`
404 Not Found

Errors

Fields

`errorValue`
illegalId

`Field`
id

`Message`
ID(s) not found

A merchant's Unique ID was entered with an invalid format - over 255 characters.

Fields

`Message`
Invalid/Malformed data.

`Status`
400 Bad Request

A merchant was created but the URL field was not filled.

Fields

`Message`
1 Merchants have incomplete data. Missing URL

`Status`

Merchant details were updated using the wrong format of input fields: email, URL, phone, etc.

Fields

`Message`
The request was not in the expected format.

`Status`
400 Bad Request

Errors

Fields

`errorValue`
Null

`Field`
emails, urls, phones, addresses, etc.

`Message`
Unsupported field

Error code example:

```
"extendedMessage":
        {
            "errors": [
                {
                    "errorValue": null,
                    "field": "emails",
                    "message": "Unsupported field"
                },
                {
                    "errorValue": null,
                    "field": "urls",
                    "message": "Unsupported field"
                },
                {
                    "errorValue": null,
                    "field": "addresses",
                    "message": "Unsupported field"
                },
                            ],

    "message": "The request was not in the expected format.",
    "status": 400;
```

Login and Logout

Logging In

`POST /api/v4/login`

Send a Login Object to receive a Session Object with a session token. This is the only request you can send without the `Authorization` header.

```
curl "https://{{server name}}.everc.com/api/v4/login"
  -H "Content-Type: application/json"
  -H "Accept: application/json"
  -X POST
  -d '{ \
```

```
    "username": "user", \
    "password": "password", \
  }'
```

This returns the session object

```
200 OK

{

    "username": "user",

    "roles": ["ROLE_ADMIN"],

    "token_type": "Bearer",

    "access_token": "qmliip4cuqgvciro6a11fg5ibofs8u95"

}
```

Logging Out

```
POST /api/v4/logout
```

Send an empty request in order to revoke the session token.

```
200 OK
{
    "timestamp": 1562491748643,
    "status": 200,
    "error": "OK",
    "message": "No message available",
    "path": "/MerchantViewServer/api/v4/logout"
```

Callbacks

A Callback object will be sent to your system for Quick Insights and Monitoring scans when they are completed.

A single callback will be sent for each scanned merchant and will include the scan results of all the URLs connected to that merchant.

The MerchantView API supports callback endpoints through REST and AWS SQS.

To configure callbacks to your system contact EverC Support at support@everc.com and provide the following information:

REST

- Authentication method
- endpoint for receiving the callbacks

AWS SQS

Contact EverC Support to receive the EverC AWS Account ID, and provide the following information:

- S3 bucket name – the bucket name where the message payload will be saved for long messages.
- SQS Queue name – the queue name to receive the callback.
- Role name – the name of the role that the client assigned to EverC for cross-account permissions.
- Account ID – the account ID of the client where the permissions were granted.
- Region – The region within the AWS account where the SQS and S3 Bucket are located.

AWS SQS has a max message length of 256k. To support longer messages we will send a message that contains a reference to a message payload in the AWS S3 bucket.

Example:


```
{
  "callbacks": [
    {
      "callbackType": "MERCHANT_SCAN_AVAILABLE",
      "callbackObject": {
        "id": "5798700eb00f7e68761f1c0557075ec7",
        "href":
"/api/v4/merchants/42b9165ff50bad8a3b87279f6e7d02f3/scans/5798700eb00f7e68761f1c0557075ec7",
        "created": "2023-11-08T10:35:07",
        "delivered": "2023-11-08T10:35:12",
        "scanType": "quick_insights",
        "total": 1,
        "scanItems": [
          {
            "id": "66717b24392e1dc9d76c7a1ca81535d5",
```

```
            "isMerchantUrl": true,
            "url": "http://casino.buzz.ecqa.xyz/",
            "link":
"/api/v4/merchants/42b9165ff50bad8a3b87279f6e7d02f3/urls/1cf3b552397eb6451998878e5752fd76",
            "urlRisk": "critical",
            "riskQuantifier": 1,
            "total": 0,
            "findings": [
              {
                "id": "ba28a39721b1fe16ef13139050d9e900",
                "findingRisk": "critical",
                "findingType": "gambling",
                "findingName": "Gambling",
                "findingCategory": "content",
                "findingCategoryName": "Content",
                "reviewerNotes": null,
                "findingStatus": "not_checked"
              },
              {
                "id": "d0ed286ec0067c53db13b09e064f45a1",
                "findingRisk": "low",
                "findingType": "payment_page",
                "findingName": "Payment Page",
                "findingCategory": "payment_page",
                "findingCategoryName": "Payment Page",
                "reviewerNotes": null,
                "findingStatus": "no_action_required"
              },
              {
                "id": "bb0048cefe6f5e77a1814572c1711e07",
                "findingRisk": "low",
```

```
    "findingType": "online",
    "findingName": "Online",
    "findingCategory": "availability",
    "findingCategoryName": "Availability",
    "reviewerNotes": null,
    "findingStatus": "no_action_required"
  },
  {
    "id": "577e676becbb0c79f40b9184f945f6e9",
    "findingRisk": "no_risk",
    "findingType": "contact_us_page",
    "findingName": "Contact Us Page",
    "findingCategory": "website_section",
    "findingCategoryName": "Site Section",
    "reviewerNotes": null,
    "findingStatus": "no_action_required"
  },
  {
    "id": "b0cf4afce9a402871661bf65ccdd7509",
    "findingRisk": "no_risk",
    "findingType": "privacy_policy_page",
    "findingName": "Privacy Policy Page",
    "findingCategory": "website_section",
    "findingCategoryName": "Site Section",
    "reviewerNotes": null,
    "findingStatus": "no_action_required"
  },
  {
    "id": "69d88ffad49158d7fa2bda800ca40041",
    "findingRisk": "no_risk",
```

```
                "findingType": "terms_and_conditions_page",
                "findingName": "Terms and Conditions Page",
                "findingCategory": "website_section",
                "findingCategoryName": "Site Section",
                "reviewerNotes": null,
                "findingStatus": "no_action_required"
              }
            ]
          }
        ],
        "scanRisk": "critical",
        "riskQuantifier": 1,
        "scanStatus": "completed"
      },
      "merchantUniqueId": "qICallback2O1Ia"
    }
  ]
}
```


Object Reference

The Account Object

Read Only Fields

`id` *String*
The ID of the account

`name` *String*
The name of the account

The Merchant Object

Fields	Description	Example
`legalName` *String* **Required**	The legal name of the merchant under which the merchant is conducting its operations. Free format string (can be digits, letters, URLs). By default, merchants are displayed in the system according to the Legal Name. Customer Success can configure the display name to be based on the unique ID. Limited to 100 characters.	The Flowers Shop
`uniqueId` *String* **Required**	Unique merchant identifier as it appears in your system, used to enable cross referencing between the merchant in EverC systems and your internal systems. Free format string (can be digits, letters, URLs). Limited to 255 characters.	The Flowers Shop
`note` *String* **Optional**	A free-text note, usually for credential–restricted areas within the website. For Internal use only, not displayed in the system.	Username: JennyD, Password: 12345
`mccs` *Array of MCC Integers* **Optional**	A four-digit number from Visa's or Mastercard's MCC list, indicating the merchant's line of business	[5193]
`mids` *Array of MID Strings* **Optional**	The merchant's ID as used in your system. Numerals or letters, no special characters. Limited to 255 characters.	[1234567]
`dbas` *Array of DBA Strings* **Optional**	The merchant's company name ("doing business as"). Free format string (can be digits, letters, URLs). Limited to 255 characters.	[Flowers 4U]
`deboardReason` *String* **Optional**	The reason the merchant was deboarded from the portfolio. Can be one of the following options: Terminated after investigation of findings,	Removed from EverC monitoring

	Removed from EverC monitoring, Terminated due to internal/business reasons, Other	
`assignedOwner` *String* **Optional**	The username of the MerchantView user responsible for managing this merchant	JohnJ

Automatically Generated Fields	**Description**
`id` *String*	Generated by EverC when the merchant is created and is required to perform various operations on the merchant, such as retrieve a merchant, update merchant, etc.
`href` *String*	The URI of the object
`created` *String*	The date and time on which the object was created, encoded in the ISO-8601 format
`active` *Boolean*	Indicates an active merchant (`true` unless merchant has been deleted)
`monitoring` *Boolean*	Indicates if the merchant is being actively monitored by EverC (`true` unless merchant has been deleted)
`merchantRisk` *String:Risk Level*	The merchant's current risk level. Equals the risk level determined by the merchant's last scan
`riskQuantifier` *Integer*	The merchant's current risk quantifier. Equals the risk quantifier determined by the merchant's last scan
`lastScanned` *String*	The date and time of the merchant's last scan, encoded in the ISO-8601 format

Nested Objects	**Description**

urls *Array of URL Object* (default: [ ])	The URLs associated with the merchant. Must be standard URL syntax.
addresses *Array of Address Object* (default: [ ])	The addresses of the merchant
aliases *Array of Alias Object* (default: [ ])	The aliases of the merchant
emails *Array of Email Object* (default: [ ])	The email addresses of the merchant. Standard email syntax. Limited to 100 characters.
phones *Array of Phone Object* (default: [ ])	The phone numbers of the merchant. Country code (including +), area code and phone number.

The URL Object

Fields	Description	Example
url *String*	The merchant's URL in standard URL syntax. EC validates the URL format according to the international list of Top Level Domains. Required for all scan types except WebID scans.	www.flowers.com
urlType *String:URL Type* (default: website)	The URL type; website or mobile app.	website
mid *String*	The Merchant ID associated with the URL. Numerals or letters, no special characters. Limited to 255 characters.	1234567
dba *String*	The merchant's company name ('Doing Business As'). Free format string (can be digits, letters, URLs). Limited to 255 characters.	Flowers 4U

mcc *String*	The URL's MCC, or reported line of business, indicated by a four-digit number from Visa's or Mastercard's MCC list.	1520

Read Only Fields

id *String*
The ID of the object

href *String*
The URI of the object

created *String*
The date and time on which the object was added, encoded in the ISO-8601 format

active *Boolean*
Indicates an active URL (true unless URL has been deleted)

The Address Object

Fields	Description	Example
line1 *String*	The street name, house number and suite number. Limited to 255 characters.	669 Lexington Ave
line2 *String*	Additional address details that were not provided in Address 1 (for example, P.O. Box).Limited to 255 characters.	P.O. Box 5647
city *String*	The full city name (for example, New York and not NY). Limited to 45 characters.	
state *String*	The full state name or the state's initials (New York / NY)	NY
postalCode *String*	Legitimate postal code according to the country. Can contain digits or letters. Limited to 20 characters.	10025

`country` *String*	The full country name or 2-letter initials, in English	US
`infoType` *String:Contact Information Type* (default: `business`)	The content information type; owner or business	business

The address is optional, however if one of the address object fields is filled, then `line1` becomes required. For example, if you enter a country, then you must also enter an address in `line1`.

Read Only Fields

`id` *String*
The ID of the object

`href` *String*
The URI of the object

`created` *String*
The date and time on which the object was added, encoded in the ISO-8601 format

The Alias Object

Fields	Description
`alias` *String*	The merchant's alias
`infoType` *String:Contact Information Type* (default: `business`)	The content information type

Read Only Fields

`id` *String*
The ID of the object

`href` *String*
The URI of the object

`created` *String*
The date and time on which the object was added, encoded in the ISO-8601 format

The Email Object

Fields	Description	Example
`email` *String*	The merchant's email, in standard email syntax. Limited to 100 characters.	info@flowers.com
`infoType` *String:Contact Information Type* (default: `business`)	The content information type	business

Read Only Fields

`id` *String*
The ID of the object

`href` *String*
The URI of the object

`created` *String*
The date and time on which the object was added, encoded in the ISO-8601 format

The Phone Object

Fields	Description	Example
`phone` *String*	The merchant's phone number, including country code (including +), area code and phone	+12127591111

	number, without spaces or hyphens.	
`infoType` *String:Contact Information Type* (default: `business`)	The content information type	business

Read Only Fields

`id` *String*
The ID of the object

`href` *String*
The URI of the object

`created` *String*
The date and time on which the object was added, encoded in the ISO-8601 format

The Scan Object

Nested Objects

`scanItems` *Array of Scan Item Object* (default: `[]`)
The URLs that have been scanned

Read Only Fields

`id` *String*
The ID of the object

`href` *String*
The URI of the object

`created` *String*
The date and time on which the object was created, encoded in the ISO-8601 format

`delivered` *String*
The date and time on which the object was delivered, encoded in the ISO-8601 format

`scanType` *String:Scan Type*
The scan type

`scanRisk` *String:Risk Level*
The risk level determined by this scan. This equals to the highest risk level among the scanned URLs (`scanItems`)

`riskQuantifier` *Integer*
The risk quantifier. This equals to the number of scanned URLs (scanItems) with the highest risk level for this scan (`scanRisk`)

`scanStatus` *String:Scan Status*
The scan state

`total` *Integer*
The number of scan items in scanItems

The Finding Object

Read Only Fields

`reviewerNotes` *String*
Notes inserted by the user (max length: 1000 characters)

`findingStatus` *String:Finding Status*
Current workflow status of the finding

Read Only Fields

`id` *String*
The ID of the object

`findingRisk` *String:Risk Level*
The risk level of this finding

`findingType` *String:Finding Type*
The finding type

`findingName` *String*
The verbose description of this finding

`findingCategory` *String:Finding Category*
The finding category

`findingCategoryName` *String*
The verbose description of this finding's category

The Snooze Object

Fields	Description
`findingStatus` *String:Finding Status*	The status of the finding when the snooze period ends
`period` *Number*	The number of days that the snooze period will last. You can enter the period when creating a snooze object, but you cannot edit it in an existing snooze object.

Read Only Fields

`snoozedDate` *Date*
The date and time the finding was snoozed

`period` *Number*
The number of days remaining until the end of the snooze period

`plannedDate` *Date*
The date and time when the snooze period will end

The Callback Object

Nested Objects

`callbackObject` *Merchant Scan Object*
The scan results of the merchant including the updated risk and all updated categories

Read Only Fields

`callbackType` *String: Callback Type*
The type of callback

`merchantUniqueId` *String*
The unique ID of the relevant merchant

The Scan Item Object

Read Only Fields

`id` *String*
The ID of the object

`urlRisk` *String:Risk Level*
The risk level determined for this URL. This equals to the highest risk level among the findings for this URL (`findings`)

`riskQuantifier` *Integer*
The risk quantifier. This equals to the number of findings (`findings`) with the highest risk level for this scan (`urlRisk`)

`isMerchantUrl` *Boolean*
Indicates whether this is one of the merchant's URLs

`url` *String*
The scanned url

`link` *String*
A link to the URL Object if `isMerchantUrl` is true

`total` *Integer*
The number of findings in `findings`

`assignedOwner` *String*
The username of the MerchantView user responsible for managing this merchant

Nested Objects

`findings` *Array of Finding Objects*
The findings for this URL

The Evidence Object

Read Only Fields

findingId *String*
The id of the finding

findingType *String:Finding Type*
The finding type

findingName *String*
The verbose description of this finding

findingCategory *String:Finding Category*
The finding category

findingCategoryName *String*
The verbose description of this finding's category

contentType *String*
The mimeType of the evidence content

evidenceType *enum:Evidence Type*
The verbose description of the evidence content type

content *String*
Base64-encoded file data

extendedContent *Object: According to the evidenceType*
The content fields of the evidence, depending on the evidence type

Although all evidence types return an evidence object, each type has different fields in the `extendedContent`. Following are all of the evidence types' `extendedContent` fields, with a sample of each.

The Text Evidence Object


```
{
    "findingId": "d422498a52ddb478082972902fe6aasd",
    "findingType": "marijuana_indication",
    "findingName": "Marijuana Indication",
    "findingCategory": "content",
    "findingCategoryName": "Content",
    "contentType": null,
    "evidenceType": "text",
```

```
        "content": null,
        "extendedContent": {
            "text": "for hotels turning to thuds betting on bogota tourism to",
            "sourceUrl": "http://tours.com/travel-intel/global-travel-booms-as-inbound-us-travel-bombs/"
        }
    },
    {
        "findingId": "d422498a52ddb478082972902fe6aasd",
        "findingType": "marijuana_indication",
        "findingName": "Marijuana Indication",
        "findingCategory": "content",
        "findingCategoryName": "Content",
        "contentType": null,
        "evidenceType": "text",
        "content": null,
        "extendedContent": {
            "text": "i hate this product",
            "sourceUrl":
"https://de.trustpilot.com/review/www.elitepartner.de?languages=all&stars=1"

        }
    }
```


Read Only Fields

`text` *String*
The text evidence that was located in the website

`sourceUrl` *String*
The URL where the evidence was located

The Screenshot Evidence Object

The Screenshot Evidence Object


```
[
  {
    "findingId": "d9c8a29b481e1241447ca5b81e4ff1e8",
    "findingType": "academic_fraud",
    "findingName": "Academic Fraud",
    "findingCategory": "content",
```

```
    "findingCategoryName": "Content",
    "contentType": "image/png",
    "evidenceType": "screenshot",
    "content": "iVBORw0KGgoAAAANSUhEUgAAAecAAAJ...",
    "extendedContent": {
      "sourceUrl": null,
      "url": "https://bramscreenshots.s3-us-west-
2.amazonaws.com/%2F18/801911/1161/11_2019_70da32551a867c6f6a692be70956206c4f55b1fc_15743320957
77_Paste_2019-11-21T102810.024Z.png?X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-
Date=20191203T124317Z&X-Amz-SignedHeaders=host&X-Amz-Expires=1799&X-Amz-
Credential=AKIAJ65NVHXO65RM4FEA%2F20191203%2Fus-west-2%2Fs3%2Faws4_request&X-Amz-
Signature=65c95ace5148440543a271f6ece903b03d2e67e57b0564af63f492c09fa1dbfc"
    }
  }
```


Read Only Fields

`url` *String*
The URL where the screenshot is stored

`sourceUrl` *String*
The URL where the evidence was located

The Keyword Evidence Object

The Keyword Evidence Object


```
[
    {
        "findingId": "d422498a52ddb478082972902fe6aasd",
        "findingType": "keywords_matching_critical",
        "findingName": "Keywords Matching Critical",
        "findingCategory": "keyword",
        "findingCategoryName": "keyword",
        "contentType": null,
        "evidenceType": "keyword",
        "content": null,
        "extendedContent": {
            "keyword": "bets",
            "url":
"https://de.trustpilot.com/review/www.elitepartner.de?languages=all&stars=1",
```

```
            "textItems": [
              "trends in luxury travel best bets for jet set amazing",
               "trends in for best jet set amazing",
               "trends in for best set amazing",
               "trends in best set amazing"
            ]
        }
    }
]
```

Read Only Fields

`keyword` *String*
The evidence keyword located in the URL

`url` *String*
The URL where the evidence was located

`textItems` *Array of String*
The text strings in which the keywords were found

The MCC Evidence Object

The MCC Evidence Object

```
[
    {
        "findingId": "5600023ebe892d36bbe7c8c8bbe40a8c",
        "findingType": "_5814",
        "findingName": "5814",
        "findingCategory": "mcc",
        "findingCategoryName": "MCC",
        "groupInfo": {
            "groupId": "eb9e2448231989c06d6b056588c500bd",
            "groupName": "Food & Bev Enterprises",
            "groupDescription": "Establishments that operate within the culinary industry,
providing a variety of food and drink products to consumers. These businesses can range from
small local eateries to large multinational chains providing sustenance, culinary experiences,
and social gathering spaces to customers.",
            "groupMccCodes": [
                "5813",
                "5811",
```

```
                "5812",
                "5814",
                "4723",
                "0743",
                "0744"
            ]
        },
        "contentType": "image/jpeg",
        "evidenceType": "mcc",
        "content": null,
        "extendedContent": {
            "value": "5814",
            "mccType": "detected",
            "name": "5814 - Fast Food Restaurants"
        }
    }
]
```


The MCC Mismatch object


```
[
    {
        "findingId": "bba845457df022585f327e2d3c3c7535",
        "findingType": "mcc_miscode",
        "findingName": "MCC Miscode",
        "findingCategory": "mcc",
        "findingCategoryName": "MCC",
        "groupInfo": null,
        "contentType": "image/jpeg",
        "evidenceType": "mcc",
        "content": null,
        "extendedContent": {
            "value": "5651",
            "mccType": "reported",
            "name": "5651 - Family Clothing Stores"
        },
        "reportedMccGroup": {
            "groupId": "1412db5862b820e08aa807ee85e63637",
            "groupName": "Fashion",
            "groupDescription": "Enterprises that design, manufacture, market, and sell
clothing, accessories, and related products in the fashion industry.",
            "groupMccCodes": [
                "5137",
```

```
                "5139",
                "5611",
                "5621",
                "5641",
                "5651",
                "5655",
                "5661",
                "5681",
                "5691",
                "5697",
                "5948",
                "5631",
                "5698",
                "5699",
                "7296",
                "5094",
                "7278"
            ]
        },
        "detectedMccGroup": {
            "groupId": "f82affe42815ff4c2f8e04e2bd1ac25f",
            "groupName": "Contractors",
            "groupDescription": "Professional services provided by individuals or companies
who specialize in a specific trade or field on a contractual basis for a set period of time.",
            "groupMccCodes": [
                "2842",
                "1520",
                "1731",
                "1740",
                "1750",
                "1761",
                "1771",
                "1799",
                "5039",
                "5085",
                "1711",
                "2741"
            ]
        }
    }
]
```


Read Only Fields

value *String*
The MCC code number

name *String*
The name of the MCC item

mccType *enum:MCC Evidence Type*
The type of MCC evidence (Detected, Reported, Reported and Detected)

The Link Evidence Object


```
[
    {
        "findingId": "d422498a52ddb478082972902fe6aasd",
        "findingType": "pharmaceuticals",
        "findingName": "Pharmaceuticals",
        "findingCategory": "content",
        "findingCategoryName": "Content",
        "contentType": null,
        "evidenceType": "link",
        "content": null,
        "extendedContent": {
            "url": "http://www.mydomain.com/s3/mysite.org"

        }
    }
]
```


Read Only Fields

url *String*
The URL of the link that was found

The Network Evidence Object


```
[
    {
        "findingId": "d422498a52ddb478082972902fe6aasd",
        "findingType": "suspected_transaction_launderer",
```

```
        "findingName": "Suspected Transaction Launderer",
        "findingCategory": "link",
        "findingCategoryName": "Link",
        "contentType": null,
        "evidenceType": "network",
        "content": null,
        "extendedContent": {
            "paths": [
                [
                    "mysite.biz",
                    "-- (Whois Registrant Phone) --",
                    "+39 352 647 5882",
                    "-- (Whois Registrant Phone) --",
                    "http://connectedsite1.com/"
                ]
            ]
        }
    }
]
```


Read Only Fields

`paths` *String*
The ecosystem network paths located for the merchant and their connection to the merchant

The Insight Evidence Object

Read Only Fields

`originFindingTypes` *Array of Finding Type object*
An array of Underwriting evidence type objects, including Alexa Details, IP Country Details, Page Views Details, Registrant Country Details, Reputation, and Site Data Details.

The IP Country Details Evidence Object


```
[
    {
        "findingId": "27307f381022fb5659884b3f227202be",
        "findingType": "ip_country",
```

```
        "findingName": "IP Country",
        "findingCategory": "whois",
        "findingCategoryName": "Whois",
        "contentType": "image/jpeg",
        "evidenceType": "ip_country_details",
        "content": null,
        "extendedContent": {
            "url": null,
            "ipCountry": "SE"
        }
    }
]
```


Read Only Fields

`ipCountry` *String*
The country of operation of the URL's IP address

`url` *String*
The URL where the evidence was located

The Page Views Details Evidence Object

The Page Views Details Evidence Object


```
[
    {
        "findingId": "27307f381022fb5659884b3f227202be",
        "findingType": "page_views",
        "findingName": "Page Views",
        "findingCategory": "whois",
        "findingCategoryName": "Whois",
        "contentType": "image/jpeg",
        "evidenceType": "page_views_details",
        "content": null,
        "extendedContent": {
            "url": null,
            "pageviews": 452467
        }
    }
]
```

Read Only Fields

`pageviews` *int*
The number of times the URL was viewed

`url` *String*
The URL where the evidence was located

The Registrant Country Details Evidence Object


```
[
    {
        "findingId": "11313fcfebeb445a6184b70886bda28e",
        "findingType": "registrant_country",
        "findingName": "Registrant Country",
        "findingCategory": "whois",
        "findingCategoryName": "Whois",
        "contentType": "image/jpeg",
        "evidenceType": "registrant_country_details",
        "content": null,
        "extendedContent": {
            "registrantCountry": "US",
            "url": null
        }
    }
]
```


Read Only Fields

`registrantCountry` *String*
The country where the URL is registered

`url` *String*
The URL where the evidence was located

The Reputation Evidence Object


```
[
    {
        "findingId": "ddfe79dd348453e2afea9fa86a24177f",
        "findingType": "trustpilot",
        "findingName": "Trustpilot",
        "findingCategory": "reputation",
        "findingCategoryName": "Reputation",
        "contentType": "image/jpeg",
        "evidenceType": "reputation",
        "content": null,
        "extendedContent": {
            "countScore3": 104,
            "countScore5": 3757,
            "countScore2": 43,
            "averageScore": 4.4,
            "url": "https://www.trustpilot.com/review/onecasino.com",
            "countScore4": 547,
            "countScore1": 238,
            "count": 4689
        }
    }
]
```


Read Only Fields

`url` *String*
The URL where the evidence was located

`averageScore` *int*
The average score that the URL received

`count` *int*
The number of scores that the URL received

`countScore` *int*
The score that the URL received

The Site Data Details Evidence Object

The Site Data Details Evidence Object


```
[
    {
        "findingId": "75c52443491a13dd6eb0fc03a99a88bc",
        "findingType": "site_data",
        "findingName": "Site Data",
        "findingCategory": "website_section",
        "findingCategoryName": "Site Section",
        "contentType": "image/jpeg",
        "evidenceType": "site_data_details",
        "content": null,
        "extendedContent": {
            "type": "OV",
            "title": "Hallandsposten | Lokala nyheter från Halmstad, Laholm & Hylte",
            "keywords": null,
            "invalidSsl": false,
            "affiliateLinks": false,
            "redirectingDomains": null,
            "issuer": "Cloudflare, Inc.",
            "description": "Senaste nyheterna från Hallandsposten",
            "url": null,
            "shoppingPlatform": null
        }
    }
]
```


Read Only Fields

`title` *String*
The meta-title of the home page

`description` *String*
The meta-description of the home page

`keywords` *String*
The meta-keywords used on the home page

affiliateLinks *bool*
Indication if affiliate links appear in the URL's home page

invalidSsl *bool*
Indication if the URL's SSL is valid (true) or invalid (false)

type *String*
The SSL Type: DV (Domain Validation), the lowest level of SSL certification; OV (Organization Validation), the middle level of SSL certification; EV (Extended Validation), the most extended level of SSL certification

issuer *String*
The SSL issuer

redirectedDomains *String*
A list of domains that redirect to this domain

url *String*
The URL where the evidence was located

shoppingPlatform *String*
The shopping platform where the evidence was located

The WhoIS Details Evidence Object


```
[
    {
        "findingId": "0b681dbdf13906c6e4e85ec5f022ce6a",
        "findingType": "whois_data",
        "findingName": "Whois Data",
        "findingCategory": "whois",
        "findingCategoryName": "Whois",
        "contentType": "image/jpeg",
        "evidenceType": "whois_details",
        "content": null,
        "extendedContent": {
            "createdAt": "1994-06-14",
            "expiresAt": "2021-12-31",
            "url": null,
```

```
            "updatedAt": "2020-12-25"
        }
    }
]
```

Read Only Fields

`createdAt` *String*
The date that the URL was first created

`expiresAt` *String*
The date that the URL expires

`url` *String*
The URL where the evidence was located

`updatedAt` *bool*
The last time the URL license was updated

The Network Object

```
{
  "id": "06f38bf625dd3ab2d592656d93567853",
  "scanId": "06f38bf625dd3ab2d592656d974b6905",
  "merchantId": "427003ed20e94507af52ff32d50eb69f",
  "network": {
    "http://mysite.biz/": {
      "reported": true,
      "paths": []
    },
    "http://connectedsite1.com/": {
      "reported": false,
      "paths": [
        [
          "mysite.biz",
          "-- (Whois Registrant Phone) --",
          "+39 352 647 5882",
          "-- (Whois Registrant Phone) --",
```

```
          "http://connectedsite1.com/"
        ]
      ]
    },
    "http://connectedsite2.it/": {
      "reported": false,
      "paths": [
        [
          "mysite.biz",
          "-- (IFrame in Site ) --",
          "http://connectedsite2.it/"
        ]
      ]
    }
  }
}
```


Read Only Fields

`id` *String*
The ID of the object

`scanId` *String*
The ID of the scan

`merchantId` *String*
The ID of the merchant

`network` *String*
The string representation of the merchant's detected network

The Search Results Object

Nested Objects

`merchants` *Array of Merchant Object*
The URLs that have been scanned

Read Only Fields

`total` *Integer*
The number of merchants objects in merchants

`offset` *Integer*
The starting position of the current page

`limit` *Integer*
The number of records on the current page

The Create Scan Results Object

Read Only Fields

`total` *Long*
Total number of merchants in the request

`valid` *Long*
Number of merchants in a valid state for the requested scan

`merchants` *Array of Scan Objects*
Merchant scan objects created in the request

`confirmMessage` *Array of Error Message Objects*
Merchants that were not scanned successfully

The Error Message Object

Read Only Fields

`message` *String*
Error message

`objectList` *Json Object*
The object that triggered the error

The Category Object

Field	Description	Possible Values
`categoryName`	The name of the category	
`categoryDescription`	The description of the category	
`registeredSeverity`	The risk severity of the category when detected on reported domains	no risk, low, medium, high, critical
`unregisteredSeverity`	The risk severity of the category when detected on unreported domains	no risk, low, medium, high, critical
`changeDate`	The date of the last change to the category's settings	

The Portfolio Search Results Object

Nested Objects

`portfolio merchants` *Array of Portfolio Result Object*
The query returned

Read Only Fields

`total` *Integer*
The number of merchant objects in merchants

`offset` *Integer*
The starting position of the current page

`limit` *Integer*
The number of records on the current page

The Portfolio Merchant Object

The return object from the portfolio search.

Fields

`legalName` *String* **Required**
The legal name of the merchant under which the merchant conducts its operations

`uniqueId` *String* **Required**
Unique merchant identifier as it appears in your system

Read Only Fields

`id` *String*
The unique merchant identifier in the EverC system

`dba` *String*
Concatenated DBA of the merchant's URLs

`mid` *String*
Concatenated MID of the merchant's URLs

`regCount` *Integer*
The merchant's current registered sites count

`merchantStatus` *String:Merchant Status*
The merchant's current status

`severity` *String:Risk Level*
The merchant's current risk level. Equals the highest risk level found in the merchant's last scan

`riskScore` *Integer*
The merchant's current risk quantifier. Equals the number of findings with the highest risk level found in the merchant's last scan

`boardingDate` *String*
The date and time of the merchant's last onboard scan, encoded in the ISO-8601 format

The `id` value is generated by EverC when the merchant is created and is required to perform various operations on the merchant, such as retrieve a merchant, update merchant, etc.

The `uniqueId` is provided when the merchant is created and is intended to enable cross referencing between the merchant in the EverC system and your internal systems.

The Login Object

Fields

`username` *String* **Required**
The username

`password` *String* **Required**
The password

The Session Object

Read-Only Fields

`access_token` *String* **Required**
The access token

`token_type` *String* **Required**
The token type (should equal Bearer)

`username` *String* **Required**
The username

`roles` *String[]* **Required**
Roles assigned to the user

The Error Object

Read Only Fields

`timestamp` *String*
The date and time on which the error was created, encoded in the ISO-8601 format

`status` *Integer*
The HTTP status code of the message

`message` *String*
A short message describing the nature of the error

extendedMessage *Array of JSON*
extended information about the error, if available

Field Values

Risk Level

Value	Name
unknown	Unknown Risk
no_risk	No Risk
low	Low Risk
medium	Medium Risk
high	High Risk
critical	Critical Risk

Contact Information Type

Value	Name	Description
owner	Owner	Indicates merchant owner contact information
business	Business	Indicates business contact information

URL Type

Value	Name	Description
`website`	Website	The URL leads to a website
`app`	Mobile App	The URL leads to a mobile app listing on an app store (e.g. Google Play, Apple App Store)

Scan Type

Value	Name	Description
`monitoring`	Monitoring	Periodic full system scan
`quick_insights`	Quick Insights	Onboarding new merchants for risk assessment

Merchant Status

Indicates the merchant's status.

Value	Name	Description
`pending`	Pending	Merchant was added but not boarded to the portfolio yet
`portfolio_not_monitored`	Portfolio Not Monitored	Merchant was paused from the monitoring process

`monitoring`	Monitored	Merchant is monitored and will be scanned automatically on a periodic basis
`deleted`	Deleted	Merchant was removed from the portfolio

Scan Status

Value	Name	Description
`submitted`	Submitted	The scan has been requested and is pending
`in_progress`	In Progress	The scan is currently in progress
`completed`	Completed	The scan has completed successfully
`error`	Error	The scan failed to complete

Evidence Type

Value	Name	Description
`screenshot`	Screenshot	The download URL and the source URL of a screenshot
`keyword`	Keyword	The keyword, its source URL and text where the keyword appears
`mcc`	MCC	The MCC code and name, and type (Detected, Reported, Reported and Detected)
`text`	Text	The located text and the source URL
`link`	Link	A URL located in the scanned merchant site

`network`	Network	Network of connections between the scanned merchant and other entities, and the type of connection
`reputation`	Reputation	
`ip_country_details`	Ip Country Details	
`registrant_country_details`	Registrant Country Details	
`page_views_details`	Page Views Details	
`site_data_details`	Site Data Details	
`whois_details`	Whois Details	

MCC Evidence Type

Value	Name	Description
`detected`	Detected	The MCC was detected by MerchantView
`reported`	Reported	The MCC was reported by the merchant
`reported_and_detected`	Reported and Detected	The MCC detected by MerchantView matches the MCC reported by the merchant

Event Type

Value	Name	Description

`add_merchant`	Add Merchant	The event type is add_merchant
`onboard`	Onboard	The scan type is boarding
`start_monitoring`	Start Monitoring	The merchant status has been changed to monitoring
`stop_monitoring`	Stop Monitoring	The merchant status has been changed to portfolio_not_monitored
`deboard_merchant`	Deboard Merchant	The merchant status has been changed to deleted

Event Status

Value	Name	Description
`successful`	Successful	The scan status is completed or null
`in_progress`	In Progress	The scan status is not completed and is not null

Dispute Status

Value	Name
`submitted`	Submitted
`in progress`	In Progress
`additional info required`	Additional Info Required
`rejected`	Rejected

`accepted`	Accepted
`withdrawn`	Withdraw Dispute

Finding Status

Value	Name
`not_checked`	Not Checked
`in_progress`	In Progress
`allowed`	Allowed
`remediated`	Remediated
`review_completed`	Review Completed
`rejected`	Rejected

Read Only

Value	Name
`disputed`	Disputed
`false_positive`	False Positive
`dispute_rejected`	Dispute Rejected
`no_action_required`	No Action Required

Node Type

Value	Name
psp_key	Psp Key
domain	Domain
email	Email
ip_address	IP Address
phone	Phone
address	Address
geo_address	Geo Address
alias	Alias

Edge Type

1. Whois Has Registrant Organization
2. Whois Has Registrant Email
3. Whois Has Registrant Phone
4. Whois Has Registrant Fax
5. Website Owned By
6. Website Has Ip
7. Bank Reported Has Address
8. Bank Reported Has Phone
9. Bank Reported Has Legal Name

10. Bank Reported Owned By
11. Bank Reported Owner Address
12. Bank Reported Owner Phone
13. Bank Reported Owner Email
14. Website Has Similar Identifiers
15. Bank Reported Has Email
16. Website Has Meaningful Email
17. Website Has Meaningful Phone
18. Website Has Seo Phone
19. Website Has Company Name
20. Website Has Psp

Callback Type

Value	Name	Description
`MERCHANT_SCAN_AVAILABLE`	Callback Type	Indicates that a merchant's risk has changed and that the latest scan is available

Glossary

Risk

Each finding in MerchantView is assigned a risk that indicates the level of threat the finding has on the portfolio. The risk is comprised of a risk level and risk score, which together give a granular risk level that allows for better prioritizing of work.

Risk levels, Risk Score

There are 6 risk levels in the system today.

Critical Risk

The finding represents an immediate risk and needs to be mitigated immediately.

High Risk

The finding represents a significant risk, and needs to be communicated to the merchant and investigated further.

Medium Risk

The finding represents some risk, but the risk does not require immediate attention.

Low Risk

The finding represents little risk, and no action is required in order to mitigate it.

No Risk

The finding represents no risk, and no action is required in order to mitigate it.

Unknown Risk

The finding's risk is unknown. This is usually a temporary status, and the risk will be updated once a scan is completed.

For each risk level, the risk score aggregates the number of findings with that risk level and are associated to the object, or to its children. For example, if a URL has 2 findings with critical risk, and one finding with high risk, its risk level will be critical, and its risk score will be 2.

Risk Matrix

MerchantView supports the customization of risk levels to allow prioritizing findings according to the customer's policies. Customizing the findings' risk levels is performed in the Risk Matrix. Default risk values for findings represent the best practices collected by EverC, using years of experience in the market. Risk customization is done as part of the initial onboarding of the account, and can be tweaked and altered throughout the account life-cycle on demand.

Each finding can have two separate risk severities:

- Reported domain risk severity - the configured risk for findings detected on reported domains.
- Unreported domains (Ecosystem) risk severity - the configured risk for findings detected on Unreported domains (domains found by EverC).

Portfolio

A portfolio is the collection of all active merchants conducting business through the network. The portfolio is updated throughout the account life cycle, with merchants added and removed according to the ongoing business activity and risk policy.

The base unit in the portfolio is the merchant, which is managed as an independent risk entity.

The Merchant

A merchant is the basic business entity in the portfolio. The merchant's minimum required properties are its unique ID and legal name. For merchants where online monitoring is needed, a website or app address is also required.

Merchant Attributes

Merchant Legal Name - The merchant's legal registered name (mandatory). By default, this is the name by which the merchant will appear in MerchantView

Merchant Unique ID) - The unique identifier used to identify a single merchant in the portfolio (mandatory)

Merchant Alias - The merchant's known alias

Merchant Address - A full address (country, state, city street…) associated with the merchant

Merchant Phone - The phone number associated with the merchant

Merchant Email - the Email address associated with the merchant

URL - All the URLs associated with the merchant

Merchant Risk

The merchant risk is the compound risk of all business activity connected to it. This includes the reported websites, ecosystem websites, blacklist matches, previous violations, etc.

Merchant Workflow

A merchant is considered part of the portfolio only after an Onboarding process (scan) has been performed on it. Once in the portfolio the merchant can be removed from the portfolio by a deboarding process.

Scans

A scan is the action of retrieving information about the merchant in order to determine its risk level. There are several levels of scan profiles that reflect different levels of depth and detail of the scan.

Types of scans

Quick Insights

The Quick Insights scan is EverC's Onboarding solution that provides insights about the merchant and aids in the assessment of its risk before adding it into the portfolio.

It also can use the WebID mechanism to retrieve a URL for the merchant, if one was not provided.

Monitoring

Over time websites often change, go offline, and new sites emerge. Ongoing monitoring of merchants updates the merchant data over time and makes sure the most updated information is presented at any given time.

Monitoring scans includes a full analysis of the merchant's reported URLs and ecosystem. Once a merchant is monitored, it will receive Monitoring scans on a regular basis according to the defined SLA.

In order to avoid information loss during updates, finding status and reviewer notes of findings are carried with the site, as long as they remain relevant. For example, a note on the Online finding will remain with

the finding for as long as the website is online. If the website becomes offline, the note will no longer be visible. You can always return to previous scans, where the information remains available.

Any change in the merchant updates the /api/v4/merchants/<MerchantID>/scans/latest scan result, reflecting the new change.

Findings

Findings are information elements found by MerchantView that are relevant to the merchants' sites. They span across many topics, from content classification to security violations on web pages. Each finding is assigned a risk that in turn affects the overall risk of the merchant. As you review findings, you can update notes and progress status (which affect the finding's risk) in order to track progress.

Findings are divided into types representing the area to which the findings relate (e.g Content, Payment, MCC, etc.). Each type contains multiple finding categories MerchantView is able to detect and flag the merchant URL with (e.g Prescription Drugs, Marijuana, Gambling, Payment page, Terms and Conditions, etc.)

The list of findings types and categories are constantly updated periodically, you would need to make sure to stay up to date using the Release Notes and make sure you are able to support and consume them.

Evidence

For specific findings, we provide evidence to support the finding in the form of textual excerpts, screenshots, links and connection diagrams. The evidence is saved on EverC servers and will be available even if the website has changed or shut down, for more accurate review and inspection over time.

Ecosystem and Connections

A Merchant ecosystem is the sum of all merchant's online activity, both reported and unreported and the connections between them. Each of the unreported websites in the ecosystem is connected through one or more connections to the merchant; through a link in its reported websites or via any of its attributes (emails, addresses, phones, names, etc).

If an unreported website does not have an e-commerce environment the website will receive the finding Associated. The reported website will then receive the finding Associator.

Types of Connectors

There are many connection types, which reflect a variety of different ways online activity can be connected to the merchant. A connection between two websites is a path composed of nodes and edges. The last node will always be the unreported website, and the first - an attribute or website reported by the merchant. Every two nodes are connected by an edge, which provides information regarding the nature of the connection.

For example, if a known website resides on the same IP address as an unreported website, the connection will be: reportedweb.com –(website_has_ip)–> nonreportredweb.com

Connection evidence

For each unreported website, complete connection information is available to allow for ecosystem analysis. Detailed connection information is available via API or UI.