COMPUTER PROGRAMMING

Pointers and Strings

Topics to be covered

Reading, writing and manipulating Strings,
Understanding computer memory, accessing via
pointers, pointers to arrays, dynamic
allocation, drawback of pointers.

String definition

- String is a 1-d array of characters terminated by a null ('\0')
- char C[] = {'A','B','C','\0'};
- char S[] = "ABC";
- Both C and S have length = 3
- You can also have NULL instead of '\0' defined in stdio.h and string.h

String input including blanks

```
main(){
char name[25];
printf ("Enter name: ");
scanf ("%s", name);
printf("hello %s",name);
}
```

Another way

```
main(){
char C[20];
gets(C); // accepts blank spaces
puts(C);
}
```

NULL and strlen()

```
main(){
int i=0;
char C[10];
gets(C);
while(C[i]!=NULL) printf("%c",C[i++]);
//OR while(i<strlen(C)) printf("%c",C[i++]);</pre>
```

Few Inbuilt functions

```
main() {
char A[] = \text{wxYZ}, B[] = \text{78}, C[20];
printf("length of %s = %d",A,strlen(A));
if(strcmp(A,B)==0) printf("\nA,B same srings");
printf("\nC = %s", strcpy(C,A));
printf("\nUppercase of A = %s",strupr(A));
printf("\nConcat A+C = %s",strcat(C,A));
printf("\n Reverse A = %s",strrev(A));
```

2-d character array

```
char Names[6][10] = {"akshay",
"parag",
"raman"};

puts(Names[0]); //akshay
```

char Names[6][10] storage

65454	a	k	S	h	a	У	\0			
65464	p	a	r	a	og)	/0				
65474	Γ	a	m	a	n	/0				
65484	S	ľ	i	n	i	V	a	S	/0	
65494	QQ O	0	p	a	1	\0				
65504	r	a	j	e	S	h	\0			

(last location)

 Reading, writing and manipulating Strings,

Understanding computer memory, accessing via pointers, pointers to arrays, dynamic allocation, drawback of pointers.

What is a pointer

Sweet Home



- ➤Own Property
- ➤ Fixed space

Smart Hotel



- ✓ Leased Property
- √Space can be increased dynamically

Variables


VS.

pointers

Advantages of pointers

- Dynamic memory allocation
- System level programming
- To modify a variable in another function
- Illusion of multiple returns
- Passing and returning arrays

Variable, value and location



& - address of operator

```
main(){
int i = 3;
printf("\nAddress of i = %u", &i);
printf("\nValue of i = %d", i);
}
```

//%u means unsigned integer, what is %p,%i,%e

* is value at address

```
main() {
int i = 3;
printf ("\nAddress of i = \%u", &i);
printf ("\nValue of i = %d'', i);
printf ("\nValue of i = %d", *( &i ) );
// output: some address, 3 and 3
```

int *j;

 This declaration tells the compiler that j will be used to store the address of an integer value.

```
main() {
int i = 3,*;
i = \&i;
printf ( "\nAddr of i = \%u", &i );
printf ("\nAddr of i = \%u", i);
printf ("\nAddr of j = \%u", &j);
printf ( "\n i = %u", i ); printf ( "\n i = %d", i );
printf ("\n i = %d", *(&i)); printf ("\n i = %d", *j);
```

```
Addr of i = 65524
Addr of i = 65524
Addr of j = 65522
j = 65524
i = 3
i = 3
Value of i = 3
```

Pointers for other datatypes

```
int *alpha;char *ch;float *s;
```


Pointers are variables that contain addresses, and since addresses are whole numbers, pointers would always contain whole numbers.

char *ch;

- *ch will contain a character
- ch is an unsigned int containing the address

```
main(){
inti=3,*i,**k;
j=&i; k=&j;
printf("\naddr of i=%u",&i);
printf("\naddr of i=%u",j);
printf("\naddr of i=%u",*k);
printf("\naddr of j=%u",&j);
printf("\naddr of j=%u",k);
printf("\naddr of k=%u",&k);
printf("\nj=%u",j); printf("\nk=%u",k);
printf("\ni=%d",i); printf("\ni=%d",*(&i));
printf("\ni=%d",*j); printf("\ni=%d",**k);
```

Situation



addr of i=6487628

addr of i=6487628

addr of i=6487628

addr of j=6487616

addr of j=6487616

addr of k=6487608

j=6487628

k=6487616

i=3

i=3

i=3

i=3

```
main() {
int Var = 10;
int *ptr = &Var;
printf("Var = %d\n", *ptr);
printf("Var Addr = %u\n", ptr);
*ptr = 20;
printf("Var = %d\n", Var);
```

Var = 10

Var Addr = 6487620

Var = 20

```
main() {
int v[3] = \{10, 100, 200\}, i;
int *ptr;
ptr = v;
for(i = 0; i < 3; i++) {
printf("*ptr = %d\n", *ptr);
printf("ptr = %u\n", ptr);
ptr++;
```

```
*ptr = 10
ptr = 6487600
*ptr = 100
ptr = 6487604
*ptr = 200
ptr = 6487608
```

```
main() {
int i=3,*x; float j=1.5,*y; char k='c',*z;
printf("\n i=%d, j=%f, k=%c",i,j,k);
x = &i ; y = &j ; z = &k ;
printf("\n Addr of x,y,z = %u, %u, %u",x,y,z);
X++; Y++; Z++;
printf("\n New Addr of x,y,z = %u, %u, %u",x,y,z);
```

- i=3, j=1.500000, k=c
- Addr of x,y,z = 6487604, 6487600, 6487599
- New Addr of x,y,z = 6487608, 6487604,
 6487600

```
main() {
int arr[] = { 10, 20, 30, 45, 67, 56, 74 };
int *i, *j;
i = &arr[1]; j = &arr[5];
printf("%d %d", j-i, *j-*i);
```

• 4 36

```
main(){
int arr[]=\{10,20,36,72,45,36\};
int*j,*k;
j=&arr[4];
k=(arr+4);
if(j==k)
printf("Same locations");
else printf("Different locations");
```

Same locations

```
main(){
   int a = 10, b = 20;
   swapv (a, b);
   printf ("\na = %d b = %d", a, b);
7 d swapv ( int x, int y ) {
   int t = x;
   x = y; y = t;
    printf ("\nx = %d y = %d", x, y);
```



$$x = 20 y = 10$$

$$a = 10 b = 20$$

Problem 9: Pointer swap

```
main() {
int a = 10, b = 20;
swapr ( &a, &b );
printf ( "\na = %d, b = %d", a, b );
swapr( int *x, int *y ) {
int t = *x ; *x = *y ; *y = t ;
```

Problem 10: One * for 1-d

```
main() {
int a[3]={1,2,3},*b,i;
b=a;
for(i=0;i<3;i++) {
  printf("\n %d %d",a[i],b[i]);
}}</pre>
```

Output

- 11
- 22
- 33

Problem 11: Multiple returns

```
AreaPeri(int r, float *A, float *P){
*A = 3.14*r*r; *P = 2*3.14*r;
main(){
int r; float A,P;
printf("\nEnter radius: " ); scanf("%d",&r);
AreaPeri(r,&A,&P); printf("Area = %f, Peri = %f",A,P);
```

Same things

- name[i]
- *(name + i)
- *(i + name)
- i[name]

Problem 12: Array vs *

```
main(){
char A[] = "Hello", B[10];
char *C = "Good Morning", *D;
//B = A ; /* error */
D = C; /* Okay */
printf("%s",D);
pointer to pointer
```

Problem 13: * are dynamic

```
main() {
char A[] = "Hello";
char *B = "Hello";
//A = "Bye" ; /* error */
B = "Bye"; /* works */
printf("%s",B);
```

Problem 14: Returning an array

```
int *incr(int X[3],int k){
int i;
for(i=0;i<k;i++) ++X[i];
return X;
main(){
int A[] = \{1,2,3\}, n=3,i,*B;
B = incr(A,n);
for(i=0;i<n;i++) printf(" %d",B[i]);
```

Output


• 234

Array of pointers

 char*names[]={"akshay","parag","raman","sri nivas", "gopal","rajesh"};

It contains base address of various names

Array of pointers



Problem 15: Dynamic allocation

```
main(){
int *ptr, n,i;
printf("Size of array? "); scanf("%d",&n);
ptr = (int*)malloc(n*sizeof(int));
for(i=0;i<n;i++) ptr[i]=i;
for(i=0;i<n;i++) printf(" %d",ptr[i]);
free (ptr);
```

Output

Size of array? 10 0 1 2 3 4 5 6 7 8 9

Drawback of pointers

- Complicated to use and debug
- Uninitialized pointers might cause segmentation fault
- Dynamically allocated block needs to be freed explicitly. Otherwise, it would lead to memory leak (occupied but unused memory)
- If pointers are updated with incorrect values, it might lead to memory corruption

Topics covered were

Reading, writing and manipulating Strings, Understanding computer memory, accessing via pointers, pointers to arrays, dynamic allocation, drawback of pointers.