



✓ **Congratulations! You passed!**

TO PASS 80% or higher

Keep Learning

Retake the assignment in 7h 33m

GRADE
92.3%

Final Exam

LATEST SUBMISSION GRADE

92.3%

1. Let (E, D) be an authenticated encryption system built by combining

1 / 1 point

a CPA-secure symmetric cipher and a MAC. The system is combined with an error-correction code to correct random transmission errors.

In what order should encryption and error correction be applied?

- ☐ The order does not matter -- neither one can correct errors.
- ☐ The order does not matter -- either one is fine.
- ☒ Encrypt and then apply the error correction code.
- ☐ Apply the error correction code and then encrypt the result.

✓ **Correct**

That is correct. The error correction code will do its best to correct random errors after which the MAC in the ciphertext will be checked to ensure no other errors remains.

2. Let X be a uniform random variable over the set $\{0, 1\}^n$.

1 / 1 point

Let Y be an arbitrary random variable over the set $\{0, 1\}^n$ (not necessarily uniform) that is independent of X .

Define the random variable $Z = X \oplus Y$. What is the probability that Z equals 0^n ?

- ☒ $1/2^n$
- ☐ $2/2^n$
- ☐ $1 - (1/2^n)$
- ☐ $1/n^2$

✓ **Correct**

The probability is $1/2^n$. To see why, observe that whatever Y is, the probability that $Z = X \oplus Y = 0^n$ is the same as the probability that $X = Y$ which is exactly $1/2^n$ because X is uniform.

3. Suppose (E_1, D_1) is a symmetric cipher that uses 128 bit keys to

0 / 1 point

encrypt 1024 bit messages. Suppose (E_2, D_2) is a symmetric cipher that uses 128 bit keys to encrypt 128 bit messages.

The encryption algorithms E_1 and E_2 are deterministic and do not use nonces. Which of the following statements is true?

- ☒ (E_2, D_2) can be one-time semantically secure and perfectly secure.

✓ **Correct**

Yes, for example (E_2, D_2) can be the one time pad.

- ☐ (E_2, D_2) can be perfectly secure.
- ☐ (E_1, D_1) can be perfectly secure.
- ☐ (E_1, D_1) can be semantically secure under a chosen plaintext attack.

You didn't select all the correct answers

4. Which of the following statements regarding CBC and counter mode is correct?

1 / 1 point

- ☐ Both counter mode and CBC mode can operate just using a PRF.
- ☒ CBC mode encryption requires a block cipher (PRP), but counter mode encryption only needs a PRF.
- ☐ counter mode encryption requires a block cipher (PRP), but CBC mode encryption only needs a PRF.
- ☐ Both counter mode and CBC mode require a block cipher (PRP).

✓ Correct

Yes, CBC needs to invert the PRP for decryption, while counter mode only needs to evaluate the PRF in the forward direction for both encryption and decryption. Therefore, a PRF is sufficient for counter mode.

5. Let $G : X \rightarrow X^2$ be a secure PRG where $X = \{0, 1\}^{256}$.

1 / 1 point

We let $G(k)[0]$ denote

the left half of the output and $G(k)[1]$ denote the right half.

Which of the following statements is true?

- ☐ $F(k, m) = G(k)[0] \oplus m$ is a secure PRF with key space and message space X .
- ☒ $F(k, m) = G(k)[m]$ is a secure PRF with key space X and message space $m \in \{0, 1\}$.
- ☐ $F(k, m) = G(m)[0] \oplus k$ is a secure PRF with key space and message space X .
- ☐ $F(k, m) = m \oplus k$ is a secure PRF with key space and message space X .

✓ Correct

Yes, since the output of $G(k)$ is indistinguishable from random, the left and right halves are indistinguishable from random independent values.

6. Let (E, D) be a nonce-based symmetric encryption system (i.e. algorithm

1 / 1 point

E takes as input a key, a message, and a nonce, and similarly the decryption algorithm takes a nonce as one of its inputs). The system provides chosen plaintext security (CPA-security) as long as the nonce never repeats. Suppose a single encryption key is used to encrypt 2^{32} messages and the nonces are generated independently at random for each encryption, how long should the nonce be to ensure that it never repeats with high probability?

- ☒ 128 bits
- ☐ 64 bits
- ☐ 16 bits
- ☐ 32 bits

✓ Correct

Yes, the probability of repetition after 2^{32} samples is negligible.

7. Same as question 6 except that now the nonce is generated using a counter. The counter resets to 0 when a new key is chosen and is incremented by 1 after every encryption. What is the shortest nonce possible to ensure that the nonce does not repeat when encrypting 2^{32} messages using a single key?

1 / 1 point

- ☒ 32 bits
- ☐ the nonce must be chosen at random, otherwise the system cannot be CPA secure.
- ☐ 128 bits
- ☐ 48 bits

✓ Correct

Yes, with 32 bits there are 2^{32} nonces and each message will use a different nonce.

8. Let (S, V) be a deterministic MAC system with message space M and key space K . Which of the following properties is implied by the standard MAC security definition?

1 / 1 point

- ☐ $S(k, m)$ preserves semantic security of m .
That is, the adversary learns nothing about m given $S(k, m)$.
- ☐ Given a key k in K it is difficult to find distinct messages m_0 and m_1 such that $S(k, m_0) = S(k, m_1)$.
- ☐ The function $S(k, m)$ is a secure PRF.
- ☒ Given m and $S(k, m)$ it is difficult to compute k .

✓ Correct

yes, otherwise the attacker can easily mount an existential forgery.

9. Let $H : M \rightarrow T$ be a collision resistant hash function where $|T|$ is smaller than $|M|$.

1 / 1 point

Which of the following properties is implied by collision resistance?

- ☐ For all m in M , $H(m)$ must be shorter than m .
- ☐ it is difficult to find m_0 and m_1 such that $H(m_0) = H(m_1) + 1$. (here we treat the outputs of H as integers)
- ☐ $H(m)$ preserves semantic security of m
(that is, given $H(m)$ the attacker learns nothing about m).
- ☒ It is difficult to construct two distinct messages m_0 and m_1 such that $H(m_0) = H(m_1)$.

✓ Correct

yes, this is the definition of collision resistance.

10. Recall that when encrypting data you should typically use a symmetric encryption system that provides authenticated encryption. Let (E, D) be a symmetric encryption system providing authenticated encryption. Which of the following statements is implied by authenticated encryption?

1 / 1 point

- ☒ Given m and $E(k, m)$ it is difficult to find k .

✓ Correct

yes, otherwise the system would not even be chosen plaintext secure.

- ☐ Given k, m and $E(k, m)$ the attacker cannot create a valid encryption of $m + 1$ under key k .
(here we treat plaintexts as integers)

- ☒ (E, D) provides chosen-ciphertext security.

✓ Correct

yes, we showed this in class.

- ☐ Given $c = E(k, m)$ for some secret k, m ,
the attacker cannot find k', m' such that $c = E(k', m')$.

11. Which of the following statements is true about the basic Diffie-Hellman

1 / 1 point

key-exchange protocol.

- ☐ As with RSA, the protocol only provides
eavesdropping security in the group \mathbb{Z}_N^* where N is an
RSA modulus.
- ☒ The basic protocol enables key exchange secure against
eavesdropping, but is insecure against active adversaries that can
inject and modify messages.

✓ Correct

yes, Diffie-Hellman is secure against eavesdropping,
but is insecure against man in the middle attacks.

- ☒ The protocol can be converted to a public-key
encryption system called the ElGamal public-key system.

✓ Correct

yes, that is correct.

- ☐ The protocol is based on the concept of a trapdoor
function.

12. Suppose $n + 1$ parties, call them B, A_1, \dots, A_n , wish to setup

1 / 1 point

a shared group key. They want a protocol so that at the end
of the protocol they all have a common secret key k , but an eavesdropper
who sees the entire conversation cannot determine k . The parties
agree on the following protocol that runs in a group G of prime order q
with generator g :

- for $i = 1, \dots, n$ party A_i chooses a random a_i in $\{1, \dots, q\}$ and sends to Party B the quantity $X_i \leftarrow g^{a_i}$.
- Party B generates a random b in $\{1, \dots, q\}$ and for $i = 1, \dots, n$ responds to Party A_i with the messages $Y_i \leftarrow X_i^b$.

The final group key should be g^b . Clearly Party B can compute
this group key. How would each Party A_i compute this group key?

- ☐ Party A_i computes g^b as $Y_i^{a_i}$
- ☐ Party A_i computes g^b as Y_i^{-1/a_i}
- ☒ Party A_i computes g^b as Y_i^{1/a_i}
- ☐ Party A_i computes g^b as $Y_i^{-a_i}$

✓ Correct

Yes, $Y_i^{1/a_i} = g^{(ba_i)/a_i} = g^b$.

13. Recall that the RSA trapdoor permutation is defined in the group

1 / 1 point

\mathbb{Z}_N^* where N is a product of two large
primes. The public key is (N, e) and the private key is (N, d)
where d is the inverse of e in $\mathbb{Z}_{\varphi(N)}^*$.
Suppose RSA was defined modulo a prime p instead of an RSA

composite N . Show that in that case anyone can compute the private

key (N, d) from the public key (N, e) by computing:

- ☒ $d \leftarrow e^{-1} \pmod{p-1}.$
- ☐ $d \leftarrow e^{-1} \pmod{p+1}.$
- ☐ $d \leftarrow -e \pmod{p}.$
- ☐ $d \leftarrow e^{-1} \pmod{p}.$



Correct

yes, that is correct.