

RuangTemu

Mobile API Documentation

Panduan integrasi API untuk aplikasi mobile Android/iOS
Generated from docs/API_MOBILE.md • Last updated: 2026-07-05

Last updated: 2026-07-05

Dokumen ini dibuat sebagai panduan integrasi API RuangTemu untuk aplikasi mobile Android/iOS. API yang dijelaskan mengikuti route backend Express saat ini.

1. Base URL

Production:

`https://api.ruangtemu.biz.id`

Alternatif via web reverse proxy jika dipakai:

`https://ruangtemu.biz.id/api`

Local development:

`http://localhost:3200`

Semua path di bawah ditulis relatif dari Base URL.

Contoh:

POST `https://api.ruangtemu.biz.id/auth/login`

2. Format Umum

Request JSON

Content-Type: `application/json`

Accept: `application/json`

Request Authenticated

Authorization: Bearer `<accessToken>`

Upload File

Gunakan `multipart/form-data`.

Content-Type: `multipart/form-data`

Authorization: Bearer `<accessToken>`

Response Error Standar

```
{
  "message": "Pesan error"
}
```

HTTP Status yang Umum

Status	Arti
200	Berhasil
201	Berhasil membuat data
400	Request tidak valid / validasi gagal
401	Token tidak ada / token invalid / token expired
403	Tidak punya akses / akun suspended
404	Data tidak ditemukan

Status	Arti
409	Konflik data, misalnya email sudah terdaftar
429	Rate limit
500	Error server

3. Auth & Token Flow

Backend memakai JWT:

- `accessToken`: token pendek, default sekitar 15 menit.
- `refreshToken`: token panjang, default sekitar 7 hari.

Mobile app sebaiknya menyimpan token di secure storage:

- Android: `EncryptedSharedPreferences` / `Keystore`.
- iOS: `Keychain`.

Flow Login Mobile

1. User login/register.
2. Simpan `accessToken`, `refreshToken`, dan data user.
3. Semua request private pakai header:

Authorization: Bearer <accessToken>

4. Jika API membalas 401, panggil `POST /auth/refresh` dengan `refreshToken`.
5. Simpan token baru.
6. Ulangi request yang gagal.
7. Jika refresh gagal, logout user dari app.

4. Enum Penting

User Role

USER
ADMIN

Gender

MALE
FEMALE
OTHER

Catatan: register/update profile saat ini menerima `MALE` dan `FEMALE`; data lama/backend matching bisa menampilkan `OTHER`.

Dinner Status

OPEN
MATCHING
CONFIRMED
COMPLETED
CANCELLED

Booking/Event Registration Status

PENDING_PAYMENT
PENDING_VERIFICATION
CONFIRMED
MATCHED
CANCELLED
REFUNDED

Payment Status

PENDING
VERIFIED
REJECTED

5. Model Ringkas

User

```
type User = {  
  id: string;  
  email: string;  
  phone?: string | null;  
  name: string;  
  gender?: "MALE" | "FEMALE" | "OTHER" | null;  
  birthDate?: string | null;  
  city?: string | null;  
  bio?: string | null;  
  avatarUrl?: string | null;  
  activity?: string | null;  
  industry?: string | null;  
  socialComfort?: number | null;  
  personalityType?: "Introvert" | "Ekstrovert" | "Ambivert" | null;  
  leisureTopics?: string[] | null;  
  conversationTopics?: string[] | null;  
  smokes?: boolean | null;  
  drinksAlcohol?: boolean | null;  
  dietaryNotes?: string | null;  
  role: "USER" | "ADMIN";  
  isVerified?: boolean;  
  isSuspended?: boolean;  
}
```

City

```
type City = {  
  id: string;  
  name: string;  
  areas: string; // JSON string array  
  isActive: boolean;  
}
```

Dinner

```
type Dinner = {
  id: string;
  cityId: string;
  date: string;
  startTime: string;
  maxPerTable: number;
  status: "OPEN" | "MATCHING" | "CONFIRMED" | "COMPLETED" | "CANCELLED";
  revealedAt?: string | null;
  venueName?: string | null;
  venueAddress?: string | null;
  arrivalTime?: string | null;
  reservationName?: string | null;
  hostName?: string | null;
  hostPhone?: string | null;
  venueNotes?: string | null;
  city?: City;
  budgetTiers?: BudgetTier[];
}
```

BudgetTier

```
type BudgetTier = {
  id: string;
  dinnerId: string;
  label: string;
  price: number;
}
```

Booking

```
type Booking = {
  id: string;
  userId: string;
  dinnerId: string;
  budgetTierId: string;
  status: "PENDING_PAYMENT" | "PENDING_VERIFICATION" | "CONFIRMED" | "MATCHED" |
"CANCELLED" | "REFUNDED";
  tableId?: string | null;
  dinner?: Dinner;
  budgetTier?: BudgetTier;
  payment?: Payment;
  table?: DinnerTable | null;
  createdAt: string;
}
```

Payment

```
type Payment = {
  id: string;
  bookingId: string;
  amount: number;
  method: string;
  proofUrl?: string | null;
  status: "PENDING" | "VERIFIED" | "REJECTED";
  verifiedById?: string | null;
  verifiedAt?: string | null;
  note?: string | null;
  expiredAt: string;
  createdAt: string;
}
```

Event

```
type Event = {
  id: string;
  title: string;
  slug: string;
  description: string;
  posterUrl?: string | null;
  date: string;
  cityId?: string | null;
  price: number;
  capacity: number;
  status: string;
  createdAt: string;
}
```

EventRegistration

```
type EventRegistration = {
  id: string;
  eventId: string;
  userId: string;
  status: "PENDING_PAYMENT" | "PENDING_VERIFICATION" | "CONFIRMED" | "MATCHED" |
"CANCELLED" | "REFUNDED";
  payment?: {
    amount?: number;
    method?: string;
    status?: "PENDING" | "VERIFIED" | "REJECTED";
    expiredAt?: string;
    proofUrl?: string;
    uploadedAt?: string;
    verifiedById?: string;
    verifiedAt?: string;
    note?: string;
  } | null;
  event?: Event;
  createdAt: string;
}
```

6. Public Endpoints

Endpoint public tidak perlu token.

6.1 Health Check

GET /health

Response:

```
{
  "status": "ok",
  "timestamp": "2026-07-05T06:15:25.408Z"
}
```

6.2 List Kota Aktif

GET /cities

Response:

```
[
  {
    "id": "city_id",
    "name": "Magelang",
    "areas": ["\"Magelang Utara\"", "\"Magelang Selatan\""],
    "isActive": true
  }
]
```

6.3 Request Kota Baru

POST /cities/request

Body:

```
{
  "cityName": "Semarang",
  "email": "user@email.com"
}
```

Response:

```
{
  "message": "Request kota tersimpan"
}
```

6.4 List Interest

GET /interests

Response:

```
[
  { "id": "interest_id", "name": "Musik" }
]
```

6.5 List Testimonial Published

GET /testimonials

Response:

```
[
  {
    "id": "testimonial_id",
    "name": "Ayu",
    "age": 24,
    "content": "Seru banget!",
    "isPublished": true,
    "createdAt": "2026-01-01T00:00:00.000Z"
  }
]
```

6.6 Public Payment Settings

GET /admin/public-settings

Dipakai mobile untuk menampilkan QRIS/bank transfer/nomor WhatsApp payment.

Response contoh:

```
{
  "qris_image_url": "/uploads/qris/qris-file.png",
  "payment_deadline_hours": "24",
  "payment_whatsapp_number": "628xxxx",
  "payment_bank_enabled": "true",
  "payment_bank_name": "BCA",
  "payment_bank_account_number": "1234567890",
  "payment_bank_account_name": "RuangTemu"
}
```

Untuk file upload yang return path relatif /uploads/..., gabungkan dengan API base URL:

```
const fullUrl = `${API_BASE_URL}${path}`;
```

6.7 Public Overview

GET /admin/public-overview

Response berisi metrik landing/public overview.

6.8 List Event Public

GET /events

Query optional:

Query	Tipe	Keterangan
cityId	string	Filter event kota; event global cityId = null tetap ikut

Response:


```
[
  {
    "id": "event_id",
    "title": "Bertemu with strangers",
    "slug": "bertemu-with-strangers",
    "description": "...",
    "posterUrl": "/uploads/posters/file.jpg",
    "date": "2026-07-20T12:00:00.000Z",
    "cityId": null,
    "price": 55000,
    "capacity": 50,
    "status": "OPEN",
    "_count": { "registrations": 10 }
  }
]
```

6.9 Detail Event Public

GET /events/:slug

Response: object Event + `_count.registrations`.

7. Auth Endpoints

7.1 Register

POST /auth/register

Body:

```
{
  "name": "Aditya",
  "email": "aditya@example.com",
  "password": "Password123",
  "phone": "+6281234567890",
  "gender": "MALE",
  "birthDate": "2000-06-12T00:00:00.000Z",
  "city": "Magelang",
  "interestIds": ["interest_id_1", "interest_id_2", "interest_id_3"],
  "activity": "Mahasiswa",
  "industry": "Teknologi",
  "socialComfort": 4,
  "personalityType": "Ambivert",
  "leisureTopics": ["Film", "Kopi"],
  "conversationTopics": ["Karier", "Traveling"],
  "smokes": false,
  "drinksAlcohol": false,
  "dietaryNotes": "Tidak pedas"
}
```

Validasi penting:

- password minimal 8 karakter, ada huruf kapital dan angka.
- phone optional, format internasional: +6281234567890.
- gender: MALE atau FEMALE.
- birthDate: ISO datetime.
- interestIds: minimal 3.
- city harus tersedia di sistem lokasi.

Response 201:

```
{
  "user": {
    "id": "user_id",
    "email": "aditya@example.com",
    "name": "Aditya",
    "role": "USER",
    "avatarUrl": null
  },
  "accessToken": "jwt_access",
  "refreshToken": "jwt_refresh"
}
```

7.2 Login

POST /auth/login

Body:

```
{
  "email": "aditya@example.com",
  "password": "Password123"
}
```

Response:

```
{
  "user": {
    "id": "user_id",
    "email": "aditya@example.com",
    "name": "Aditya",
    "role": "USER",
    "avatarUrl": null
  },
  "accessToken": "jwt_access",
  "refreshToken": "jwt_refresh"
}
```

7.3 Refresh Token

POST /auth/refresh

Body:

```
{
  "refreshToken": "jwt_refresh"
}
```

Response:

```
{
  "accessToken": "new_access_token",
  "refreshToken": "new_refresh_token"
}
```

Catatan mobile:

- Refresh token lama akan diganti.
- Simpan kedua token baru.

7.4 Logout

POST /auth/logout

Authorization: Bearer <accessToken>

Body:

```
{
  "refreshToken": "jwt_refresh"
}
```

Response:

```
{
  "message": "Logout berhasil"
}
```

7.5 Get Current User

GET /auth/me

Authorization: Bearer <accessToken>

Response: object user login.

7.6 Google Auth Mobile

POST /auth/google

Body:

```
{
  "idToken": "google_id_token_from_mobile_sdk"
}
```

Response sama seperti login:

```
{
  "user": {},
  "accessToken": "jwt_access",
  "refreshToken": "jwt_refresh"
}
```

Catatan: Google OAuth saat ini bergantung konfigurasi env Google di server.

7.7 Email Verification Legacy

Endpoint masih ada tetapi flow register aktif saat ini langsung verified.

POST /auth/verify-email

POST /auth/resend-verification

8. User Profile Endpoints

Semua endpoint di bagian ini perlu token.

8.1 Update Profile

PATCH /users/me

Authorization: Bearer <accessToken>

Body semua field optional:

```
{
  "name": "Aditya Anugrah",
  "phone": "+6281234567890",
  "gender": "MALE",
  "birthDate": "2000-06-12T00:00:00.000Z",
  "city": "Magelang",
  "bio": "Suka ngobrol dan kuliner",
  "activity": "Founder",
  "industry": "Technology",
  "socialComfort": 4,
  "personalityType": "Ambivert",
  "leisureTopics": ["Kopi", "Film"],
  "conversationTopics": ["Bisnis", "Traveling"],
  "smokes": false,
  "drinksAlcohol": false,
  "dietaryNotes": "Tidak pedas",
  "interestIds": ["interest_id_1", "interest_id_2", "interest_id_3"]
}
```

Response: object user terbaru lengkap dengan `interests`.

8.2 My Bookings

GET /users/me/bookings

Authorization: Bearer <accessToken>

Response:

```
[
  {
    "id": "booking_id",
    "status": "PENDING_PAYMENT",
    "dinner": {},
    "budgetTier": {},
    "payment": {},
    "table": null,
    "createdAt": "2026-07-01T00:00:00.000Z"
  }
]
```

8.3 My Event Registrations

GET /users/me/event-registrations

Authorization: Bearer <accessToken>

Response:

```
[
  {
    "id": "registration_id",
    "status": "PENDING_PAYMENT",
    "payment": {},
    "event": {}
  }
]
```

9. Dinner & Booking Endpoints

9.1 List Dinner

GET /dinners

Authorization: Bearer <accessToken>

Query optional:

Query	Tipe	Keterangan
cityId	string	Filter kota
status	string	Filter status dinner

Default status jika tidak dikirim:

OPEN, MATCHING, CONFIRMED

Response:

```
[
  {
    "id": "dinner_id",
    "cityId": "city_id",
    "date": "2026-07-20T00:00:00.000Z",
    "startTime": "19:00",
    "status": "OPEN",
    "venueName": "Akan diumumkan H-1",
    "venueAddress": null,
    "city": { "id": "city_id", "name": "Magelang" },
    "budgetTiers": [
      { "id": "tier_id", "label": "Casual", "price": 175000 }
    ],
    "_count": { "bookings": 4 }
  }
]
```

Catatan: lokasi venue disembunyikan sampai dinner CONFIRMED/COMPLETED.

9.2 Detail Dinner

GET /dinners/:id

Authorization: Bearer <accessToken>

Response: object Dinner + city, budgetTiers, _count.bookings.

9.3 Create Booking

POST /bookings

Authorization: Bearer <accessToken>

Body:

```
{
  "dinnerId": "dinner_id",
  "budgetTierId": "tier_id"
}
```

Validasi:

- Dinner harus OPEN.
- Budget tier harus milik dinner tersebut.

- User wajib punya profile lengkap: birth date, gender, city, minimal 3 minat.
- Jika user sudah booking dinner yang sama, API mengembalikan booking existing.

Response 201:

```
{
  "id": "booking_id",
  "status": "PENDING_PAYMENT",
  "dinner": {},
  "budgetTier": {},
  "payment": {
    "id": "payment_id",
    "amount": 175000,
    "method": "QRIS",
    "status": "PENDING",
    "expiredAt": "2026-07-06T10:00:00.000Z"
  }
}
```

9.4 Detail Booking

GET /bookings/:id
Authorization: Bearer <accessToken>

User hanya bisa melihat booking sendiri. Admin bisa melihat semua.

Response: object Booking + dinner, tier, payment, table.

Jika lokasi belum reveal, field venue disamarkan.

9.5 Upload Bukti Pembayaran Booking

POST /bookings/:id/upload-proof
Authorization: Bearer <accessToken>
Content-Type: multipart/form-data

Form field:

Field	Tipe	Wajib
proof	file image	Ya

Response:

```
{
  "message": "Bukti pembayaran berhasil diupload",
  "proofUrl": "/uploads/payments/filename.jpg"
}
```

Setelah upload:

- booking status menjadi PENDING_VERIFICATION.
- payment status tetap PENDING sampai admin verify.

9.6 Cancel Booking

DELETE /bookings/:id
Authorization: Bearer <accessToken>

Response:

```
{
  "message": "Booking dibatalkan"
}
```


10. Event Registration Endpoints

10.1 Register Event

POST /events/:id/register
Authorization: Bearer <accessToken>

Response 201:

```
{
  "id": "registration_id",
  "eventId": "event_id",
  "userId": "user_id",
  "status": "PENDING_PAYMENT",
  "payment": {
    "amount": 55000,
    "method": "QRIS",
    "status": "PENDING",
    "expiredAt": "2026-07-06T10:00:00.000Z"
  },
  "event": {}
}
```

Jika event gratis (price <= 0), status langsung **CONFIRMED** dan payment **VERIFIED**.

10.2 Detail Event Registration

GET /events/registrations/:id
Authorization: Bearer <accessToken>

Response: object EventRegistration + event.

10.3 Upload Bukti Pembayaran Event

POST /events/registrations/:id/upload-proof
Authorization: Bearer <accessToken>
Content-Type: multipart/form-data

Form field:

Field	Tipe	Wajib
proof	file image	Ya

Response:

```
{
  "message": "Bukti pembayaran berhasil diupload",
  "proofUrl": "/uploads/payments/filename.jpg"
}
```

11. Notification Endpoints

11.1 List Notifications

GET /notifications

Authorization: Bearer <accessToken>

Response:

```
[
  {
    "id": "notification_id",
    "channel": "IN_APP",
    "type": "PAYMENT_CONFIRMED",
    "payload": {},
    "sentAt": "2026-07-01T00:00:00.000Z",
    "isRead": false,
    "createdAt": "2026-07-01T00:00:00.000Z"
  }
]
```

11.2 Mark Notification Read

PATCH /notifications/:id/read

Authorization: Bearer <accessToken>

Response: notification updated.

11.3 Mark All Notifications Read

PATCH /notifications/read-all/all

Authorization: Bearer <accessToken>

Response:

```
{
  "message": "Semua notifikasi dibaca"
}
```

12. Admin API

Endpoint admin tidak wajib dipakai mobile user app, tetapi berguna jika nanti dibuat mobile admin app. Semua perlu token role ADMIN.

12.1 Admin Overview

GET /admin/overview

Authorization: Bearer <adminAccessToken>

Response:

```
{
  "totalUsers": 100,
  "totalBookings": 50,
  "confirmedBookings": 30,
  "pendingPayments": 3,
  "upcomingDinners": 2,
  "totalEventRegistrations": 20,
  "activeEvents": 1,
  "revenue": 5000000
}
```

12.2 Admin Settings

GET /admin/settings

PATCH /admin/settings

POST /admin/settings/qris

Upload QRIS:

POST /admin/settings/qris

Content-Type: multipart/form-data

Form field:

Field	Tipe
qris	file image

12.3 Admin User Management

GET /users

GET /users/:id

PATCH /users/:id/role

PATCH /users/:id/suspend

Change role body:

```
{ "role": "ADMIN" }
```

Suspend body:

```
{ "isSuspended": true }
```

12.4 Admin City Management

GET /cities/all

POST /cities

PUT /cities/:id

DELETE /cities/:id

GET /cities/requests/all

Create/update city body:

```
{
  "name": "Magelang",
  "areas": ["Magelang Utara", "Magelang Selatan"],
  "isActive": true
}
```

12.5 Admin Dinner Management

GET /dinners/all
POST /dinners
PUT /dinners/:id
PATCH /dinners/:id/status
PATCH /dinners/:id/reveal
DELETE /dinners/:id

Create dinner body:

```
{
  "cityId": "city_id",
  "date": "2026-07-20T00:00:00.000Z",
  "startTime": "19:00",
  "maxPerTable": 6,
  "venueName": "Nama venue optional",
  "venueAddress": "Alamat optional",
  "arrivalTime": "18:45",
  "reservationName": "RuangTemu",
  "hostName": "Aditya",
  "hostPhone": "+6281234567890",
  "venueNotes": "Datang tepat waktu",
  "budgetTiers": [
    { "label": "Casual", "price": 175000 },
    { "label": "Premium", "price": 275000 }
  ]
}
```

Update status body:

```
{ "status": "MATCHING" }
```

Reveal body:

```
{
  "venueName": "Cafe Contoh",
  "venueAddress": "Jl. Contoh No. 1",
  "arrivalTime": "18:45",
  "reservationName": "RuangTemu",
  "hostName": "Aditya",
  "hostPhone": "+6281234567890",
  "venueNotes": "Tunjukkan nama reservasi ke kasir",
  "tables": [
    { "id": "table_id", "venueTableLabel": "Meja A1" }
  ]
}
```

12.6 Admin Payment Management

GET /payments
GET /payments/pending
PATCH /payments/:id/verify
PATCH /payments/:id/reject

Query optional:

GET /payments?status=PENDING

Reject body:

```
{
  "note": "Bukti tidak jelas"
}
```

Catatan:

- Untuk booking, `:id` adalah `Payment.id`.
- Untuk event registration, `:id` adalah `EventRegistration.id` karena payment event tersimpan sebagai JSON.
- Response list payment mengandung field `type`: `BOOKING` atau `EVENT`.
- Field `isActionable` menandai item pending yang masih bisa diverifikasi/ditolak.

12.7 Admin Booking Management

GET /bookings

POST /bookings/manual-confirmed

PATCH /bookings/:id/reschedule

Manual confirmed body:

```
{
  "userId": "user_id",
  "dinnerId": "dinner_id",
  "budgetTierId": "tier_id",
  "method": "BANK_TRANSFER",
  "note": "Sudah bayar offline"
}
```

Reschedule body:

```
{
  "dinnerId": "target_dinner_id",
  "budgetTierId": "target_tier_id"
}
```

12.8 Admin Event Management

GET /events/all

POST /events

PUT /events/:id

POST /events/:id/poster

DELETE /events/:id

GET /events/:id/registrations

POST /events/manual-confirmed

PATCH /events/registrations/:id/reschedule

Create/update event body:

```
{
  "title": "Bertemu with strangers",
  "slug": "bertemu-with-strangers",
  "description": "Deskripsi event",
  "date": "2026-07-20T12:00:00.000Z",
  "cityId": null,
  "price": 55000,
  "capacity": 50,
  "status": "OPEN"
}
```

Upload poster:

POST /events/:id/poster
Content-Type: multipart/form-data

Form field:

Field	Type
poster	file image

Manual confirmed event body:

```
{
  "userId": "user_id",
  "eventId": "event_id",
  "method": "BANK_TRANSFER",
  "note": "Sudah bayar offline"
}
```

Reschedule event body:

```
{
  "eventId": "target_event_id"
}
```

12.9 Admin Matching

GET /matching/:dinnerId/preview
POST /matching/:dinnerId/commit
GET /matching/:dinnerId/tables
GET /matching/:dinnerId/manual
POST /matching/:dinnerId/manual/setup
POST /matching/:dinnerId/manual/tables
PATCH /matching/bookings/:bookingId/table

Preview response:

```
{
  "tables": [
    {
      "tableScore": 8.5,
      "participants": [
        {
          "bookingId": "booking_id",
          "userId": "user_id",
          "name": "Ayu",
          "age": 24,
          "gender": "FEMALE",
          "location": "Magelang",
          "interests": ["Musik", "Kopi"],
          "matchProfile": {}
        }
      ]
    }
  ],
  "unassigned": 0
}
```

Manual board response:

```
{
  "dinner": {},
  "tables": [
    {
      "id": "table_id",
      "name": "Meja 1",
      "venueTableLabel": null,
      "participants": []
    }
  ],
  "unassigned": []
}
```

Setup manual body optional:

```
{
  "tableCount": 3
}
```

Move participant body:

```
{
  "tableId": "table_id"
}
```

Unassign participant body:

```
{
  "tableId": null
}
```

12.10 Admin Interest/Testimonial

```
POST /interests
DELETE /interests/:id
POST /testimonials
PATCH /testimonials/:id
DELETE /testimonials/:id
```

Create interest body:

```
{ "name": "Musik" }
```

Create/update testimonial body:

```
{
  "name": "Ayu",
  "age": 24,
  "content": "Seru banget!",
  "isPublished": true
}
```


13. Mobile Implementation Notes

13.1 API Client Pseudocode

```
const API_BASE_URL = "https://api.ruangtemu.biz.id";

async function apiRequest(path, options = {}) {
  const accessToken = await secureStorage.get("accessToken");

  let response = await fetch(`${API_BASE_URL}${path}`, {
    ...options,
    headers: {
      Accept: "application/json",
      ...(options.body instanceof FormData ? {} : { "Content-Type": "application/json" }),
      ...(accessToken ? { Authorization: `Bearer ${accessToken}` } : {}),
      ...options.headers,
    },
  });

  if (response.status === 401) {
    const refreshed = await refreshToken();
    if (refreshed) {
      const newAccessToken = await secureStorage.get("accessToken");
      response = await fetch(`${API_BASE_URL}${path}`, {
        ...options,
        headers: {
          Accept: "application/json",
          ...(options.body instanceof FormData ? {} : { "Content-Type": "application/json" }),
          Authorization: `Bearer ${newAccessToken}`,
          ...options.headers,
        },
      });
    }
  }

  const json = await response.json().catch(() => null);
  if (!response.ok) throw new Error(json?.message || "Request gagal");
  return json;
}
```

13.2 Refresh Token Pseudocode

```
async function refreshToken() {
  const refreshToken = await secureStorage.get("refreshToken");
  if (!refreshToken) return false;

  const response = await fetch(`${API_BASE_URL}/auth/refresh`, {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({ refreshToken }),
  });

  if (!response.ok) {
    await secureStorage.remove("accessToken");
    await secureStorage.remove("refreshToken");
    return false;
  }

  const data = await response.json();
  await secureStorage.set("accessToken", data.accessToken);
  await secureStorage.set("refreshToken", data.refreshToken);
  return true;
}
```

13.3 Upload Bukti Pembayaran Mobile

React Native style:

```
const form = new FormData();
form.append("proof", {
  uri: imageUri,
  name: "proof.jpg",
  type: "image/jpeg",
});

await fetch(`${API_BASE_URL}/bookings/${bookingId}/upload-proof`, {
  method: "POST",
  headers: {
    Authorization: `Bearer ${accessToken}`,
  },
  body: form,
});
```

Untuk event:

POST /events/registrations/:id/upload-proof

13.4 Asset URL

Jika API mengembalikan:

```
{ "proofUrl": "/uploads/payments/file.jpg" }
```

Mobile harus menampilkan:

```
const imageUrl = `${API_BASE_URL}${proofUrl}`;
```

13.5 Payment Flow Mobile

Dinner

1. GET /dinners
2. User pilih dinner dan tier.
3. POST /bookings
4. GET /admin/public-settings untuk QRIS/bank.

5. Tampilkan instruksi pembayaran.
6. Upload bukti: `POST /bookings/:id/upload-proof`.
7. Poll/refresh `GET /bookings/:id` atau `GET /users/me/bookings`.
8. Jika `payment.status = VERIFIED`, tampilkan booking confirmed.
9. Jika `booking.status = MATCHED`, tampilkan table info.
10. Jika dinner sudah reveal, tampilkan lokasi.

Event

1. `GET /events`
2. `GET /events/:slug`
3. `POST /events/:id/register`
4. Tampilkan payment instruction.
5. Upload bukti: `POST /events/registrations/:id/upload-proof`.
6. Poll `GET /events/registrations/:id` atau `GET /users/me/event-registrations`.

13.6 Reschedule Flow Mobile

Saat ini user tidak melakukan reschedule langsung dari API mobile. User diarahkan menghubungi WhatsApp. Admin yang menjalankan reschedule melalui admin endpoint.

13.7 Push Notification Future

Backend saat ini punya `Notification` in-app, email, dan WA. Untuk push notification mobile di masa depan, disarankan tambah model baru:

```
DeviceToken
- id
- userId
- provider: FCM/APNS
- token
- platform: android/ios
- createdAt
- updatedAt
```

Endpoint future yang disarankan:

```
POST /devices
DELETE /devices/:token
```

Body:

```
{
  "token": "fcm_or_apns_token",
  "platform": "android"
}
```

14. Checklist Integrasi Mobile

Minimal User App

- Register/login/logout.
- Secure token storage.
- Auto refresh token saat 401.
- Ambil kota dan interest onboarding.
- Update profile.
- List dinner.
- Detail dinner.
- Create booking.
- Ambil payment settings.
- Upload bukti pembayaran.
- Riwayat booking.
- Detail booking/table/lokasi reveal.
- List event.
- Register event.
- Upload bukti event.
- List notification.

Optional Admin Mobile App

- Admin overview.
- Payment verification.
- Dinner CRUD.
- Event CRUD.
- Matching auto/manual.
- Reveal lokasi.

15. Catatan Keamanan Mobile

- Jangan simpan token di plain AsyncStorage tanpa encryption.
- Jangan hardcode admin token.
- Jangan hardcode credential production.
- Semua request production wajib HTTPS.
- Untuk upload, batasi tipe file ke image dan ukuran file sesuai setting backend `MAX_FILE_SIZE_MB`.
- Jika mendapat `403 Akun disuspend`, paksa logout dan tampilkan pesan kontak admin.