

PHISHING SIMULATION IMPLEMENTATION ASSESSMENT

Controlled Reconnaissance, Scanning, Exploitation & Evidence Findings

Assessment Type	Controlled Security Implementation	Date	August 11, 2026
Framework Used	Zphisher v2.3.5 (htr-tech)	Target Binding	Loopback (127.0.0.1:8080)
Template Targeted	Instagram Traditional Login	Status	Controlled Capture Verified

1. RECONNAISSANCE & ENVIRONMENT SETUP

During the initial phase, social engineering toolsets were prepared in an isolated environment. The Zphisher framework was executed on Kali Linux to configure automated phishing templates. **Option 02 (Instagram)** was selected, followed by **Option 01 (Traditional Login Page)** to instantiate the localized cloning engine.

EVIDENCE 1: RECONNAISSANCE & FRAMEWORK SELECTION

Terminal interaction displaying Zphisher menu navigation and selection of the target template interface.

Zphisher Terminal Setup

2. SCANNING & SERVICE VERIFICATION

Following template configuration, the embedded web server bound to local address 127.0.0.1:8080 hosting login.html. Web browser inspection confirmed the presentation of a cloned Instagram login interface. Technical analysis revealed plain HTTP transport and non-standard port deployment as key indicators of compromise.

EVIDENCE 2: CLONED WEB SERVICE VERIFICATION

Browser rendering of the hosted login portal at address http://127.0.0.1:8080/login.html.

Cloned Login Interface

3. CONTROLLED EXPLOITATION & DATA CAPTURE

A controlled interaction was executed by submitting mock credentials (absbabsa / saaaaaaaaaa) into the input fields to evaluate data parsing and local storage mechanisms.

EVIDENCE 3: FORM INTERACTION & PAYLOAD ENTRY

Simulation of victim submitting mock trial credentials into the cloned input fields.

Mock Credential Submission

Upon form submission, the local listener immediately captured the HTTP POST request payload, logging the client IP (127.0.0.1) to auth/ip.txt and plain-text credentials to auth/usernames.dat.

EVIDENCE 4: SERVER-SIDE DATA EXTRACTION LOGS

Terminal console displaying immediate IP capture and harvested credential output saved to local files.

Captured Log Output

4. SUMMARY OF FINDINGS & INDICATORS OF COMPROMISE (IOCS)

Parameter	Observed Technical Finding / Anomaly
URL Host Header	Bound to plain IP address (127.0.0.1) rather than legitimate corporate or service domains.
Transport Protocol	Unencrypted HTTP connection (http://) lacking valid SSL/TLS certificate chains.
Port Hosting	Non-standard port allocation (:8080) typically unassociated with standard HTTPS authentication portals.
Data Extraction	Clear-text local storage in flat files (auth/ip.txt and auth/usernames.dat).

5. RECOMMENDED MITIGATION STRATEGIES

Key Enterprise Defensive Controls:

- FIDO2 / WebAuthn Hardware Authentication:** Implement domain-bound MFA tokens. WebAuthn validates the origin domain in the address bar before issuing authentication tokens, mitigating credential harvesting even if users enter passwords on spoofed portals.
- URL & Certificate Validation Controls:** Educate users to systematically check address bars for domain accuracy and valid TLS certificates.
- Automated DNS & Endpoint Filtering:** Enforce security controls blocking unrated external IP connections, custom non-standard web ports, and newly registered domains.