Scenario	Outcome	As expected
Valid token + fresh DPoP proof	200	yes
Replayed proof (same jti)	401 (jti)	yes
Stolen token, attacker's own key	401 (key_binding)	yes
Proof for different URL (htu)	401 (htu)	yes
Proof for different method (htm)	401 (htm)	yes
Stale proof (iat -5 min)	401 (iat)	yes
Tampered access token	401 (token_mac)	yes
Proof made for another access token (ath)	401 (ath)	yes
Stolen token sent as a bearer token, no proof	401 (proof_format)	yes
Proof with the owner's public key, signed by the attacker	401 (signature)	yes
Proof that declares another algorithm (HS256)	401 (alg)	yes
Valid ticket + proof of the same key	open (ready)	yes
Ticket reused	close 4401 (ticket_unused)	yes
Ticket presented with a different key	close 4401 (ticket_key)	yes
Ticket presented after 31 s	close 4401 (ticket_exp)	yes
Expired access token	401 (token_exp)	yes
Refresh-token rotation	200	yes
Refresh token presented with the attacker's key	401 (key_binding)	yes
Old refresh token reused	401 (reuse)	yes
Rotated token after reuse detected	401 (family_revoked)	yes
Access token of the revoked family	401 (token_revoked)	yes
Logout while a socket is open	close 4001 (session_ended)	yes
Access token after logout	401 (token_revoked)	yes
Login brute force: sixth guess on one account	429 (rate_limited)	yes
Login brute force: the right password while the limit holds	429 (rate_limited)	yes
X25519+HKDF content key agreement	keys equal	yes