

# Program Analysis and Transformation (PAT)

Robert Glück University of Copenhagen

Block 4, 2025

#### Motivation & This Course

- Despite tremendous progress in <u>hardware</u>, the production of <u>software</u> is
  - manual
  - error prone
  - costly
- Exploding demand for software leds to low SW quality (and lack of skilled CS graduates ©
- Methods for more automatized SW construction needed.
- This course: Foundations and methods that have the potential to raise program development to a more automated process.

#### Approach: Programs as Data Objects

#### Build programs that treat programs as data objects:

- · Analyze, transform, generate programs
- · Manipulate programs by means of programs

#### Three <u>basic operations</u> on programs [Glück,Klimov'94]

1. Specialize: e.g. generating extensions, staging

2. Invert: e.g. reversible computing

3. Compose: e.g. deforestation, program slicing

Programs are semantically the most complex data objects in the computer.

## Familiar: Equivalence Transformation



- optimize in time, space...
- · high abstraction levels
- · close algorithmic gap
- · preserve original semantics
- · Example: compilers

### Inversion of Programs



- · choose which direction to write
- $\bullet$  two programs from one program
- transform by inverse semantics
- Example: inverse interpreter [AbramovGlück'00], LR-program inverter [GlückKawabe'03]


### Inversion of Programs



- · choose which direction to write
- two programs from one program
- transform by inverse semantics
- Example: inverse interpreter [AbramovGlück'00], LR-program inverter [GlückKawabe'03]

8






[ReillyFederighi65,LutzDerby82]

## Specialization of Programs

 Partial evaluation: technique to specialize programs by dividing a computation into two stages.




- Literature: standard book [JonesGomardSestoft'93].
- · Most intense research phase from mid 80ies to end 90ies.

#### **Examples of Staged Computations**

Program  1-stage computation	Generating Extension 2-stage computation
[interpreter] (p, data)	[[translator] p] data
[parser] (grm, text)	[[parser-gen] grm] text

# Composition



- remove interface operations
- remove redundant operations
- reduce memory consumption

18

22

• Example: deforestation [Wadler'90]

## "Generation of Algorithms by Algorithms"

Such investigations would appear to <u>lead into the regions of meta-mathematics</u>, where the problems deal with the generation of systems rather than the systems themselves.

Future work may depend very strongly on an understanding of just these problems arising in the "generation" of algorithms by other algorithms.

[Brown,Carr'54]

20

# Metacomputation = Programs as Data + Metasystem Transition

#### Programs-as-Data Operations [Glück,Klimov'94]

Specialize: e.g. staging computation
 Invert: e.g. reversible computing
 Compose: e.g. deforestation, unstaging

#### Metalevels of Programs on Programs

- 1. Programs as data objects (Jones)
- 2. Self-application as method (Futamura)
- 3. Metasystem transition (Turchin)

# "Programs produce Programs"



Build programs that treat programs as data objects

- · Automatically manipulate programs by programs
- Analyze & transform programs by programs
- Metacomputation a long-term goal in CS
- ▲ Programs are semantically the **most complex** form of **data objects** in the computer.

23