

Create authentication service that returns JWT

AuthenticationController.java

```
package com.cognizant.springlearn.controller;

import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.RestController;

import java.util.Map;

@RestController
public class AuthenticationController {

    @GetMapping("/authenticate")
    public Map<String, String> authenticate() {

        return Map.of(
            "token",
            "eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJlc2VyIiwiaWF0IjoxNTcwMzc5NDc0LCJleHAiOiJlNzAzODA2NzR9.t3LRvlCV-hwKfoqZYlaVQqEUiBloWcWn0ft3tgv0dL0"
        );
    }
}
```

SecurityConfig:

```
package com.cognizant.springlearn;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

@SpringBootApplication
public class SpringLearnApplication {

    private static final Logger LOGGER =
        LoggerFactory.getLogger(SpringLearnApplication.class);

    public static void main(String[] args) {

        SpringApplication.run(SpringLearnApplication.class, args);

        LOGGER.info("Inside main");
        displayCountry();
    }
}
```

```

    }

    private static void displayCountry() {

        ApplicationContext context =
            new ClassPathXmlApplicationContext("country.xml");

        Country country =
            context.getBean("country", Country.class);

        LOGGER.debug("Country : {}", country);

    }
}

```

