K. J. Somaiya College of Engineering
Somaiya Vidyavihar University
Department of Computer Engineering

DEVOPS · MINI PROJECT REPORT

Automated Release Management Pipeline with Semantic Versioning and Git Tags

Submitted by	Roll No.
Aditey Kshirsagar	16010123017
Aditya Baheti	16010123023

Faculty in-charge: **Dr. Nirmala Baloorkar**

Course: DevOps (216U01E744) · L.Y. B.Tech Computer Engineering · Semester VII
Academic year 2026–27 · LAB CA, Activity 2

Repository: https://github.com/Aditey1908/semver-release-pipeline
Live deployment: https://devopslabca.onrender.com

October 2026

Contents

Abstract 3

1. Introduction 3

2. Background 4

3. Tools and technologies 4

4. System architecture 5

5. Implementation 6

6. Results 9

7. Mapping to the evaluation requirements 16

8. Challenges and solutions 16

9. Conclusion and future scope 17

10. References 17

Abstract

Releasing software by hand is slow and error-prone. Versions are bumped inconsistently, changelogs go stale, and it is often unclear which build is running in which environment. This project automates the whole release process. Developers write commit messages in the Conventional Commits format. A GitHub Actions pipeline validates every change, then works out the next Semantic Version from the commit history. It records the release as a Git tag, generates the changelog and GitHub Release, and publishes a versioned, multi-architecture Docker image to the GitHub Container Registry. It then promotes that same image through staging and production, checking each deployment against the expected version. Rollback is a redeployment of any earlier version tag. The delivered application is a release dashboard and semantic-version REST API, which also exposes the versioning rules to users.

1. Introduction

1.1 Problem statement

In many teams, releasing means editing a version number, writing release notes, tagging and building by hand. Each manual step can go wrong:

- a breaking change shipped as a patch version breaks users who trusted the version number;
- a missed tag makes it impossible to tell which commit is running in production;
- a changelog written from memory leaves changes out;
- an image rebuilt between test and deployment means production is not running what was tested.

1.2 Objectives

1. Enforce a commit convention that captures the *intent* of each change (fix, feature, breaking change).
2. Calculate the next version automatically according to Semantic Versioning 2.0.0.
3. Use Git tags as the single source of truth for releases.
4. Generate changelogs, GitHub Releases and release assets with no manual editing.
5. Gate every release behind automated quality checks: lint, tests, coverage, dependency audit, and a container build with a smoke test.
6. Containerise the application and publish immutable, versioned images.
7. Deploy through staging to production, verify each deployment, and support one-click rollback.

1.3 Scope

The project covers every stage named in the evaluation scheme: version control, build, automated testing, containerisation, CI/CD, deployment and documentation. It uses only free services: GitHub, GitHub Actions, GHCR and Render's free tier.

2. Background

Semantic Versioning (SemVer 2.0.0). A version `MAJOR.MINOR.PATCH` tells users what to expect. A PATCH contains backwards-compatible bug fixes. A MINOR adds backwards-compatible functionality. A MAJOR contains incompatible changes. Pre-release versions such as `2.0.0-beta.1` have lower precedence than the release they lead up to.

Conventional Commits. A lightweight convention for commit messages: `type(scope)!: subject`, with an optional body and footers. The type and the optional `!` or `BREAKING CHANGE:` footer can be read by machines, so the release impact of a commit can be calculated:

Commit	Release
`fix:`, `perf:`, a git revert	PATCH
`feat:`	MINOR
`type!:` or a `BREAKING CHANGE:` footer	MAJOR
`docs:`, `test:`, `ci:`, `chore:`, `refactor:`, `style:`, `build:`	none

Git tags are named references to specific commits. Tagging each release `vX.Y.Z` permanently links a version to the exact source it was built from, and makes it easy to compare two releases (`git diff v1.1.0 v1.2.0`).

3. Tools and technologies

Area	Tool	Use in this project
Version control	Git, GitHub	Source history, pull requests, tags, releases
Commit convention	commitlint, Husky	Rejects non-conforming commits locally (Git hook) and in CI
Application	Node.js 24 LTS, Express 5, Helmet	Semantic-version REST API and static file server
Frontend	React 19, Tailwind CSS 4, neobrutalism.dev components	Release dashboard UI
Build	Vite 8, Node build script	Bundles the dashboard into `dist/` and stamps version metadata into it
Testing	Vitest, Supertest, V8 coverage	Unit and API integration tests, coverage thresholds, JUnit report
Code quality	ESLint 10, npm audit	Static analysis, dependency vulnerability gate
Release automation	semantic-release	Version calculation, CHANGELOG, Git tag, GitHub Release
Containerisation	Docker, Buildx, Docker Compose	Multi-stage image, multi-arch build, deployment manifest
Registry	GitHub Container Registry (GHCR)	Versioned image storage with SBOM and provenance
CI/CD	GitHub Actions	CI, release, deployment and rollback workflows

Area	Tool	Use in this project
Hosting	Render; GitHub Pages (optional)	Production container; an optional static copy of the dashboard
Maintenance	Dependabot	Automated dependency updates with conventional prefixes

4. System architecture




Figure 1: Pipeline overview

The pipeline consists of three GitHub Actions workflows:

Workflow	Trigger	Stages
`ci.yml`	Every pull request; called by `release.yml`	Commit and PR-title lint · ESLint · tests on Node 22 and 24 with coverage · dependency audit · build artifact · Docker build and container smoke test · release preview
`release.yml`	Push to `main` (stable) or `beta` (pre-release)	Quality gate → semantic release → image publish → staging → production
`deploy.yml`	Called by `release.yml`; manual for rollback	Validate version → confirm image → deploy → smoke test → publish Pages (optional)

`ci.yml` is a *reusable workflow*. The checks that guard pull requests run again, unchanged, as the first stage of every release, so the same definition is never duplicated. `deploy.yml` is reusable in the same way, so a normal release and a rollback follow the same, already-tested deployment path.

5. Implementation

5.1 Version control and branching

- **Trunk-based branching.** Short-lived feature branches merge into `main` through pull requests, and every merge to `main` is a release candidate. A `beta` branch publishes pre-releases (`X.Y.Z-beta.N`).
- **Commit convention enforced twice.** Husky installs a `commit-msg` hook that runs commitlint, and a `pre-commit` hook that runs lint and tests. Hooks can be skipped locally, so CI checks every commit in the PR, and the PR title, again.
- **Dependabot** opens update PRs with `fix(deps):` for production dependencies, which produces a patch release, and `chore(deps):` for development tooling, which produces no release.

5.2 Application

The application under delivery is a Node.js/Express service:

- `src/core/` is a dependency-free semantic-versioning engine. It parses, compares and bumps versions according to SemVer 2.0.0, analyses Conventional Commits, and parses the generated changelog. Because it has no Node-specific imports (enforced by an ESLint rule), the same code runs on the server and in the browser.
- `src/server/` contains the REST API: `/health`, `/api/version`, `/api/releases`, `/api/semver/next`, `/api/semver/bump` and `/api/semver/compare`. It validates input, applies security headers with Helmet, and returns errors as JSON without exposing internals.
- `web/` is a React dashboard showing the deployed version, commit, build time and environment, the release history, and an interactive next-version calculator. It is styled with Tailwind CSS and the open-source neobrutalism.dev component library (Card, Button, Badge, Input, Textarea, Table and Marquee). The components are copied into the project from the library's registry, as the library intends, and use its "Blue" theme. The calculator imports the same `src/core` engine as the server, so the browser and the API cannot disagree.
- `src/index.js` writes structured JSON logs and shuts down gracefully on `SIGTERM`, which matters for containers.

5.3 Build

`npm run build` uses Vite to bundle the React dashboard into `dist/`, a self-contained static site with minified, content-hashed assets and self-hosted fonts. The container serves it, the same build can be published to GitHub Pages, and asset URLs are relative so the same build works at any URL path. The build also writes:

- `build-info.json`, containing the version, commit SHA, build time and repository URL. These come from the pipeline (`APP_VERSION`, `GIT_SHA`, …), with local fallbacks.
- `releases.json`, the release history parsed from `CHANGELOG.md`.

The build fails if the version is not valid SemVer. This is how the release version reaches the running application: `/api/version` and the dashboard read the values stamped in at build time.

5.4 Automated testing

94 automated tests run with Vitest:

Suite	Covers
`tests/unit/semver.test.js`	Parsing (including invalid inputs), the precedence ordering example from the SemVer specification, bumping, pre-releases
`tests/unit/commits.test.js`	Commit parsing, `!` and `BREAKING CHANGE` detection, reverts, highest-impact selection, first release = 1.0.0
`tests/unit/changelog.test.js`	Parsing of a **real** CHANGELOG produced by semantic-release
`tests/integration/api.test.js`	Every endpoint via Supertest, input validation, malformed JSON, 404/500 handling, security headers
`tests/unit/dashboard.test.js`	Dashboard helpers: release-type classification, development-build detection, date formatting, data loading and its fallback when no API exists

Coverage thresholds of 90% lines, statements and functions and 85% branches are enforced, so CI fails if coverage drops. The achieved coverage is about 99% of lines. In CI the tests run on Node 22 and Node 24, and a JUnit report and an HTML coverage report are uploaded as artifacts.

After each deployment, `scripts/smoke-test.js` checks the live service. It verifies that `/health` is OK and that `/api/version` reports the *expected* version, retrying while the deployment rolls out. It also checks that the dashboard is served and that the API computes a correct result.

5.5 Containerisation

The `Dockerfile` has three stages:

1. **deps**: `npm ci --omit=dev`, so the image contains production dependencies only.
2. **build**: installs the build tooling and runs the Vite build, with the version metadata passed as build arguments. It runs on the build machine's native platform (`--platform=$BUILDPLATFORM`) because its output is plain static files, so multi-architecture builds don't have to emulate the slowest stage.
3. **runtime**: `node:24-alpine` with only `package.json`, `src/`, `dist/` and the production `node_modules`.

Hardening measures:

- The app runs as a non-root user (UID 1000).
- The application files are owned by root, so the process cannot modify them.
- The container works with a read-only root filesystem.
- `no-new-privileges` is set.
- A `HEALTHCHECK` probes `/health`.
- OCI labels record the version, revision and creation time.
- `.dockerignore` keeps tests, docs, `.git` and secrets out of the build context.

`docker-compose.yml` is the deployment manifest for local runs and for staging.

5.6 Continuous integration

Every pull request runs `ci.yml`. Its jobs run in parallel where possible:

1. **Conventional commits**: commitlint over the PR's commit range and the PR title.
2. **Lint & test**: a matrix over Node 22 and 24, with coverage thresholds.
3. **Dependency audit**: fails on high-severity vulnerabilities in production dependencies.
4. **Build application**: uploads `dist/` as an artifact.
5. **Docker build & container smoke test**: builds the image with layer caching, runs it with production hardening flags, smoke-tests it, and checks that Docker reports it as `healthy`.
6. **Release preview**: predicts the version the PR will release and posts it in the job summary.

5.7 Release automation with semantic versioning and Git tags

On every push to `main`, `release.yml` first re-runs the full quality gate. semantic-release (configured in `.releaserc.json`) then performs the release through its plugins:

Plugin	Step
`commit-analyzer`	Finds the last `v*` tag, reads the commits since it, and decides patch, minor, major or no release
`release-notes-generator`	Groups commits into Features, Bug Fixes, BREAKING CHANGES and so on
`changelog`	Prepends the notes to `CHANGELOG.md`
`npm`	Writes the new version into `package.json` (publishing to npm is disabled)
`exec`	Builds `dist/` and packages it as `…-vX.Y.Z.tar.gz` with a `SHA256SUMS.txt`
`git`	Commits the changed files as `chore(release): X.Y.Z [skip ci]` and pushes
`github`	Creates the `vX.Y.Z` tag and GitHub Release, uploads the assets, and comments on the released issues and PRs

The workflow compares the repository's tags before and after this step to detect whether a new version was published, and passes `version`, `tag`, `prerelease` and `channel` as job outputs to the later stages. If nothing is releasable, the run ends with a "No release" summary.

Image publication. The image job checks out the new tag rather than the triggering commit, so the build includes the bumped version and changelog. It builds for `linux/amd64` and `linux/arm64` and pushes to GHCR with these tags:

- `X.Y.Z` (never changed once published)
- `X.Y` and `X` (move to the newest matching release)
- `latest` (newest stable release)

Pre-releases are tagged only with their full version and the channel name (`beta`). Each image carries an SBOM and build-provenance attestations.

5.8 Deployment

Deployment *promotes* the image that was already built. Nothing is rebuilt between environments.

- **Staging**: an ephemeral environment on the runner. The released image is pulled from GHCR and started with `docker compose up --wait`, which waits for the health check. The smoke test then verifies the version, the logs are collected, and the environment is torn down.

- **Production**: the GitHub `production` environment can require a reviewer's approval, which gives a manual release gate. The job calls Render's deploy hook with `imgURL=ghcr.io/…:X.Y.Z`. It then polls the public URL until it reports the new version. When Pages is enabled, it also publishes the dashboard for that version there; it is switched off for this private repository.
- **Pre-releases** from `beta` stop at staging.

Concurrency groups ensure two releases never run at once and that a release is never cancelled midway.

5.9 Rollback

Every released image stays in GHCR under its version tag, so rolling back is an ordinary deployment. Run **Actions → Deploy → Run workflow** with an older version, and the same validated deployment path redeploys that image and verifies it.

5.10 Security practices

- Workflow `GITHUB_TOKEN` permissions are least-privilege and set per job.
- User-controlled values such as PR titles and inputs are passed through environment variables and never interpolated into scripts.
- The release job runs `npm audit signatures` to verify the integrity of installed packages.
- The image is non-root and read-only, and carries an SBOM and provenance.
- Helmet sets security headers, request bodies are size-limited, the dashboard is protected from XSS, and internal error details are hidden.
- Secrets (the Render deploy hook) are scoped to the `production` environment.

6. Results

All figures come from real runs of this project's pipeline between 6 and 21 October 2026. The repository is private, so the pipeline evidence is shown as GitHub CLI output and GitHub Actions log excerpts rather than screenshots of GitHub's web pages. Excerpts are filtered with `grep`, and timestamps, long URLs and image digests are shortened for readability; nothing else is changed.

6.1 Version control

```
zsh — local commit rejected by the commit-msg hook

$ git commit -m "updated stuff"
⧗   --- input ---
updated stuff
✖   subject may not be empty [subject-empty]
✖   type may not be empty [type-empty]
✖   found 2 problems, 0 warnings
ⓘ   Get help: https://github.com/conventional-changelog/commitlint/#what-is-commitlint
husky - commit-msg script failed (code 1)

$ git commit -m "Feat: Added Parse Endpoint."
✖   subject must not be sentence-case [subject-case]
✖   subject may not end with full stop [subject-full-stop]
✖   type must be lower-case [type-case]
✖   type must be one of [build, chore, ci, docs, feat, fix, perf, refactor, revert, style, test] [type-enum]
✖   found 4 problems, 0 warnings
husky - commit-msg script failed (code 1)
```

Figure 2: The `commit-msg` Git hook runs commitlint and rejects messages that don't follow Conventional Commits, before the commit is created.

```
zsh — Git history, release tags and generated CHANGELOG

$ git log --oneline --decorate --graph -14 v1.1.0
* f093d9e (tag: v1.1.0) chore(release): 1.1.0 [skip ci]
* 44797c6 docs: describe the new dashboard stack and add team members to the report
* 459f6f5 feat(ui): rebuild the dashboard in React with neobrutalism.dev components
* 6d6f5c4 ci(commitlint): accept Dependabot's capitalised "Bump" subjects
* bd26962 ci(dependabot): hold the changelog preset at v9 until semantic-release supports v10
* 5388362 docs(setup): cover private repositories and private GHCR images
* c4cdb29 (tag: v1.0.0) chore(release): 1.0.0 [skip ci]
* 942c568 docs: add README, setup guide, demo guide and project report
* 9571489 ci: automate releases with semantic-release and versioned deployments
* a556443 build(docker): add multi-stage image and compose deployment manifest
* 84b1209 feat(ui): add release dashboard with next-version calculator
* 105e97f feat(api): add version, release and semver endpoints
* 1ca2d64 feat(core): parse the generated changelog into release history
* 9b02bdb feat(core): predict the next release from conventional commits

$ git tag --list "v*"
v1.0.0
v1.1.0

$ head -14 CHANGELOG.md
# Changelog

All notable changes to this project are documented in this file. It is generated automatically by [semantic-release] from
[Conventional Commits] — do not edit it by hand.

## [1.1.0] (2026-10-07)

### Features

* **ui:** rebuild the dashboard in React with neobrutalism.dev components (459f6f5)

### Documentation

* describe the new dashboard stack and add team members to the report (44797c6)
* **setup:** cover private repositories and private GHCR images (5388362)
```

Figure 3: The history up to the v1.1.0 release. Every commit follows Conventional Commits, each release is a `chore(release)` commit tagged `vX.Y.Z`, and `CHANGELOG.md` is generated from the commit messages.

6.2 Automated testing




Figure 4: All 94 unit and API tests pass, and coverage is well above the enforced thresholds (90% lines, statements and functions; 85% branches).

6.3 Continuous integration on a pull request




Figure 5: The pull request that added this section. Every CI check passes, and the release preview correctly reports that a documentation-only change will not create a release.

6.4 Automated release: v1.1.0

Merging `feat(ui): rebuild the dashboard in React with neobrutalism.dev components` into `main` produced release v1.1.0 with no manual steps.

GitHub CLI — Release workflow run for v1.1.0

```
$ gh run view 37600034355
✓ main Release · 37600034355
Triggered via push about 20 minutes ago
JOBS
✓ Quality gate / Release preview in 6s (ID 112721878377)
✓ Quality gate / Dependency audit in 7s (ID 112721878570)
✓ Quality gate / Lint & test (Node 24) in 29s (ID 112721878677)
✓ Quality gate / Lint & test (Node 22) in 29s (ID 112721878694)
- Quality gate / Conventional commits in 0s (ID 112721879945)
✓ Quality gate / Build application in 24s (ID 112722073398)
✓ Quality gate / Docker build & container smoke test in 1m29s (ID 112722073744)
✓ Semantic release in 44s (ID 112722655518)
✓ Container image → GHCR in 2m6s (ID 112722952500)
✓ Staging / Deploy v1.1.0 → staging in 23s (ID 112723772294)
✓ Production / Deploy v1.1.0 → production in 28s (ID 112723942556)
- Staging / Release dashboard → GitHub Pages in 0s (ID 112723942673)
- Production / Release dashboard → GitHub Pages in 0s (ID 112724145241)
ARTIFACTS
Aditey1908~semver-release-pipeline~09WGU6.dockerbuild
test-reports
dist
Aditey1908~semver-release-pipeline~75PR1N.dockerbuild
```

Figure 6: The Release workflow. The quality gate, semantic release, image publication, staging and production all succeeded. The Conventional commits job only runs on pull requests, and the Pages jobs are switched off for this private repository.

GitHub Actions log — semantic-release

```
$ gh run view 37600034355 --log --job 112722655518 | grep semantic-release
[semantic-release] › ℹ  Running semantic-release version 25.0.9
[semantic-release] › ℹ  Found git tag v1.0.0 associated with version 1.0.0 on branch main
[semantic-release] › ℹ  Found 5 commits since last release
[semantic-release] › ℹ  Analyzing commit: docs: describe the new dashboard stack and add team members to the report
[semantic-release] › ℹ  Analyzing commit: feat(ui): rebuild the dashboard in React with neobrutalism.dev components
[semantic-release] › ℹ  The release type for the commit is minor
[semantic-release] › ℹ  Analyzing commit: ci(commitlint): accept Dependabot's capitalised "Bump" subjects
[semantic-release] › ℹ  Analyzing commit: ci(dependabot): hold the changelog preset at v9 until semantic-release supports v10
[semantic-release] › ℹ  Analyzing commit: docs(setup): cover private repositories and private GHCR images
[semantic-release] › ℹ  Analysis of 5 commits complete: minor release
[semantic-release] › ℹ  The next release version is 1.1.0
[semantic-release] › ✔  Created tag v1.1.0
[semantic-release] [@semantic-release/github] › ℹ  Published GitHub release: https://github.com/Aditey1908/semver-release-
pipeline/releases/tag/v1.1.0
[semantic-release] › ✔  Published release 1.1.0 on default channel
```

Figure 7: semantic-release finds the previous tag (v1.0.0), analyses the five commits since it, identifies the `feat` commit as a minor change, and creates tag v1.1.0.

GitHub CLI — generated GitHub Release

```
$ gh release view v1.1.0
title:  v1.1.0
tag:    v1.1.0
draft:  false
prerelease:     false
immutable:      false
author: github-actions[bot]
created:        2026-10-07T09:24:01Z
published:      2026-10-07T09:24:08Z
url:    https://github.com/Aditey1908/semver-release-pipeline/releases/tag/v1.1.0
asset:  semver-release-pipeline-v1.1.0.tar.gz
asset:  SHA256SUMS.txt
--
## 1.1.0 (2026-10-07)
### Features
* **ui:** rebuild the dashboard in React with neobrutalism.dev components (459f6f5)
### Documentation
* describe the new dashboard stack and add team members to the report (44797c6)
* **setup:** cover private repositories and private GHCR images (5388362)
### Continuous Integration
* **commitlint:** accept Dependabot's capitalised "Bump" subjects (6d6f5c4)
* **dependabot:** hold the changelog preset at v9 until semantic-release supports v10 (bd26962)
```

Figure 8: The GitHub Release, with notes grouped by commit type and the versioned build artifact and checksum attached.

GitHub Actions log — image pushed to GHCR

```
$ gh run view 37600034355 --log --job 112722952500 | grep 'pushing manifest'
#38 pushing manifest for ghcr.io/aditey1908/semver-release-pipeline:1.1.0@sha256:1046c3c5618e…
#38 pushing manifest for ghcr.io/aditey1908/semver-release-pipeline:1.1@sha256:1046c3c5618e…
#38 pushing manifest for ghcr.io/aditey1908/semver-release-pipeline:1@sha256:1046c3c5618e…
#38 pushing manifest for ghcr.io/aditey1908/semver-release-pipeline:latest@sha256:1046c3c5618e…
```

Figure 9: One multi-architecture image, pushed to GHCR under the tags `1.1.0`, `1.1`, `1` and `latest`. All four tags point to the same digest.

6.5 Deployment

GitHub Actions logs — staging and production verification

```
$ gh run view 37600034355 --log --job 112723772294 | grep -E 'Container|✔'      # staging
 Container semver-release-pipeline-app-1  Started
 Container semver-release-pipeline-app-1  Healthy
  ✔ Health endpoint — status ok
  ✔ Deployed version — v1.1.0 (990e1b7) in "staging"
  ✔ Dashboard page — HTML served
  ✔ Semver API — feat on 1.4.2 -> 1.5.0
All smoke checks passed

$ gh run view 37600034355 --log --job 112723942556 | grep -E 'Render|✔|…'   # production
Render deployment of ghcr.io/aditey1908/semver-release-pipeline:1.1.0 triggered
  ✔ Health endpoint — status ok
  … Deployed version: serving v1.0.0, expected v1.1.0 (attempt 1/40, retrying in 15s)
  ✔ Deployed version — v1.1.0 (990e1b7) in "production"
  ✔ Dashboard page — HTML served
  ✔ Semver API — feat on 1.4.2 -> 1.5.0
All smoke checks passed
```

Figure 10: Staging starts the released image with Docker Compose and waits until it is healthy. In production, the first check found Render still serving v1.0.0, so the smoke test waited and passed only once v1.1.0 was live.




Figure 11: The production deployment at https://devopslabca.onrender.com, showing the version, commit and build time stamped in by the pipeline.

6.6 Rollback

On 21 October, release v1.1.1 (an upgrade of Express to 5.3.0) gave a second version with the current interface. Production was then rolled back to v1.1.0 and forward again.

```
GitHub CLI — rollback: Deploy workflow run with v1.1.0

$ gh workflow run deploy.yml -f version=1.1.0 -f environment=production

$ gh run view 39565658556
✓ main Deploy · 39565658556
Triggered via workflow_dispatch about 43 minutes ago
JOBS
✓ Deploy v1.1.0 → production in 31s (ID 119107191013)
- Release dashboard → GitHub Pages (ID 119107414504)

$ gh run view 39565658556 --log --job 119107191013 | grep -E 'Render|✓|…'
Render deployment of ghcr.io/aditey1908/semver-release-pipeline:1.1.0 triggered
  ✓ Health endpoint — status ok
  … Deployed version: serving v1.1.1, expected v1.1.0 (attempt 1/40, retrying in 15s)
  ✓ Deployed version — v1.1.0 (990e1b7) in "production"
  ✓ Dashboard page — HTML served
  ✓ Semver API — feat on 1.4.2 -> 1.5.0
```

Figure 12: A rollback is a manual run of the Deploy workflow with an earlier version. Production was serving v1.1.1, so the check waited until it served v1.1.0.




Figure 13: Production after the rollback, running v1.1.0. The same workflow then rolled production forward to v1.1.1.

The following were verified during development:

- All 94 tests pass, with about 99% line coverage.

- semantic-release was run against a test repository for four successive scenarios. A `fix` commit produced **1.0.1**, a `feat` produced **1.1.0**, a `ci`-only change produced **no release**, and a breaking change produced **2.0.0**. The app's own release preview predicted the same result in every case.
- The production container layout passed every smoke check, and the smoke test failed as expected when the deployed version did not match the expected one.

7. Mapping to the evaluation requirements

Requirement (LAB CA, Activity 2)	Where it is implemented
Version control using Git/GitHub	Conventional Commits, Husky hooks, PR workflow, Git tags `vX.Y.Z`, GitHub Releases
Application build	Vite production bundle of the React dashboard plus stamped version metadata (`scripts/build.js` → `dist/`); release tarball and checksum
Automated testing	94 Vitest unit and API tests, coverage thresholds, Node 22/24 matrix, post-deployment smoke tests
Containerisation using Docker	Multi-stage `Dockerfile`, hardened runtime, `HEALTHCHECK`, Compose manifest, multi-arch images in GHCR
CI/CD pipeline using GitHub Actions	`ci.yml`, `release.yml`, `deploy.yml` (reusable workflows, environments, concurrency)
Deployment to a suitable environment	Staging (Compose on the runner) → production (Render container, optional approval gate), with rollback
Project documentation	`README.md`, `docs/SETUP.md`, `docs/DEMO_GUIDE.md`, this report, generated `CHANGELOG.md`

8. Challenges and solutions

Challenge	Solution
Tags and releases pushed with `GITHUB_TOKEN` do not trigger other workflows, so a separate "on tag" workflow would never run	Image publishing and deployment are later jobs in the same workflow and receive the release version as job outputs
The release commit could start the pipeline again, in a loop	The release commit message contains `[skip ci]`
Git hooks installed by `npm ci` would run commitlint on the release commit inside CI	`HUSKY=0` disables hooks in all workflows, and commitlint ignores `chore(release)` commits
`docker/build-push-action` builds the *triggering* commit by default, which does not contain the bumped version	The image job checks out the new tag and builds with `context: .`
The newest changelog preset (`conventional-changelog-conventionalcommits@10`) failed at release time because it needs a newer changelog writer than semantic-release 25 ships. A dry run against a local test remote caught this.	Pinned the preset to the compatible major version (`^9`) and re-ran the full release simulation

Challenge	Solution
The React build uses native binaries (Rolldown, Tailwind's engine, LightningCSS), and a lockfile created on macOS might not include the Linux and Alpine builds needed by CI and Docker	Checked that `package-lock.json` lists the Linux glibc and musl builds for x64 and arm64, and tested the Docker build stage with only the files it copies
A broken release must not reach users	The quality gate runs before any version is created, staging must pass before production, and the smoke test checks the exact deployed version

9. Conclusion and future scope

The project turns releasing from a manual, error-prone procedure into a repeatable, auditable process. The version number is derived from what changed and is recorded as a Git tag. Every artifact, from the changelog and GitHub Release to the image tags and the running application, reports the same version. Each deployment is checked against it, and any earlier version can be restored with one action.

Possible extensions:

- Deploy to Kubernetes with Helm, versioning the chart in step with the application.
- Use canary or blue-green releases with automatic rollback on failing health metrics.
- Sign images with Sigstore cosign and verify the signatures before deployment.
- Add a Jenkins pipeline that runs the same stages, for comparison with GitHub Actions.
- Version packages independently in a monorepo.

10. References

1. T. Preston-Werner, *Semantic Versioning 2.0.0*. https://semver.org
2. *Conventional Commits 1.0.0*. https://www.conventionalcommits.org
3. semantic-release documentation. https://semantic-release.gitbook.io
4. GitHub Actions documentation: reusable workflows, environments and deployments. https://docs.github.com/actions
5. Docker documentation: multi-stage builds and Buildx. https://docs.docker.com
6. Render documentation: deploy hooks and deploying a prebuilt image. https://render.com/docs
7. commitlint documentation. https://commitlint.js.org