Submitted by: Adithya Mohanan
Registration no: 23BCE7300
Course title: Internet of Things
Course Code: CSE4011
Slot: E2+TE2

IoT - Assignment - I

Connected vehicles.

1). Introduction

Overview of Connected vehicles

Connected vehicles represents one of the most transformative applications of the Internet of Things (IOT) in modern transportation. A Connected vehicle is equipped with internet access and typically a wireless local area network (WLAN). enabling it to share data with other devices both inside and outside the vehicle. This category includes passenger cars, commercial vehicles etc. and even autonomous vehicles that rely heavily on constant connectivity.

The concept goes far beyond simple GPS navigation. Through a network of sensors, communication modules, cloud platforms, and data analytics engines, connected vehicles can interact with infrastructure, other vehicles, pedestrians and service providers in real time. Technologies such as vehicle to vehicle (V2V), vehicle to infrastructure (V2I) and vehicle to everything (V2X) communication form the backbone of this ecosystem.

Importance and relevance in Modern Society

The global automotive industry is undergoing a paradigm shift with rising urbanization, increasing traffic congestion, growing road accident fatalities, and environmental concerns related to carbon emissions, there is an urgent demand for smarter, safer and more efficient transportation systems. Connected vehicles addresses each of these challenges systematically

According to industry estimates, the global connected car market was valued over USD 63 billion in 2023 and is projected to exceed USD 200 billion by 2030. Governments across the world - from the United States and European union to India and China - are investing heavily in intelligent transportation infrastructure to accomodate connected and autonomous vehicles. In India, the Smart Cities Mission and the National Intelligent Transportation System (ITS) policy actively promote connected vehicle deployments.

Connected vehicles are not just a luxury feature, they are rapidly becoming a public safety and environmental necessity. They hold the promise of reducing traffic fatalities by up to 80%, optimizing fuel consumption, enabling predictive vehicle maintenance, and laying the groundwork for fully autonomous driving in the near future.

2) Problem Statement

Traditional transportation systems face a multitude of challenges that have become increasingly difficult to manage without intelligent, technology - driven solutions. The following core problems necessitate the adoption of IoT- enabled connected vehicle systems:-

Road Safety Crisis

Road accidents claim over 1.35 million lives globally each year, making them one of the leading causes of preventable death. In India alone, more than 150,000 deaths occur anually due to road accident. A significant proportion of these accident result from human error - including distracted driving, fatigue, over-speeding and failure to responds to hazards in real time.

Traffic Congestion and Inefficiency:

Urban congestion cost the global economy hundreds of dollars each year in lost productivity and excess fuel consumption without real-time data sharing between vehicles and traffic infrastructure - signal timing, route optimization and emergency vehicle prioritization suffer significantly from the lack of coordination.

Environmental Degradation:

Conventional vehicle operating in stop and go traffic produce disproportionally high levels of carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter. The absence of intelligent routing and eco-driving assistance means that millions of vehicles waste fuel unnecessarily. Contributing to pollution and climate change

Inefficient fleet Management and Logistics

Commercial fleet operators - including logistics companies, public transport authorities and emergency services - lack real-time visibility in every aspects. This results in inefficiencies

Lack of Preventive vehicle Maintenance

breakdowns on highways and city roads are a common occurrence, often due to undetected mechanical faults. Traditional maintenance schedules are based on mileage or time intervals rather than actual vehicle health data, leading to both premature servicing and unexpected failures. A data-driven, predictive approach is urgently needed.

3). Solution Overview.

IoT Architecture for Connected Vehicles.

The IoT-based Connected vehicle Solution consists of four primary architectural layers that work in tandem to collect, transmit etc. act on vehicle and environmental data.

Layer

Perception Layer:- OBD-II Sensors, GPS modules, LiDAR cameras etc - Collect real-time vehicle and environmental data (accelerometer, gyroscope sensors etc).

Connectivity Layer: DSRC (5.9 GHz), 4G/5G cellular modems, Wi-Fi 802.11p, Bluetooth - enable V2V, V2I and V2X communication

Processing Layer: Edge computing units in-vehicle and cloud platforms (AWS IoT, Azure IoT Hub) process, filter and analyze data streams

Application Layer: Driver assistance systems, fleet management dashboards, traffic management centers etc - deliver actionable insights

Block Diagram: Connected vehicle IoT System.
Representation of high-level architecture of IoT connected device

[vehicle Sensors & OBD-II] → [In vehicle ECU / Edge Processor]
↓ (DSRC / 5G / Wi-Fi)
[V2V Communication] ↔ [V2I: RSU / Traffic Signals]
↓ (4G / 5G cellular networks)
[Cloud platform: AWS IoT / Azure IoT Hub]
↓
[Driver App] [Fleet Dashboard] [Traffic Control Center] [OEM Backend]

Key Technologies Addressing Identified Problems:

- **V2X Communication (DSRC & C-V2X)** - Enables real-time alerts for collision avoidance, emergency braking - directly addressing road safety

- 5G Telematics: ultra-low latency (<1ms) data transmission support real-time navigation, traffic signal optimization and remote diagnostics

- OBD-II + CAN Bus Integration: Continuous monitoring of engine health, battery voltage, tire pressure, and brake wear enables predictive maintenance

- AI-based Driver Monitoring Systems (DMS): Camera + IR sensors detect drowsiness, distraction and aggressive driving patterns.

- Cloud based fleet Management Platforms: Aggregate data from hundreds of vehicles to optimize routes, reduce idle time, and minimize fuel costs

4) Implementation Process:-

- Device Selection:-

  - Telematics Control Unit (TCU): Central IoT gateway - eg: Sierra Wireless Airlink RV55 etc.

- GPS / GNSS module: u-blox NEO-M8N for precise positioning with ±2.5m accuracy and 10Hz update rate.

- OBD-II adapter: ELM327 or similar Bluetooth / WiFi OBD reads vehicle ECU data

- Microcontrollers / SBC: Raspberry Pi 4 or NVIDIA Jetson Nano for edge processing, camera inference (DMS), and local decision making

Sensors: MPU-6050 IMU (accelerometer + gyroscope) for harsh braking / cornering detection.
DHT22 for ambient temperature monitoring

Cellular Modem: SIM7060 (4G LTE) for cloud connectivity

Circuit Description

The core circuit integrates the OBD-II adapter, GPS module, and cellular modem with the central microcontroller. The OBD-II adapter interfaces with the vehicle's diagnostic port via a 16 pin connector and communicates with Raspberry Pi via UART/Bluetooth.
The GPS module connects to the Pi via UART. SIM7600 cellular module uses a USB or UART interface. The IMU (MPU-6050) connects via the I2C bus. DC-DC buck converter steps down the 12V supply to power the system safely.
A watchdog timer ensures the system restarts automatically in case of software hang. All components are housed in a ruggedized, vibration-resistant enclosure rated IP54 or better for automotive environments.

Software and Programming The software spans multiple layers. On the vehicle edge device, Python scripts handle sensor data acquisition. MQTT protocol is used for lightweight data publishing from the vehicle to the cloud. AWS IoT Service the MQTT messages and route them

Sensors: MPU-6050 IMU (accelerometer + gyroscope) for harsh braking / cornering detection
DHT22 for ambient temperature monitoring

Cellular Modem: SIM7060 (4G LTE) for cloud connectivity

Circuit Description

The core circuit integrates the OBD-II adapter, GPS module, and cellular modem with the central microcontroller. The OBD-II adapter interfaces with the vehicle's diagnostic port via a 16 pin connector and communicate with Raspberry Pi via UART/Bluetooth.
The GPS module connects to the Pi via UART
SIM7600 cellular module uses a USB or UART interface. The IMU (MPU-6050) connects via the I2C bus DC-DC buck converter steps down the 12V supply to power the system safely.
A watchdog timer ensures the system restarts automatically in case of software hang or
All components are housed in a ruggedized vibration-resistant enclosure rated IP54 or better for automotive environments.

Software and Programming The software spans multiple layers. On the vehicle edge device, Python scripts handle sensor data acquisition. MQTT protocol is used for lightweight data publishing from the vehicle to the cloud. AWS IoT receives the MQTT message and routes them to processing pipeline

cloud-side, Apache Kafka handles high-throughput stream processing, Apache Spark performs aggregation and analytics and machine learning models run anomaly detection. A Node JS or React JS frontend dashboard provides real-time visualization for fleet operations

• Integration with Existing Systems:

Connected vehicles are designed to integrate with existing city traffic management systems using standard APIs. In Smart City contexts, integration with traffic signal controllers enables green wave signaling for emergency vehicles and adaptive signal control for reduced congestion. Integration with OEM vehicle platform occurs through the AUTOSAR software architecture standards

5). features and functionality

Real time Navigation and Traffic Management:

Connected traffic system receive live traffic density data, alerts etc. Dynamic rerouting algorithm minimize travel time and fuel consumption. Integration with Smart Signals allows the vehicle to receive green light advisories. predicting speeds etc. reducing stops etc

Collision avoidance and ADAS:-

Advanced Driver Assistance Systems (ADAS) enabled by IoT include forward collision warning, Automatic Emergency Braking. Lane Departure warning, Blind Spot Detection. and Pedestrian Detection. V2V Communication extends the sensing range to vehicles own sensors.

Remote Diagnostics and Predictive Maintenance

The System continuously monitors over 200 vehicle parameters via the OBD-II interface. Machine learning algorithms analyze patterns in engine temp, oil pressure etc. to predict failures before they occur. Service alerts are automatically pushed to the driver's phone etc.

Driver Behaviour Monitoring and Scoring:

Telematics data including acceleration profiles, etc are aggregated to compute a driver Safety Score. Insurance Company use this for evaluation.

Stolen vehicle tracking and Remote Immobilization

GPS tracking with geofencing capabilities allows vehicle owners and fleet managers to receive instant alerts when a vehicle leaves a predefined geographic boundary. In case of theft, authorized parties can immobilize the engine via cloud.

Infotainment and Over-the-Air (OTA) updates:

They will recieve software update for navigation maps, ECU firmwares, and ADAS algorithms over air - similar to smartphone update. This improves efficiency

6) Benefits:-

Enhanced Road Safety:- Studies by the US National Highway Traffic Safety Administration (NHTSA) estimate that V2X communication could prevent upto 615,000 crashes and save approximately 1,366 lives annually in the US alone. European NCAP show that vehicles with advanced IoT ADAS feature secure more safety rating. It will reduce crash by 20 to 30% globally.

Reduced Traffic Congestion: Pilot deployments of connected vehicle infrastructure in cities like Columbus, Singapore and Amsterdam have demonstrated traffic flow improvements by 15 to 20%.

Environmental and fuel Efficiency Gains:-

Connected vehicle technologies including eco routing, green wave signaling, and predictive cruise control contribute to measurable reductions in fuel consumption and emissions. Research by European Commission ~~suggest~~ suggest C-ITS can reduce CO2 emissions by 10-20%

Economic Benefits for fleet operators:-

A study found that connected fleet management system reduce overall fleet operating cost by 10-20% through optimized routing, reduced fuel consumption, lower maintenance etc.

Improved Emergency Response:-

Connected vehicle platforms will integrate with emergency dispatch systems allow ambulances, fire engines and police vehicles to communicate with traffic signal ahead of them clearing green corridors for faster response.

7). Challenges and Lessons Learned.

Cybersecurity and vulnerabilities

As vehicle become more connected they also become potential targets for cyber attacks. High profile demonstration by security researchers expose the vullnerabilities that can be faced.

Data Privacy Concerns:- Connected vehicle generate enormous volume of personal data - location history etc. Ensuring compliance with data protection regulation. Lesson learned include importance of data minimization

Interoperability and Standardization challenge:

The connected vehicle ecosystem involves multiple stakeholders- each with their own proprietary systems and standards. Achieving seamless interoperability required strong standardization efforts.

Infrastructure Readiness and Investment:

It deals with a lot of capital investment and infrastructure unless it can't be put to use. So that much amount need to be nurtured

Connectivity gaps in Rural and Remote areas:

Deployment in Remote and Rural areas pose to be a problem due to network issues and terrain.

8). Future Outlook:

- 5G and Network Slicing for ultra-Reliable V2X.

The rollout of 5G network globally is set to be transformational for connected vehicles. 5G's ultra low latency, massive device density support etc enable this effectively.

10) Autonomous vehicle and Role of IOT.

Level 4 and 5 autonomous vehicles will be fundamentally IOT dependant systems. The vehicle's perception, planning and control system will continuously consume data from its own sensor suite etc.

Edge AI and on-vehicle Intelligence

The next generation of connected vehicles will move towards greater on-device intelligence, reducing reliance on cloud connectivity for latency-critical decisions. AI chips such as NVIDIA DRIVE Orin, etc provide unprecedented computing power.

vehicle to Grid (V2G) and Energy Management.

As electric vehicles (EVs) become mainstream, the connected vehicle ecosystem is expanding to include vehicle to Grid (V2G) capabilities.

Integration with Smart City Platforms.

The future of connected vehicles lies in deep integration with the broader Smart City ecosystem- including smart parking systems, and public transport management platform.

9) Conclusion:

This Case Study has presented a comprehensive examination of IoT enabled connected vehicle systems. Covering full spectrum from foundational concepts and architecture to real world implementation and benefits, challenges and the exciting road ahead.

Connected vehicles represent far more than a technological upgrade to the ~~aut~~ automobile they signify a fundamental reimagining of transportation as a networked, intelligent data driven system. By integrating everything IoT enables the platforms that address some of the most pressing challenges faced by the modern transportation.

In conclusion, IoT-based connected vehicles are not a future aspiration - they are an accelerating present reality with the potential to save countless lives, power sustainable urban mobility etc.

10). References.

1). National Highway Traffic Safety Administration (NHTSA) (2022). Vehicle to Vehicle Communication Readiness of V2V Technology for Application. US Department of Transportation

2). European Telecommunications Standards Institute (ETSI) (2021).

3). McKinsey & Company (2021): The future of mobility.

4). SAE International (2021).

5). Ministry of Road Transport and Highways, Government of India 2021-

6). Siegel, A Survey of the Connected vehicle landscape (2018)

7). Kenney J.B (2011). Dedicated Short-Range Communications (DSRC). Standards in the United states. Proceedings of the IEEE.