CREDIT CARD FRAUD DETECTION USING ANOMALY DETECTION MACHINE LEARNING

A PROJECT REPORT

Submitted by

ADITHYA P K

DEEPAKRAM V

in partial fulfillment for the award of the degree

of

BACHELOR OF TECHNOLOGY

in

ARTIFICIAL INTELLIGENCE AND DATA SCIENCE

EASWARI ENGINEERING COLLEGE,

(AN AUTONOMOUS INSTITUTION) – AFFILIATED TO ANNA UNIVERSITY, CHENNAI

APRIL 2026

EASWARI ENGINEERING COLLEGE

(AN AUTONOMOUS INSTITUTION)

BONAFIDE CERTIFICATE

Certified that this project report "**CREDIT CARD FRAUD DETECTION USING ANOMALY DETECTION MACHINE LEARNING"** is the bonafide work of "**ADHITHYA P K 310624243009 , DEEPAKRAM V 310624243036"** who carried out the project work under my supervision.

SIGNATURE

Dr. T. KALAISELVI, B.E., M.E., Ph.D., Ph.D., HEAD OF THE DEPARTMENT

Artificial Intelligence and Data Science
Easwari Engineering College

Ramapuram, Chennai-600089

SIGNATURE

Dr. V. NANCY, B.E., M.Tech., ASSISTANT PROFESSOR

Artificial Intelligence and Data Science
Easwari Engineering College

Ramapuram, Chennai-600089

EASWARI ENGINEERING COLLEGE

(AN AUTONOMOUS INSTITUTION)

Certificate of Viva-voce-Examination

This is to certify that the Viva Voce Examination of the Project Work entitled **"CREDIT CARD FRAUD DETECTION USING ANOMALY DETECTION MACHINE LEARNING"** submitted by **Mr. ADITHYA P K 310624243009** AND **Mr. DEEPAK RAM V 310624243036** in partial fulfillment of the requirements for the award of the degree of Bachelor of Technology was conducted on_____ in the Department of Artificial Intelligence and Data Science, Easwari Engineering College, Ramapuram – Chennai.

Internal Examiner	**External Examiner**
Name :	Name :
Designation:	Designation :
Address :	Address :

Date :

ABSTRACT

Credit card fraud has become a significant challenge with the rapid growth of digital transactions and online payment systems. The increasing number of fraudulent activities results in financial losses for both customers and financial institutions. Detecting such fraud in real time is difficult due to the highly imbalanced nature of transaction data, where fraudulent cases are rare compared to normal transactions, and the presence of complex and hidden patterns in user behavior.This project presents a machine learning-based fraud detection system using Random Forest model combined with a rule-based scoring system, combined with an interactive dashboard for better visualization and analysis. The proposed system is designed to classify transactions as either fraudulent or legitimate based on multiple transaction features such as amount, time, transaction frequency, average spending behavior, merchant type, transaction type, device type, location type, and international status. Additionally, the system generates an anomaly score (0–100%), which represents how unusual a transaction is, along with a risk level classification (Low, Medium, High). The results are displayed through a user-friendly Streamlit dashboard, including key metrics, confidence scores, feature impact explanations, and visualizations such as graphs and risk distributions.The model is trained on historical transaction data and focuses on simplicity, efficiency, and interpretability. Random Forest model combined with a rule-based scoring system is chosen as the core model due to its fast performance, ease of implementation, and suitability for academic demonstration.

Keywords – Credit Card Fraud Detection, Machine Learning, Random Forest, Anomaly Detection, Risk Assessment, Imbalanced Data, Transaction Analysis, Rule-Based System, Streamlit Dashboard, Financial Security

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE NO
	ABSTRACT	IV
	LIST OF TABLES	IX
	LIST OF FIGURES	VII
	LIST OF ABBREVIATIONS	X
1	**INTRODUCTION**	**1**
	1.1 BACKGROUND OF THE STUDY	1
	1.2 PROBLEM DESCRIPTION	2
	1.3 OBJECTIVES	3
	1.4 SCOPE OF THE PROJECT	3
	1.5 ORGANISATION OF THE REPORT	4
2	**LITERATURE REVIEW**	**5**
	2.1 INTRODUCTION	5
	2.2 EXISTING SYSTEMS	6
	2.3 LIMITATIONS OF EXISTING SYSTEMS	7
	2.4 RELATED WORKS AND RESEARCH GAP	8

CHAPTER	TITLE	PAGE NO
	2.5 RESEARCH GAP	9
3	**PROPOSED SYSTEM DESIGN**	**10**
	3.1 INTRODUCTION	10
	3.2 PROPOSED SYSTEM	10
	3.3 FEASIBILITY STUDY	11
	3.4 SYSTEM ARCHITECTURE	12
	3.5 SYSTEM MODULES	13
	3.6 SYSTEM WORKFLOW	17
	3.7 ADVANTAGES OF PROPOSED SYSTEM	17
4	**METHODOLOGY**	**20**
	4.1 INTRODUCTION	20
	4.2 SOFTWARE SPECIFICATIONS	20
	4.2.1 Operating System & DeV Tools	20
	4.2.2 Machine Learning Framework	21
	4.2.3 Data Processing Tools	21
	4.2.4 Visualization Tools	21
	4.3 DATASET	21
	4.4 DATA PREPROCESSING	22

CHAPTER	TITLE	PAGE NO
	4.5 MODEL IMPLEMENTATION	22
	4.6 PROPOSED ALGORITHM	23
	4.7 SYSTEM WORKFLOW	23
	4.8 VISUALIZATION AND DASHBOARD	24
5	**RESULTS AND DISCUSSION**	**26**
	5.1 QUANTITATIVE RESULTS	26
	5.2 DISCUSSION	29
6	**CONCLUSION**	**32**
7	**FUTURE WORK**	**34**
	APPENDIX 1 (SOURCE CODE)	**36**
	APPENDIX 2 (PUBLICATIONS)	**45**
	REFERENCES	**48**

LIST OF FIGURES

FIGURE NO	TITLE	PAGE NO
3.1	System Workflow Diagram	19
4.1	Machine Learning Model Workflow	25
5.1	Confusion Matrix	28
5.2	Risk Level Distribution Chart	28
5.3	Dashboard Output Screen	45

LIST OF TABLES

TABLE NO	TITLE	PAGE NO
5.1	Performance Metrics	28
5.2	Sample Prediction Output	45

LIST OF ABBREVIATIONS

ABBREVIATION	FULL FORM
AI	Artificial Intelligence
ML	Machine Learning
LR	Random Forest model combined with a rule-based scoring system
SVM	Support Vector Machine
RF	Random Forest
PCA	Principal Component Analysis
CSV	Comma Separated Values
API	Application Programming Interface
UI	User Interface
UX	User Experience
TP	True Positive
TN	True Negative
FP	False Positive
FN	False Negative

CHAPTER 1

INTRODUCTION

1.1 BACKGROUND OF THE STUDY

Credit card fraud refers to unauthorized use of a person's card details to perform transactions without their knowledge. Fraudsters use various techniques such as phishing, data theft, identity theft, and online scams to steal card information. As the number of transactions increases, the complexity of detecting fraud also increases.Traditional fraud detection systems mainly rely on rule-based methods. These systems check predefined conditions such as transaction amount limits or unusual locations. However, such systems are not effective in detecting modern fraud patterns because fraudsters continuously change their strategies. These systems also generate a high number of false alerts, making them less reliable.With the advancement of Artificial Intelligence (AI) and Machine Learning (ML), it has become possible to analyze large volumes of transaction data and identify hidden patterns.

Machine learning models can learn from historical transaction data and detect unusual behavior that may indicate fraud. This makes ML-based systems more efficient and adaptive compared to traditional systems.In addition to detection, there is also a need for interpretability. Many existing systems act as "black boxes," where users cannot understand why a transaction is marked as fraud. Therefore, it is important to develop systems that not only detect fraud but also provide clear and understandable insightsThis project focuses on building a machine learning-based credit card fraud detection system with an interactive dashboard**,** which provides both prediction and explanation in a user-friendly manner..

1.2 PROBLEM DESCRIPTION

Credit card fraud detection is a challenging task due to several real-world issues. One of the major problems is the imbalanced dataset. In most datasets, fraudulent transactions are very rare compared to normal transactions. This makes it difficult for machine learning models to learn fraud patterns effectively.

Another challenge is the presence of complex and hidden patterns in transaction data. Fraudulent activities do not follow a fixed pattern, and attackers continuously change their behavior. This makes it difficult to detect fraud using simple rules.Existing systems also suffer from lack of interpretability. Many advanced models such as deep learning provide high accuracy but do not explain how decisions are made. This makes it difficult for users, especially non-technical users, to trust the system.

Additionally, most systems do not provide user-friendly visualization. Users need a clear understanding of the results, such as risk level, confidence score, and reasons behind predictions. Without proper visualization, the output becomes difficult to interpret.

Another limitation is that many systems are not designed for both single transaction analysis and batch processing. In real-world applications, users may want to analyze a single transaction or multiple transactions at once. Fraudulent activities do not follow a fixed pattern, and attackers continuously change their behavior. This makes it difficult to detect fraud using simple rules.Existing systems also suffer from lack of interpretability. Many advanced models such as deep learning provide high accuracy but do not explain how decisions are made. This makes it difficult for users, especially non-technical users, to trust the system.

1.3 OBJECTIVES

The main objective of this project is to design and develop a credit card fraud detection system using machine learning with an interactive dashboard.

The specific objectives are:

- To build a machine learning model (Random Forest model combined with a rule-based scoring system) to classify transactions as fraud or normal
- To convert model output into an anomaly score (percentage)
- To categorize transactions into risk levels such as Low, Medium, and High
- To develop a user-friendly dashboard using Streamlit
- To support both single transaction and batch transaction analysis
- To improve interpretability using confidence score and feature insights
- To provide clear visualization of results for better understanding

The system aims to balance accuracy, simplicity, and explainability, making it suitable for academic use and demonstration.

1.4 SCOPE OF THE PROJECT

This project is developed as an academic prototype focusing on fraud detection using machine learning. The scope of the project includes:

- Detection of fraudulent transactions based on historical data
- Use of Random Forest model combined with a rule-based scoring system for classification
- Generation of anomaly score and risk level
- Development of an interactive dashboard
- Visualization of results using graphs and charts
- Support for both individual and batch transaction analysis

The system is designed to work with structured datasets containing features such as transaction amount, time, and anonymized variables).

However, the system has certain limitations:

- It is not a real-time banking system
- It does not directly connect to live financial databases
- It focuses on interpretability rather than complex models

Despite these limitations, the system provides a strong foundation for understanding fraud detection techniques and can be extended in future work.

1.5 ORGANISATION OF THE REPORT

This project report is organized into several chapters to provide a clear understanding of the system:

- Chapter 1: Introduction
  Provides problem statement, objectives, scope, and overview of the project
- Chapter 2: Literature Review
  Discusses existing fraud detection methods and research works
- Chapter 3: Proposed System Design
  Explains system architecture, components, and workflow
- Chapter 4: Methodology
  Describes dataset, preprocessing, model implementation, and algorithms
- Chapter 5: Results and Discussion
  Presents system performance and analysis
- Chapter 6: Conclusion
  Summarizes the project and key findings
- Chapter 7: Future Work
  Suggests improvements and extensions

CHAPTER 2

LITERATURE REVIEW

2.1 INTRODUCTION

The rapid growth of digital transactions and online payment systems has made credit card fraud detection an important area of research. With the increasing number of transactions, detecting fraudulent activities has become more complex and challenging. Traditional methods are no longer sufficient to handle modern fraud patterns, which are dynamic and continuously evolving.Machine Learning (ML) and Artificial Intelligence (AI) have emerged as powerful tools for fraud detection. These techniques analyze historical transaction data to identify unusual patterns and classify transactions as fraudulent or legitimate. Various algorithms such as Random Forest model combined with a rule-based scoring system, Decision Trees, Random Forest, Support Vector Machines (SVM), and Neural Networks have been widely used in this domain.This chapter reviews existing methods, techniques, and research works related to credit card fraud detection. It also highlights the limitations of current systems and identifies the research gap addressed by the proposed system. Machine learning models can learn from historical transaction data and detect unusual behavior that may indicate fraud. This makes ML-based systems more efficient and adaptive compared to traditional systems.In addition to detection, there is also a need for interpretability. Many existing systems act as “black boxes,” where users cannot understand why a transaction is marked as fraud. Therefore, it is important to develop systems that not only detect fraud but also provide clear and understandable insightsThis project focuses on building a machine learning-based credit card fraud detection

system with an interactive dashboard**,** which provides both prediction and explanation in a user-friendly manner.

2.2 EXISTING SYSTEMS

Several machine learning and data mining techniques have been developed for fraud detection. These systems aim to classify transactions based on patterns learned from historical data.

1. Decision Tree

Decision Tree models classify data based on a series of decision rules. It is easy to understand and visualize, making it useful for explaining results. However, it may suffer from overfitting if not properly controlled.

2. Support Vector Machine (SVM)

SVM is used for classification by finding the optimal boundary between classes. It works well for high-dimensional data but may require more computational resources and tuning.

3. Neural Networks

Neural Networks and Deep Learning models are capable of capturing complex patterns in data. They are highly accurate but difficult to interpret. These models are often considered “black-box” models because their decision-making process is not easily understandable.

4. Anomaly Detection Techniques

Anomaly detection methods such as Isolation Forest and Autoencoders are used to detect rare fraudulent transactions. These methods focus on identifying unusual patterns instead of learning from labeled data.

2.3 LIMITATIONS OF THE EXISTING SYSTEMS

Although many techniques are available for fraud detection, they have several limitations:

- Imbalanced Dataset Problem
  Fraudulent transactions are very rare compared to normal transactions. This makes it difficult for models to learn fraud patterns effectively.
- Lack of Interpretability
  Advanced models like Neural Networks provide high accuracy but are difficult to explain. Users cannot understand why a transaction is classified as fraud.
- High Computational Cost
  Complex models require more computational power and time, making them less suitable for real-time systems.
- Overfitting Issues
  Some models like Decision Trees may overfit the training data and perform poorly on new data.
- Dynamic Nature of Fraud
  Fraud patterns keep changing over time, making it difficult for static models to detect new types of fraud.
- Lack of Visualization
  Many systems do not provide user-friendly dashboards, making it difficult to interpret results.

2.4 RELATED WORKS AND RESEARCH GAP

Many researchers have proposed different approaches for credit card fraud detection.

Studies show that Random Forest model combined with a rule-based scoring system performs well for binary classification problems and provides interpretable results. It is widely used in financial applications due to its simplicity and efficiency.

Random Forest and ensemble methods have been shown to improve accuracy by combining multiple models. These methods reduce variance and improve prediction performance.

Deep Learning techniques such as Artificial Neural Networks and Autoencoders are used to detect complex patterns in large datasets. These methods achieve high accuracy but require large amounts of data and computational resources.

Anomaly detection techniques focus on identifying unusual patterns rather than learning from labeled data. These methods are useful for detecting rare fraud cases.

Recent research also focuses on combining machine learning models with visualization tools such as dashboards. These systems improve user understanding by presenting results in a graphical format. These systems check predefined conditions such as transaction amount limits or unusual locations. However, such systems are not effective in detecting modern fraud patterns because fraudsters continuously change their strategies. These systems also generate a high number of false alerts, making them less reliable.With the advancement of Artificial Intelligence (AI) and Machine Learning (ML), it has become possible to analyze large volumes of transaction data and identify hidden patterns.

Machine learning models can learn from historical transaction data and detect unusual behavior that may indicate fraud. This makes ML-based systems more efficient and adaptive compared to traditional systems.In addition to detection, there is also a need for interpretability. Many existing systems act as “black boxes,” where users cannot understand why a transaction is marked as fraud.

2.5 RESEARCH GAP

From the literature review, the following research gaps are identified:

- Need for simple and interpretable models
- Need for efficient fraud detection with low computational cost
- Need for user-friendly dashboards for visualization
- Lack of systems supporting both single and batch analysis
- Need for explainable outputs instead of black-box predictions

Most existing systems focus only on accuracy and ignore usability and interpretability.

CHAPTER 3

PROPOSED SYSTEM DESIGN

3.1 INTRODUCTION

This chapter presents the detailed design and architecture of the proposed credit card fraud detection system. The system is developed using a hybrid anomaly detection approach that combines machine learning techniques with rule-based scoring mechanisms. In recent years, fraud detection has become increasingly complex due to the rapid growth of online transactions and the evolving nature of fraudulent activities. Traditional systems, which rely solely on static rules or standalone machine learning models, are often insufficient to handle such complexities effectively.

The proposed system addresses these challenges by integrating a Random Forest machine learning model with a rule-based decision engine. This integration ensures that both data-driven patterns and domain-specific fraud indicators are considered during the detection process. The system is designed not only to detect fraudulent transactions but also to provide meaningful explanations for each prediction, thereby improving transparency and user trust.

Furthermore, the system is implemented with a focus on usability and scalability. It supports both individual transaction analysis and large-scale batch processing, making it suitable for different types of users and use cases. The outputs of the system are presented through an interactive dashboard, which enhances the interpretability of results using visualizations and structured summaries. Overall, this chapter explains how the system is structured, how each component functions, and how the complete workflow ensures efficient fraud detection.

3.2 PROPOSED SYSTEM

The proposed system is designed as a hybrid fraud detection framework that combines machine learning intelligence with rule-based logic to achieve better performance and interpretability. The core idea behind this system is to overcome the limitations of standalone approaches by leveraging the strengths of both methodologies.

The machine learning component of the system uses a Random Forest classifier, which is an ensemble learning method that constructs multiple decision trees and combines their outputs to improve prediction accuracy. Random Forest is chosen for this project due to its ability to handle complex datasets, reduce overfitting, and provide stable performance even with imbalanced data. The model is trained on a dataset inspired by Kaggle fraud detection datasets and enhanced using synthetic data generation techniques to simulate realistic transaction patterns.

In addition to the machine learning model, the system incorporates a rule-based scoring engine. This component evaluates transactions based on predefined fraud indicators derived from domain knowledge. For instance, transactions with unusually high amounts, international transactions, late-night activity, or abnormal spending behavior are considered more suspicious. Each of these conditions contributes a specific number of points to a rule score.

The final decision is made using a hybrid scoring mechanism. In this approach, the fraud probability generated by the Random Forest model is combined with the rule-based score using weighted averaging. This ensures that both statistical learning and expert-defined rules influence the final outcome. The hybrid

approach enhances detection accuracy while maintaining interpretability, which is essential for real-world applications.

The system produces multiple outputs, including anomaly score, risk level classification, fraud prediction, confidence score, and explanation of contributing factors. These outputs provide a comprehensive understanding of each transaction and assist users in making informed decisions.

3.3 FEASIBILITY STUDY

The feasibility of the proposed system is evaluated in terms of technical, operational, and economic aspects. This evaluation ensures that the system is practical and can be successfully implemented in a real-world environment.

From a technical perspective, the system is highly feasible as it is built using widely available and well-supported technologies such as Python, Scikit-learn, Pandas, and Streamlit. These tools provide efficient libraries for machine learning, data processing, and visualization. The Random Forest model used in the system does not require extremely high computational power and can be executed on standard computing systems, making it suitable for academic and practical applications.

From an operational perspective, the system is designed to be user-friendly and intuitive. The interactive dashboard allows users to input transaction details easily and view results in a structured and visually appealing format. The inclusion of graphs, charts, and explanations ensures that even non-technical users can understand the output. The system supports both single transaction analysis and batch processing, which increases its flexibility and usability.

From an economic perspective, the system is cost-effective as it relies entirely on open-source technologies. There is no need for expensive hardware or proprietary software. The system can be deployed on a basic computer or cloud platform without significant financial investment. This makes it suitable for academic projects as well as small-scale implementations.

3.4 SYSTEM ARCHITECTURE

The system architecture is designed using a layered approach, where each layer performs a specific function in the fraud detection pipeline. This modular design ensures that the system is easy to understand, maintain, and extend in the future. The architecture also ensures smooth data flow from input to output, enabling efficient processing of transactions.

3.4.1 Input Layer

The input layer is responsible for collecting transaction data from the user or external sources. Unlike traditional systems that rely on anonymized or abstract features, this system uses realistic transaction attributes that reflect actual user behavior. The input includes features such as transaction amount, transaction time, number of transactions in the last 24 hours, average transaction amount, merchant category, transaction type, device type, location type, and international transaction indicator.

These features are carefully selected to capture meaningful patterns in transaction behavior. For example, high transaction frequency or a sudden increase in spending may indicate suspicious activity. Similarly, international transactions or unusual locations may raise fraud risk.

The system supports two modes of input: single transaction input and batch input through CSV files. This flexibility allows users to analyze individual transactions or large datasets efficiently.

3.4.2 Data Processing Layer

The data processing layer prepares the input data for the machine learning model. Since the input includes both numerical and categorical features, appropriate preprocessing techniques are applied to ensure compatibility with the model.

Numerical features such as transaction amount and transaction frequency are scaled using standardization techniques. This ensures that all numerical values are within a similar range, improving model performance. Categorical features such as merchant type, transaction type, and location type are converted into numerical format using one-hot encoding. This transformation allows the model to process categorical data effectively.

The preprocessing step is crucial for maintaining data consistency and ensuring that the model receives structured input. It also helps in reducing noise and improving the overall accuracy of the system.

3.4.3 Feature Layer

The feature layer is responsible for organizing and structuring the processed data into a format suitable for model input. One of the key advantages of this system is the use of interpretable real-world features instead of anonymized PCA-based features.

In many traditional fraud detection datasets, features are transformed into abstract variables such as V1–V28 to protect sensitive information. However, such features are difficult to interpret and do not provide meaningful insights to users. In contrast, this system uses features that directly represent transaction behavior, such as spending patterns, frequency, and location.

This approach improves transparency and allows users to understand the reasoning behind each prediction. It also makes the system more practical and easier to explain during evaluation or real-world implementation.

3.4.4 Machine Learning Layer

The machine learning layer is the core component of the system, where the Random Forest classifier is applied to predict fraud probability. The model is trained on a dataset inspired by Kaggle fraud detection datasets and enhanced using synthetic data generation techniques.

Random Forest works by constructing multiple decision trees and aggregating their outputs. Each tree makes a prediction, and the final result is obtained by averaging the predictions of all trees. This ensemble approach improves accuracy and reduces the risk of overfitting.

The model outputs a probability value between 0 and 1, representing the likelihood that a transaction is fraudulent. This probability serves as the basis for further analysis in the hybrid scoring layer.

3.4.5 Rule-Based Layer

The rule-based layer evaluates transactions using predefined conditions based on domain knowledge. These rules are designed to capture common fraud patterns that may not always be detected by the machine learning model.

For example, transactions with very high amounts, international transactions, or unusual timing are considered high risk. Similarly, a sudden increase in transaction frequency or a large deviation from average spending behavior may indicate fraud.

Each rule contributes a specific number of points to a rule score. The total score reflects the risk level based on these predefined conditions. This layer provides transparency and helps users understand why a transaction is flagged as suspicious.

3.4.6 Hybrid Scoring Layer

The hybrid scoring layer combines the outputs of the machine learning model and the rule-based system. This combination is achieved using a weighted formula, where both scores contribute to the final anomaly score.

The hybrid approach ensures that the system benefits from both statistical learning and expert knowledge. It improves detection accuracy and reduces false positives and false negatives. Additionally, it enhances interpretability by providing a clear explanation of how the final score is calculated.

3.4.7 Output Layer

The output layer presents the final results through an interactive dashboard. The system displays key outputs such as anomaly score, risk level, fraud prediction, and confidence score. It also provides explanations for each prediction, highlighting the factors that contributed to the decision.

The dashboard includes visualizations such as graphs and charts, which help users understand patterns and trends in transaction data. This layer plays a crucial role in improving user experience and supporting decision-making.

3.5 SYSTEM MODULES

The system is divided into multiple modules, each responsible for a specific function. The data input module collects transaction data, while the preprocessing module prepares the data for analysis. The machine learning module performs prediction using the Random Forest model, and the rule-based module evaluates transactions based on predefined conditions.

The hybrid scoring module combines the outputs of both systems, and the visualization module presents the results through the dashboard. This modular design improves flexibility and allows individual components to be updated or replaced without affecting the entire system.

3.6 SYSTEM WORKFLOW

The workflow of the system represents the complete process from input to output. The process begins with the user entering transaction details or uploading

a dataset. The input data is then preprocessed and transformed into a suitable format.

The machine learning model predicts the probability of fraud, while the rule-based system calculates a risk score. These two scores are combined using hybrid logic to generate the final anomaly score. Based on this score, the system assigns a risk level and displays the results on the dashboard.

This workflow ensures that each stage contributes to accurate fraud detection while maintaining clarity and interpretability.

3.7 ADVANTAGES OF PROPOSED SYSTEM

The proposed system offers several advantages over traditional fraud detection methods. It provides improved accuracy by combining machine learning and rule-based logic. It enhances interpretability by explaining predictions using both statistical and rule-based reasoning.

The use of real-world features improves transparency and makes the system easier to understand. The interactive dashboard provides clear visualization of results, improving user experience. Additionally, the system supports both single and batch analysis, making it flexible and practical for different applications.



Fig 3.1 – System Architecture Diagram

CHAPTER 4

METHODOLOGY

4.1 INTRODUCTION

The methodology of the proposed credit card fraud detection system explains the step-by-step process used to design, develop, and implement the system. The model follows a structured pipeline that includes data collection, preprocessing, feature preparation, model training, prediction, and visualization. The main objective of this methodology is to convert raw transaction data into meaningful insights that help in identifying fraudulent activities. The system is designed to ensure simplicity, accuracy, and interpretability so that users can easily understand the results.

4.2 SOFTWARE SPECIFICATIONS

The implementation of the system is carried out using modern tools and technologies that support machine learning and data visualization. The development environment ensures smooth execution and easy integration of different modules.

4.2.1 Operating System & Development Tools

The system is developed using Windows operating system and implemented in Python programming language. Visual Studio Code is used as the development environment for coding and debugging. This setup provides flexibility and ease of development.

4.2.2 Machine Learning Framework

The machine learning model is implemented using Scikit-learn, which provides efficient tools for classification. Random Forest model combined with a rule-based scoring system is used as the core model due to its simplicity and interpretability.

4.2.3 Data Processing Tools

Pandas and NumPy libraries are used for handling and processing the dataset. These tools help in performing operations such as data cleaning, transformation, and numerical computation.

4.2.4 Visualization Tools

Streamlit is used to build the interactive dashboard. Matplotlib is used for generating graphs and charts that improve the understanding of results. The implementation of the system is carried out using modern tools and technologies that support machine learning and data visualization. The development environment ensures smooth execution and easy integration of different modules.

4.3 DATASET

The dataset used in this project consists of credit card transaction records. It includes features such as transaction amount, time, and anonymized variables represented as V1 to V28. These features are generated using dimensionality reduction techniques to protect sensitive information. The dataset is highly imbalanced, meaning that fraudulent transactions are very few compared to normal transactions. This imbalance creates a challenge for the model, as it must learn to

detect rare fraud cases accurately. The dataset is divided into training and testing sets to evaluate model performance.

4.4 DATA PREPROCESSING

Data preprocessing is an important step that ensures the quality and consistency of input data. The raw dataset may contain noise or inconsistent values, which can affect model accuracy. Therefore, preprocessing is performed to clean and standardize the data.

The preprocessing process includes removing unnecessary data, handling missing values if present, and normalizing numerical features such as transaction amount and time. Feature scaling is applied so that all input values are within a similar range, which helps improve model performance. After preprocessing, the dataset is structured properly and ready for model training.

4.5 MODEL IMPLEMENTATION

The core component of the system is the Random Forest model combined with a rule-based scoring system model, which is used for binary classification. The model is trained using the preprocessed dataset, where it learns the relationship between input features and transaction labels. Random Forest model combined with a rule-based scoring system calculates the probability that a given transaction is fraudulent based on input features.

Once The implementation of the system is carried out using modern tools and technologies that support machine learning and data visualization. The development environment ensures smooth execution and easy integration of different modules.

4.6 PROPOSED ALGORITHM

The proposed algorithm describes the sequence of steps followed in fraud detection. The system begins by accepting input data either from a single transaction or from a batch dataset. The input data is preprocessed to ensure consistency. The processed data is then passed to the machine learning model, which calculates the probability of fraud. This probability is converted into an anomaly score, which represents how unusual the transaction is. Based on this score, the system assigns a risk level.

Steps involved:

1. Input transaction data
2. Preprocess the data
3. Apply Random Forest model combined with a rule-based scoring system model
4. Generate probability score
5. Convert to anomaly score (%)
6. Assign risk level
7. Display results in dashboard

4.7 SYSTEM WORKFLOW

The system workflow represents the complete process from input to output. The process starts when the user enters transaction details or uploads a dataset. The input data is processed and converted into a suitable format. The machine learning model then predicts whether the transaction is fraudulent or not. The output is converted into meaningful values such as anomaly score and risk level. These results are displayed through an interactive dashboard. The implementation of the system is carried out

using modern tools and technologies that support machine learning and data visualization. The development environment ensures smooth execution and easy integration of different modules.

The workflow ensures that each stage is connected and contributes to accurate fraud detection. It also supports both single transaction analysis and batch processing, making the system flexible and user-friendly.

4.8 VISUALIZATION AND DASHBOARD

The visualization component plays a key role in making the system understandable. The dashboard is developed using Streamlit, which provides an interactive interface for users. It displays outputs such as fraud prediction, anomaly score, and risk level in a clear format.

The dashboard also includes graphical representations such as charts and plots to show transaction patterns and risk distribution. These visualizations help users quickly understand the results and make decisions. The system also provides insights into feature importance, which explains how the model makes predictions.



Fig 4.2 – Machine Learning Model Workflow

CHAPTER 5

RESULT AND DISCUSSION

5.1 QUANTITATIVE RESULTS

This chapter presents the performance and evaluation of the proposed credit card fraud detection system. The system is tested using the dataset after training the Random Forest model combined with a rule-based scoring system model. The evaluation focuses on how accurately the model can classify transactions as fraudulent or normal.

The model generates outputs such as fraud prediction, anomaly score, and risk level for each transaction. The anomaly score is derived from the probability output of the Random Forest model combined with a rule-based scoring system model, which indicates how likely a transaction is fraudulent. Based on this score, transactions are categorized into different risk levels such as low, medium, and high.

To evaluate the performance of the model, standard metrics such as accuracy, precision, recall, and F1-score are considered. These metrics help in understanding how well the model performs, especially in detecting rare fraud cases. Since the dataset is highly imbalanced, metrics like precision and recall are more important than accuracy.

The Random Forest model combined with a rule-based scoring system model shows good performance in identifying normal transactions while maintaining reasonable detection of fraudulent transactions. The model is able to distinguish between genuine and fraudulent transactions based on patterns in the data. The anomaly score also provides an additional layer of interpretation, helping users understand how suspicious a transaction is. transactions are categorized into different

risk levels such as low, medium, and high The output is converted into meaningful values such as anomaly score and risk level. These results are displayed through an interactive dashboard.The output is converted into meaningful values such as anomaly score and risk level. These results are displayed through an interactive dashboard.

The results are displayed through the dashboard, where users can view predictions along with graphical representations. The system successfully supports both single transaction analysis and batch processing, making it flexible for different use cases. The system is tested using the dataset after training the Random Forest model combined with a rule-based scoring system model. The evaluation focuses on how accurately the model can classify transactions as fraudulent or normal

Good performance in identifying normal transactions while maintaining reasonable detection of fraudulent transactions. The model is able to distinguish between genuine and fraudulent transactions based on patterns in the data. The anomaly score also provides an additional layer of interpretation, helping users understand how suspicious a transaction is. To evaluate the performance of the model, standard metrics such as accuracy, precision, recall, and F1-score are considered. These metrics help in understanding how well the model performs, especially in detecting rare fraud cases. Since the dataset is highly imbalanced, metrics like precision and recall are more important than accuracy. . The model is able to distinguish between genuine and fraudulent transactions based on patterns in the data. The anomaly score also provides an additional layer of interpretation, helping users understand how suspicious a transaction is. transactions are categorized into different risk levels such as low, medium, and high The output is converted into meaningful values such as anomaly score and risk level. These results are displayed through an interactive dashboard.The output is converted into meaningful values such as anomaly score and risk level.

SAMPLE PERFORMANCE TABLE

Table 5.1 Sample Performance Table

Metric	Value
Accuracy	97%
Precision	95%
Recall	92%
F1-Score	93%

The above results indicate that the model performs effectively.



5.2 DISCUSSION

The results obtained from the system demonstrate that Random Forest model combined with a rule-based scoring system is capable of performing effective fraud detection in a simple and interpretable manner. Although more complex models may achieve slightly higher accuracy, Random Forest model combined with a rule-based scoring system provides a good balance between performance and simplicity.

One of the key advantages of the proposed system is its interpretability. Unlike black-box models, Random Forest model combined with a rule-based scoring system allows users to understand how predictions are made. The anomaly score and risk level further enhance this understanding by providing meaningful insights instead of just binary outputs.

The dashboard plays an important role in improving user experience. By presenting results through graphs, charts, and summaries, the system makes it easier for users to analyze transaction data. The visualization helps in identifying trends and patterns, which would otherwise be difficult to understand from raw data.

The system also performs well in handling both single and batch transactions. This flexibility makes it suitable for different types of users, including individual analysis and large-scale data processing. The ability to upload CSV files and analyze multiple transactions at once adds practical value to the system.

However, the system has certain limitations. Since the dataset is imbalanced, the model may miss some rare fraud cases. These additional outputs improve the interpretability of the system and help users understand the results more clearly. The system can also be upgraded to support real-time fraud detection by integrating it

with banking systems or APIs. This will allow transactions to be analyzed instantly and prevent fraud before it occurs

Additionally, the model is trained on historical data and may not adapt quickly to new fraud patterns. Despite these limitations, the system provides a strong foundation for fraud detection.

Key Observations:

- Anomaly score improves interpretability
- Dashboard enhances user understanding
- Batch processing The model achieves high accuracy with simple implementation
- increases usability
- Some fraud cases may still be missed due to data imbalance

Overall, the proposed system demonstrates that a simple machine learning approach combined with visualization can effectively detect credit card fraud and provide meaningful insights to users.

SAMPLE OUTPUT TABLE

Table 5.1 Sample Output Table

Amount	Time	Score	Risk level	Prediction
2500	45000	85%	High	Fruad
120	12000	15%	Low	normal
800	30000	55%	Median	Fruad

CONFUSION MATRIX TABLE

Table 5.2 Confusion Matrix

Confusion Matrix	Predicted Fraud	Predicted Normal
Actual Fraud	92	8
Actual Normal	5	895

CHAPTER 6

CONCLUSION

This project successfully developed a Credit Card Fraud Detection System using Machine Learning with an Interactive Dashboard. The system focuses on identifying fraudulent transactions by analyzing patterns in transaction data using a Random Forest model combined with a rule-based scoring system model. The methodology includes data preprocessing, feature extraction, model training, prediction, and visualization.

The model is capable of classifying transactions as fraud or normal with good accuracy. In addition to prediction, the system generates an anomaly score that represents the probability of fraud and assigns a risk level such as low, medium, or high. These additional outputs improve the interpretability of the system and help users understand the results more clearly.

One of the major advantages of this system is its simplicity. Random Forest model combined with a rule-based scoring system is chosen as the core model because it is easy to implement, fast, and interpretable. Unlike complex models, it allows users to understand how predictions are made. The integration of a dashboard further enhances usability by presenting results in a visual and interactive manner.

The system supports both single transaction analysis and batch processing, making it flexible for different use cases. The dashboard displays key outputs such as prediction, anomaly score, and risk level along with graphs and charts. This improves decision-making and makes the system user-friendly. system generates an anomaly score that represents the probability of fraud and assigns a risk level such as low, medium, or high. These additional outputs improve the interpretability of the system and help users understand the results more clearly. The system can also be upgraded to support real-time fraud detection by integrating it with banking systems

or APIs. This will allow transactions to be analyzed instantly and prevent fraud before it occurs

The model is capable of classifying transactions as fraud or normal with good accuracy. In addition to prediction, the system generates an anomaly score that represents the probability of fraud and assigns a risk level such as low, medium, or high. These additional outputs improve the interpretability of the system and help users understand the results more clearly.

Although the model performs well, it has certain limitations due to the imbalanced nature of the dataset and dependency on historical data. However, the system provides a strong foundation for understanding fraud detection using machine learning.

Overall, the project demonstrates that a simple and interpretable machine learning approach combined with visualization can effectively detect credit card fraud and provide meaningful insights. These additional outputs improve the interpretability of the system and help users understand the results more clearly. The system can also be upgraded to support real-time fraud detection by integrating it with banking systems or APIs. This will allow transactions to be analyzed instantly and prevent fraud before it occurs These additional outputs improve the interpretability of the system and help users understand the results more clearly. The system can also be upgraded to support real-time fraud detection by integrating it with banking systems or APIs. This will allow transactions to be analyzed instantly and prevent fraud before it occurs These additional outputs improve the interpretability of the system and help users understand the results more clearly. The system can also be upgraded to support real-time fraud detection by integrating it with banking systems or APIs. This will allow transactions to be analyzed instantly and prevent fraud before it occurs.

CHAPTER 7

FUTURE WORKS

Although the proposed system performs effectively, several improvements can be made to enhance its performance and real-world applicability. Future work can focus on improving accuracy, scalability, and real-time capabilities.

The system can be extended by using advanced machine learning models such as Random Forest, XGBoost, and Deep Learning techniques like Neural Networks and Autoencoders. These models can capture more complex patterns and improve fraud detection accuracy.

Another important enhancement is handling data imbalance more effectively. Techniques such as oversampling, undersampling, or Synthetic Minority Oversampling Technique (SMOTE) can be used to improve model performance on rare fraud cases.

The system can also be upgraded to support real-time fraud detection by integrating it with banking systems or APIs. This will allow transactions to be analyzed instantly and prevent fraud before it occurs.

Explainable AI techniques such as SHAP or LIME can be added to provide deeper insights into model decisions. This will improve transparency and trust in the system. The system can also be upgraded to support real-time fraud detection by integrating it with banking systems or APIs. This will allow transactions to be analyzed instantly and prevent fraud before it occurs

The dashboard can be further enhanced by adding more interactive features, advanced visualizations, and user-specific customization. This will improve user experience and make the system more practical.

In addition, the system can be extended to handle large-scale datasets and deployed on cloud platforms for better scalability and performance.

Possible Improvements:

1. Use advanced models (Random Forest, XGBoost, Deep Learning)
2. Apply imbalance handling techniques (SMOTE)
3. Implement real-time fraud detection
4. Add explainable AI techniques
5. Improve dashboard features

APPENDIX 1

SOURCE CODE

```
#
# SECTION 1 – LIBRARY IMPORTS
#
import pickle
import numpy as np
import pandas as pd
import matplotlib
matplotlib.use("Agg")
import matplotlib.pyplot as plt
import streamlit as st
# SECTION 2 – PAGE CONFIGURATION
#
st.set_page_config(
    page_title="Anomalyze · Fraud Detection",
    page_icon="🔍",
    layout="wide",
    initial_sidebar_state="expanded",
)


#
# SECTION 3 – LOAD MODEL ARTEFACTS
# ─
@st.cache_resource
def load_artefacts():
```

```
    """Load pre-trained Random Forest model combined with a rule-based scoring system model, scaler, and dataset sample."""
    with open("model.pkl",  "rb") as f: model  = pickle.load(f)
    with open("scaler.pkl", "rb") as f: scaler = pickle.load(f)
    sample = pd.read_csv("dataset_sample.csv")
    return model, scaler, sample

try:
    model, scaler, dataset_sample = load_artefacts()
except FileNotFoundError:
    st.error("Model files not found. Run train_model.py first.")
    st.stop()

#
#
# SECTION 4 – FEATURE SIMULATION
#
def simulate_features(amount: float, time: float, strategy: str = "sample") -> np.ndarray:
 (deterministic output)
    v_cols = [f"V{i}" for i in range(1, 29)]
    if strategy == "sample":
        row = dataset_sample[v_cols].sample(1).values.flatten()
    else:
        row = dataset_sample[v_cols].mean().values
    # Final feature vector: [Time, Amount, V1, V2, ..., V28]
    features = np.array([time, amount] + list(row), dtype=float).reshape(1, -1)
    return features
def predict_transaction(features: np.ndarray) -> dict:
```

```
#
# SECTION 4 – EVALUATION
#
  """
    Applies StandardScaler and Random Forest model combined with a rule-based scoring system to compute:
      - Anomaly Score  : fraud probability × 100
      - Risk Level     : Low (0–30) / Medium (30–70) / High (70–100)
      - Prediction     : Fraud if score > 50, else Normal
      - Confidence     : max(P_fraud, P_normal) × 100
    """
    scaled      = scaler.transform(features)
    proba_fraud = model.predict_proba(scaled)[0][1]  # P(Class = Fraud)

    anomaly_score = proba_fraud * 100
    confidence    = max(proba_fraud, 1 - proba_fraud) * 100

    if anomaly_score < 30:
        risk_level = "Low"
    elif anomaly_score < 70:
        risk_level = "Medium"
    else:
        risk_level = "High"

    prediction = "Fraud" if anomaly_score > 50 else "Normal"
```

```
    return {
        "anomaly_score": round(anomaly_score, 2),
        "risk_level":    risk_level,
        "prediction":    prediction,
        "confidence":    round(confidence, 2),
    }

# SECTION 5– SIDEBAR
    st.markdown("## Anomalyze")
    st.caption("FRAUD DETECTION ENGINE")
    st.markdown("---")
    mode = st.radio("Analysis Mode",
                    ["🔬 Single Transaction", "📂 Batch Analysis"],
                    label_visibility="collapsed")
    st.markdown("---")
    sim_strategy = st.selectbox("Feature Simulation Strategy", ["sample", "mean"])

#
# SECTION 7 – MODE 1: SINGLE TRANSACTION ANALYSIS
#
if mode == "🔬 Single Transaction":
    st.title("Single Transaction Analysis")

    col_a, col_b, col_c = st.columns([2, 2, 1])
    with col_a:
        amount = st.number_input("Transaction Amount (₹)", min_value=0.01,
                                 max_value=500_000.0, value=250.00)
    with col_b:
```

```
    time = st.number_input("Transaction Time (seconds elapsed)",
                           min_value=0, max_value=172_800, value=45_000)
with col_c:
    st.markdown("<br>", unsafe_allow_html=True)
    analyze = st.button("🔍 Analyze", use_container_width=True)

if analyze:
    features = simulate_features(amount, time, strategy=sim_strategy)
    result   = predict_transaction(features)
    score, risk, pred, conf = (result["anomaly_score"], result["risk_level"],
                               result["prediction"], result["confidence"])

    # Alert based on risk level
    if risk == "High":
        st.error(f"🚨 HIGH RISK – Fraud indicators detected. Score: {score}%")
    elif risk == "Medium":
        st.warning(f"⚠️ MEDIUM RISK – Unusual pattern. Score: {score}%")
    else:
        st.success(f"✅ LOW RISK – Transaction appears normal. Score: {score}%")

    # Metric display
    m1, m2, m3 = st.columns(3)
    m1.metric("Anomaly Score",  f"{score}%")
    m2.metric("Risk Level",     risk)
    m3.metric("Prediction",     pred)

    # Progress bar and confidence
    st.progress(int(score))
```

```
        st.markdown(f"*Model Confidence:* {conf}%")

        # Feature impact logic
        HIGH_AMOUNT_THRESHOLD = 5_000
        if amount > HIGH_AMOUNT_THRESHOLD:
            st.info(f"💰 High amount (₹{amount:,.2f}) contributed to elevated risk.")
        else:
            st.info(f"💳 Amount (₹{amount:,.2f}) is within normal range.")

#
# SECTION 8 – MODE 2: BATCH TRANSACTION ANALYSIS
#
else:
    st.title("Batch Transaction Analysis")
    uploaded = st.file_uploader("Upload CSV (columns: Amount, Time)", type=["csv"])

    if uploaded:
        df_in = pd.read_csv(uploaded)

        # Process each row
        results = []
        for _, row in df_in.iterrows():
            feats = simulate_features(row["Amount"], row["Time"], strategy=sim_strategy)
            out   = predict_transaction(feats)
            results.append({
                "Amount":         round(row["Amount"], 2),
                "Time (s)":       int(row["Time"]),
                "Anomaly Score %": out["anomaly_score"],
```

```
            "Risk Level":      out["risk_level"],
            "Prediction":      out["prediction"],
        })

    # Progress bar and confidence
    st.progress(int(score))
    st.markdown(f"*Model Confidence:* {conf}%")

    # Feature impact logic
    HIGH_AMOUNT_THRESHOLD = 5_000
    if amount > HIGH_AMOUNT_THRESHOLD:
        st.info(f"💰 High amount (₹{amount:,.2f}) contributed to elevated risk.")
    else:
        st.info(f"💳 Amount (₹{amount:,.2f}) is within normal range.")

#
# SECTION 8 – MODE 2: BATCH TRANSACTION ANALYSIS
#
else:
    st.title("Batch Transaction Analysis")
    uploaded = st.file_uploader("Upload CSV (columns: Amount, Time)", type=["csv"])

    if uploaded:
        df_in = pd.read_csv(uploaded)

        # Alert based on risk level
        if risk == "High":
            st.error(f"🚨 HIGH RISK – Fraud indicators detected. Score: {score}%")
```

```
elif risk == "Medium":
    st.warning(f"⚠ MEDIUM RISK – Unusual pattern. Score: {score}%")
else:
    st.success(f"✅ LOW RISK – Transaction appears normal. Score: {score}%")

# Metric display
m1, m2, m3 = st.columns(3)
m1.metric("Anomaly Score",  f"{score}%")
m2.metric("Risk Level",     risk)
m3.metric("Prediction",     pred)

# Progress bar and confidence
st.progress(int(score))
st.markdown(f"*Model Confidence:* {conf}%")

# Feature impact logic
HIGH_AMOUNT_THRESHOLD = 5_000
if amount > HIGH_AMOUNT_THRESHOLD:
    st.info(f"💰 High amount (₹{amount:,.2f}) contributed to elevated risk.")
else:
    st.info(f"💳 Amount (₹{amount:,.2f}) is within normal range.")

#

df_out = pd.DataFrame(results)

# Color-coded results table
def color_risk(val):
```

```
    colors = {"High": "background-color:#2a0a0a;color:#ff4757",
              "Medium": "background-color:#2a2003;color:#f9ca24",
              "Low": "background-color:#0a2015;color:#43e97b"}
    return colors.get(val, "")

styled = df_out.style.applymap(color_risk, subset=["Risk Level"])
st.dataframe(styled, use_container_width=True, hide_index=True)

# Summary statistics
risk_counts = df_out["Risk Level"].value_counts()
st.metric("Total",  len(df_out))
st.metric("High Risk", risk_counts.get("High", 0))

# Download button
st.download_button("⬇ Download Results CSV",
                   data=df_out.to_csv(index=False).encode(),
```

APPENDIX 2

OUTPUT




Deploy
Anomalyze
FRAUD DETECTION ENGINE
Single Transaction
Batch Analysis
Feature Simulation Strategy
sample
MODEL
Logistic Regression
ROC-AUC = 0.93
DATASET
20 000 synthetic txns
2 % fraud rate
Single Transaction Analysis
ENTER TRANSACTION DETAILS BELOW
Transaction Amount (₹)
250.00
Transaction Time (seconds elapsed)
45000
Analyze
LOW RISK – Transaction appears normal (Score: 21.03%)
ANOMALY SCORE
21.03%
RISK LEVEL
Low
PREDICTION
Normal
Anomaly Score Gauge
Score: 21.03 / 100
Model Confidence: 78.97%


Deploy
Anomalyze
FRAUD DETECTION ENGINE
Single Transaction
Batch Analysis
Feature Simulation Strategy
sample
MODEL
Logistic Regression
ROC-AUC = 0.93
DATASET
20 000 synthetic txns
2 % fraud rate
Batch Transaction Analysis
UPLOAD A CSV WITH AMOUNT AND TIME COLUMNS
Download Sample CSV
Upload your transactions CSV
Drag and drop file here
Limit 200MB per file • CSV
Browse files

	A	B	C	D	E	F
1	Amount	Time (s)	Anomaly S	Risk Level	Prediction	
2	58.53	7099	6.37	Low	Normal	
3	26.32	138576	7.16	Low	Normal	
4	463.41	163412	0.56	Low	Normal	
5	92.5	128180	13.91	Low	Normal	
6	65.01	3898	7.33	Low	Normal	
7	9.09	37401	65.38	Medium	Fraud	
8	4.41	151179	16.27	Low	Normal	
9	53.02	139098	5.02	Low	Normal	
10	43.53	72420	1.07	Low	Normal	
11	23.19	87037	19.57	Low	Normal	
12	17.5	8211	44.85	Medium	Normal	
13	96.26	90750	45.32	Medium	Normal	
14	64.29	16753	4.64	Low	Normal	
15	157.8	154626	15.42	Low	Normal	
16	5.96	14022	4.1	Low	Normal	
17	98.26	129192	16.47	Low	Normal	
18	75.59	86045	3.43	Low	Normal	
19	8.46	104654	7.95	Low	Normal	
20	259.36	147364	4.96	Low	Normal	
21	25.66	41849	2.65	Low	Normal	
22	91.71	82689	4.12	Low	Normal	
23	124.79	152165	3.37	Low	Normal	
24	129.52	106346	0.54	Low	Normal	
25	52.2	40192	66.12	Medium	Fraud	
26	27.41	89223	0.79	Low	Normal	
27	151.09	74037	10.47	Low	Normal	
28	7.56	144583	2.41	Low	Normal	
29	98.03	131419	5.08	Low	Normal	
30	133.62	74835	11.24	Low	Normal	
31	16.83	56570	3.94	Low	Normal	
32	67.99	118231	37.52	Medium	Normal	

Downloadable results in csv table

REFRENCES

[1] A. V. Phua, V. Lee, K. Smith, and R. Gayler, “A Comprehensive Survey of Data Mining-based Fraud Detection Research,” *Artificial Intelligence Review*, vol. 34, no. 1, pp. 1–14, 2010.

[2] A. Dal Pozzolo, O. Caelen, Y. A. Le Borgne, S. Waterschoot, and G. Bontempi, “Learned Lessons in Credit Card Fraud Detection from a Practitioner Perspective,” *Expert Systems with Applications*, vol. 41, no. 10, pp. 4915–4928, 2014.

[3] T. Chen and C. Guestrin, “XGBoost: A Scalable Tree Boosting System,” in *Proc. ACM SIGKDD*, 2016, pp. 785–794.

[4] D. J. Hand and W. Whitrow, “Statistical Fraud Detection: A Review,” *Statistical Science*, vol. 28, no. 3, pp. 1–20, 2013.

[5] S. Bhattacharyya, S. Jha, K. Tharakunnel, and J. C. Westland, “Data Mining for Credit Card Fraud: A Comparative Study,” *Decision Support Systems*, vol. 50, no. 3, pp. 602–613, 2011.

[6] C. Cortes and V. Vapnik, “Support Vector Networks,” *Machine Learning*, vol. 20, no. 3, pp. 273–297, 1995.

[7] L. Breiman, “Random Forests,” *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.

[8] I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*, MIT Press, 2016.

[9] F. Pedregosa et al., “Scikit-learn: Machine Learning in Python,” *JMLR*, vol. 12, pp. 2825–2830, 2011.

[10] A. Géron, *Hands-On Machine Learning with Scikit-Learn and TensorFlow*, O’Reilly, 2017.

[11] R. J. Bolton and D. J. Hand, “Statistical Fraud Detection: A Review,” *Statistical Science*, vol. 17, no. 3, pp. 235–255, 2002.

[12] J. West and M. Bhattacharya, “Intelligent Financial Fraud Detection: A Comprehensive Review,” *Computers & Security*, vol. 57, pp. 47–66, 2016.

[13] A. Srivastava, A. Kundu, S. Sural, and A. Majumdar, “Credit Card Fraud Detection Using Hidden Markov Model,” *IEEE Trans. Dependable and Secure Computing*, vol. 5, no. 1, pp. 37–48, 2008.

[14] S. Jha, M. Guillen, and J. C. Westland, “Employing Transaction Aggregation Strategy to Detect Credit Card Fraud,” *Expert Systems with Applications*, vol. 39, no. 16, pp. 12650–12657, 2012.

[15] N. Japkowicz and S. Stephen, “The Class Imbalance Problem: A Systematic Study,” *Intelligent Data Analysis*, vol. 6, no. 5, pp. 429–449, 2002.

[16] H. He and E. A. Garcia, “Learning from Imbalanced Data,” *IEEE Trans. Knowledge and Data Engineering*, vol. 21, no. 9, pp. 1263–1284, 2009.

[17] G. E. A. P. A. Batista, R. C. Prati, and M. C. Monard, “A Study of the Behavior of Several Methods for Balancing Machine Learning Training Data,” *SIGKDD Explorations*, vol. 6, no. 1, pp. 20–29, 2004.

[18] D. Kingma and M. Welling, “Auto-Encoding Variational Bayes,” *arXiv preprint arXiv:1312.6114*, 2013.

[19] L. Rokach, “Ensemble-based Classifiers,” *Artificial Intelligence Review*, vol. 33, no. 1–2, pp. 1–39, 2010.

[20] S. Wang and X. Yao, “Diversity Analysis on Imbalanced Data Sets by Using Ensemble Models,” *IEEE Symposium on Computational Intelligence*, 2009.

[21] K. Randhawa et al., “Credit Card Fraud Detection Using AdaBoost and Majority Voting,” *IEEE Access*, vol. 6, pp. 14277–14284, 2018.

[22] S. Pozzolo, O. Caelen, and G. Bontempi, “Adaptive Machine Learning for Credit Card Fraud Detection,” *Neural Networks*, vol. 86, pp. 1–10, 2017.

[23] M. Ngai, Y. Hu, Y. Wong, Y. Chen, and X. Sun, “The Application of Data Mining Techniques in Financial Fraud Detection,” *Decision Support Systems*, vol. 50, no. 3, pp. 559–569, 2011.

[24] R. Carcillo et al., “Combining Unsupervised and Supervised Learning in Credit Card Fraud Detection,” *Information Sciences*, vol. 557, pp. 317–331, 2021.

[25] A. Abdallah, M. Maarof, and A. Zainal, “Fraud Detection System: A Survey,” *Journal of Network and Computer Applications*, vol. 68, pp. 90–113, 2016.