

Rajalakshmi Engineering College

Name: Adithya Varman
Email: 240801010@rajalakshmi.edu.in
Roll no: 240801010
Phone: 8122197670
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next *n* lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
#include <stdio.h>
```

```
#include <string.h>
```

```
struct Contact
```

```
{
```

```
char name[11];  
char number[15];
```

```
};
```

```
int main()
```

```
{
```

```
    int n;  
    scanf("%d", &n);  
    struct Contact contacts[50];  
    char key[11];
```

```
    for (int i = 0; i < n; i++)
```

```
    {
```

```
        scanf("%s %s", contacts[i].name, contacts[i].number);
```

```
    }
```

```
    scanf("%s", key);  
    int found = 0;
```

```
    for (int i = 0; i < n; i++)
```

```
    {
```

```
        if (strcmp(contacts[i].name, key) == 0)
```

```
        {
```

```
            found = 1;  
            printf("The given key is removed!\n");
```

```
    for (int j = 0; j < n; j++)
    {

        if (j != i)

        {

            printf("Key: %s; Value: %s\n", contacts[j].name, contacts[j].number);

        }

    }

    break;

}

}

if (!found)
{

    printf("The given key is not found!\n");
    for (int i = 0; i < n; i++)

    {

        printf("Key: %s; Value: %s\n", contacts[i].name, contacts[i].number);

    }

}
```

```
}  
    return 0;  
}
```

Status : Correct

Marks : 10/10