

Rajalakshmi Engineering College

Name: Adithya B
Email: 240701018@rajalakshmi.edu.in
Roll no: 240701018
Phone: 9444117405
Branch: REC
Department: CSE - Section 10
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_Week 12_Java_Lamba Expressions_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 37.5

Section 1 : COD

1. Problem Statement

Rishi is working as an HR analyst in a software company. He wants to filter a list of employees based on their salary using modern Java techniques. He has a list of employee names and salaries and wants to use lambda expressions to filter those who earn more than a specific threshold.

Implement a program using lambda expressions and functional interfaces to print the names of employees whose salary is greater than or equal to 50,000.

Input Format

The first line of input consists of an integer n, representing the number of employees.

The next n lines. Each line contains a String (employee name) and an int (salary).

Output Format

The output prints the names of employees whose salary is greater than or equal to 50000, each on a new line.

If no employee found with salary greater than 50000, print: No employee found with salary \geq 50000

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
Amit 45000
Sneha 50000
Ravi 60000
Priya 30000
Output: Sneha
Ravi

Answer

// You are using Java
import java.util.*;

```
interface SalaryFilter {  
    boolean check(int salary);  
}
```

```
class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
        int n = sc.nextInt();  
        sc.nextLine(); // clear buffer
```

```
        String[] names = new String[n];  
        int[] salaries = new int[n];
```

```
        for (int i = 0; i < n; i++) {
```

```

names[i] = sc.next(); // employee name
salaries[i] = sc.nextInt(); // salary
}

// Lambda to check if salary >= 50000
SalaryFilter filter = (sal) -> sal >= 50000;

boolean found = false;

for (int i = 0; i < n; i++) {
    if (filter.check(salaries[i])) {
        System.out.println(names[i]);
        found = true;
    }
}

if (!found) {
    System.out.println("No employee found with salary >= 50000");
}
}
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

Sneha is developing a feature for an e-commerce application that helps display product details after applying a seasonal discount.

She decides to use lambda expressions with the Consumer functional interface to print each product's name, original price, and discounted price neatly.

The program should:

Accept a list of product names and their prices. Apply a 15% discount on all products. Use a Consumer lambda expression to display the details in a formatted manner.

Input Format

The first line of input consists of an integer n, representing the number of products.

The next n lines each contain a String (product name) and a double (price) separated by a space.

Output Format

For each product, print the details in the format:

Product: <name>, Original Price: <price>, Discounted Price: <discounted price>

If there are no products, print:

No products available

Sample Test Case

Input: 1

Phone 60000

Output: Product: Phone, Original Price: 60000.0, Discounted Price: 51000.0

Answer

```
import java.util.*;
```

```
interface ProductPrinter {  
    void print(String name, double originalPrice, double discountedPrice);  
}
```

```
class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
        int n = sc.nextInt();
```

```
        if (n == 0) {  
            System.out.println("No products available");  
            return;  
        }
```

```
        String[] names = new String[n];  
        double[] prices = new double[n];
```

```
        for (int i = 0; i < n; i++) {
```

```

        names[i] = sc.next();
        prices[i] = sc.nextDouble();
    }

    ProductPrinter printer = (name, original, discounted) -> {
        System.out.println("Product: " + name +
            ", Original Price: " + original +
            ", Discounted Price: " + discounted);
    };

    for (int i = 0; i < n; i++) {
        double discountedPrice = prices[i] - (prices[i] * 0.15);
        printer.print(names[i], prices[i], discountedPrice);
    }
}
}
}

```

Status : Partially correct

Marks : 7.5/10

3. Problem Statement

Emily, an analyst at a data processing firm, is tasked with cleaning up datasets to remove duplicate values from lists of integers.

Create a Java program that allows Emily to input a series of integers, with the program then utilizing a lambda expression to efficiently remove any duplicates.

Input Format

The first line of input consists of an integer N, representing the size of the array.

The second line consists of N space-separated integers, each denoting an array element.

Output Format

The output prints the array elements after removing the duplicates inside the square bracket separated by a comma and space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 15

1 2 3 4 3 2 1 2 3 4 4 4 5 5 6

Output: [1, 2, 3, 4, 5, 6]

Answer

// You are using Java

import java.util.*;

```
interface DuplicateRemover {  
    List<Integer> remove(List<Integer> list);  
}
```

```
class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
        int N = sc.nextInt();  
        List<Integer> list = new ArrayList<>();
```

```
        for (int i = 0; i < N; i++) {  
            list.add(sc.nextInt());  
        }
```

```
        // Lambda to remove duplicates while keeping original order
```

```
        DuplicateRemover remover = (arr) -> {  
            List<Integer> unique = new ArrayList<>();  
            for (int num : arr) {  
                if (!unique.contains(num)) {  
                    unique.add(num);  
                }  
            }  
            return unique;  
        };
```

```
        List<Integer> result = remover.remove(list);
```

```
        System.out.println(result.toString());  
    }
```

}

Status : Correct

Marks : 10/10

4. Problem Statement

Aditya is developing a reading app that recommends books to users based on a predefined list.

Each time a user opens the app, it should supply the next book title in the list, one at a time, using a lambda expression and the Supplier functional interface.

When all books have been recommended, the list should start again from the beginning.

Input Format

The first line contains an integer n — the total number of available book titles.

The next n lines each contain a book title (a string).

The next line contains an integer m — the number of times users open the app (i.e., the number of recommendations to be made).

Output Format

Print the supplied book title for each recommendation, one per line.

If $m > n$, repeat the list from the start.

Sample Test Case

Input: 3

The Alchemist

Atomic Habits

Ikigai

5

Output: The Alchemist

Atomic Habits

Ikigai

The Alchemist

Atomic Habits

Answer

```
import java.util.*;

interface BookSupplier {
    String getNext();
}

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = Integer.parseInt(sc.nextLine()); // number of books
        String[] books = new String[n];

        for (int i = 0; i < n; i++) {
            books[i] = sc.nextLine();           // book titles
        }

        int m = Integer.parseInt(sc.nextLine()); // number of recommendations

        // index holder (array used to modify inside lambda)
        int[] index = {0};

        // Lambda to supply next book cyclically
        BookSupplier supplier = () -> {
            String nextBook = books[index[0]];
            index[0] = (index[0] + 1) % books.length; // cycle back to start
            return nextBook;
        };

        for (int i = 0; i < m; i++) {
            System.out.println(supplier.getNext());
        }
    }
}
```

Status : Correct

Marks : 10/10