Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void* a, const void* b) {
    return (*(int*)a - *(int*)b);
}


int main(){
    int n;
    scanf("%d",&n);
    int arr[n];
    for(int i=0; i<n; i++){
        scanf("%d",&arr[i]);
    }
    qsort(arr, n, sizeof(int), compare);
    int max_sum = 0;
    for(int i=0; i<n; i++){
        max_sum += (i * arr[i]);
    }
    printf("%d",max_sum);
}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔

	Input	Expected	Got	
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course