Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int arr[n];
    int arr1[n];
    for(int i=0; i<n; i++){
        scanf("%d",&arr[i]);
    }
    for(int i=0; i<n; i++){
        scanf("%d",&arr1[i]);
    }
    for(int i=0; i<n; i++){
        for(int j=0; j<n-1; j++){
            if(arr[j] > arr[j+1]){
                int temp = arr[j];
                arr[j] = arr[j+1];
                arr[j+1] = temp;
            }
        }
    }
    for(int i=0; i<n; i++){
        for(int j=0; j<n-1; j++){
            if(arr1[j] < arr1[j+1]){
                int temp = arr1[j];
                arr1[j] = arr1[j+1];
                arr1[j+1] = temp;
            }
        }
    }
    int min_sum = 0;
    for(int i=0; i<n; i++){
        min_sum += (arr[i] * arr1[i]);
    }
    printf("%d",min_sum);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course