Correct Marked out of 1.00

Question 1

Flag question

Given a string, **s**, consisting of alphabets and digits, find the frequency of each digit in the given string.

Input Format

The first line contains a string, *num* which is the given number.

Constraints

1 ≤ len(num) ≤ 1000

All the elements of num are made of English alphabets and digits.

Output Format

Print ten space-separated integers in a single line denoting the frequency of each digit from ${\bf 0}$ to ${\bf 9}$.

Sample Input 0

a11472o5t6

Print ten space-separated integers in a single line denoting the frequency of each digit from 0 to 9. Sample Input 0 a11472o5t6 Sample Output 0 0 2 1 0 1 1 1 1 1 0 0 Explanation 0 In the given string: 1 occurs two times. 2, 4, 5, 6 and 7 occur one time each. The remaining digits 0, 3, 8 and 9 don't occur at all.

	Input	Expected	Got	
~	a11472o5t6	0 2 1 0 1 1 1 1 0 0	0 2 1 0 1 1 1 1 0 0	~
~	lw4n88j12n1	0 2 1 0 1 0 0 0 2 0	0 2 1 0 1 0 0 0 2 0	~
~	1v888861256338ar0ekk	1 1 1 2 0 1 2 0 5 0	1 1 1 2 0 1 2 0 5 0	~

Correct

Marked out of
1.00

Flag question

Question 2

Today, Monk went for a walk in a garden. There are many trees in the garden and each tree has an English alphabet on it. While Monk was walking, he noticed that all trees with vowels on it are not in good state. He decided to take care of them. So, he asked you to tell him the count of such trees in the garden.

Note: The following letters are vowels: 'A', 'E', 'I', 'O', 'U', 'a', 'e', 'i', 'o' and 'u'.

Input:

The first line consists of an integer *T* denoting the number of test cases.

Each test case consists of only one string, each character of string denoting the alphabet (may be lowercase or uppercase) on a tree in the garden.

Output:

For each test case, print the count in a new line.

Constraints:

 $1 \le T \le 10$ $1 \le length of string \le 10^5$

SAMPLE INPUT

Output:
For each test case, print the count in a new line.
Constraints:
1 ≤ T ≤ 10 1 ≤ length of string ≤ 10 ⁵
i stength of string s to
SAMPLE INPUT
SAMPLE INPUT
2
nBBZLaosnm
JHklsnZtTL
SAMPLE OUTPUT
Explanation
In test case 1, a and o are the only vowels. So, count=2

```
#include<stdio.h>
2
   #include<string.h>
3 🔻
   int main(){
      int t,c=0;
4
5
      char v[100001];
      6
7
8 *
9
10 🔻
11 v
               if(o[j]==v[k]){
c++;
12 🔻
13
14
15
            }
16
         printf("%d\n",c);
17
18
         c=0;
19
20 }
```

Input	Expected	Got	
2 nBBZLaosnm JHkIsnZtTL	2	2	~
2 nBBZLaosnm JHkIsnZtTL	2	2	~

Question **3**Correct
Marked out of 1.00

Flag question

Input Format	
The first and only line contains a sentence, s .	
Constraints	
1 ≤ len(s) ≤ 1000	
Output Format	
Print each word of the sentence in a new line.	
Sample Input 0	
This is C	
Sample Output 0	
This	
is	

Constraints
Constants
$1 \le len(s) \le 1000$
Output Format
Print each word of the sentence in a new line.
Sample Input 0
This is C
Sample Output 0
This
is
C
Explanation 0
In the given string, there are three words ["This", "is", "C"]. We have to print each of these words in a new line.

```
#include<string.h>
#include<string.h>
int main(){
    char a[1001];
    scanf("%[^\n]\%*c",a);
    for(int i=0;isstrlen(a);i++){
        if(a[i]==' '){
            printf("\n");
            }
        else{
            printf("%c",a[i]);
            }
        }
    }
}
```

	Input	Expected	Got	
~	This is C	This	This	~
		is C	is C	
~	Learning C is fun		Learning	~
		C	C	
		is	is	
		fun	fun	

Question 4
Correct
Marked out of 1.00
Flag question

Input Format

You are given two strings, \boldsymbol{a} and \boldsymbol{b} , separated by a new line. Each string will consist of lower case Latin characters ('a'-'z').

Output Format

In the first line print two space-separated integers, representing the length of \boldsymbol{a} and \boldsymbol{b} respectively.

In the second line print the string produced by concatenating \boldsymbol{a} and \boldsymbol{b} ($\boldsymbol{a}+\boldsymbol{b}$).

In the third line print two strings separated by a space, a^* and b^* . a^* and b^* are the same as a and b, respectively, except that their first characters are swapped.

Sample Input

abcd

ef

Sample Output

42

abcdef

ebcd af

In the third line print two strings separated by a space, a' and b' . a' and b' are the same as a and b , respectively, except that their first characters are swapped.
Sample Input
abcd
ef
Sample Output
4 2
abcdef
ebcd af
Explanation
a = "abcd"
b = "ef"
a = 4
b = 2
a + b = "abcdef"
a' = "ebcd"
b' = "af"

```
Answer: (penalty regime: 0 %)
    1 #include<stdio.h>
     2 #include<string.h>
     3 v int main(){
               char a[1000],b[1000],c[1000];
scanf("%s %s",a,b);
printf("%ld %ld\n",strlen(a),strlen(b));
     4
     5
     6
                print( %td %id(in ,strien(a)
strcpy(c,a);
printf("%s\n",strcat(a,b));
char t=c[0];
c[0]=b[0];
     7
     8
     9
    10
                b[0]=t;
printf("%s %s",c,b);
    11
    12
    13
    14 }
```