

VPI INNOVATIVE SOLUTIONS

VG SERIES COLLET CHUCKS / FULL SPECIFICATIONS / VG-20 MODEL RANGE

MODEL	SPINDLE	MAX RPM	WEIGHT (KG)	OPERATING FORCE kN	CLAMPING FORCE kN	SLEEVE STROKE MM	MIN-MAX L MM
VG-20 A8-80	A2-8	3500	23	29.4 (3000)	63.7 (6500)	10	5-60
VG-20 A6-60	A2-6	4000	11.35	19.6 (2000)	42.1 (4300)	3	2-25
VG-20 FL 220-80	220 (h6)	6000	5.5	29.4 (3000)	52.9 (5400)	8	3-42
VG-20 FL 110-25	110 mm (h6)	5000	14.1	33 (7260)	63.7 (6500)	10	5-60
VG-20 FL 170-42	170 mm (h6)	4000	16	33 (7260)	57.75 (12705)	10	10-80
VG-20 FL 170-60	170 mm (h6)	3500	23	24.5 (2500)	57.75 (12705)	10	10-80
VG-20 A5-42	A2-5	5000	6.35	19.6 (2000)	52.9 (5400)	8	3-42
VG-20 A4-25	A2-4	6000	5.1	29.4 (3000)	42.1 (4300)	3	2-25
VO-20 A6-60	M83 x 2.0p	69	-	M87 x 1.5p	106.36	133	165
VG-20 A8-80	M80 x 2.0p	91	-	M100 x 1.5	139.7	171	220

Force values shown as kN (kgf). Specifications are representative - confirm application-specific data with the VPI engineering desk.

vpisolutions@gmail.com / tech@vpisolutions.net / +91 99009911202