

MERN STACK

DAY – 12

8 July 2026

JAVASCRIPT

onclick Event

The onclick event is an event handler in JavaScript that executes a function when the user clicks an HTML element such as a button, image, or link. It is commonly used to perform actions like displaying messages, calculating values, or changing webpage content.

Syntax

```
<element onclick="functionName()">
```

or

```
<button onclick="functionName()">Click Me</button>
```

.value Property

The .value property is used to get (read) or set (change) the value of form elements such as <input>, <textarea>, and <select>. It is commonly used to access user input or display data in a form field.

Syntax

Get the value:

```
element.value;
```

Set the value:

```
element.value = "new value";
```

General Syntax:

```
document.getElementById("elementId").value;
```

TASK: CALCULATOR

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      background-color: #f2f2f2;
      text-align: center;
    }

    .cal {
      width: 220px;
      margin: 30px auto;
      padding: 15px;
      background-color: white;
      border: 1px solid #ccc;
      border-radius: 8px;
    }

    #num {
      width: 95%;
      height: 35px;
      margin-bottom: 10px;
      font-size: 18px;
      text-align: right;
      padding-right: 5px;
    }

    .up {
      margin: 5px 0;
    }

    button {
      width: 45px;
      height: 45px;
      font-size: 18px;
      margin: 2px;
      cursor: pointer;
      border: 1px solid #999;
      border-radius: 5px;
      background-color: #e6e6e6;
    }

    button:hover {
      background-color: #d4d4d4;
    }
  </style>
</head>
```

```
<body>
  <h1 align="center">TASK 3</h1>
  <h2 align="center">CALCULATOR</h2>
  <div class="cal">
    <div>
      <input type="text" id="num">
    </div>
    <div class="up">
      <button onclick="addvalue(7)">7</button>
      <button onclick="addvalue(8)">8</button>
      <button onclick="addvalue(9)">9</button>
      <button onclick="addvalue('/')">/</button>
    </div>
    <div class="up">
      <button onclick="addvalue(4)">4</button>
      <button onclick="addvalue(5)">5</button>
      <button onclick="addvalue(6)">6</button>
      <button onclick="addvalue('*')">*</button>
    </div>
    <div class="up">
      <button onclick="addvalue(1)">1</button>
      <button onclick="addvalue(2)">2</button>
      <button onclick="addvalue(3)">3</button>
      <button onclick="addvalue('-')">-</button>
    </div>
    <div class="up">
      <button onclick="addvalue(0)">0</button>
      <button onclick="cleard()">C</button>
      <button onclick="eva()">=</button>
      <button onclick="addvalue('+')">+</button>
    </div>
  </div>
```

```
<script>
  let op = "";

  function addvalue(a) {
    let p = document.getElementById("num");
    p.value = p.value + a;
  }

  function cleard() {
    let p = document.getElementById("num");
    p.value = "";
  }

  function eva() {
    let p = document.getElementById("num");
    let val = p.value;
    let n1 = "";
    let n2 = "";
    for (let i = 0; i < val.length; i++) {
      if (val[i] == "+" || val[i] == "-" || val[i] == "*" || val[i] == "/" ) {
        op = val[i];
        n1 = val.substring(0, i);
        n2 = val.substring(i + 1);
        break;
      }
    }
    let ans;
    switch (op) {
      case "+":
        ans = Number(n1) + Number(n2);
        break;

      case "-":
        ans = Number(n1) - Number(n2);
        break;

      case "*":
        ans = Number(n1) * Number(n2);
        break;

      case "/":
        ans = Number(n1) / Number(n2);
        break;

      default:
        ans = "Invalid";
    }

    p.value = ans;
  }
}
</script>
/body>
```

TASK 3

CALCULATOR

5*2

7

8

9

/

4

5

6

*

1

2

3

-

0

C

=

+

TASK 3

CALCULATOR

10

7

8

9

/

4

5

6

*

1

2

3

-

0

C

=

+