

MERN STACK

DAY – 6

1 July 2026

CSS Positioning

CSS positioning is about controlling the placement of elements within a web page.

With CSS positioning, you can override the normal document flow.

The CSS position Property

The position property specifies the positioning type for an element.

This property can have one of the following values:

- static - This is default. Element is positioned according to the normal document flow
- relative - Element is positioned relative to its normal position in the document flow
- fixed - Element is positioned relative to the viewport
- absolute - Element is positioned relative to the nearest positioned ancestor
- sticky - Element toggles between a relative and fixed position, depending on the scroll position

Elements are then positioned to their final location with the top, bottom, left, and right properties.

CSS top, right, bottom, left

These properties are called offset properties. They are used to control the position of an element when it is positioned using relative, absolute, fixed, or sticky. They do nothing for position: static.

These properties move an element from a reference point.

- top → moves the element downward from the top reference
- bottom → moves the element upward from the bottom reference
- left → moves the element right from the left reference
- right → moves the element left from the right reference

```
.static { position: static; }

.relative { position: relative;

  top: 10px;

  left: 10px;}

.parent { position: relative; }

.absolute { position: absolute;

  top: 0;

  right: 0;}

.fixed { position: fixed;

  bottom: 10px;

  right: 10px;}

.sticky { position: sticky;

  top: 0;}
```



CSS z-index

The z-index property in CSS controls the stacking order of elements on the screen along the z-axis (front to back).

It decides which element appears in front and which appears behind when elements overlap.