

MERN STACK

DAY – 15

11 July 2026

TASK-1 CALCULATOR

9

+ ▼

=

BOOTSTRAP

Bootstrap Container

A container is a responsive fixed-width wrapper in Bootstrap. It centers the content and provides horizontal padding.

Syntax:

```
<div class="container">  
  
    Content here  
  
</div>
```

Types of Containers:

1. .container

- Fixed-width responsive container.
- Width changes according to screen size.

```
<div class="container">  
  
    Fixed responsive container  
  
</div>
```

2. .container-fluid

- Takes 100% width of the screen.

```
<div class="container-fluid">  
  
    Full width container  
  
</div>
```

Bootstrap Row

A row creates a horizontal group of columns. Rows are used inside containers.

Syntax:

```
<div class="container">  
  
    <div class="row">  
  
        Content  
  
    </div>
```

Bootstrap Columns (col)

Bootstrap grid system uses 12 columns in one row.

Syntax:

```
<div class="col">  
  
    Content  
  
</div>
```

col-1: col-1 occupies 1 column out of 12.

Syntax:

```
<div class="col-1">  
  
    Content  
  
</div>
```

col-3: col-3 occupies 3 columns out of 12.

Syntax:

```
<div class="col-3">  
  
    Content  
  
</div>
```

Bootstrap Breakpoints : Breakpoints are screen sizes where Bootstrap changes the layout.

Breakpoint	Screen Size
xs	Less than 576px
sm	≥576px
md	≥768px
lg	≥992px
xl	≥1200px
xxl	≥1400px

col-lg-4

col-lg-4 means:

- On large screens (992px and above)
- Column takes 4 spaces out of 12.

Syntax:

```
<div class="col-lg-4">  
  
    Content  
  
</div>
```

col-md-6

col-md-6 means:

- On medium screens (768px and above)
- Column takes 6 spaces.

Syntax:

```
<div class="col-md-6">  
  
    Content  
  
</div>
```

Bootstrap Margin Classes : Margin creates space outside an element.

Syntax:

```
m-{size}
```

Sizes:

Class	Value
m-0	No margin
m-1	Small margin
m-2	Medium margin
m-3	Large margin
m-4	Extra large
m-5	Largest

Margin Direction Classes

1. mt (margin-top): Adds margin at top.

Syntax:

```
mt-{size}
```

2. mb (margin-bottom): Adds margin at bottom.

3. ms (margin-start / left): Adds margin on left side.

4. me (margin-end / right): Adds margin on right side.

5. mx (left + right margin)

Example:

```
<div class="mx-3">Content</div>
```

6. my (top + bottom margin)

Example:

```
<div class="my-3">Content</div>
```

Responsive Margin : Margins can be applied at specific breakpoints.

Syntax:

```
m-{breakpoint}-{size}
```

Bootstrap Padding Classes: Padding creates space inside an element.

Syntax:

```
p-{size}
```

Padding

Padding is the space inside an element between the content and the element's border. It is used to create internal spacing and improve the layout of a webpage. Bootstrap provides padding utility classes that allow developers to add spacing easily without writing custom CSS. Padding can be applied to all sides of an element or to specific sides like top, bottom, start, and end.

Padding helps make content look clean, organized, and easier to read. It is commonly used in cards, buttons, containers, and sections.

TASK – 2

BOOTSTRAP TASK

col1	col1	col1	col1	col1	col1	col1	col1	col1	col1	col1	col1
col3			col3			col3			col3		
col4				col4				col4			
col8								col4			
col2	col2		col4				col2		col2		
col6						col6					
col12											