

MERN STACK

DAY – 25

23 July 2026

LOGIN API

- The login API is used to authenticate a user by verifying the email and password provided during login.
- The client sends a POST request to the /api/login endpoint with the user's email and password.
- The server searches the database for a user whose email matches the entered email using:

```
usermodel.findOne({ Email: req.body.mail })
```

- If a matching user is found, the server compares the stored password (user.pass) with the password entered by the user (req.body.pass).
- If both passwords match, the user is authenticated successfully, and the server sends a success response containing:
 - statuscode: 1
 - Success message
 - User ID (user._id)
 - User type (user.usertype)
- If the password does not match, the server returns an "Invalid password" message.
- If no user with the entered email exists in the database, the server returns a "User not found" message.

Working

1. `app.post("/api/login")` creates a POST API for user login.
2. `findOne()` retrieves a single user document based on the email.
3. The `if (user)` condition checks whether the email exists in the database.
4. The password is validated by comparing `user.pass` with `req.body.pass`.
5. On successful authentication, the server responds with the user's details.
6. If authentication fails, an appropriate error message is returned.

The purpose of this login API is to verify user credentials and allow only authorized users to access the application while identifying their role through the `usertype` field.

```
app.post("/api/login",async(req,res)=>{  
  const user=await userModel.findOne({Email:req.body.mail});  
  if(user){  
    const fp=user.pass;  
    if(fp==req.body.pass){  
      res.send({statusCode:1,msg:"Login successful",id:user._id,usertype:req.body.usertype})  
    }else{  
      res.send({statusCode:0,msg:"Invalid credentials"})  
    }  
  }  
})
```