This course is uploaded by @hmaracollege

```
Last login: Sat Dec 7 20:11:29 on console
durgesh_mac@durgesh ~ % root -u root -p
zsh: command not found: root
durgesh_mac@durgesh ~ % mysql -u root -p
Enter password:
Welcome to the MySQL monitor. Commands end with ; or \g.
Your MySQL connection id is 8
Server version: 9.0.1 Homebrew

Copyright (c) 2000, 2024, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> show databases;
+--------------------+
| Database |
+--------------------+
| e_learn_batch |
| information_schema |
| jb2404 |
| mysql |
| performance_schema |
| sys |
+--------------------+
6 rows in set (0.02 sec)

mysql> use jb2404;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show tables;
+-----------------+
| Tables_in_jb2404 |
+-----------------+
| users |
+-----------------+
1 row in set (0.00 sec)
```

This course is uploaded by @coding_discussion2

This course is uploaded by @hmaracollege

```
mysql> select * from users;
+---------+------------+---------+--------+
| user_id | name | city | salary |
+---------+------------+---------+--------+
| 1100 | Pankaj | Lucknow | 34000 |
| 1101 | Vivek Ashok | Delhi | 50000 |
| 1102 | Ankit | Kanpur | 50000 |
| 1414 | Abhinav | Lucknow | 252555 |
| 1415 | Abhishek | Lucknow | 252555 |
| 5503 | Subham | Banglore | 1231 |
+---------+------------+---------+--------+
6 rows in set (0.01 sec)

mysql> update users set city='Delhi',salary=40000 where id =1415;
ERROR 1054 (42S22): Unknown column 'id' in 'where clause'
mysql> update users set city='Delhi',salary=40000 where user_id =1415;
Query OK, 1 row affected (0.01 sec)
Rows matched: 1 Changed: 1 Warnings: 0

mysql> select * from users;
+---------+------------+---------+--------+
| user_id | name | city | salary |
+---------+------------+---------+--------+
| 1100 | Pankaj | Lucknow | 34000 |
| 1101 | Vivek Ashok | Delhi | 50000 |
| 1102 | Ankit | Kanpur | 50000 |
| 1414 | Abhinav | Lucknow | 252555 |
| 1415 | Abhishek | Delhi | 40000 |
| 5503 | Subham | Banglore | 1231 |
+---------+------------+---------+--------+
6 rows in set (0.00 sec)

mysql> delete from users where user_id = 5503;
Query OK, 1 row affected (0.00 sec)

mysql> select * from users;
+---------+------------+---------+--------+
| user_id | name | city | salary |
+---------+------------+---------+--------+
| 1100 | Pankaj | Lucknow | 34000 |
| 1101 | Vivek Ashok | Delhi | 50000 |
| 1102 | Ankit | Kanpur | 50000 |
| 1414 | Abhinav | Lucknow | 252555 |
| 1415 | Abhishek | Delhi | 40000 |
+---------+------------+---------+--------+
5 rows in set (0.00 sec)
```

This course is uploaded by @coding_discussion2

```
mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql> select * from users;
+---------+-------------+---------+--------+
| user_id | name        | city    | salary |
+---------+-------------+---------+--------+
| 1100    | Pankaj      | Lucknow | 34000  |
| 1101    | Vivek Ashok | Delhi   | 50000  |
| 1102    | Ankit       | Kanpur  | 50000  |
| 1414    | Abhinav     | Lucknow | 252555 |
| 1415    | Abhishek    | Delhi   | 40000  |
+---------+-------------+---------+--------+
5 rows in set (0.00 sec)

mysql> insert into users values (555,'Ankit','LKO',2525);
Query OK, 1 row affected (0.00 sec)

mysql> select * from users;
+---------+-------------+---------+--------+
| user_id | name        | city    | salary |
+---------+-------------+---------+--------+
| 555     | Ankit       | LKO     | 2525   |
| 1100    | Pankaj      | Lucknow | 34000  |
| 1101    | Vivek Ashok | Delhi   | 50000  |
| 1102    | Ankit       | Kanpur  | 50000  |
| 1414    | Abhinav     | Lucknow | 252555 |
| 1415    | Abhishek    | Delhi   | 40000  |
+---------+-------------+---------+--------+
6 rows in set (0.00 sec)

mysql> SAVEPOINT savepoint1;
Query OK, 0 rows affected (0.00 sec)

mysql> delete form users where user_id=555;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'users where user_id=555' at line 1
mysql> delete from users where user_id=555;
Query OK, 1 row affected (0.00 sec)

mysql> select * from users;
+---------+-------------+---------+--------+
| user_id | name        | city    | salary |
+---------+-------------+---------+--------+
| 1100    | Pankaj      | Lucknow | 34000  |
| 1101    | Vivek Ashok | Delhi   | 50000  |
| 1102    | Ankit       | Kanpur  | 50000  |
| 1414    | Abhinav     | Lucknow | 252555 |
| 1415    | Abhishek    | Delhi   | 40000  |
+---------+-------------+---------+--------+
5 rows in set (0.00 sec)
```

This course is uploaded by @coding_discussion2

```
mysql> ROLLBACK TO SAVEPOINT savepoint1;
Query OK, 0 rows affected (0.00 sec)

mysql> select * from users;
+---------+------------+---------+--------+
| user_id | name | city | salary |
+---------+------------+---------+--------+
| 555 | Ankit | LKO | 2525 |
| 1100 | Pankaj | Lucknow | 34000 |
| 1101 | Vivek Ashok | Delhi | 50000 |
| 1102 | Ankit | Kanpur | 50000 |
| 1414 | Abhinav | Lucknow | 252555 |
| 1415 | Abhishek | Delhi | 40000 |
+---------+------------+---------+--------+
6 rows in set (0.00 sec)

mysql> COMMIT;
Query OK, 0 rows affected (0.00 sec)

mysql> RELEASE SAVEPOINT savepoint1;
ERROR 1305 (42000): SAVEPOINT savepoint1 does not exist
mysql> RELEASE SAVEPOINT savepoint1;
ERROR 1305 (42000): SAVEPOINT savepoint1 does not exist
mysql> RELEASE SAVEPOINT savepoint1;
ERROR 1305 (42000): SAVEPOINT savepoint1 does not exist
mysql> RELEASE SAVEPOINT savepoint1;
ERROR 1305 (42000): SAVEPOINT savepoint1 does not exist
mysql> select * from users;
+---------+------------+---------+--------+
| user_id | name | city | salary |
+---------+------------+---------+--------+
| 555 | Ankit | LKO | 2525 |
| 1100 | Pankaj | Lucknow | 34000 |
| 1101 | Vivek Ashok | Delhi | 50000 |
| 1102 | Ankit | Kanpur | 50000 |
| 1414 | Abhinav | Lucknow | 252555 |
| 1415 | Abhishek | Delhi | 40000 |
+---------+------------+---------+--------+
6 rows in set (0.00 sec)

mysql> select name,city from users;
+------------+---------+
| name | city |
+------------+---------+
| Ankit | LKO |
| Pankaj | Lucknow |
| Vivek Ashok | Delhi |
| Ankit | Kanpur |
| Abhinav | Lucknow |
| Abhishek | Delhi |
+------------+---------+
```

This course is uploaded by @hmaracollege

```
mysql> | name | city |
-> +-------------+---------+
-> | Ankit | LKO |
-> | Pankaj | Lucknow |
-> | Vivek Ashok | Delhi |
-> | Ankit | Kanpur |
-> | Abhinav | Lucknow |
-> ;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '| name | city |
+-------------+---------+
| Ankit | LKO |
| ' at line 1
mysql> select name as USER_NAME , city as USER_CITY from users;
+-------------+-----------+
| USER_NAME | USER_CITY |
+-------------+-----------+
| Ankit | LKO |
| Pankaj | Lucknow |
| Vivek Ashok | Delhi |
| Ankit | Kanpur |
| Abhinav | Lucknow |
| Abhishek | Delhi |
+-------------+-----------+
6 rows in set (0.00 sec)

mysql> select * from users as u where u.user_id=1415;
+---------+----------+-------+--------+
| user_id | name | city | salary |
+---------+----------+-------+--------+
| 1415 | Abhishek | Delhi | 40000 |
+---------+----------+-------+--------+
1 row in set (0.00 sec)

mysql> select * from users u where u.user_id=1415;
+---------+----------+-------+--------+
| user_id | name | city | salary |
+---------+----------+-------+--------+
| 1415 | Abhishek | Delhi | 40000 |
+---------+----------+-------+--------+
1 row in set (0.01 sec)
```

This course is uploaded by @hmaracollege

```
mysql> select * from users;
+---------+------------+---------+--------+
| user_id | name | city | salary |
+---------+------------+---------+--------+
| 555 | Ankit | LKO | 2525 |
| 1100 | Pankaj | Lucknow | 34000 |
| 1101 | Vivek Ashok | Delhi | 50000 |
| 1102 | Ankit | Kanpur | 50000 |
| 1414 | Abhinav | Lucknow | 252555 |
| 1415 | Abhishek | Delhi | 40000 |
+---------+------------+---------+--------+
6 rows in set (0.00 sec)

mysql> create table address (
->
-> address_id int primary key ,
-> street varchar(100),
-> zip_code int ,
-> country varchar(50) NOT NULL,
-> uid int ,
->
-> FOREIGN KEY (uid) REFERENCES users(user_id)
->
-> );
Query OK, 0 rows affected (0.02 sec)

mysql> show tables;
+-----------------+
| Tables_in_jb2404 |
+-----------------+
| address |
| users |
+-----------------+
2 rows in set (0.00 sec)

mysql> desc users;
+---------+-------------+------+-----+---------+-------+
| Field | Type | Null | Key | Default | Extra |
+---------+-------------+------+-----+---------+-------+
| user_id | int | NO | PRI | NULL | |
| name | varchar(100) | YES | | NULL | |
| city | varchar(50) | NO | | NULL | |
| salary | int | YES | | NULL | |
+---------+-------------+------+-----+---------+-------+
4 rows in set (0.01 sec)
```

This course is uploaded by @hmaracollege

```
mysql> desc address;
+------------+-------------+------+-----+---------+-------+
| Field | Type | Null | Key | Default | Extra |
+------------+-------------+------+-----+---------+-------+
| address_id | int | NO | PRI | NULL | |
| street | varchar(100) | YES | | NULL | |
| zip_code | int | YES | | NULL | |
| country | varchar(50) | NO | | NULL | |
| uid | int | YES | MUL | NULL | |
+------------+-------------+------+-----+---------+-------+
5 rows in set (0.00 sec)

mysql>
mysql> insert into address (
-> address_id,
-> street,
-> zip_code,
-> country,
-> uid
-> ) values (
-> 10101,
-> '245/325 sector 12 side abc mall',
-> 22384,
-> INDIA,
-> 1415
-> );
ERROR 1054 (42S22): Unknown column 'INDIA' in 'field list'
mysql>
mysql> insert into address (
-> address_id,
-> street,
-> zip_code,
-> country,
-> uid
-> ) values (
-> 10101,
-> '245/325 sector 12 side abc mall',
-> 22384,
-> "INDIA",
-> 1415
-> );
Query OK, 1 row affected (0.01 sec)
```

```
mysql> desc address;
+------------+-------------+------+-----+---------+-------+
| Field | Type | Null | Key | Default | Extra |
+------------+-------------+------+-----+---------+-------+
| address_id | int | NO | PRI | NULL | |
| street | varchar(100) | YES | | NULL | |
| zip_code | int | YES | | NULL | |
| country | varchar(50) | NO | | NULL | |
| uid | int | YES | MUL | NULL | |
+------------+-------------+------+-----+---------+-------+
5 rows in set (0.00 sec)

mysql>
mysql> insert into address (
-> address_id,
-> street,
-> zip_code,
-> country,
-> uid
-> ) values (
-> 10101,
-> '245/325 sector 12 side abc mall',
-> 22384,
-> INDIA,
-> 1415
-> );
ERROR 1054 (42S22): Unknown column 'INDIA' in 'field list'
mysql>
mysql> insert into address (
-> address_id,
-> street,
-> zip_code,
-> country,
-> uid
-> ) values (
-> 10101,
-> '245/325 sector 12 side abc mall',
-> 22384,
-> "INDIA",
-> 1415
-> );
Query OK, 1 row affected (0.01 sec)

mysql> select * from address;
+------------+-------------------------------+----------+---------+------+
| address_id | street | zip_code | country | uid |
+------------+-------------------------------+----------+---------+------+
| 10101 | 245/325 sector 12 side abc mall | 22384 | INDIA | 1415 |
+------------+-------------------------------+----------+---------+------+
1 row in set (0.00 sec)
```

```
mysql>
mysql> insert into address (
-> address_id,
-> street,
-> zip_code,
-> country,
-> uid
-> ) values (
-> 10102,
-> '2/14 Indra nagar ',
-> 22384,
-> "INDIA",
-> 1415
-> );
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> insert into address (
-> address_id,
-> street,
-> zip_code,
-> country,
-> uid
-> ) values (
-> 10106,
-> '2/14 gomti nagar ',
-> 22384,
-> "INDIA",
-> 1414
-> );
Query OK, 1 row affected (0.00 sec)

mysql> select * from address;
+------------+---------------------------------+----------+---------+------+
| address_id | street | zip_code | country | uid |
+------------+---------------------------------+----------+---------+------+
| 10101 | 245/325 sector 12 side abc mall | 22384 | INDIA | 1415 |
| 10102 | 2/14 Indra nagar | 22384 | INDIA | 1415 |
| 10106 | 2/14 gomti nagar | 22384 | INDIA | 1414 |
+------------+---------------------------------+----------+---------+------+
3 rows in set (0.00 sec)
```

```
mysql>
mysql> insert into address (
-> address_id,
-> street,
-> zip_code,
-> country,
-> uid
-> ) values (
-> 10107,
-> '2/14 gomti nagar ',
-> 22384,
-> "INDIA",
-> 14141235246
-> );
ERROR 1264 (22003): Out of range value for column 'uid' at row 1
mysql>
mysql> insert into address (
-> address_id,
-> street,
-> zip_code,
-> country,
-> uid
-> ) values (
-> 10107,
-> '2/14 gomti nagar ',
-> 22384,
-> "INDIA",
-> 14141
-> );
ERROR 1452 (23000): Cannot add or update a child row: a foreign key constraint fails (`jb2404`.`address`, CONSTRAINT `address_ibfk_1` FOREIGN KEY (`uid`) REFERENCES `users` (`user_id`))
mysql> insert into address ( address_id, street, zip_code, country) values ( 10107, '2/14 gomti nagar ', 22384, "INDIA" );
Query OK, 1 row affected (0.00 sec)

mysql> select * from address;
+------------+----------------------------------+----------+---------+------+
| address_id | street                           | zip_code | country | uid  |
+------------+----------------------------------+----------+---------+------+
| 10101      | 245/325 sector 12 side abc mall  | 22384    | INDIA   | 1415 |
| 10102      | 2/14 indra nagar                 | 22384    | INDIA   | 1415 |
| 10106      | 2/14 gomti nagar                 | 22384    | INDIA   | 1414 |
| 10107      | 2/14 gomti nagar                 | 22384    | INDIA   | NULL |
+------------+----------------------------------+----------+---------+------+
4 rows in set (0.00 sec)
```

This course is uploaded by
@hmaracollege

```
mysql> select * from users;
+---------+------------+---------+--------+
| user_id | name | city | salary |
+---------+------------+---------+--------+
| 555 | Ankit | LKO | 2525 |
| 1100 | Pankaj | Lucknow | 34000 |
| 1101 | Vivek Ashok | Delhi | 50000 |
| 1102 | Ankit | Kanpur | 50000 |
| 1414 | Abhinav | Lucknow | 252555 |
| 1415 | Abhishek | Delhi | 40000 |
+---------+------------+---------+--------+
6 rows in set (0.00 sec)

mysql> select
-> u.name,
-> u.salary,
-> a.street,
-> a.zip_code,
-> a.country
-> from users u
-> INNER JOIN address a
-> ON u.user_id = a.uid ;
+----------+--------+---------------------------------+----------+---------+
| name | salary | street | zip_code | country |
+----------+--------+---------------------------------+----------+---------+
| Abhishek | 40000 | 245/325 sector 12 side abc mall | 22384 | INDIA |
| Abhishek | 40000 | 2/14 Indra nagar | 22384 | INDIA |
| Abhinav | 252555 | 2/14 gomti nagar | 22384 | INDIA |
+----------+--------+---------------------------------+----------+---------+
3 rows in set (0.00 sec)

mysql>
mysql> select
-> u.name,
-> u.salary,
-> a.street,
-> a.zip_code,
-> a.country
-> from users u
-> INNER JOIN address a
-> ON u.user_id = a.uid
-> where u.name = 'Abhishek'
-> ;
+----------+--------+---------------------------------+----------+---------+
| name | salary | street | zip_code | country |
+----------+--------+---------------------------------+----------+---------+
| Abhishek | 40000 | 245/325 sector 12 side abc mall | 22384 | INDIA |
| Abhishek | 40000 | 2/14 Indra nagar | 22384 | INDIA |
+----------+--------+---------------------------------+----------+---------+
2 rows in set (0.01 sec)
```

This course is uploaded by @hmaracollege

```
mysql>
mysql> select
-> u.name,
-> u.salary,
-> a.street,
-> a.zip_code,
-> a.country
-> from users u
-> LEFT JOIN address a
-> ON u.user_id = a.uid
-> where u.name = 'Abhishek';
+----------+--------+-------------------------------+----------+---------+
| name | salary | street | zip_code | country |
+----------+--------+-------------------------------+----------+---------+
| Abhishek | 40000 | 245/325 sector 12 side abc mall | 22384 | INDIA |
| Abhishek | 40000 | 2/14 Indra nagar | 22384 | INDIA |
+----------+--------+-------------------------------+----------+---------+
2 rows in set (0.00 sec)

mysql> select u.name, u.salary, a.street, a.zip_code, a.country from users u LEFT JOIN address a ON u.user_id = a.uid;
+-------------+--------+-------------------------------+----------+---------+
| name | salary | street | zip_code | country |
+-------------+--------+-------------------------------+----------+---------+
| Ankit | 2525 | NULL | NULL | NULL |
| Pankaj | 34000 | NULL | NULL | NULL |
| Vivek Ashok | 50000 | NULL | NULL | NULL |
| Ankit | 50000 | NULL | NULL | NULL |
| Abhinav | 252555 | 2/14 gomti nagar | 22384 | INDIA |
| Abhishek | 40000 | 245/325 sector 12 side abc mall | 22384 | INDIA |
| Abhishek | 40000 | 2/14 Indra nagar | 22384 | INDIA |
+-------------+--------+-------------------------------+----------+---------+
7 rows in set (0.00 sec)

mysql>
mysql> select COUNT(user_id) from users;
+----------------+
| COUNT(user_id) |
+----------------+
| 6 |
+----------------+
1 row in set (0.00 sec)

mysql> select SUM(salary) from users;
+-------------+
| SUM(salary) |
+-------------+
| 429080 |
+-------------+
1 row in set (0.00 sec)
```

This course is uploaded by @hmaracollege

This course is uploaded by @hmaracollege

```
mysql>
mysql> select COUNT(user_id) from users;
+---------------+
| COUNT(user_id) |
+---------------+
| 6 |
+---------------+
1 row in set (0.00 sec)

mysql> select SUM(salary) from users;
+-------------+
| SUM(salary) |
+-------------+
| 429080 |
+-------------+
1 row in set (0.00 sec)

mysql> select
-> u.name,
-> u.salary,
-> a.street,
-> a.zip_code,
-> a.country
-> from users u
-> INNER JOIN address a
-> ON u.user_id = a.uid
-> where u.user_id = (select user_id from users where name ='Abhishek');
+----------+--------+-------------------------------+----------+---------+
| name | salary | street | zip_code | country |
+----------+--------+-------------------------------+----------+---------+
| Abhishek | 40000 | 245/325 sector 12 side abc mall | 22384 | INDIA |
| Abhishek | 40000 | 2/14 Indra nagar | 22384 | INDIA |
+----------+--------+-------------------------------+----------+---------+
2 rows in set (0.00 sec)

mysql>
```