

EECS 489 – FA 21

Discussion 12

Announcements

Assignment 4 is out.

Due date: **12/10 2021, 11:59 PM**

Lateday policy:

You have 3 group latedays in total for assignment 2 - 4.

Please compile your code in the VM and test it carefully.

Overview

- IEEE 802.11 Wi-Fi
 - CSMA/CA
- Datacenter Network

Q1 Getting Connected


Suppose you walk into a room, connect to Ethernet, and want to download a Web page. What are all the network protocol steps that take place, starting from powering on your PC to getting the Web page?

- Broadcast DHCP(Dynamic Host Configuration Protocol) request to get an IP address.
- Broadcast ARP message to get MAC of the next hop router.
- Issue a DNS query to get the IP address of the content server.
- Construct a TCP connection to the content server.

Q2 Datacenter

Consider the datacenter network with hierarchical topology in the figure to the right. Suppose now there are 80 pairs of flows, with ten flows between the first and ninth rack, ten flows between the second and the tenth rack, and so on. Further suppose that all links in the network are 10 Gbps, except for the links between hosts and TOR switches, which are 1 Gbps.


Assume Each flow has the same data rate.
Determine the maximum rate of a flow.



125 Mbps

Q2 Datacenter


Consider the datacenter network with hierarchical topology in the figure to the right. Suppose now there are 80 pairs of flows, with ten flows between the first and ninth rack, ten flows between the second and the tenth rack, and so on. Further suppose that all links in the network are 10 Gbps, except for the links between hosts and TOR switches, which are 1 Gbps.



Assume Each flow has the same data rate.
Determine the maximum rate of a flow.

1 Gbps

Q2 Datacenter



With the switches marked with X eliminated, are these two topologies identical? Would they have identical responses to further failures? If not, can you point out one failure scenario where they behave differently?

Q3 CSMA/CA

Suppose an 802.11b station is configured to always reserve the channel with RTS/CTS sequence. Suppose this station suddenly wants to transmit a 1,000 byte segment of data, and all other stations are idle at this time. Assume a transmission rate of 10 Mbps. Ignoring propagation delay and assuming no bit errors, calculate the time required to transmit the frame and receive the acknowledgement. Further assume that a frame without data is 32 bytes long.

$$\left(32 \times \frac{8}{10 \times 10^6}\right) \times 3 + (1000 + 32) \times \frac{8}{10 \times 10^6} = 9.024 \times 10^{-4} \text{ sec} = 902 \text{ usec}$$

Q4 Fair Share

Consider the following idealized LTE scenario. The downstream channel is slotted in time. There are four nodes, A, B, C, and D, reachable from the base station at rates of 10 Mbps, 5 Mbps, 2.5 Mbps, and 1 Mbps, respectively, on the downstream channel. These rates assume that the base station fully utilizes the time slot to send to just one station. The base station has an infinite amount of data to send to each of the nodes. If there is a fairness requirement that each node must receive an equal amount of data during each one second interval, what is the average transmission rate by the base station (to all nodes) during the downstream sub-frame?

$$10 \times \frac{1}{17} + 5 \times \frac{2}{17} + 2.5 \times \frac{4}{17} + 1 \times \frac{10}{17} = 2.35 \text{ Mbps}$$

Thanks

Have a good one!