The following opcodes are used for **Division**:

- DIVI — Divide by Signed Integer
- DIVU — Divide by Unsigned Integer
- DIVF — Divide by Floating Point

DIVI — *Divide by Signed Integer* {#DIVI}

```
    L2 = L2 / <signed_imm>
    L2 = L2 / <reg_val>
    L2 = L2 / <const>
```

=== "DIVI Example"

```
```linenums="1" hl_lines="1 3 5 7"
; imm +ve
    DIVI    1
; imm -ve
    DIVI    -123
; reg val
    DIVI    val(QT)
; const
    DIVI    SOME_CONST_VAL
```
```

=== "DIVI Properties"

```
| Opcode | Operand Type          | Destination   |
|--------|-----------------------|---------------|
| 16     | Signed 64-bit integer | L2 (implicit) |

Identified as memonic [#16](#DIVI), DIVI is used to
divide the L2 register by a 64-bit signed value
```

DIVU — *Divide by Unsigned Integer* {#DIVU}

```
    L3 = L3 / <unsigned_imm>
    L3 = L3 / <reg_val>
    L3 = L3 / <const>
```

=== "DIVU Example"

```linenums="1" hl_lines="1 3 5"
; imm +ve
    DIVU    1
; reg val
    DIVU    val(QT)
; const
    DIVU    SOME_CONST_VAL
```

=== "DIVU Properties"

```
| Opcode | Operand Type            | Destination   |
|--------|-------------------------|---------------|
| 21     | Unsigned 64-bit integer | L3 (implicit) |

Identified as memonic [#18](#DIVU), DIVU is used to
divide the L3 register by a 64-bit unsigned value
```

DIVF — *Divide by Float value* {#DIVF}

```
    L1 = L1 / <float>
    L1 = L1 / <reg_val>
    L1 = L1 / <const>
```

=== "DIVF Example"

```linenums="1" hl_lines="1 3 5"
; imm float
    DIVF    3.14
; reg val
    DIVF    val(QT)
; const
    DIVF    SOME_CONST_VAL

```

=== "DIVF Properties"

```
| Opcode | Operand Type       | Destination   |
|--------|--------------------|---------------|
| 26     | 64-bit Float Value | L1 (implicit) |
```

```
Identified as memonic [#23](#DIVF), DIVF is used to
divide the L1 register by a 64-bit float value
```
