

Chit 5 — PL/SQL: Parameterized Cursor (Merge RollCall)

Table Creation

```
CREATE TABLE O_RollCall (  
  Roll_No NUMBER PRIMARY KEY,  
  Name     VARCHAR2(50)  
);  
  
CREATE TABLE N_RollCall (  
  Roll_No NUMBER PRIMARY KEY,  
  Name     VARCHAR2(50)  
);  
  
-- Sample data  
INSERT INTO O_RollCall VALUES (1, 'Alice'), (2, 'Bob'), (3, 'Charlie');  
INSERT INTO N_RollCall VALUES (2, 'Bob'), (4, 'Diana'), (5, 'Eve');  
COMMIT;
```

PL/SQL Block with Parameterized Cursor

```
DECLARE  
  CURSOR c_new(p_roll NUMBER) IS  
    SELECT Roll_No, Name FROM N_RollCall  
    WHERE Roll_No = p_roll;  
  
  v_roll  N_RollCall.Roll_No%TYPE;  
  v_name  N_RollCall.Name%TYPE;  
  v_count NUMBER;  
BEGIN  
  FOR rec IN (SELECT Roll_No FROM N_RollCall) LOOP  
    OPEN c_new(rec.Roll_No);  
    FETCH c_new INTO v_roll, v_name;  
  
    -- Check if already exists in O_RollCall  
    SELECT COUNT(*) INTO v_count  
    FROM O_RollCall WHERE Roll_No = v_roll;  
  
    IF v_count = 0 THEN  
      INSERT INTO O_RollCall VALUES (v_roll, v_name);  
      DBMS_OUTPUT.PUT_LINE('Inserted: ' || v_roll || ' ' || v_name);  
    ELSE  
      DBMS_OUTPUT.PUT_LINE('Skipped (exists): ' || v_roll);  
    END IF;  
  
    CLOSE c_new;  
  END LOOP;  
  
  COMMIT;  
  DBMS_OUTPUT.PUT_LINE('Merge complete.');
```

EXCEPTION
 WHEN OTHERS THEN
 DBMS_OUTPUT.PUT_LINE('Error: ' || SQLERRM);
END;
/