

Non-Preemptive Shortest Job First CPU Scheduling Algorithm

Completed

Write a C program to implement the Non-Preemptive Shortest Job First (SJF) CPU Scheduling Algorithm. The program should accept the number of processes, their Arrival Times (AT), and Burst Times (BT). At any given time, the process with the minimum burst time among the arrived processes must be executed first. Calculate the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process and find the overall average TAT and WT.

Core Logic

Selection: Out of all processes that have arrived by the current time, the one with the minimum Burst Time is chosen.

Formulae:

- $\text{Turnaround Time (TAT)} = \text{Completion Time (CT)} - \text{Arrival Time (AT)}$
- $\text{Waiting Time (WT)} = \text{Turnaround Time (TAT)} - \text{Burst Time (BT)}$

Input Format

1. The first line of input contains an integer representing the number of processes.
2. The next lines contain two integers for each process, where the first integer denotes the Arrival Time (AT) of the process and the second integer denotes the Burst Time (BT) of the process.

Output Format

The output displays the Average Turnaround Time and the Average Waiting Time.

Select Language : C (GCC 9.2.0)

```
1 #include <stdio.h>
2
3 int main() {
4     int n, i, j;
5
6     printf("Enter number of processes: ");
7     scanf("%d", &n);
8     printf("\n");
9
10    int at[n], bt[n], ct[n], tat[n], wt[n];
11    int completed[n];
12
13    // Initialize completed array
14    for(i = 0; i < n; i++) {
15        completed[i] = 0;
16    }
17
18    // Input
19    for(i = 0; i < n; i++) {
20        printf("Enter Arrival Time and Burst Time for P%d: ", i + 1);
21        scanf("%d %d", &at[i], &bt[i]);
22        printf("\n");
23    }
24
25    int time = 0, done = 0;
26    float total_tat = 0, total_wt = 0;
27
28    while(done < n) {
29        int idx = -1;
30        int min_bt = 100000;
31
32        // Find process with minimum BT among arrived
```

Test Cases 2

Run Sample Cases

Run All Cases

Back To Practice

Save

Non-Preemptive Shortest Job First CPU Scheduling Algorithm

Write a C program to implement the Non-Preemptive Shortest Job First (SJF) CPU Scheduling Algorithm. The program should accept the number of processes, their Arrival Times (AT), and Burst Times (BT). At any given time, the process with the minimum burst time among the arrived processes must be executed first. Calculate the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process and find the overall average TAT and WT.

Core Logic

Selection: Out of all processes that have arrived by the current time, the one with the minimum Burst Time is chosen.

Formulae:

- $\text{Turnaround Time (TAT)} = \text{Completion Time (CT)} - \text{Arrival Time (AT)}$
- $\text{Waiting Time (WT)} = \text{Turnaround Time (TAT)} - \text{Burst Time (BT)}$

Input Format

1. The first line of input contains an integer representing the number of processes.
2. The next lines contain two integers for each process, where the first integer denotes the Arrival Time (AT) of the process and the second integer denotes the Burst Time (BT) of the process.

Output Format

The output displays the Average Turnaround Time and the Average Waiting Time.

Select Language : C (GCC 9.2.0)

```

32 // Find process with minimum BT among arrived
33 for(i = 0; i < n; i++) {
34     if(at[i] <= time && completed[i] == 0) {
35         if(bt[i] < min_bt) {
36             min_bt = bt[i];
37             idx = i;
38         }
39     }
40 }
41
42 // If no process is available
43 if(idx == -1) {
44     time++;
45 } else {
46     time += bt[idx];
47     ct[idx] = time;
48     completed[idx] = 1;
49     done++;
50
51     tat[idx] = ct[idx] - at[idx];
52     wt[idx] = tat[idx] - bt[idx];
53
54     total_tat += tat[idx];
55     total_wt += wt[idx];
56 }
57 }
58
59 printf("\nAverage Turnaround Time = %.2f\n", total_tat / n);
60 printf("Average Waiting Time = %.2f\n", total_wt / n);
61
62 return 0;
63 }
```

Test Cases 2

Run Sample Cases

Run All Cases