

Back To Practice

< Q1 >

Save

First Fit Contiguous Memory Allocation

Write a C program to implement the First Fit contiguous memory allocation technique. The program should take the sizes of various memory blocks and the sizes of processes as input. For each process, search through the memory blocks sequentially and allocate the first block that meets the size requirement. If no such block exists, indicate that the process cannot be allocated. Finally, display the allocation details and calculate internal fragmentation.

Input Format

1. The first line contains an integer m representing the number of memory blocks.
2. The next line contains m integers representing the sizes of each memory block.
3. The next line contains an integer n representing the number of processes.
4. The next line contains n integers representing the sizes of each process.

Output Format

- For each process, the program prints whether the process is allocated or not.
- If allocated, it displays the process number, process size, block number, block size, and the internal fragmentation (block size minus process size).
- If not allocated, it indicates that the process cannot be allocated.

Select Language : C (GCC 9.2.0)

```
1 #include <stdio.h>
2
3 int main()
4 {
5     int m;
6     printf("Enter number of memory blocks:\n");
7     scanf("%d",&m);
8
9     int b[m],o[m];
10    printf("Enter size of each block:\n");
11
12    for(int i=0;i<m;i++){
13        scanf("%d",&b[i]);
14        o[i]=b[i];
15    }
16
17    int n;
18    printf("Enter number of processes:\n");
19    scanf("%d",&n);
20
21    int p[n];
22    printf("Enter size of each process:\n");
23
24    for(int i=0;i<n;i++){
25        scanf("%d",&p[i]);
26    }
27
```

Test Cases 2

Run Sample Cases

Run All Cases

Back To Practice

< Q1 >

Save

First Fit Contiguous Memory Allocation

Write a C program to implement the First Fit contiguous memory allocation technique. The program should take the sizes of various memory blocks and the sizes of processes as input. For each process, search through the memory blocks sequentially and allocate the first block that meets the size requirement. If no such block exists, indicate that the process cannot be allocated. Finally, display the allocation details and calculate internal fragmentation.

Input Format

1. The first line contains an integer m representing the number of memory blocks.
2. The next line contains m integers representing the sizes of each memory block.
3. The next line contains an integer n representing the number of processes.
4. The next line contains n integers representing the sizes of each process.

Output Format

- For each process, the program prints whether the process is allocated or not.
- If allocated, it displays the process number, process size, block number, block size, and the internal fragmentation (block size minus process size).
- If not allocated, it indicates that the process cannot be allocated.

Select Language : C (GCC 9.2.0)

```
18 printf("Enter number of processes:\n");
19 scanf("%d",&n);
20
21 int p[n];
22 printf("Enter size of each process:\n");
23
24 for(int i=0;i<n;i++){
25     scanf("%d",&p[i]);
26 }
27
28 for(int i=0;i<n;i++){
29     int flag=0;
30     for(int j=0;j<m;j++){
31         if(b[j]>=p[i]){
32             int f=b[j]-p[i];
33             printf("Process %d of size %d is allocated to Block %d of size %d with Fragment %d\n",i+1,p[i],j+1,o[j],f);
34             b[j]=b[j]-p[i];
35             flag=1;
36             break;
37         }
38     }
39     if(flag==0){
40         printf("Process %d of size %d is not allocated\n",i+1,p[i]);
41     }
42 }
43 return 0;
44 }
```

Test Cases 2

Run Sample Cases

Run All Cases