

# Group B Deep Learning

## Assignment No: 2B

**Title of the Assignment:** Multiclass classification using Deep Neural Networks: Example: Use the OCR letter recognition dataset <https://archive.ics.uci.edu/ml/datasets/letter+recognition>

**Objective of the Assignment:** Students should be able to solve Multiclass classification using Deep Neural Networks

Prerequisite:

1. Basic of programming language
  2. Concept of Multi Classification
  3. Concept of Deep Neural Network
- 

### Contents for Theory:

1. What is Multi-Classification
  2. Example of Multi-Classification
  3. How Deep Neural Network Work on Multi-Classification
  4. Code Explanation with Output
- 

### What is multiclass classification ?

Multi Classification, also known as multiclass classification or multiclass classification problem, is a type of classification problem where the goal is to assign input data to one of three or more classes or categories. In other words, instead of binary classification, where the goal is to assign input data to one of two classes (e.g., positive or negative), multiclass classification involves assigning input data to one of several possible classes or categories (e.g., animal species, types of products, etc.).

In multiclass classification, each input sample is associated with a single class label, and the goal of the model is to learn a function that can accurately predict the correct class label for new, unseen input data. Multiclass classification can be approached using a variety of machine learning algorithms, including decision trees, support vector machines, and deep neural networks.

Some examples of multiclass classification problems include image classification, where the goal is to

classify images into one of several categories (e.g., animals, vehicles, buildings), and text classification, where the goal is to classify text documents into one of several categories (e.g., news topics, sentiment analysis).

### **Example of multiclass classification-**

Here are a few examples of multiclass classification problems:

**Image classification:** The goal is to classify images into one of several categories. For example, an image classification model might be trained to classify images of animals into categories such as cats, dogs, and birds.

**Text classification:** The goal is to classify text documents into one of several categories. For example, a text classification model might be trained to classify news articles into categories such as politics, sports, and entertainment.

**Disease diagnosis:** The goal is to diagnose patients with one of several diseases based on their symptoms and medical history. For example, a disease diagnosis model might be trained to classify patients into categories such as diabetes, cancer, and heart disease.

**Speech recognition:** The goal is to transcribe spoken words into text. A speech recognition model might be trained to recognize spoken words in several languages or dialects.

**Credit risk analysis:** The goal is to classify loan applicants into categories such as low risk, medium risk, and high risk. A credit risk analysis model might be trained to classify loan applicants based on their credit score, income, and other factors.

In all of these examples, the goal is to assign input data to one of several possible classes or categories. Multiclass classification is a common task in machine learning and can be approached using a variety of algorithms, including decision trees, support vector machines, and deep neural networks.

### **Source Code and Output**

```
import numpy as np
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense, Dropout
from tensorflow.keras.optimizers import RMSprop
from tensorflow.keras.datasets import mnist
import matplotlib.pyplot as plt
from sklearn import metrics
# Load the OCR dataset

# The MNIST dataset is a built-in dataset provided by Keras.
# It consists of 70,000 28x28 grayscale images, each of which displays a single handwritten digit from 0 to 9.
```

# The training set consists of 60,000 images, while the test set has 10,000 images.

```
(x_train, y_train), (x_test, y_test) = mnist.load_data()
```

# X\_train and X\_test are our array of images while y\_train and y\_test are our array of labels for each image.

# The first tuple contains the training set features (X\_train) and the training set labels (y\_train).

# The second tuple contains the testing set features (X\_test) and the testing set labels (y\_test).

# For example, if the image shows a handwritten 7, then the label will be the integer 7.

```
plt.imshow(x_train[0], cmap='gray') # imshow() function which simply displays an image.
```

```
plt.show() # cmap is responsible for mapping a specific colormap to the values found in the array that  
you passed as the first argument.
```

# This is because of the format that all the images in the dataset have:

# 1. All the images are grayscale, meaning they only contain black, white and grey.

# 2. The images are 28 pixels by 28 pixels in size (28x28).

```
print(x_train[0])
```

# image data is just an array of digits. You can almost make out a 5 from the pattern of the digits in the array.

# Array of 28 values

# a grayscale pixel is stored as a digit between 0 and 255 where 0 is black, 255 is white and values in between are different shades of gray.

# Therefore, each value in the [28][28] array tells the computer which color to put in that position when.



# reformat our X\_train array and our X\_test array because they do not have the correct shape.

# Reshape the data to fit the model

```
print("X_train shape", x_train.shape)
```

```
print("y_train shape", y_train.shape)
```

```
print("X_test shape", x_test.shape)
```

```
print("y_test shape", y_test.shape)
```

# Here you can see that for the training sets we have 60,000 elements and the testing sets have 10,000 elements.

# y\_train and y\_test only have 1 dimensional shapes because they are just the labels of each element.

# x\_train and x\_test have 3 dimensional shapes because they have a width and height (28x28 pixels) for each element.

# (60000, 28, 28) 1st parameter in the tuple shows us how much image we have 2nd and 3rd parameters are the pixel values from x to y (28x28)

# The pixel value varies between 0 to 255.

# (60000,) Training labels with integers from 0-9 with dtype of uint8. It has the shape (60000,).

```

# (10000, 28, 28) Testing data that consists of grayscale images. It has the shape (10000, 28, 28) and the
dtype of uint8. The pixel value varies between 0 to 255.
# (10000,) Testing labels that consist of integers from 0-9 with dtype uint8. It has the shape (10000,).
X_train shape (60000, 28, 28)
y_train shape (60000,)
X_test shape (10000, 28, 28)
y_test shape (10000,)
# X: Training data of shape (n_samples, n_features)
# y: Training label values of shape (n_samples, n_labels)
# 2D array of height and width, 28 pixels by 28 pixels will just become 784 pixels (28 squared).
# Remember that X_train has 60,000 elements, each with 784 total pixels so will become shape (60000,
784).
# Whereas X_test has 10,000 elements, each with each with 784 total pixels so will become shape
(10000, 784).
x_train = x_train.reshape(60000, 784)
x_test = x_test.reshape(10000, 784)
x_train = x_train.astype('float32') # use 32-bit precision when training a neural network, so at one point
the training data will have to be converted to 32 bit floats. Since the dataset fits easily in RAM, we might
as well convert to float immediately.
x_test = x_test.astype('float32')
x_train /= 255 # Each image has Intensity from 0 to 255
x_test /= 255

# Regarding the division by 255, this is the maximum value of a byte (the input feature's type before the
conversion to float32),
# so this will ensure that the input features are scaled between 0.0 and 1.0.
# Convert class vectors to binary class matrices
num_classes = 10
y_train = np.eye(num_classes)[y_train] # Return a 2-D array with ones on the diagonal and zeros
elsewhere.
y_test = np.eye(num_classes)[y_test] # f your particular categories is present then it mark as 1 else 0 in
remain row
# Define the model architecture
model = Sequential()
model.add(Dense(512, activation='relu', input_shape=(784,))) # Input consist of 784 Neuron ie 784 input,
512 in the hidden layer
model.add(Dropout(0.2)) # DROP OUT RATIO 20%

```

```

model.add(Dense(512, activation='relu')) #returns a sequence of another vectors of dimension 512
model.add(Dropout(0.2))
model.add(Dense(num_classes, activation='softmax')) # 10 neurons ie output node in the output layer.
# Compile the model
model.compile(loss='categorical_crossentropy', # for a multi-class classification problem
              optimizer=RMSprop(),
              metrics=['accuracy'])
# Train the model
batch_size = 128 # batch_size argument is passed to the layer to define a batch size for the inputs.
epochs = 20
history = model.fit(x_train, y_train,
                   batch_size=batch_size,
                   epochs=epochs,
                   verbose=1, # verbose=1 will show you an animated progress bar eg. [=====]
                   validation_data=(x_test, y_test)) # Using validation_data means you are providing the
training set and validation set yourself,
# 60000image/128=469 batch each
# Evaluate the model
score = model.evaluate(x_test, y_test, verbose=0)
print('Test loss:', score[0])
print('Test accuracy:', score[1])
Test loss: 0.08541901409626007
Test accuracy: 0.9851999878883362

```

**Conclusion-** In this way we can do Multi classification using DNN.

### Assignment Question

1. What is Batch Size?
2. What is Dropout?
3. What is RMSprop?
4. What is the Softmax Function?
5. What is the Relu Function?

**Conclusion-** In this way we can Classify the Movie Reviews by using DNN.

**Assignment Question**

1. What is Batch Size?
2. What is Dropout?
3. What is RMSprop?
4. What is the Softmax Function?
5. What is the Relu Function?