

Tracking Realizable Trajectories via Incremental Exponential Stability

Aditya Gahlawat

Contents

1	Nonlinear System	1
2	Reference Trajectory and Feedback–Feedforward Structure	2
3	General use in \mathcal{L}_1-DRAC	2
4	Error Dynamics	2
4.1	Interpretation	2
5	Special Case: Linear Time-Invariant (LTI) Systems	3
5.1	LTI Plant	3
5.2	Reference Trajectory and Feedback–Feedforward Structure	3
5.3	Error Dynamics	3
5.4	Interpretation (LTI)	3

1 Nonlinear System

Consider the control-affine system

$$\dot{x} = f_{ol}(x) + Gu.$$

Assume a state-feedback controller

$$u = k(x),$$

and define the closed-loop vector field

$$f_{cl}(x) := f_{ol}(x) + Gk(x).$$

Assumption 1 (Incremental Exponential Stability). *The system*

$$\dot{z} = f_{cl}(z)$$

*is **incrementally exponentially stable (IES)**, i.e., there exist constants $c \geq 1$ and $\lambda > 0$ such that for any two solutions $z_1(t)$, $z_2(t)$,*

$$\|z_1(t) - z_2(t)\| \leq ce^{-\lambda t} \|z_1(0) - z_2(0)\|.$$

2 Reference Trajectory and Feedback–Feedforward Structure

Let $x^*(t)$ be a realizable reference trajectory generated by

$$\dot{x}^* = f_{ol}(x^*) + Gu^*.$$

Add and subtract $k(x^*)$:

$$\dot{x}^* = f_{cl}(x^*) + G(u^* - k(x^*)).$$

Defining

$$v^* := u^* - k(x^*),$$

the reference input admits a **feedback + feedforward decomposition**. We can thus use the following **feedback + feedforward control law** for the actual system:

$$u = k(x) + v^*,$$

where v^* is the **feedforward term induced by the reference trajectory** (x^*, u^*) as defined above.

This yields the closed-loop dynamics

$$\dot{x} = f_{cl}(x) + Gv^*, \quad \dot{x}^* = f_{cl}(x^*) + Gv^*.$$

3 General use in \mathcal{L}_1 -DRAC

As in the manuscript, we define

$$f(t, x) := f_{cl}(x) + Gv^*(t) = f_{ol}(x) + G(k(x) + u^*(t) - k(x^*(t))). \quad (1)$$

For our use case, we need to find Δ_f such that

4 Error Dynamics

Define the tracking error

$$e := x - x^*.$$

Then

$$\dot{e} = f_{cl}(x) - f_{cl}(x^*) = f_{cl}(x^* + e) - f_{cl}(x^*).$$

4.1 Interpretation

Since $x(t)$ and $x^*(t)$ satisfy the **same system**

$$\dot{z} = f_{cl}(z) + Gv^*(t),$$

and $\dot{z} = f_{cl}(z)$ is incrementally exponentially stable, the error dynamics represent the distance between two trajectories of an IES system.

5 Special Case: Linear Time-Invariant (LTI) Systems

5.1 LTI Plant

Consider the LTI system

$$\dot{x} = Ax + Bu,$$

with linear state-feedback

$$u = Kx,$$

and assume

$$A + BK \text{ is Hurwitz.}$$

Define

$$f_{cl}(x) := (A + BK)x.$$

5.2 Reference Trajectory and Feedback–Feedforward Structure

Let the reference trajectory satisfy

$$\dot{x}^* = Ax^* + Bu^*.$$

Defining

$$v^* := u^* - Kx^*,$$

the reference input admits a **feedback + feedforward decomposition**.

We can thus use the following **feedback + feedforward control law** for the actual system:

$$u = Kx + v^*,$$

where v^* is the **feedforward term induced by the reference trajectory** (x^*, u^*) .

This yields

$$\dot{x} = (A + BK)x + Bv^*, \quad \dot{x}^* = (A + BK)x^* + Bv^*.$$

5.3 Error Dynamics

Define $e := x - x^*$. Then

$$\dot{e} = (A + BK)e.$$

5.4 Interpretation (LTI)

Since $A + BK$ is Hurwitz, the system is incrementally exponentially stable, and the tracking error satisfies

$$\|e(t)\| \leq ce^{-\lambda t} \|e(0)\|,$$

for some $c \geq 1$, $\lambda > 0$, independent of the reference input u^* .

References

[1] Placeholder.