

Project Configuration Report

wifi_embedded_mqtt_client_soc

Target Device:

Target Part: SIWG917M111MGTBA

Boards:

- SIWG917 Dev Kit Board (BRD2605A Rev A02)

Target SDK

Simplicity SDK Suite v2026.6.0: Bluetooth 11.1.0, Bluetooth Mesh SDK 11.0.0, Connect SDK 4.3.0.0, EmberZNet 9.1.0.0, Multiprotocol 1.1.0.0, OpenThread 3.1.0.0 (GitHub-fb274efe6), Peripheral Examples Simplicity SDK\2.1.0, RAIL SDK 3.1.0.0, Sidewalk 2.9.0, Silicon Labs AI/ML SDK 3.0.0, Silicon Labs Matter 2.9.0-1.6, Wi-Fi SDK 4.1.0-rc.40, Z-Wave SDK 8.1.0.0
SDK Version: 2026.6.0

Project Generators

- VS Code (GCC)

Installed Software Components:

- Board

- Radio Board

- BRD2605A**

- Configurable: false

- Common

- WiSeConnect Common Library**

- Sources: sl_utility.c

- Configurable: false

- Device

- Si91x

- MCU

- Common

- System Calls**

- Sources: syscalls.c

- Configurable: false

- Device Part

- SIWG917

- SIWG917M111MGTBA**

- Sources: system_si91x.c, startup_si91x.c

- Configurable: false

- Service

- IO Stream**

- Sources: sl_iostream_uart_si91x.c

- Configurable: true

- Configs: sl_iostream_uart_vcom_config.h

- SL Log Core**

- Sources: sl_log_platform_specific.c

- Configurable: false

- Log

- Log Backend I/O Stream – Formatted Output**

- Sources: sl_log_iostream_recommends.c

- Configurable: true

- Configs: sl_log_common_config.h

- Memory Configuration

- Default RAM Memory Configuration**

- Configurable: false

- Wireless

- Network Stack

- Offload Network Stack**

- Sources: sl_si91x_http_client_callback_framework.c,
sl_si91x_net_internal_stack.c, sl_net_ping.c

- Configurable: false

- Protocol

- Wi-Fi**

- Sources: sl_wifi_callback_framework.c, sl_wifi.c, sli_wifi_callback_framework.c

- Configurable: false

- RTOS

- FreeRTOS**

- FreeRTOS Heap 4**

- Sources: heap_4.c

- Configurable: false

- FreeRTOS Kernel**

- Sources: event_groups.c, timers.c, list.c, queue.c, stream_buffer.c, tasks.c, croutine.c

- Configurable: true

- Configs: FreeRTOSConfig.h

- Resources

- WiSeConnect Resources**

- Configurable: true

- Configs: sl_net_default_values.h, lwipopts.h, sl_wifi_region_db_config.h, aws_iot_config.h

- Service

- MQTT Client**

- Sources: sl_mqtt_client.c

- Configurable: false

- Services

- IO Stream

- Driver

- IO Stream: Si91x UART**

- Configurable: false

- Log

- Log None**

- Sources: sl_log_weak.c

- Configurable: true

- Configs: sl_log_common_config.h

- System Setup

- System Setup (sl_main)**

- Configurable: true

- Configs: sl_main_start_task_config.h

- Service

- Network Management

- Network Manager**

- Sources: sli_net_common_utility.c, sl_net_for_siwx3xx_lwip.c, sl_net_for_dual_stack.c, sl_net_for_lwip.c, sl_net_basic_certificate_store.c, sl_net.c

- Configurable: false

- Configuration

- Basic Network Configuration Manager**

- Sources: sli_net_credentials.c, sl_net_basic_profiles.c, sl_net_credentials.c

- Configurable: false

Pins:

Peripherals:

Peripheral	Software Component	Custom Peripheral Name
I2C0		
I2C1		
ULP_I2C		
USART0	USART	

UART1		
QEI		
OPAMP1		
OPAMP2		
OPAMP3		
ULP_UART	IO Stream	
SSI_MASTER		
SSI_SLAVE		
HSPI_SECONDARY		
ULP_SSI		
GSPI_MASTER		
I2S0		
ULP_I2S		
SCT		
PWM_CH0		
PWM_CH1		
PWM_CH2		
PWM_CH3		
PWM		
SDC_CH1		
SDC_CH2		
SDC_CH3		
SDC_CH4		
ADC_CH1		
ADC_CH2		
ADC_CH3		
ADC_CH4		
ADC_CH5		
ADC_CH6		
ADC_CH7		
ADC_CH8		
ADC_CH9		
ADC_CH10		
ADC_CH11		
ADC_CH12		
ADC_CH13		
ADC_CH14		
ADC_CH15		
ADC_CH16		
COMP1		
COMP2		
DAC0		
DAC1		
SYSRTC		
UULP_VBAT_GPIO		
SDIO		
GPIO		
MCU_CLK_OUT		