





Parabolic Reflector

Phase Center



Parabolic Reflector Antenna



Place Focus on the phase
Center of the feed horn.


$$z = \frac{\rho^2}{4f} \quad x = \rho \cos \phi$$
$$y = \rho \sin \phi$$

Physical Aperture : $A_p = \frac{\pi D^2}{4}$


Effective Aperture : $A_e = \frac{\lambda^2 G}{4\pi}$

Aperture efficiency: $\eta = \frac{A_e}{A_p}$

$$G = \frac{4\pi A_e}{\lambda^2} = \eta \left(\frac{4\pi A_p}{\lambda^2} \right)$$



$$\Rightarrow G = \frac{4\pi A_p}{\lambda^2}$$




$$\eta = \eta_{\text{illum}} \cdot \eta_{\text{spill}} \cdot \eta_{\text{phase}} \cdot \eta_{\text{pol}} \cdot \eta_{\text{block}} \cdot \eta_{\text{surface}}$$

Edge taper: Power at edge vs. center of reflector.

-3dB, -6dB, -10dB ...

taper high! $\Rightarrow \eta_{\text{spill}} \downarrow$ but $\eta_{\text{illum}} \uparrow$




$\eta \approx 0.55$ when taper = -10dB \rightarrow typical optimum.


Design Example

$$\theta_{-10dB} = 80^\circ$$

$$G = 40dB.$$



$\frac{f}{D}$ ratio



$$\tan\left(\frac{\theta_{-10dB}}{2}\right) = \frac{D}{2f}$$

$$\Rightarrow \frac{f}{D} \approx 0.596$$

$$\frac{G}{\eta} = \frac{4\pi}{\lambda^2} \cdot \frac{\pi D^2}{4} = \left(\frac{\pi D}{\lambda}\right)^2 \Rightarrow \boxed{D = \frac{\lambda}{\pi} \sqrt{\frac{G}{\eta}}}$$

$$\frac{D}{\lambda} = \frac{1}{\pi} \sqrt{\frac{10^4}{0.55}} = 42.9$$

$$@ 10 \text{ GHz} : \lambda = 3 \times 10^{-2} \Rightarrow$$

$$\boxed{\begin{aligned} D &= 1.29 \text{ m} \\ f &= 0.77 \text{ m} \end{aligned}}$$