Module 4

Network Layer

Module 4: outline

4.1 Introduction

4.2 Virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol
- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms
- link state
- distance vector

4.6 routing in the Internet
- RIP
- OSPF
- BGP

Network layer

- transport segment from sending to receiving host
- on sending side encapsulates segments into datagrams
- on receiving side, delivers segments to transport layer
- network layer protocols in *every* host, router
- router examines header fields in all IP datagrams passing through it



Two key network-layer functions

- *forwarding:* move packets from router's input to appropriate router output
- *routing:* determine route taken by packets from source to dest.
  - *routing algorithms*

forwarding

routing

Interplay between routing and forwarding



Connection setup

- 3rd important function in *some* network architectures:
  - ATM, frame relay, X.25
- before datagrams flow, two end hosts *and* intervening routers establish virtual connection
  - routers get involved
- network vs transport layer connection service:
  - *network:* between two hosts (may also involve intervening routers in case of VCs)
  - *transport:* between two processes

Network service model

Q: What *service model* for "channel" transporting datagrams from sender to receiver?

example services for individual datagrams:

- guaranteed delivery
- guaranteed delivery with (bounded)delay

example services for a flow of datagrams:

- in-order datagram delivery
- guaranteed minimum bandwidth to flow.
- Guaranteed maximum jitter
- Security services

specific services that could be provided by the network layer

Network layer service models:

Network Architecture	Service Model	Bandwidth Guarantee	No-Loss Guarantee	Ordering	Timing	Congestion Indication
Internet	Best Effort	None	None	Any order possible	Not maintained	None
ATM	CBR	Guaranteed constant rate	Yes	In order	Maintained	Congestion will not occur
ATM	ABR	Guaranteed minimum	None	In order	Not maintained	Congestion indication provided

Chapter 4: outline

Connection, connection-less service

- *datagram* network provides network-layer *connectionless* service
- *virtual-circuit* network provides network-layer *connection* service
- analogy to TCP/UDP connecton-oriented / connectionless transport-layer services, but:
  - *service:* host-to-host
  - *no choice:* network provides one or the other
  - *implementation:* in network core

Virtual circuits

"source-to-dest path behaves much like telephone circuit"
- performance-wise
- network actions along source-to-dest path

- call setup, teardown for each call *before* data can flow
- each packet carries VC identifier (not destination host address)
- *every* router on source-dest path maintains "state" for each passing connection
- link, router resources (bandwidth, buffers) may be *allocated* to VC (dedicated resources = predictable service)

VC implementation

a VC consists of:

1. *path* from source to destination
2. *VC numbers*, one number for each link along path
3. *entries in forwarding tables* in routers along path

- packet belonging to VC carries VC number (rather than dest address)
- VC number can be changed on each link.
  - new VC number comes from forwarding table

VC forwarding table



forwarding table in northwest router:

Incoming interface	Incoming VC #	Outgoing interface	Outgoing VC #
1	12	3	22
2	63	1	18
3	7	2	17
1	97	3	87
…	…	…	…

VC routers maintain connection state information!

Virtual circuits

- signaling protocols used to setup, maintain teardown VC
- used in ATM, frame-relay, X.25
- not used in today's Internet

Virtual-circuit setup



Datagram networks

- no call setup at network layer
- routers: no state about end-to-end connections
  - no network-level concept of "connection"
- packets forwarded using destination host address



Datagram forwarding table

4 billion IP addresses, so rather than list individual destination address
list *range* of addresses
(aggregate table entries)



Figure 4.3: A connectionless packet-switched network



Figure 4.4: *Forwarding process in a router when used in a connectionless network*



Consider the network below.

a. Suppose that this network is a datagram network. Show the forwarding table in router A, such that all traffic destined to host H3 is forwarded through interface 3.

b. Suppose that this network is a datagram network. Can you write down a forwarding table in router A, such that all traffic from H1 destined to host H3 is forwarded through interface 3, while all traffic from H2 destined to host H3 is forwarded through interface 4? (Hint: this is a trick question.)

c. Now suppose that this network is a virtual circuit network and that there is one ongoing call between H1 and H3, and another ongoing call between H2 and H3. Write down a forwarding table in router A, such that all traffic from H1 destined to host H3 is forwarded through interface 3, while all traffic from H2 destined to host H3 is forwarded through interface 4.

d. Assuming the same scenario as (c), write down the forwarding tables in nodes B, C, and D.



Suppose there are three routers between a source host and a destination host. Ignoring fragmentation, an IP datagram sent from the source host to the destination host will travel over how many interfaces? How many forwarding tables will be indexed to move the datagram from the source to the destination?

Datagram forwarding table

Destination Address Range	Link Interface
11001000 00010111 00010000 00000000 through **11001000 00010111 00010111 11111111**	0
11001000 00010111 00011000 00000000 through **11001000 00010111 00011000 11111111**	1
11001000 00010111 00011001 00000000 through **11001000 00010111 00011111 11111111**	2
otherwise	3

Q: but what happens if ranges don't divide up so nicely?

Destination Address Range	Interface
200.23.16.0 – 200.23.23.255	0
200.23.24.0 – 200.23.24.255	1
200.23.25.0 – 200.23.31.255	2
Otherwise	3

Longest prefix matching

longest prefix matching

when looking for forwarding table entry for given destination address, use *longest* address prefix that matches destination address.

Destination Address Range	Link interface
11001000 00010111 00010*** *********	0
11001000 00010111 00011000 *********	1
11001000 00010111 00011*** *********	2
otherwise	3

examples:

DA: 11001000 00010111 00010110 10100001 which interface?

DA: 11001000 00010111 00011000 10101010 which interface?

Consider a datagram network using 8-bit host addresses.
Suppose a router uses longest-prefix matching, and has the following forwarding table:

Prefix Match	Interface
00	1
10	2
001	3
101	4
110	5
otherwise	6

1. Suppose a datagram arrives at the router, with destination address 00000110. To which interface will this datagram be forwarded using longest-prefix matching?

2. Suppose a datagram arrives at the router, with destination address 10010000. To which interface will this datagram be forwarded using longest-prefix matching?

3. Suppose a datagram arrives at the router, with destination address 00010111. To which interface will this datagram be forwarded using longest-prefix matching?

Consider a datagram network using 8-bit host addresses.
Suppose a router uses longest-prefix matching, and has the following forwarding table:

Prefix Match	Interface
00	1
10	2
001	3
101	4
111	5
otherwise	6

1. Suppose a datagram arrives at the router, with destination address 11011101. To which interface will this datagram be forwarded using longest-prefix matching?

2. Suppose a datagram arrives at the router, with destination address 01011100. To which interface will this datagram be forwarded using longest-prefix matching?

3. Suppose a datagram arrives at the router, with destination address 01001011. To which interface will this datagram be forwarded using longest-prefix matching?

Consider a datagram network using 32-bit host addresses. Suppose a router has four links, numbered 0 through 3, and packets are to be forwarded to the link interfaces as follows:

Destination Address Range	Link Interface
11100000 00000000 00000000 00000000 through 11100000 00111111 11111111 11111111	0
11100000 01000000 00000000 00000000 through 11100000 01000000 11111111 11111111	1
11100000 01000001 00000000 00000000 through 11100001 01111111 11111111 11111111	2
otherwise	3

Provide a forwarding table that uses longest prefix matching, and forwards packets to the correct link interfaces.

Describe how your forwarding table determines the appropriate link interface for datagrams with destination addresses:

11001000 10010001 01010001 01010101

11100001 01000000 11000011 00111100

11100001 10000000 00010001 01110111

Consider a datagram network using 8-bit host addresses. Suppose a router uses longest prefix matching and has the following forwarding table:

Prefix Match	Interface
00	0
010	1
011	2
10	2
11	3

For each of the four interfaces, give the associated range of destination host addresses and the number of addresses in the range.

Destination Address Range	Link Interface
00000000 – 00111111	0
01000000 – 01011111	1
01100000 – 01111111	2
10000000 – 10111111	2
11000000 – 11111111	3

number of addresses for interface 0 = 2pow6 =64
number of addresses for interface 1 = 2pow5 =32
number of addresses for interface 2 = 2pow5 +2pow6 =32+64 =96
number of addresses for interface 3 = 2pow6 =64

Datagram or VC network: why?

Internet (datagram)

- data exchange among computers
  - "elastic" service, no strict timing req.
- many link types
  - different characteristics
  - uniform service difficult
- "smart" end systems (computers)
  - can adapt, perform control, error recovery
  - ***simple inside network, complexity at "edge"***

ATM (VC)

- evolved from telephony
- human conversation:
  - strict timing, reliability requirements
  - need for guaranteed service
- "dumb" end systems
  - telephones
  - ***complexity inside network***

Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol
- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms
- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet
- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

Router architecture overview

two key router functions:

- run routing algorithms/protocol (RIP, OSPF, BGP)
- *forwarding* datagrams from incoming to outgoing link



Input port functions



physical layer:
bit-level reception

data link layer:
e.g., Ethernet
see chapter 5

decentralized switching:

- given datagram dest., lookup output port using forwarding table in input port memory *("match plus action")*
- goal: complete input port processing at 'line speed'
- queuing: if datagrams arrive faster than forwarding rate into switch fabric

Switching fabrics

- transfer packet from input buffer to appropriate output buffer
- switching rate: rate at which packets can be transfer from inputs to outputs
  - often measured as multiple of input/output line rate
  - N inputs: switching rate N times line rate desirable
- three types of switching fabrics



Switching via memory

first generation routers:

- traditional computers with switching under direct control of CPU
- packet copied to system's memory
- speed limited by memory bandwidth (2 bus crossings per datagram)



Switching via a bus

- datagram from input port memory to output port memory via a shared bus
- *bus contention:* switching speed limited by bus bandwidth
- 32 Gbps bus, Cisco 5600: sufficient speed for access and enterprise routers



bus

Switching via interconnection network

- overcome bus bandwidth limitations
- banyan networks, crossbar, other interconnection nets initially developed to connect processors in multiprocessor
- advanced design: fragmenting datagram into fixed length cells, switch cells through the fabric.
- Cisco 12000: switches 60 Gbps through the interconnection network



Output ports

This slide in HUGELY important!



- *buffering* required w
  fabric faster than the

Datagram (packets) can be lost due to congestion, lack of buffers

- *scheduling discipline* chooses among queued datagrams for transmission

Priority scheduling – who gets best performance, network neutrality

Output port queueing



- buffering when arrival rate via switch exceeds output line speed
- *queueing (delay) and loss due to output port buffer overflow!*

How much buffering?

- RFC 3439 rule of thumb: average buffering equal to "typical" RTT (say 250 msec) times link capacity C
  - e.g., C = 10 Gbps link: 2.5 Gbit buffer
- recent recommendation: with *N* flows, buffering equal to

$$\frac{\mathrm{RTT} \cdot \mathrm{C}}{\sqrt{\mathrm{N}}}$$

Input port queuing

- fabric slower than input ports combined -> queueing may occur at input queues
  - *queueing delay and loss due to input buffer overflow!*
- Head-of-the-Line (HOL) blocking: queued datagram at front of queue prevents others in queue from moving forward



output port contention:
only one red datagram can
be transferred.
lower red packet is blocked



one packet time
later: green packet
experiences HOL
blocking

Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol
- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms
- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet
- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

The Internet network layer

host, router network layer functions:



IP datagram format



how much overhead?

- 20 bytes of TCP
- 20 bytes of IP
- = 40 bytes + app layer overhead

IP fragmentation, reassembly

- network links have MTU (max.transfer size) - largest possible link-level frame
  - different link types, different MTUs
- large IP datagram divided ("fragmented") within net
  - one datagram becomes several datagrams
  - "reassembled" only at final destination
  - IP header bits used to identify, order related fragments



***IP fragmentation, reassembly

example:

- 4000 byte datagram
- MTU = 1500 bytes



1480 bytes in data field

offset = 1480/8

Fragment	Bytes	ID	Offset	Flag
1st fragment	1,480 bytes in the data field of the IP datagram	identification = 777	offset = 0 (meaning the data should be inserted beginning at byte 0)	flag = 1 (meaning there is more)
2nd fragment	1,480 bytes of data	identification = 777	offset = 185 (meaning the data should be inserted beginning at byte 1,480. Note that 185 · 8 = 1,480)	flag = 1 (meaning there is more)
3rd fragment	1,020 bytes (= 3,980–1,480–1,480) of data	identification = 777	offset = 370 (meaning the data should be inserted beginning at byte 2,960. Note that 370 · 8 = 2,960)	flag = 0 (meaning this is the last fragment)

An IP packet of size 1600 bytes passes through network segment before it reaches its destination. The header size of this packet is 30 bytes. The maximum size of an IP packet in intermediate network (MTU) is 1400 bytes. How the IP packet would be fragmented in a router. Find all the information for each fragments.

- Original packet = **1600 B** → data = **1600 − 30 = 1570 B**
- MTU = **1400 B** → max **payload per fragment = 1400 − 30 = 1370 B**
- Fragment offset is in **8-byte units** ⇒ all but the last fragment's data must be a multiple of 8.

Choose payloads

- First fragment payload = largest ≤ 1370 that's multiple of 8 ⇒ **1368 B** (8×171)
- Remaining data = **1570 − 1368 = 202 B** (last fragment can be non-multiple of 8)

Fragment details

Frag	Total Length (B)	Header (B)	Data (B)	MF	Offset (8-byte units)	Byte range in original data
1	**1398**	30	1368	1	**0**	0–1367
2	**232**	30	202	0	**171** (1368/8)	1368–1569

Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol
- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms
- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet
- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

IP addressing: introduction

- *IP address:* 32-bit identifier for host, router *interface*
- *interface:* connection between host/router and physical link
  - router's typically have multiple interfaces
  - host typically has one or two interfaces (e.g., wired Ethernet, wireless 802.11)
- *IP addresses associated with each interface*



$$223.1.1.1 = \underbrace{11011111}_{223}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}$$

IP addressing: introduction

Q: how are interfaces actually connected?

A: we'll learn about that in chapter 5, 6.



A: wired Ethernet interfaces connected by Ethernet switches

A: wireless WiFi interfaces connected by WiFi base station

For now: don't need to worry about how one interface is connected to another (with no intervening router)

Subnets

- IP address:
  - subnet part - high order bits
  - host part - low order bits
- *what's a subnet ?*
  - device interfaces with same subnet part of IP address
  - can physically reach each other *without intervening router*



network consisting of 3 subnets

Subnets

recipe

- to determine the subnets, detach each interface from its host or router, creating islands of isolated networks
- each isolated network is called a *subnet*



subnet mask: /24

Subnets

how many?



IP addressing: CIDR

CIDR: Classless InterDomain Routing

- subnet portion of address of arbitrary length
- address format: a.b.c.d/x, where x is # bits in subnet portion of address

subnet part | host part

11001000 00010111 00010000 00000000

200.23.16.0/23

IP addresses: how to get one?

Q: How does a *host* get IP address?

- hard-coded by system admin in a file
  - Windows: control-panel->network->configuration->tcp/ip->properties
  - UNIX: /etc/rc.config
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
  - "plug-and-play"

DHCP: Dynamic Host Configuration Protocol

goal: allow host to *dynamically* obtain its IP address from network server when it joins network

- can renew its lease on address in use
- allows reuse of addresses (only hold address while connected/“on”)
- support for mobile users who want to join network (more shortly)

DHCP overview:

- host broadcasts “DHCP discover” msg [optional]
- DHCP server responds with “DHCP offer” msg [optional]
- host requests IP address: “DHCP request” msg
- DHCP server sends address: “DHCP ack” msg

DHCP client-server scenario



DHCP client-server scenario



DHCP: more than IP addresses

DHCP can return more than just allocated IP address on subnet:

- address of first-hop router for client
- name and IP address of DNS sever
- network mask (indicating network versus host portion of address)

DHCP: example



- connecting laptop needs its IP address, addr of first-hop router, addr of DNS server: use DHCP
- DHCP request encapsulated in UDP, encapsulated in IP, encapsulated in 802.1 Ethernet
- Ethernet frame broadcast (dest: FFFFFFFFFFFF) on LAN, received at router running DHCP server
- Ethernet demuxed to IP demuxed, UDP demuxed to DHCP

DHCP: example



router with DHCP server built into router

- DCP server formulates DHCP ACK containing client's IP address, IP address of first-hop router for client, name & IP address of DNS server
- encapsulation of DHCP server, frame forwarded to client, demuxing up to DHCP at client
- client now knows its IP address, name and IP address of DSN server, IP address of its first-hop router

DHCP: Wireshark output (home LAN)

request

Message type: **Boot Request (1)**
Hardware type: Ethernet
Hardware address length: 6
Hops: 0
Transaction ID: 0x6b3a11b7
Seconds elapsed: 0
Bootp flags: 0x0000 (Unicast)
Client IP address: 0.0.0.0 (0.0.0.0)
Your (client) IP address: 0.0.0.0 (0.0.0.0)
Next server IP address: 0.0.0.0 (0.0.0.0)
Relay agent IP address: 0.0.0.0 (0.0.0.0)
Client MAC address: Wistron_23:68:8a (00:16:d3:23:68:8a)
Server host name not given
Boot file name not given
Magic cookie: (OK)
Option: (t=53,l=1) **DHCP Message Type = DHCP Request**
Option: (61) Client identifier
  Length: 7; Value: 010016D323688A;
  Hardware type: Ethernet
  Client MAC address: Wistron_23:68:8a (00:16:d3:23:68:8a)
Option: (t=50,l=4) Requested IP Address = 192.168.1.101
Option: (t=12,l=5) Host Name = "nomad"
Option: (55) Parameter Request List
  Length: 11; Value: 010F03062C2E2F1F21F92B
  1 = Subnet Mask; 15 = Domain Name
  3 = Router; 6 = Domain Name Server
  44 = NetBIOS over TCP/IP Name Server
  ……

reply

Message type: **Boot Reply (2)**
Hardware type: Ethernet
Hardware address length: 6
Hops: 0
Transaction ID: 0x6b3a11b7
Seconds elapsed: 0
Bootp flags: 0x0000 (Unicast)
Client IP address: 192.168.1.101 (192.168.1.101)
Your (client) IP address: 0.0.0.0 (0.0.0.0)
Next server IP address: 192.168.1.1 (192.168.1.1)
Relay agent IP address: 0.0.0.0 (0.0.0.0)
Client MAC address: Wistron_23:68:8a (00:16:d3:23:68:8a)
Server host name not given
Boot file name not given
Magic cookie: (OK)
Option: (t=53,l=1) DHCP Message Type = DHCP ACK
Option: (t=54,l=4) Server Identifier = 192.168.1.1
Option: (t=1,l=4) Subnet Mask = 255.255.255.0
Option: (t=3,l=4) Router = 192.168.1.1
Option: (6) Domain Name Server
  Length: 12; Value: 445747E2445749F244574092;
  IP Address: 68.87.71.226;
  IP Address: 68.87.73.242;
  IP Address: 68.87.64.146
Option: (t=15,l=20) Domain Name = "hsd1.ma.comcast.net."

IP addresses: how to get one?

Q: how does *network* get subnet part of IP addr?

A: gets allocated portion of its provider ISP's address space

ISP's block	11001000 00010111 00010000 00000000		200.23.16.0/20
Organization 0	11001000 00010111 00010000 00000000		200.23.16.0/23
Organization 1	11001000 00010111 00010010 00000000		200.23.18.0/23
Organization 2	11001000 00010111 00010100 00000000		200.23.20.0/23
...	…..	….	….
Organization 7	11001000 00010111 00011110 00000000		200.23.30.0/23

Hierarchical addressing: route aggregation

hierarchical addressing allows efficient advertisement of routing information:



Hierarchical addressing: more specific routes

ISPs-R-Us has a more specific route to Organization 1



IP addressing: the last word...

Q: how does an ISP get block of addresses?

A: ICANN: Internet Corporation for Assigned Names and Numbers http://www.icann.org/

- allocates addresses
- manages DNS
- assigns domain names, resolves disputes

NAT: network address translation



all datagrams *leaving* local network have *same* single source NAT IP address: 138.76.29.7,different source port numbers

datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as

NAT: network address translation

motivation: local network uses just one IP address as far as outside world is concerned:

- range of addresses not needed from ISP: just one IP address for all devices
- can change addresses of devices in local network without notifying outside world
- can change ISP without changing addresses of devices in local network
- devices inside local net not explicitly addressable, visible by outside world (a security plus)

NAT: network address translation

implementation: NAT router must:

- *outgoing datagrams: replace* (source IP address, port #) of every outgoing datagram to (NAT IP address, new port #)

  . . . remote clients/servers will respond using (NAT IP address, new port #) as destination addr

- *remember (in NAT translation table)* every (source IP address, port #) to (NAT IP address, new port #) translation pair

- *incoming datagrams: replace* (NAT IP address, new port #) in dest fields of every incoming datagram with corresponding (source IP address, port #) stored in NAT table

NAT: network address translation

NAT translation table	
WAN side addr	LAN side addr
138.76.29.7, 5001	10.0.0.1, 3345
……	……

1: host 10.0.0.1 sends datagram to 128.119.40.186, 80

2: NAT router changes datagram source addr from 10.0.0.1, 3345 to 138.76.29.7, 5001, updates table



3: reply arrives dest. address: 138.76.29.7, 5001

4: NAT router changes datagram dest addr from 138.76.29.7, 5001 to 10.0.0.1, 3345

NAT: network address translation

- 16-bit port-number field:
  - 60,000 simultaneous connections with a single LAN-side address!
- NAT is controversial:
  - routers should only process up to layer 3
  - violates end-to-end argument
    - NAT possibility must be taken into account by app designers, e.g., P2P applications
  - address shortage should instead be solved by IPv6

NAT traversal problem

- client wants to connect to server with address 10.0.0.1
  - server address 10.0.0.1 local to LAN (client can't use it as destination addr)
  - only one externally visible NATed address: 138.76.29.7
- *solution1:* statically configure NAT to forward incoming connection requests at given port to server
  - e.g., (123.76.29.7, port 2500) always forwarded to 10.0.0.1 port 25000



NAT traversal problem

- *solution 2:* Universal Plug and Play (UPnP) Internet Gateway Device (IGD) Protocol. Allows NATed host to:
  - learn public IP address (138.76.29.7)
  - add/remove port mappings (with lease times)

  i.e., automate static NAT port map configuration



NAT traversal problem

- *solution 3:* relaying (used in Skype)
  - NATed client establishes connection to relay
  - external client connects to relay
  - relay bridges packets between to connections



Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol

- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms

- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet

- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

ICMP: internet control message protocol

- used by hosts & routers to communicate network-level information
  - error reporting: unreachable host, network, port, protocol
  - echo request/reply (used by ping)
- network-layer "above" IP:
  - ICMP msgs carried in IP datagrams
- ICMP message: type, code plus first 8 bytes of IP datagram causing error

Type	Code	description
0	0	echo reply (ping)
3	0	dest. network unreachable
3	1	dest host unreachable
3	2	dest protocol unreachable
3	3	dest port unreachable
3	6	dest network unknown
3	7	dest host unknown
4	0	source quench (congestion control - not used)
8	0	echo request (ping)
9	0	route advertisement
10	0	router discovery
11	0	TTL expired
12	0	bad IP header

Traceroute and ICMP

- source sends series of UDP segments to dest
  - first set has TTL =1
  - second set has TTL=2, etc.
  - unlikely port number
- when *n*th set of datagrams arrives to nth router:
  - router discards datagrams
  - and sends source ICMP messages (type 11, code 0)
  - ICMP messages includes name of router & IP address
- when ICMP messages arrives, source records RTTs

stopping criteria:

- UDP segment eventually arrives at destination host
- destination returns ICMP "port unreachable" message (type 3, code 3)
- source stops



IP Security

- To communicate securely in the nonsecure public Internet. E.g. VPN

- The services provided by an IPsec session include:

- Cryptographic agreement.
- Encryption of IP datagram payloads.
- Data integrity.
- Origin authentication.

Consider a router that interconnects three subnets: Subnet 1, Subnet 2, and Subnet 3. Suppose all of the interfaces in each of these three subnets are required to have the prefix 223.1.17/24. Also suppose that Subnet 1 is required to support at least 60 interfaces, Subnet 2 is to support at least 90 interfaces, and Subnet 3 is to support at least 12 interfaces. Provide three network addresses (of the form a.b.c.d/x) that satisfy these constraints.

Consider sending a 2400-byte datagram into a link that has an MTU of 700 bytes. Suppose the original datagram is stamped with the identification number 422. How many fragments are generated? What are the values in the various fields in the IP datagram(s) generated related to fragmentation?

Suppose datagrams are limited to 1,500 bytes (including header) between source Host A and destination Host B. Assuming a 20-byte IP header, how many datagrams would be required to send an MP3 consisting of 5 million bytes? Explain how you computed your answer.

Suppose two packets arrive to two different input ports of a router at exactly the same time. Also suppose there are no other packets anywhere in the router.

a. Suppose the two packets are to be forwarded to two different output ports. Is it possible to forward the two packets through the switch fabric at the same time when the fabric uses a shared bus?

b. Suppose the two packets are to be forwarded to two different output ports. Is it possible to forward the two packets through the switch fabric at the same time when the fabric uses a crossbar?

c. Suppose the two packets are to be forwarded to the same output port. Is it possible to forward the two packets through the switch fabric at the same time when the fabric uses a crossbar?