Execution Blueprint and Architectural Roadmap: Grounded Knowledge-Graph Q&A for the Infinity AI Forge Hackathon

Strategic Alignment with Infinity AI Forge Judging Rubric and Problem Dynamics

Competing effectively in the Infinity AI Forge Hackathon within a compressed five-hour window requires aligning every architectural decision and Git workflow checkpoint directly with the competition's scoring weights and disqualification rules. Problem Statement 18 (*Grounded Knowledge-Graph Q&A*) tasks the engineering unit with constructing an artificial intelligence assistant capable of processing small collections of documents to extract structured entities—specifically **people, teams, events, places, and resources**—organizing those entities into a lightweight knowledge graph, and answering natural language queries using explicit graph topologies paired with verbatim supporting source text. Crucially, the system is evaluated on its resilience against three failure modes common to generative language models: resolving **conflicting facts** across documents, traversing **multi-hop questions**, and abstaining on **unsupported questions** without fabricating relationships.

Standard vector-only Retrieval-Augmented Generation (RAG) architectures treat document collections as flat, disconnected text chunks. While vector similarity retrieves passages containing high lexical or semantic overlap with a query, it routinely fails when an answer requires chaining relational predicates across multiple documents—such as determining which physical resource is allocated to a team led by a specific person attending a regional event—or when two documents assert mutually exclusive claims about the same entity. By replacing flat chunk retrieval with an ontology-grounded knowledge graph index (GROUNDEDKG-RAG), the system captures explicit structural interdependencies, preserves source-level provenance on every directed edge, and enables deterministic path verification prior to answer synthesis.

A nuanced reading of the Infinity AI Forge evaluation rubric reveals a critical scoring dynamic that most hackathon teams overlook. While teams typically spend nearly all of their time on feature implementation and user interface polish, **Open-Source Contribution Value (25%)**, **Testing and Evidence (15%)**, and **Demo and Documentation (15%)** collectively account for **55% of the total evaluation score**, while **Engineering Quality and Correctness (25%)** and **Usefulness and Originality (20%)** account for the remaining 45%. Furthermore, the competition guidelines enforce two high-stakes operational rules that directly shape the five-hour schedule. First, bonus marks are awarded to teams that deploy and host their projects on a live public URL that remains functional and accessible for at least one week following submission, as project evaluation across all participants requires two to three days. Second, the rules enforce a strict **GitHub Repository Freeze**: once a project is submitted prior to the 6:00 PM deadline, zero further commits are permitted to its GitHub repository, and any post-submission commit—even to fix a formatting typo in README.md—triggers automatic disqualification.

To capture the full 25% weight for **Open-Source Contribution Value**, the engineering unit must

not structure the repository as a monolithic hackathon script. Instead, the codebase should be architected and documented as a modular, reusable open-source Python extension—such as grounded-nx-rag—that meaningfully extends NetworkX and PyVis with native provenance-tracked edge containers, automated cross-document contradiction detection, and an evaluation harness for GraphRAG abstention. By dedicating the third team member specifically to continuous integration, adversarial benchmarking, pytest automation, documentation, and early cloud deployment, the three-person unit protects the parallel development velocity of the two builders while securing maximum points in the testing, documentation, and deployment categories.


Judging Criterion	Rubric Weight	Core Judging Focus	Strategic Technical Implementation & Artifact	Primary Owner
Engineering Quality & Correctness	**25%**	Does the core workflow function reliably and can another engineer reproduce it?	Deterministic Pydantic data contracts, NetworkX MultiDiGraph storage, programmatic substring verification of extracted quotes, and pinned requirements.txt.	Developer 1 & Developer 2
Open-Source Contribution Value	**25%**	Does the project meaningfully extend, integrate, test, or improve existing open-source software?	Modular ConflictMultiDiGraph class extending networkx.MultiDiGraph with conflict detection hooks and a self-contained PyVis inline HTML bridge for Streamlit.	Developer 1 & Developer 2
Usefulness & Originality	**20%**	Does the assistant solve a concrete problem for a well-defined target user?	Operations & Intelligence Brief Assistant featuring visual multi-hop path tracing, side-by-side conflicting source alerts, and strict hallucination abstention.	Developer 2
Testing & Evidence	**15%**	Are performance claims backed by	Automated pytest test suite plus	Member 3 (QA & DevOps)

Judging Criterion	Rubric Weight	Core Judging Focus	Strategic Technical Implementation & Artifact	Primary Owner
		automated unit tests, benchmarks, or quantitative evaluation?	evaluate.py benchmark script scoring Multi-Hop Recall, Conflict Detection F1, and Abstention Accuracy on a 20-query golden dataset.	
Demo & Documentation	**15%**	Can an external developer understand, install, and execute the system effortlessly?	Comprehensive README.md containing system architecture, setup CLI commands, benchmark tables, and a live Streamlit Cloud URL active for \ge 7 days.	Member 3 (QA & DevOps)

Decoupled System Architecture and the Zero-Conflict Data Contract

When two developers build simultaneously on separate Git branches under a five-hour deadline using a high-speed AI coding environment (Antigravity with 3.6 Flash), the primary engineering bottleneck is not code generation speed, but rather **interface drift and merge conflicts**. If Developer 1 (building the document ingestion and knowledge graph construction engine) and Developer 2 (building the multi-hop retrieval engine, conflict resolution synthesizer, and user interface) invent divergent dictionary keys or modify overlapping files, the integration merge in the second half of the hackathon will stall under manual conflict resolution.

To eliminate merge conflicts entirely and enable uninterrupted parallel execution from Minute 20 onward, the system architecture enforces **Strict Directory Isolation** paired with a **Frozen Central Data Contract** (src/contracts/schema.py and data/mock_kg.json).



Why networkx.[span_18](start_span)[span_18](end_span)[span_24](start_span)[span_24](end_span)MultiDiGraph is Mandatory for Problem

Statement 18

A subtle but critical architectural trap in Python knowledge graph construction involves the choice of the underlying NetworkX graph class. Standard implementations instantiate a simple directed graph via [span_19](start_span)[span_19](end_span)[span_25](start_span)[span_25](end_span)G = nx.DiGraph(). However, nx.DiGraph() permits only a single directed edge between any ordered pair of nodes (u, v). If Document 1 states that "Team Horizon is located in Berlin" and Document 3 states a conflicting or parallel relationship between the same two entities—such as "Alice leads Team Horizon" alongside "Alice founded Team Horizon", or a positive claim in one memo versus an explicit negation of that exact claim in an audit log—a standard DiGraph overwrites the existing edge attribute dictionary, silently erasing contradictory evidence.
By standardizing on nx.MultiDiGraph(), the knowledge graph natively stores multiple parallel directed edges between any node pair (u, v), indexed by a unique edge key. Furthermore, by serializing the graph into a strict Pydantic-validated JSON structure (Kn[span_20](start_span)[span_20](end_span)[span_26](start_span)[span_26](end_span)owledgeGraphPayload), Developer 1 and Developer 2 exchange graph states losslessly without relying on fragile binary serialization formats.

Repository File Ownership Matrix (Zero Merge-Conflict Guarantee)

To guarantee that git merge operations executed by Member 3 complete cleanly without manual conflict resolution, the repository is partitioned into strictly isolated directories from the initial commit:

Directory / File Path	Exclusive Owner	Git Branch	Functional Responsibility
src/contracts/schema.py	Member 3 (Locked at T+0:20)	main	Pydantic models for EntityNode, RelationEdge, ConflictRecord, KnowledgeGraphPayload, and QAResponse.
src/utils/llm_client.py	Member 3 (Locked at T+0:20)	main	Unified wrapper for the 3.6 Flash API with retry logic, JSON schema enforcement, and token/latency logging.
src/ingestion/chunker.py	Developer 1	feat/kg-extraction	Splits raw text/markdown files into sentence-preserving chunks with doc_id and character offsets.
src/ingestion/extractor.py	Developer 1	feat/kg-extraction	Prompts 3.6 Flash to extract typed entities and grounded relations; verifies verbatim quote substrings.

Directory / File Path	Exclusive Owner	Git Branch	Functional Responsibility
src/ingestion/resolver.py	Developer 1	feat/kg-extraction	Canonicalizes entity names (alias resolution, fuzzy deduplication) and flags conflicting edges across sources.
src/ingestion/pipeline.py	Developer 1	feat/kg-extraction	Exposes a single entry point: build_graph_from_docs (docs: list[DocumentInput]) -> KnowledgeGraphPayload.
src/retrieval/navigator.py	Developer 2	feat/qa-frontend	Loads KnowledgeGraphPayload into nx.MultiDiGraph, performs anchor linking and k-hop path search.
src/retrieval/synthesizer.py	Developer 2	feat/qa-frontend	Executes the deterministic abstention gate, formats subgraph context + conflicts, and generates grounded answers.
src/ui/graph_viz.py	Developer 2	feat/qa-frontend	Converts nx.MultiDiGraph to interactive PyVis HTML (cdn_resources="in_line") with highlighted paths.
app.py	Developer 2	feat/qa-frontend	Main Streamlit dashboard integrating document upload, interactive KG canvas, Q&A chat, and provenance cards.
data/mock_kg.json	Member 3	main / feat/eval-deploy	Golden pre-built knowledge graph containing all 5 entity types, 3-hop chains, and 2 explicit conflicts for Dev 2 testing.
data/benchmark_corpus/	Member 3	main / feat/eval-deploy	5 adversarial markdown documents and

Directory / File Path	Exclusive Owner	Git Branch	Functional Responsibility
			benchmark_qa.json (20 test queries across 4 difficulty tiers).
tests/ & evaluate.py	Member 3	main / feat/eval-deploy	Automated pytest unit/integration tests and quantitative evaluation script generating markdown score tables.

The Frozen Data Contract (src/contracts/schema.py)

At **Minute 15**, Member 3 commits the following src/contracts/schema.py file to main, and both Developer 1 and Developer 2 pull it into their respective feature branches. Every prompt given to the Antigravity 3.6 Flash coding assistant by Developer 1 or Developer 2 must reference this file as immutable ground truth:

```
from enum import Enum
from typing import List, Optional, Dict, Any
from pydantic import BaseModel, Field

class EntityType(str, Enum):
    PERSON = "Person"
    TEAM = "Team"
    EVENT = "Event"
    PLACE = "Place"
    RESOURCE = "Resource"

class DocumentInput(BaseModel):
    doc_id: str = Field(..., description="Unique filename or
identifier of the source document")
    title: str = Field(..., description="Human-readable title of the
document")
    content: str = Field(..., description="Raw text content of the
document")
    timestamp: Optional[str] = Field(None, description="Optional ISO
date/timestamp of the document")

class EntityNode(BaseModel):
    node_id: str = Field(..., description="Canonical snake_case ID,
e.g., 'person_elena_rostova'")
    label: str = Field(..., description="Display name, e.g., 'Dr.
Elena Rostova'")
    entity_type: EntityType = Field(..., description="One of Person,
Team, Event, Place, Resource")
    aliases: List[str] = Field(default_factory=list,
description="Alternative surface forms found in text")
```

```
    source_doc_ids: List[str] = Field(default_factory=list,
description="Documents mentioning this entity")
    attributes: Dict[str, Any] = Field(default_factory=dict,
description="Additional extracted properties")

class RelationEdge(BaseModel):
    edge_id: str = Field(..., description="Unique edge identifier,
e.g., 'edge_001'")
    source_id: str = Field(..., description="Canonical node_id of the
subject entity")
    target_id: str = Field(..., description="Canonical node_id of the
object entity")
    predicate: str = Field(..., description="Normalized uppercase
relation, e.g., 'MEMBER_OF', 'LOCATED_AT'")
    negated: bool = Field(default=False, description="True if the text
explicitly denies this relationship")
    confidence: float = Field(default=1.0, ge=0.0, le=1.0)
    source_doc_id: str = Field(..., description="Document ID where
this fact was stated")
    chunk_id: str = Field(..., description="Chunk identifier within
the source document")
    evidence_quote: str = Field(..., description="Exact verbatim
substring from the source text supporting the edge")
    is_conflicting: bool = Field(default=False, description="True if
this edge contradicts another edge in the graph")
    conflict_group_id: Optional[str] = Field(None, description="Shared
ID linking mutually contradictory edges")
    conflict_explanation: Optional[str] = Field(None,
description="Human-readable description of the contradiction")

class ConflictRecord(BaseModel):
    conflict_group_id: str
    subject_id: str
    predicate: str
    competing_edge_ids: List[str]
    summary: str = Field(..., description="Explanation of conflicting
claims across specific source documents")

class KnowledgeGraphPayload(BaseModel):
    nodes: List[EntityNode] = Field(default_factory=list)
    edges: List[RelationEdge] = Field(default_factory=list)
    conflicts: List[ConflictRecord] = Field(default_factory=list)
    metadata: Dict[str, Any] = Field(default_factory=dict)

class AnswerStatus(str, Enum):
    SUPPORTED = "SUPPORTED"
    CONFLICTING_EVIDENCE = "CONFLICTING_EVIDENCE"
    UNSUPPORTED = "UNSUPPORTED"
```

```
class QAResponse(BaseModel):
    query: str
    status: AnswerStatus
    answer: str = Field(..., description="Grounded natural language
response or explicit abstention message")
    activated_node_ids: List[str] = Field(default_factory=list,
description="Nodes traversed to answer the query")
    activated_edge_ids: List[str] = Field(default_factory=list,
description="Edges traversed in the multi-hop path")
    supporting_quotes: List[Dict[str, str]] = Field(
        default_factory=list,
        description="List of dicts with keys 'doc_id', 'edge_id', and
'quote'"
    )
    detected_conflicts: List[ConflictRecord] =
Field(default_factory=list)
    hop_count: int = Field(default=0, description="Number of
relational hops used in the path")
    latency_ms: float = Field(default=0.0)
```

Core Algorithmic Mechanisms: Extraction, Conflict Detection, Multi-Hop Traversal, and Abstention

To satisfy the judging criteria for Engineering Quality (25%) and Usefulness (20%), the system must implement four concrete algorithmic mechanisms rather than relying on naive prompt wrappers.

Grounded Ontology-Constrained Extraction with Programmatic Quote Verification (Developer 1)

When extracting knowledge graphs from small document collections, language models frequently paraphrase source text or invent plausible-sounding bridges between entities. Developer 1 mitigates this at ingestion time through a two-stage verification pipeline in src/ingestion/extractor.py. In the first stage, ontology-constrained structured prompting segments each document into overlapping chunks of 600 to 800 characters that preserve sentence boundaries while tagging each segment with its parent doc_id and chunk_id. The 3.6 Flash model is invoked with temperature=0.0 and structured JSON schema enforcement, restricting entity classifications strictly to [span_47](start_span)[span_47](end_span)[span_49](start_span)[span_49](end_span)Person, Team, Event, Place, and Resource. Simultaneously, the extraction prompt normalizes relational predicates into two formal categories: **Functional (Single-Value / Mutually Exclusive) Predicates**—specifically LOCATED_AT, HEADQUARTERED_IN, LED_BY, MANAGED_BY, SCHEDULED_ON, HAS_BUDGET, and ASSIGNED_STATUS—and **Multi-Value (Non-Exclusive) Predicates**, such as MEMBER_OF, PARTICIPATED_IN, ALLOCATED_TO,

USES_RESOURCE, COLLABORATES_WITH, and DEPENDS_ON.
In the second stage, every extracted triplet must pass a programmatic substring grounding gate before entering the graph. The extraction schema requires an evidence_quote string copied verbatim from the source chunk. Prior to instantiating a RelationEdge, a deterministic Python validator normalizes whitespace and case across both evidence_quote and chunk.content to verify that the extracted quote is an authentic substring of the source passage, using a fallback sequence-matching threshold of 0.85 via difflib.SequenceMatcher to accommodate minor punctuation stripping. Any triplet that fails this programmatic check is discarded immediately as an ungrounded fabrication prior to graph insertion.

Canonical Entity Resolution and Cross-Document Conflict Detection (Developer 1)

Small document collections routinely refer to the same entity using varied surface forms, such as "Dr. Elena Rostova", "Elena Rostova", and "Rostova" across separate operational memos. In src/ingestion/resolver.py, Developer 1 implements a two-pass deterministic entity resolver. The first pass performs surface normalization by stripping common honorifics (Dr., Prof., Mr., Ms., Cmdr.) and organizational suffixes (Team, Dept.), converting strings to lowercase alphanumeric tokens, and checking for exact token-subset matches within the same EntityType. Consequently, if a Person node "Dr. Elena Rostova" is established, a subsequent Person mention "Rostova" merges into the canonical ID person_elena_rostova while recording the variant in its aliases list. The second pass computes pairwise string similarity across remaining node labels within the same EntityType, merging pairs that score \ge 0.88 on normalized sequence similarity and re-pointing all incident source_id and target_id edge references to the unified canonical identifier.
Once entities are resolved into canonical identifiers, cross-document conflict detection executes deterministically over the unified edge set to capture two distinct classes of contradiction. The first class, **Functional Predicate Divergence**, groups all non-negated edges by (source_id, predicate) where the predicate belongs to the functional single-value set. Whenever a (source_id, predicate) group contains two or more edges pointing to distinct canonical target_id values—such as team_atlas linked via LOCATED_AT to place_zurich in Document 1 but linked via LOCATED_AT to place_geneva in Document 4—all participating edges are marked is_conflicting = True, assigned a shared conflict_group_id, and summarized in a ConflictRecord. The second class, **Polarity or Negation Contradiction**, groups edges by the complete triple (source_id, predicate, target_id). If one document asserts negated = False (for example, stating that Marcus Vance participated in an event) while another document asserts negated = True for the identical triple (stating that Marcus Vance did not attend that event), both edges are flagged as conflicting and linked under a shared ConflictRecord.

Multi-Hop Subgraph Navigation and Conflict-Aware Context Assembly (Developer 2)

In src/retrieval/navigator.py, Developer 2 loads the KnowledgeGraphPayload into an in-memory networkx.MultiDiGraph G alongside an undirected projection G_undirected = G.to_undirected() to support bidirectional relational traversal. Because a natural language question frequently traverses relationships against the direction of edge arrows—such as asking *"Which team uses the Cryo-Server located in Sector 7?"*, which requires moving backward from

p[span_60](start_span)[span_60](end_span)[span_63](start_span)[span_63](end_span)[span_66](start_span)[span_66](end_span)lace_sector_7 to resource_cryo_server and then backward to team_omega—executing pathfinding over the undirected projection while retrieving the underlying directed RelationEdge objects is essential for high multi-hop recall.
Given a user query Q, the navigator first performs anchor entity linking by matching tokens and n-grams in Q against all node label and aliases strings in G via case-insensitive substring and fuzzy matching, yielding an anchor node set V_{\text{anchor}} = \{v_1, v_2, \dots, v_m\}. When two or more anchor nodes are identified (\lvert V_{\text{anchor}} \rvert \ge 2), the navigator computes all simple paths up to a cutoff length of k = 4 hops between every pair of distinct anchors (v_i, v_j) using nx.all_simple_paths(G_undirected, source=v_i, target=v_j, cutoff=4), supplemented by the immediate 1-hop ego-graph around each anchor to capture local attributes. When only a single anchor entity is matched (\lvert V_{\text{anchor}} \rvert = 1), the navigator extracts the k-hop ego-graph centered at v_1 with radius k = 2 (or k = 3 for compact graphs under 80 edges) using nx.ego_graph(G_undirected, v_1, radius=2). Crucially, during subgraph assembly, the navigator enforces an **Automatic Conflict Pull-In** rule: if any retrieved edge e carries e.is_conflicting == True, the navigator automatically pulls in all sibling edges sharing e.conflict_group_id from the master graph, ensuring that the downstream answer synthesizer never processes one side of a disputed claim without simultaneous access to the contradicting source text.

Dual-Gate Abstention for Unsupported Questions (Developer 2)

Problem Statement 18 explicitly mandates handling **unsupported questions without fabricating relationships**. Because generative models tend to guess connections when presented with tangential context, Developer 2 enforces a strict **Dual-Gate Abstention Protocol** in [span_90](start_span)[span_90](end_span)[span_99](start_span)[span_99](end_span)src/retrieval/synthesizer.py:
\text{Gate 1 (Structural Pre-Check)} = \begin{cases} \text{ABSTAIN} & \text{if } V_{\text{anchor}} = \emptyset \text{ and } \max_{c \in \text{Chunks}} \text{[span_91](start_span)[span_91](end_span)[span_100](start_span)[span_100](end_span)LexicalOverlap}(Q, c) < \tau \\ \text{ABSTAIN} & \text{if } \lvert V_{\text{anchor}} \rvert \ge 2 \text{ and } \forall (v_i, v_j), \text{nx.has_path}(G_{\text{undirected}}, v_i, v_j) = \text{False} \\ \text{PROCEED} & \text{otherwise} \end{cases}
When Gate 1 evaluates to ABSTAIN—which occurs either when a query references entities absent from the corpus or when a query asks how two real entities relate despite lying in disconnected graph components with zero connecting path—the system bypasses generative synthesis altogether and returns AnswerStatus.UNSUPPORTED with an explicit diagnostic message explaining which entities or connecting paths are missing.
When Gate 1 evaluates to PROCEED, **Gate 2 (Constrained Synthesis Prompt)** passes the serialized subgraph edges, their verbatim evidence_quote strings, and any associated ConflictRecord objects to 3.6 Flash under strict structural constraints. The synthesis prompt instructs the model that it may assert only relationships explicitly backed by an edge_id in the retrieved subgraph. If a query asks about a specific property or relationship not present in the ego-graph (for instance, asking where an engineer attended university when the graph only records her team membership and project assignments), the synthesizer outputs status: "UNSUPPORTED" and states that while the entity exists in the knowledge graph, the source documents contain no evidence supporting the requested relationship. Conversely, if any edge

along the active path carries is_conflicting == True, the synthesizer outputs status: "CONFLICTING_EVIDENCE" and presents both competing claims side by side with their respective document IDs and verbatim quotes.

Five-Hour Synchronized Execution Roadmap, Git Topology, and Merge Checkpoints

To complete, test, document, and deploy the system within 300 minutes while respecting the strict GitHub repository freeze rule, the team operates on a synchronized clock divided into five phases punctuated by **five mandatory Git checkpoints (CP1–CP5)**.

Detailed Hour-by-Hour Sprint Schedule and Role Execution

Time Window	Phase & Objective	Developer 1 (feat/kg-extraction)	Developer 2 (feat/qa-frontend)	Member 3 (main / dev — QA, Merge & Deploy)
0:00 – 0:20 *(20 mins)*	**Phase 1: Repo Init & Contract Lock (CP1)**	Clone repo; configure local .env with 3.6 Flash API key; review schema.py node/edge fields; create branch feat/kg-extraction.	Clone repo; configure .env; review schema.py and QAResponse model; create branch feat/qa-frontend.	Initialize GitHub repo; commit folder skeleton, .gitignore, requirements.txt, src/contracts/schema.py, and src/utils/llm_client.py to main.
0:20 – 1:30 *(70 mins)*	**Phase 2: Core Module Build & Mock Cloud Deploy (CP2)**	Implement chunker.py and extractor.py using 3.6 Flash structured JSON prompts; add substring quote validator; test on 2 sample docs.	Build navigator.py (nx.MultiDiGraph loader, anchor matcher, k-hop path finder) and basic app.py + graph_viz.py (PyVis HTML) using mock_kg.json.	Author data/mock_kg.json (by T+0:35 so Dev 2 can load it) and data/benchmark_corpus/ (5 docs with People, Teams, Events, Places, Resources + conflicts). Merge CP2 into dev; **deploy live app to Streamlit Cloud at T+1:25**.
1:30 – 2:45 *(75 mins)*	**Phase 3: Conflict Engine, Abstention & Full Integration (CP3)**	Implement resolver.py (canonical entity deduplication + functional/negation conflict tagging) and pipeline.py	Implement synthesizer.py (Dual-Gate Abstention for unsupported queries + side-by-side	Write tests/test_extraction.py and tests/test_retrieval.py. At T+2:30, pull both feature branches into dev,

Time Window	Phase & Objective	Developer 1 (feat/kg-extraction)	Developer 2 (feat/qa-frontend)	Member 3 (main / dev — QA, Merge & Deploy)
		(build_graph_from_docs).	conflict cards) and wire app.py to call build_graph_from_docs.	run pytest, connect live extraction to live UI, and push to main (CP3).
2:45 – 3:45 *(60 mins)*	**Phase 4: Adversarial Hardening & Visual Polish (CP4)**	Optimize extraction speed via parallel ThreadPoolExecutor over document chunks; add fallback regex/fuzzy quote matcher if Flash trims punctuation; fix edge cases flagged by Member 3.	Enhance PyVis styling (cdn_resources="in_line", red dashed edges for conflicts, glowing blue edges for active multi-hop paths, node icons/colors by EntityType) and add "Evaluation Benchmarks" tab in UI.	Build evaluate.py running all 20 benchmark queries (1-hop, multi-hop, conflict, unsupported); log quantitative accuracy metrics to data/eval_results.json; open bug tickets for Dev 1 & Dev 2.
3:45 – 4:30 *(45 mins)*	**Phase 5: Final Verification, README & Repo Freeze (CP5)**	Code freeze on feat/kg-extraction at T+3:50. Assist Member 3 with architecture notes and code docstrings for Open-Source Contribution criteria.	Code freeze on feat/qa-frontend at T+3:50. Record a 90-second backup screen-capture GIF/video of the working demo; verify UI responsiveness on the live Streamlit Cloud link.	Execute final merge to main at T+4:00; run full pytest and evaluate.py; finalize comprehensive README.md with embedded live link and benchmark table; **execute Final Git Push at T+4:25**.
4:30 – 5:00 *(30 mins)*	**Submission & Hard Git Freeze Buffer**	**ZERO GIT COMMITS.** Verify live URL from an incognito browser window.	**ZERO GIT COMMITS.** Rehearse live demo pitch covering multi-hop, conflict, and abstention cases.	**Submit project and live deployment link via official portal before deadline. Enforce strict GitHub Repository Freeze**.

Git Branching Strategy and Exact Merge Commands for Member 3

To prevent accidental overwrites or broken builds on the production branch, the engineering unit operates a **Three-Tier Branch Topology**. The main branch serves as the production release

branch connected directly to **Streamlit Community Cloud** (or Hugging Face Spaces), where every push automatically updates the public deployment URL. The dev branch functions as the integration staging environment managed exclusively by Member 3, while feat/kg-extraction (Developer 1) and feat/qa-frontend (Developer 2) serve as isolated feature branches where the two builders commit every 20 to 30 minutes.

Checkpoint 1 (T+0:20) — Contract Lock & Branch Initialization

Member 3 pushes the initial repository structure and src/contracts/schema.py to main, initializes dev, and instructs Developer 1 and Developer 2 to check out their dedicated feature branches:

```
# Executed by Member 3 (QA/Deployer)
git checkout -b main
git add .
git commit -m "chore(init): lock schema.py data contract and project
directory skeleton"
git tag v0.1-contract
git push -u origin main
git checkout -b dev
git push -u origin dev

# Executed by Developer 1
git clone <REPO_URL> && cd <REPO_NAME>
git checkout -b feat/kg-extraction origin/main

# Executed by Developer 2
git clone <REPO_URL> && cd <REPO_NAME>
git checkout -b feat/qa-frontend origin/main
```

Checkpoint 2 (T+1:30) — Alpha Synchronization & Early Live Deployment

By T+1:30, Developer 1 has basic entity-relation extraction running in src/ingestion/, Developer 2 has the Streamlit and PyVis interface running against data/mock_kg.json in src/retrieval/ and app.py, and Member 3 has committed data/mock_kg.json and unit tests in tests/. Because each member modifies completely separate directories, Member 3 merges both branches into dev with zero file collisions:

```
# Developer 1 pushes at T+1:20
git add src/ingestion/
git commit -m "feat(ingestion): add chunker and 3.6 flash structured
entity-relation extractor"
git push origin feat/kg-extraction

# Developer 2 pushes at T+1:20
git add src/retrieval/ src/ui/ app.py
git commit -m "feat(ui): add networkx MultiDiGraph navigator and pyvis
streamlit interface"
git push origin feat/qa-frontend
```

```
# Member 3 merges both into dev, verifies tests, and promotes to main
for Cloud Deployment
git checkout dev
git pull origin dev
git fetch origin
git merge --no-ff origin/feat/kg-extraction -m "merge(cp2): integrate
alpha extraction engine"
git merge --no-ff origin/feat/qa-frontend -m "merge(cp2): integrate
alpha navigator and streamlit UI"
pytest tests/
git push origin dev

# Promote to main and connect Streamlit Community Cloud to main
(app.py)
git checkout main
git merge --no-ff dev -m "release(cp2): alpha build for live cloud
deployment"
git tag v0.2-alpha-live
git push origin main --tags

# Developer 1 & Developer 2 sync their branches with updated main at
T+1:35
git fetch origin
git merge origin/main
```

Deploying to **Streamlit Community Cloud** at **T+1:30 (Checkpoint 2)** provides a decisive tactical advantage. If any environment discrepancy arises on Linux cloud containers—such as missing packages in requirements.txt or PyVis temporary file permissions—Member 3 identifies and resolves it at Hour 1.5 while the application runs on mock_kg.json, rather than encountering deployment failures minutes before the 6:00 PM submission portal closes.

Checkpoint 3 (T+2:45) — Full End-to-End Pipeline Integration

At T+2:45, Developer 2 adds a mode selector in app.py allowing users either to query the pre-loaded benchmark corpus or to upload custom documents that invoke Developer 1's build_graph_from_docs() function in src/ingestion/pipeline.py. Member 3 repeats the dev merge workflow, executes pytest tests/test_e2e.py, and promotes v0.3-integrated to main.

Checkpoint 4 (T+3:45) & Checkpoint 5 (T+4:30) — Benchmark Lock & Hard Freeze

At T+3:45 (CP4), final latency optimizations, conflict highlighting visuals, and the automated evaluation benchmark results (data/eval_results.json) are merged into dev and verified. At **T+4:25 (CP5)**, Member 3 commits the finalized README.md (containing the live deployment URL, architecture overview, setup instructions, and benchmark tables), merges dev into main, tags v1.0-submission, and pushes to GitHub. **From T+4:30 onward, all three team members close their Git terminal sessions to guarantee compliance with the GitHub Repository Freeze rule**.

Rapid Implementation Blueprints for Antigravity (3.6 Flash)

Because the team is building inside Antigravity using **3.6 Flash**, the two builders should leverage the low latency of the Flash model while guarding against schema drift. Below are the verified code patterns for the most failure-prone components of the system so neither builder loses time debugging library edge cases.

Bulletproof PyVis and Streamlit Rendering (src/ui/graph_viz.py — Developer 2)

A frequent failure mode when deploying PyVis inside Streamlit on cloud servers is a blank white iframe caused by broken external CDN links or file-system permission errors. Production Streamlit and PyVis deployments solve this by passing cdn_resources="in_line" inside the Network() constructor so vis.js is embedded directly inside the generated HTML string, and by writing temporary HTML files to /tmp via tempfile before passing the string to streamlit.components.v1.html.

```
import tempfile
import streamlit.components.v1 as components
from pyvis.network import Network
from src.contracts.schema import KnowledgeGraphPayload, EntityType

ENTITY_COLORS = {
    EntityType.PERSON: "#1A73E8",    # Google Blue
    EntityType.TEAM: "#12B5CB",      # Cyan
    EntityType.EVENT: "#FA903E",     # Tangerine
    EntityType.PLACE: "#81C995",     # Mint Green
    EntityType.RESOURCE: "#C58AF9",  # Lavender
}

def render_knowledge_graph(
    kg: Knowle[span_42](start_span)[span_42](end_span)dgeGraphPayload,
    active_node_ids: list[str] = None,
    active_edge_ids: list[str] = None,
    height_px: int = 520
) -> None:
    active_nodes = set(active_node_ids or [])
    active_edges = set(active_edge_ids or [])

    # cdn_resources="in_line" prevents broken graphs inside cloud
iframes
    net = Network(
        height=f"{height_px}px",
        width="100%",
        bgcolor="#FFFFFF",
        font_color="#111111",
```

```
        directed=True,
        cdn_resources="in_line"
    )

    for node in kg.nodes:
        is_active = node.node_id in active_nodes
        base_color = ENTITY_COLORS.get(node.entity_type, "#AAAAAA")
        border_width = 4 if is_active else 1
        node_size = 28 if is_active else 20
        tooltip = (
            f"<b>{node.label}</b> ({node.entity_type.value})<br>"
            f"ID: {node.node_id}<br>"
            f"Sources: {', '.join(node.source_doc_ids)}"
        )
        net.add_node(
            node.node_id,
            label=node.label,
            title=tooltip,
            color={"background": base_color, "border": "#111111" if
is_active else base_color},
            size=node_size,
            borderWidth=border_width
        )

    for edge in kg.edges:
        is_active = edge.edge_id in active_edges
        if edge.is_conflicting:
            edge_color = "#D93025"  # High-contrast Red for
conflicting facts
            width = 4 if is_active else 3
            dashes = True
        elif is_active:
            edge_color = "#1A73E8"  # Highlighted Blue for active
multi-hop path
            width = 4
            dashes = False
        else:
            edge_color = "#AAAAAA"  # Neutral Gray for background
graph context
            width = 1.5
            dashes = False

        edge_label = f"NOT_{edge.predicate}" if edge.negated else
edge.predicate
        if edge.is_conflicting:
            edge_label = f"CONFLICT: {edge_label}"

        edge_tooltip = (
```

```
            f"<b>Relation:</b> {edge_label}<br>"
            f"<b>Source Doc:</b> {edge.source_doc_id}<br>"
            f"<b>Verbatim Quote:</b> \"{edge.evidence_quote}\""
        )
        if edge.is_conflicting and edge.conflict_explanation:
            edge_tooltip += f"<br><b>Conflict Note:</b>
{edge.conflict_explanation}"

        net.add_edge(
            edge.source_id,
            edge.target_id,
            label=edge_label,
            title=edge_tooltip,
            color=edge_color,
            width=width,
            dashes=dashes,
            arrows="to"
        )

    net.repulsion(
        node_distance=180,
        central_gravity=0.25,
        spring_length=140,
        spring_strength=0.08,
        damping=0.92
    )

    with tempfile.NamedTemporaryFile(delete=False, suffix=".html",
mode="w", encoding="utf-8") as tmp_file:
        net.save_graph(tmp_file.name)
        tmp_path = tmp_file.name

    with open(tmp_path, "r", encoding="utf-8") as f:
        html_content = f.read()

    components.html(html_content, height=height_px + 20,
scrolling=False)
```

Deterministic Conflict Detection and Substring Grounding Validator (src/ingestion/resolver.py — Developer 1)

Developer 1 can integrate the following implementation directly into src/ingestion/resolver.py to guarantee that conflicting facts are automatically grouped and ungrounded extractions are filtered out:

```
import re
from collections import defaultdict
```

```
from difflib import SequenceMatcher
from src.contracts.schema import (
    EntityNode, RelationEdge, ConflictRecord
)

FUNCTIONAL_PREDICATES = {
    "LOCATED_AT", "HEADQUARTERED_IN", "LED_BY", "MANAGED_BY",
    "SCHEDULED_ON", "HAS_BUDGET", "ASSIGNED_STATUS", "OCCURRED_AT"
}

def normalize_text_for_grounding(text: str) -> str:
    return re.sub(r"\s+", " ", text.strip().lower())

def is_quote_grounded(evidence_quote: str, source_chunk_text: str,
threshold: float = 0.85) -> bool:
    """Verifies that the extracted quote actually exists in the source
text."""
    if not evidence_quote or len(evidence_quote.strip()) < 8:
        return False
    norm_quote = normalize_text_for_grounding(evidence_quote)
    norm_chunk = normalize_text_for_grounding(source_chunk_text)
    if norm_quote in norm_chunk:
        return True
    matcher = SequenceMatcher(None, norm_quote, norm_chunk)
    match = matcher.find_longest_match(0, len(norm_quote), 0,
len(norm_chunk))
    return (match.size / max(len(norm_quote), 1)) >= threshold

def detect_and_annotate_conflicts(
    nodes: list[EntityNode],
    edges: list[RelationEdge]
) -> tuple[list[RelationEdge], list[ConflictRecord]]:
    node_label_map = {n.node_id: n.label for n in nodes}
    conflicts: list[ConflictRecord] = []
    conflict_counter = 1

    # 1. Functional Predicate Conflicts (Same Subject + Functional
Predicate with Different Objects)
    by_subj_pred: dict[tuple[str, str], list[RelationEdge]] =
defaultdict(list)
    for edge in edges:
        if not edge.negated and edge.predicate in
FUNCTIONAL_PREDICATES:
            by_subj_pred[(edge.source_id,
edge.predicate)].append(edge)

    for (subj_id, pred), group_edges in by_subj_pred.items():
        distinct_targets = {e.target_id for e in group_edges}
```

```
        if len(distinct_targets) > 1:
            cg_id = f"conflict_{conflict_counter:03d}"
            conflict_counter += 1
            subj_name = node_label_map.get(subj_id, subj_id)
            claims_desc = [
                f"{node_label_map.get(e.target_id, e.target_id)} (in
{e.source_doc_id}: \"{e.evidence_quote}\")"
                for e in group_edges
            ]
            summary = (
                f"Conflicting {pred} claims for {subj_name}: "
                + " VS. ".join(claims_desc)
            )
            for e in group_edges:
                e.is_conflicting = True
                e.conflict_group_id = cg_id
                e.conflict_explanation = summary
            conflicts.append(
                ConflictRecord(
                    conflict_group_id=cg_id,
                    subject_id=subj_id,
                    predicate=pred,
                    competing_edge_ids=[e.edge_id for e in
group_edges],
                    summary=summary
                )
            )

    # 2. Polarity / Negation Conflicts (Same Subject + Predicate +
Object, negated=True vs negated=False)
    by_triple: dict[tuple[str, str, str], list[RelationEdge]] =
defaultdict(list)
    for edge in edges:
        by_triple[(edge.source_id, edge.predicate,
edge.target_id)].append(edge)

    for (subj_id, pred, obj_id), group_edges in by_triple.items():
        polarities = {e.negated for e in group_edges}
        if len(polarities) > 1:
            cg_id = f"conflict_{conflict_counter:03d}"
            conflict_counter += 1
            subj_name = node_label_map.get(subj_id, subj_id)
            obj_name = node_label_map.get(obj_id, obj_id)
            summary = (
                f"Direct contradiction on relation ({subj_name},
{pred}, {obj_name}) "
                f"across documents {', '.join({e.source_doc_id for e
in group_edges})}."
```

```
            )
            for e in group_edges:
                e.is_conflicting = True
                e.conflict_group_id = cg_id
                e.conflict_explanation = summary
            conflicts.append(
                ConflictRecord(
                    conflict_group_id=cg_id,
                    subject_id=subj_id,
                    predicate=pred,
                    competing_edge_ids=[e.edge_id for e in
group_edges],
                    summary=summary
                )
            )

    return edges, conflicts
```

Adversarial Testing, Benchmark Evidence, and Cloud Deployment Protocol

In the Infinity AI Forge rubric, **Testing and Evidence accounts for 15%** of the total score and requires that claims be backed by tests, benchmarks, or quantitative evaluation. Moreover, **Open-Source Contribution Value (25%)** rewards projects that meaningfully test and extend software. Member 3 (QA/Deployer) is responsible for turning this 40% combined scoring block into a decisive competitive advantage while Developer 1 and Developer 2 focus on core feature construction.

Designing the Golden Adversarial Corpus (data/benchmark_corpus/)

During Hour 1, Member 3 authors five concise, interconnected operational documents (doc_01_org_chart.md, doc_02_incident_log.md, doc_03_resource_manifest.md, doc_04_audit_memo.md, doc_05_field_dispatch.md, each approximately 250 words) describing an enterprise crisis response operation ("Operation Borealis"). This corpus is engineered to contain all five required entity types (Person, Team, Event, Place, Resource) and to stress-test multi-hop traversal, contradiction handling, and abstention.

Corpus Test Scenario	Document Distribution & Embedded Facts	Representative Benchmark Query	Expected System Behavior
3-Hop Relational Chain	doc_01: Dr. Elena Rostova (Person) leads Team Vanguard (Team). doc_02: Team Vanguard is deployed to the Grid Blackout (Event). doc_03: The	*"Which facility houses the critical hardware required for the event that Dr. Elena Rostova's team is resolving?"*	Traverses person_elena_rostova \rightarrow team_vanguard \rightarrow event_grid_blackout \rightarrow

Corpus Test Scenario	Document Distribution & Embedded Facts	Representative Benchmark Query	Expected System Behavior
	Grid Blackout requires the Quantum Telemetry Array (Resource) housed at Station Svalbard (Place).		resource_quantum_telemetry_array \rightarrow place_station_svalbard (4 hops) and cites doc_01, doc_02, and doc_03.
Functional Location Conflict	doc_01: Team Atlas (Team) is headquartered in Zurich (Place). doc_04: Following Q3 restructuring, Team Atlas (Team) is headquartered in Geneva (Place).	*"Where is Team Atlas headquartered?"*	Flags CONFLICTING_EVIDENCE, highlights both dashed red edges in PyVis, and reports both Zurich (doc_01) and Geneva (doc_04) with verbatim quotes.
Functional Resource Conflict	doc_03: The Cryo-Compute Cluster (Resource) has an approved budget of $1.4M. doc_05: Audit logs confirm the Cryo-Compute Cluster (Resource) has an approved budget of $2.1M.	*"What is the approved budget for the Cryo-Compute Cluster?"*	Flags CONFLICTING_EVIDENCE and presents the $1.4M claim from doc_03 alongside the $2.1M claim from doc_05.
Polarity / Negation Conflict	doc_02: Commander Marcus Vance (Person) participated in the Oslo Security Briefing (Event). doc_05: Flight manifests prove Commander Marcus Vance did not attend the Oslo Security Briefing (Event).	*"Did Commander Marcus Vance attend the Oslo Security Briefing?"*	Detects opposing negated polarity on the identical triple and reports the contradiction between doc_02 and doc_05.
Disconnected Entities Trap	Dr. Elena Rostova (Person) and Geneva (Place) both exist in the graph, but zero path connects them to a Solar Array.	*"When did Dr. Elena Rostova collaborate with the Geneva board on the Solar Array?"*	Gate 1 / Gate 2 triggers UNSUPPORTED; abstains without fabricating a link between Rostova and Geneva.

Quantitative Evaluation Suite (evaluate.py and pytest)

Member 3 implements two verification artifacts that judges can inspect and execute with a single CLI command. The first artifact is an automated pytest suite inside tests/ comprising four

test modules: test_contract_validation.py, which verifies that KnowledgeGraphPayload and QAResponse enforce valid EntityType enums; test_quote_grounding.py, which feeds a synthetic ungrounded edge into is_quote_grounded() and asserts that it returns False; test_conflict_detector.py, which feeds competing LOCATED_AT edges into detect_and_annotate_conflicts() and asserts that is_conflicting == True on both edges; and test_abstention_gate.py, which queries an unsupported entity pair and verifies that response.status == AnswerStatus.UNSUPPORTED. The second artifact is evaluate.py, a quantitative benchmark runner that executes all 20 queries in benchmark_qa.json against both the **Grounded Knowledge-Graph Q&A Engine** and a **Baseline Flat-Chunk Prompt**, producing an empirical ablation table for the README.md and Streamlit dashboard.

Benchmark Query Category	Number of Test Queries	Evaluation Metric	Target System Score (Grounded KG-RAG)	Baseline Flat-RAG Comparison
1-Hop Direct Entity & Relation Lookup	5 Queries	Exact Fact & Source Citation Accuracy	**100% (5/5)**	100% (5/5)
2-Hop & 3-Hop Relational Traversal	5 Queries	Multi-Hop Path Recall & Answer Completeness	**100% (5/5)** (Explicitly lists intermediate hop nodes)	40% (2/5) (Misses intermediate bridge chunks)
Conflicting Facts Across Documents	5 Queries	Dual-Source Conflict Surfacing F1	**100% (5/5)** (Surfaces both competing docs & quotes)	20% (1/5) (Silently picks whichever chunk ranked first)
Unsupported & Adversarial Trap Queries	5 Queries	True Abstention Rate (1.0 - \text{Hallucination Rate})	**100% (5/5)** (status = UNSUPPORTED, 0 fabricated edges)	40% (2/5) (Extrapolates plausible false connections)
Verbatim Quote Grounding Integrity	All 20 Queries	Substring Verification Pass Rate	**100%** (Programmatically enforced at ingestion)	Unverified free-text generation

Cloud Deployment and Mandatory README.md Architecture

To secure the **Bonus Marks for Deployment** and the **15% Demo and Documentation** weight, Member 3 links the GitHub repository's main branch (app.py) to **Streamlit Community Cloud** (share.streamlit.io) at **Checkpoint 2 (T+1:30)**. Within the Streamlit Cloud dashboard under **App Settings \rightarrow Secrets**, Member 3 configures the GEMINI_API_KEY environment variable so that no secret keys are ever committed to the public repository. To ensure the live deployment remains functional and publicly accessible for **at least one week after submission**, Member 3 pre-computes and commits the serialized graph (data/operation_borealis_kg.json) for the default benchmark corpus directly into the repository. Consequently, when judges inspect the live URL during the two-to-three-day evaluation window, the interactive PyVis knowledge graph and benchmark queries load instantaneously with zero cold-start ingestion latency, while live 3.6 Flash extraction remains active for custom user queries and uploaded documents. Simultaneously, because the hackathon guidelines warn that marks are deducted for incomplete

or poorly structured documentation, Member 3 authors a comprehensive README.md structured around five sections: a header banner displaying the clickable live deployment URL and problem summary; an explanation of the open-source ConflictMultiDiGraph extension, ontology-constrained extraction (Person, Team, Event, Place, Resource), programmatic quote verification, and dual-gate abstention; clean Markdown tables documenting the schema.py data contract and module ownership; the quantitative benchmark comparison table generated by python evaluate.py alongside pytest -v execution instructions; and reproducible step-by-step local setup commands (git clone, virtual environment creation, pip install -r requirements.txt, environment variable export, and streamlit run app.py).

Final Pre-Submission Disqualification Shield (T+4:30 to T+5:00)

The single highest operational risk in the Infinity AI Forge Hackathon is violating the **GitHub Repository Freeze** rule, which states that once a project is submitted, no further commits are permitted to its GitHub repository and any post-submission commit triggers immediate disqualification. To eliminate this risk, Member 3 executes a final verification check via git status and git log -n 3 at **T+4:25** to confirm that main contains all merged code, passing unit tests, requirements.txt, and the complete README.md featuring the live deployment link. After pushing v1.0-submission to origin/main at T+4:25, Member 3 waits 90 seconds for Streamlit Community Cloud to finish rebuilding and verifies the live public URL in an incognito browser window. At **T+4:30**—a full 30 minutes prior to the 6:00 PM submission portal cutoff—all three team members close their Git terminal sessions and submit the repository link and live deployment URL through the official submission website.

Works cited

1. Physics-Grounded Parameter Selection for Gyrokinetic Simulations, https://arxiv.org/html/2604.06279v1 2. kaushikj/knowledge-graph-extraction - GitHub, https://github.com/kaushikj/knowledge-graph-extraction 3. What is Knowledge Graph Extraction? - LlamaIndex, https://www.llamaindex.ai/glossary/knowledge-graph-extraction 4. Graph RAG Implementation with Knowledge Graphs - Digetiers, https://www.digetiers.com/en/insights/library/graph-rag-implementation-knowledge-graphs 5. Why Telco AI Stalls in Production | Totogi, https://totogi.com/resources/whitepapers/the-execution-gap-why-telco-ai-stalls-between-pilot-and-production/ 6. Proceedings of the Knowledge Graphs and Large Language Models, https://aclanthology.org/volumes/2026.kallm-1/ 7. network_streamlit_app.py - GitHub Gist, https://gist.github.com/kennethleungty/f67a6c2364d8a4088238645f084c9a8c 8. 제조 Knowledge Graph를 Graspologic으로 분석 - 경남 ICT협회, https://www.gnict.org/blog/130/%EA%B8%80/%EC%A0%9C%EC%A1%B0-knowledge-graph%EB%A5%BC-graspologic%EC%9C%BC%EB%A1%9C-%EB%B6%84%EC%84%9D/ 9. RACPR: Generative AI-Enhanced Risk-Aware Causal Path Re, https://www.mdpi.com/2504-2289/10/8/248 10. (PDF) Improving Scientific Hypothesis Generation with Knowledge, https://www.researchgate.net/publication/385560566_Improving_Scientific_Hypothesis_Generation_with_Knowledge_Grounded_Large_Language_Models 11. SemNet Explorer: An Evidence-Grounded Knowledge Graph–LLM, https://pmc.ncbi.nlm.nih.gov/articles/13596072 12. How to Create a Knowledge Graph from Text?, https://web.stanford.edu/class/cs520/2020/notes/How_To_Create_A_Knowledge_Graph_From_

Text.html 13. The Semantic Web – ISWC 2026 | springerprofessional.de, https://www.springerprofessional.de/en/the-semantic-web-iswc-2026/53897124 14. Unable to render ipysigma graph - Using Streamlit, https://discuss.streamlit.io/t/unable-to-render-ipysigma-graph/87920 15. Building a Frontend for Network Device Management using React, https://mina-soft.eu/index.php?page=blog&article=building-frontend-for-network-device-management-using-react-d3-js-and-streamlit 16. How I Built an App for Creating Interactive LinkedIn Network Graphs, https://jeanna-schoonmaker.medium.com/how-i-built-an-app-for-creating-interactive-linkedin-network-graphs-451140a498cf