

Solution week-2

1. Regularized Logistic Regression – Gradient Update Term

The cost function in L2-regularized logistic regression adds a penalty on the weights.

Which term in the gradient update reflects the effect of L2 regularization?

- A) Subtract $\text{learning_rate} * \text{weight}$
- B) Subtract $\text{learning_rate} * \text{weight} / m$
- C) Subtract $\text{learning_rate} * \text{weight} * (\text{lambda} / m)$
- D) Add $\text{learning_rate} * \text{weight} * (\text{lambda} / m)$

Answer: C

2. Non-linear Data Handling

Which algorithm can handle non-linearly separable data by implicitly mapping to a higher-dimensional space?

- A) Perceptron
- B) k-Means
- C) Kernel SVM
- D) Naive Bayes

Answer: C

3. Bias-Variance Trade-off (Select two)

Which of the following are true about the bias-variance trade-off?

- A) High bias models underfit
- B) High variance models generalize well
- C) Increasing model complexity lowers bias but increases variance
- D) Regularization increases variance and decreases bias

Answer: A, C

4. Simple Linear Regression Intercept

What does the intercept term in a simple linear regression represent?

- A) The slope of the line
- B) The predicted value of Y when $X = 0$
- C) The average of all Y values
- D) The average residual

Answer: B

5. Logistic Function

Which function does logistic regression use to map the linear combination of features to a probability?

- A) Identity

- B) Softmax
- C) Sigmoid
- D) Tanh

Answer: C

6. Error Metric Sensitivity

Which error metric is most sensitive to large individual errors because it squares the residuals?

- A) Mean Absolute Error (MAE)
- B) Mean Squared Error (MSE)
- C) Accuracy
- D) Area Under the ROC Curve (AUC)

Answer: B

7. Role of Learning Rate

In gradient descent, what role does the learning rate play?

- A) It sets the initial values of the parameters
- B) It determines the size of each update step
- C) It selects the loss function
- D) It decides when to stop training

Answer: B

8. Naive Bayes Independence Assumption

Which algorithm assumes that all features are conditionally independent given the class label?

- A) k-Nearest Neighbors
- B) Decision Tree
- C) Naive Bayes
- D) Support Vector Machine

Answer: C

9. L1 (Lasso) Regularization (Select two)

Which of the following are characteristics of L1 regularization?

- A) Promotes sparse solutions (many coefficients become exactly zero)
- B) Penalizes the square of coefficients
- C) Shrinks coefficients continuously toward zero
- D) Uses the absolute value of coefficients in the penalty

Answer: A, D

10. Imbalanced-Data Metrics (Select three)

When evaluating a classifier on highly imbalanced data, which metrics should you consider?

- A) Accuracy
- B) Precision

- C) Recall
- D) F1-score

Answer: B, C, D

11. Naive Bayes Distributions (Select three)

Which probability distributions are commonly used in Naive Bayes variants?

- A) Gaussian (for continuous features)
- B) Bernoulli (for binary features)
- C) Multinomial (for word counts)
- D) Exponential (for time-to-event data)

Answer: A, B, C

12. Overfitting Indicators (Select two)

Which statements about overfitting are true?

- A) It occurs when model complexity is too low
- B) It leads to low training error but high test error
- C) Regularization techniques can help reduce it
- D) It always improves model generalization

Answer: B, C

13. Gradient Descent Use Cases (Select two)

For which tasks can gradient descent be used?

- A) Convex optimization problems
- B) Discrete combinatorial search
- C) Parameter estimation in linear regression
- D) Exact global optimization of arbitrary functions

Answer: A, C

14. Threshold Classifier Maximum Accuracy

Table of Feature X and Label values for binary classification:

Sample	Feature X	Label
1	2.0	+1
2	-1.0	-1
3	0.5	+1
4	-0.5	-1
5	1.0	+1

A simple threshold classifier predicts +1 if $X > t$, else -1.

Which threshold t maximizes accuracy?

- A) 0.75
- B) 0.25

C) -0.25

D) 0.0

Answer: D

15. Gradient Descent Update for Linear Model (MSE)

Given points $(x, y) = (1, 2), (2, 3)$ and model $y = w x$ (no intercept), starting $w = 0$.

After one GD step with $\alpha = 0.1$ under MSE cost, what is the updated w ?

A) 0.2

B) 0.4

C) 0.6

D) 0.8

Answer: B

16. Logistic Regression Predicted Probability

For $w = 2$, $b = -1$, what is $P(y = 1 \mid x = 1)$? ($\sigma(z) = 1/(1+e^{-z})$)

A) 0.27

B) 0.50

C) 0.73

D) 0.88

Answer: C

17. Naive Bayes Posterior Probability

$P(\text{Spam})=0.4$, $P(\text{NotSpam})=0.6$; $P(\text{Free}|\text{Spam})=0.8$; $P(\text{Free}|\text{NotSpam})=0.1$.

If "Free"=true, what is $P(\text{Spam}|\text{Free})$?

A) 0.20

B) 0.50

C) 0.67

D) 0.84

Answer: D

18. Linear Regression with scikit-learn

What does this code print?

```
import numpy as np
from sklearn.linear_model import LinearRegression
X = np.array([[1],[2],[3],[4]])
y = np.array([2,4,6,8])
lr = LinearRegression()
lr.fit(X,y)
print(lr.coef_, lr.intercept_)
```

A) [2.] 0.0

B) [0.5] 10.0

C) [2.] 1.0

D) [4.] -2.0

Answer: A

19. Ordinary Least Squares Singularity

If one feature is constant across all samples, what happens to the normal equation?

A) Its coefficient becomes zero.

B) $X^T X$ is singular (non-invertible), no unique solution.

C) GD ignores that feature.

D) The model fits perfectly regardless of targets.

Answer: B

20. Confusion Matrix Accuracy

	Actual Positive	Actual Negative
Pred Positive	40	10
Pred Negative	5	45

What is the accuracy?

A) 0.85

B) 0.90

C) 0.88

D) 0.95

Answer: A

21. Mean Absolute Error (MAE)

Sample	Actual	Predicted
1	100	95
2	110	120
3	90	85

Compute MAE.

A) 6.00

B) 6.67

C) 7.00

D) 8.00

Answer: B