



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



EXPERIMENT-1

AIM: Write a program to implement CPU scheduling for first come first serve.

PROGRAM CODE:

```
#include <stdio.h>

int main()
{
    int pid[15];
    int bt[15];
    printf("____BHUMIKA____\n");
    int n;
    printf("Enter the number of processes: ");
    scanf("%d",&n);

    printf("Enter process id of all the processes: ");
    for(int i=0;i<n;i++)
    {
        scanf("%d",&pid[i]);
    }
    printf("Enter burst time of all the processes: ");
    for(int i=0;i<n;i++)
    {
        scanf("%d",&bt[i]);
    }
}
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
int i, wt[n];  
wt[0]=0;  
  
for(i=1; i<n; i++)  
{  
    wt[i]= bt[i-1]+ wt[i-1];  
}  
printf("ProcessID   Burst Time   Waiting Time   TurnAround Time\n");  
float twt=0.0;  
float tat= 0.0;  
for(i=0; i<n; i++)  
{  
    printf("%d\t\t\t\t", pid[i]);  
    printf("%d\t\t\t\t", bt[i]);  
    printf("%d\t\t\t\t\t", wt[i]);  
    printf("%d\t\t\t\t\t\t", bt[i]+wt[i]);  
    printf("\n");  
    twt += wt[i];  
    tat += (wt[i]+bt[i]);  
}  
float att,awt;  
awt = twt/n;
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
att = tat/n;  
printf("Avg. waiting time= %f\n",awt);  
printf("Avg. turnaround time= %f",att);  
}
```

OUTPUT:

```
_____
|      BHUMIKA      |
|_____            |
|Enter the number of processes: 5|
|Enter process id of all the processes: 1 2 3 4 5|
|Enter burst time of all the processes: 4 6 8 11 9|
|ProcessID      Burst Time      Waiting Time      TurnAround Time|
|1              4              0              4|
|2              6              4              10|
|3              8              10             18|
|4              11             18             29|
|5              9              29             38|
|Avg. waiting time= 12.200000|
|Avg. turnaround time= 19.799999|
```



EXPERIMENT-2

AIM: Write a program to implement CPU scheduling for shortest job first.

PROGRAM CODE:

```
#include<stdio.h>

int main()
{
    int bt[20],p[20],wt[20],tat[20],i,j,n,total=0,totalT=0,pos,temp;
    float avg_wt,avg_tat;
    printf("____BHUMIKA____\n");
    printf("Enter number of process:");
    scanf("%d",&n);

    printf("\nEnter Burst Time:\n");
    for(i=0;i<n;i++)
    {
        printf("p%d:",i+1);
        scanf("%d",&bt[i]);
        p[i]=i+1;
    }
    for(i=0;i<n;i++)
    {
        pos=i;
        for(j=i+1;j<n;j++)
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
{  
    if(bt[j]<bt[pos])  
        pos=j;  
}  
temp=bt[i];  
bt[i]=bt[pos];  
bt[pos]=temp;  
  
temp=p[i];  
p[i]=p[pos];  
p[pos]=temp;  
}  
wt[0]=0;  
for(i=1;i<n;i++)  
{  
    wt[i]=0;  
    for(j=0;j<i;j++)  
        wt[i]+=bt[j];  
    total+=wt[i];  
}  
avg_wt=(float)total/n;  
printf("\nProcess\tBurst Time \tWaiting Time\tTurnaround Time");  
for(i=0;i<n;i++)
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
{  
    tat[i]=bt[i]+wt[i];  
    totalT+=tat[i];  
    printf("\np%d\t\t\t %d\t\t\t\t %d\t\t\t\t\t %d",p[i],bt[i],wt[i],tat[i]);  
}  
avg_tat=(float)totalT/n;  
printf("\n\nAverage Waiting Time=%f",avg_wt);  
printf("\n\nAverage Turnaround Time=%f",avg_tat);  
}
```

OUTPUT:



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



BHUMIKA

Enter number of process:4

Enter Burst Time:

p1:6

p2:9

p3:9

p4:8

Process	Burst Time	Waiting Time	Turnaround Time
p1	6	0	6
p4	8	6	14
p3	9	14	23
p2	9	23	32

Average Waiting Time=10.750000

Average Turnaround Time=18.750000



EXPERIMENT-3

AIM: Write a program to perform priority scheduling.

PROGRAM CODE:

```
#include <stdio.h>

void swap(int *a,int *b)
{
    int temp=*a;
    *a=*b;
    *b=temp;
}

int main()
{
    int n;
    printf("____BHUMIKA____\n");
    printf("Enter Number of Processes: ");
    scanf("%d",&n);
    // b is array for burst time, p for priority and index for process id
    int b[n],p[n],index[n];
    for(int i=0;i<n;i++)
    {
        printf("Enter Burst Time and Priority Value for Process %d: ",i+1);
        scanf("%d %d",&b[i],&p[i]);
        index[i]=i+1;
    }
```




**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
}  
for(int i=0;i<n;i++)  
{  
    int a=p[i],m=i;  
  
    //Finding out highest priority element and placing it at its desired position  
    for(int j=i;j<n;j++)  
    {  
        if(p[j] > a)  
        {  
            a=p[j];  
            m=j;  
        }  
    }  
  
    //Swapping processes  
    swap(&p[i], &p[m]);  
    swap(&b[i], &b[m]);  
    swap(&index[i],&index[m]);  
}  
  
// T stores the starting time of process  
int t=0;
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
//Printing scheduled process
printf("Order of process Execution is\n");
for(int i=0;i<n;i++)
{
    printf("P%d is executed from %d to %d\n",index[i],t,t+b[i]);
    t+=b[i];
}
printf("\n");
printf("Process Id    Burst Time    Wait Time    TurnAround Time\n");
int wait_time=0;
for(int i=0;i<n;i++)
{
    printf("P%d        %d        %d        %d\n",index[i],b[i],wait_time,wait_time
+ b[i]);
    wait_time += b[i];
}
return 0;
}
```

OUTPUT:

BHUMIKA

Enter Number of Processes: 5

Enter Burst Time and Priority Value for Process 1: 4 3

Enter Burst Time and Priority Value for Process 2: 8 2

Enter Burst Time and Priority Value for Process 3: 11 1

Enter Burst Time and Priority Value for Process 4: 6 4

Enter Burst Time and Priority Value for Process 5: 13 5

Order of process Execution is

P5 is executed from 0 to 13

P4 is executed from 13 to 19

P1 is executed from 19 to 23

P2 is executed from 23 to 31

P3 is executed from 31 to 42

Process Id	Burst Time	Wait Time	TurnAround Time
P5	13	0	13
P4	6	13	19
P1	4	19	23
P2	8	23	31
P3	11	31	42



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



EXPERIMENT-4

AIM: Write a program to implement CPU scheduling for Round Robin.

PROGRAM CODE:

```
#include<stdio.h>

int main()
{
    int n;
    printf("____BHUMIKA____\n");
    printf("Enter Total Number of Processes:");
    scanf("%d", &n);

    int wait_time = 0, ta_time = 0, arr_time[n], burst_time[n],
    temp_burst_time[n];

    int x = n;
    for(int i = 0; i < n; i++)
    {
        printf("Enter Details of Process %d \n", i + 1);
        printf("Arrival Time: ");
        scanf("%d", &arr_time[i]);
        printf("Burst Time: ");
        scanf("%d", &burst_time[i]);
        temp_burst_time[i] = burst_time[i];
    }
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
int time_slot;

printf("Enter Time Slot:");

scanf("%d", &time_slot);


int total = 0, counter = 0,i;

printf("Process ID    Burst Time    Turnaround Time    Waiting Time\n");

for(total=0, i = 0; x!=0; )
{
    if(temp_burst_time[i] <= time_slot && temp_burst_time[i] > 0)
    {
        total = total + temp_burst_time[i];

        temp_burst_time[i] = 0;

        counter=1;
    }
    else if(temp_burst_time[i] > 0)
    {
        temp_burst_time[i] = temp_burst_time[i] - time_slot;

        total += time_slot;
    }
    if(temp_burst_time[i]==0 && counter==1)
    {
        x--;

        printf("\nProcess No %d \t\t %d\t\t\t\t %d\t\t\t\t %d", i+1, burst_time[i],
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
total_arr_time[i], total_arr_time[i]-burst_time[i]);
wait_time = wait_time+total_arr_time[i]-burst_time[i];
ta_time += total_arr_time[i];
counter =0;
}
if(i==n-1)
{
    i=0;
}
else if(arr_time[i+1]<=total)
{
    i++;
}
else
{
    i=0;
}
}

float average_wait_time = wait_time * 1.0 / n;
float average_turnaround_time = ta_time * 1.0 / n;
printf("\nAverage Waiting Time:%f", average_wait_time);
printf("\nAvg Turnaround Time:%f", average_turnaround_time);
return 0;
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



}

OUTPUT:

```
_____BHUMIKA_____
Enter Total Number of Processes:4
Enter Details of Process 1
Arrival Time: 1
Burst Time: 4
Enter Details of Process 2
Arrival Time: 2
Burst Time: 8
Enter Details of Process 3
Arrival Time: 3
Burst Time: 9
Enter Details of Process 4
Arrival Time: 4
Burst Time: 14
Enter Time Slot:8
Process ID      Burst Time      Turnaround Time      Waiting Time

Process No 1      4              3              -1
Process No 2      8              10             2
Process No 3      9              26             17
Process No 4      14             31             17
Average Waiting Time:8.750000
Avg Turnaround Time:17.500000
```



EXPERIMENT-5

AIM: Write a program for page replacement policy using

a. LRU

PROGRAM CODE:

```
#include<stdio.h>
```

```
#include<limits.h>
```

```
int checkHit(int incomingPage, int queue[], int occupied){
```

```
    for(int i = 0; i < occupied; i++){
```

```
        if(incomingPage == queue[i])
```

```
            return 1;
```

```
    }
```

```
    return 0;
```

```
}
```

```
void printFrame(int queue[], int occupied)
```

```
{
```

```
    for(int i = 0; i < occupied; i++)
```

```
        printf("%d\t\t\t",queue[i]);
```

```
}
```




**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
int main()
{

    int incomingStream[] = {1, 2, 3, 2, 1, 5, 2, 1, 6, 2, 5, 6, 3, 1, 3};

    int n = sizeof(incomingStream)/sizeof(incomingStream[0]);
    int frames = 3;
    int queue[n];
    int distance[n];
    int occupied = 0;
    int pagefault = 0;
    printf("_____BHUMIKA_____\\n");
    printf("Page\\t Frame1 \\t Frame2 \\t Frame3\\n");

    for(int i = 0;i < n; i++)
    {
        printf("%d: \\t\\t",incomingStream[i]);
        if(checkHit(incomingStream[i], queue, occupied)){
            printFrame(queue, occupied);
        }

        else if(occupied < frames){
            queue[occupied] = incomingStream[i];
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
pagefault++;  
occupied++;  
  
printFrame(queue, occupied);  
}  
else{  
  
    int max = INT_MIN;  
    int index;  
    for (int j = 0; j < frames; j++)  
    {  
        distance[j] = 0;  
  
        for(int k = i - 1; k >= 0; k--)  
        {  
            ++distance[j];  
  
            if(queue[j] == incomingStream[k])  
                break;  
        }  
  
        if(distance[j] > max){
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
        max = distance[j];  
        index = j;  
    }  
}  
queue[index] = incomingStream[i];  
printFrame(queue, occupied);  
pagefault++;  
}  
  
printf("\n");  
}  
  
printf("Page Fault: %d",pagefault);  
  
return 0;  
}
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



OUTPUT:

BHUMIKA			
Page	Frame1	Frame2	Frame3
1:	1		
2:	1	2	
3:	1	2	3
2:	1	2	3
1:	1	2	3
5:	1	2	5
2:	1	2	5
1:	1	2	5
6:	1	2	6
2:	1	2	6
5:	5	2	6
6:	5	2	6
3:	5	3	6
1:	1	3	6
3:	1	3	6
Page Fault: 8			



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



b. FIFO:

PROGRAM CODE:

```
#include<stdio.h>

int main()
{
    int incomingStream[] = {4, 1, 2, 4, 5};
    int pageFaults = 0;
    int frames = 3;
    int m, n, s, pages;

    pages = sizeof(incomingStream)/sizeof(incomingStream[0]);
    printf("_____BHUMIKA_____\n");
    printf("Incoming \t Frame 1 \t Frame 2 \t Frame 3");
    int temp[frames];
    for(m = 0; m < frames; m++)
    {
        temp[m] = -1;
    }

    for(m = 0; m < pages; m++)
    {
        s = 0;
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
for(n = 0; n < frames; n++)
{
    if(incomingStream[m] == temp[n])
    {
        s++;
        pageFaults--;
    }
}
pageFaults++;

if((pageFaults <= frames) && (s == 0))
{
    temp[m] = incomingStream[m];
}
else if(s == 0)
{
    temp[(pageFaults - 1) % frames] = incomingStream[m];
}

printf("\n");
printf("%d\t\t\t",incomingStream[m]);
for(n = 0; n < frames; n++)
{
```

```
if(temp[n] != -1)
    printf(" %d\t\t", temp[n]);
else
    printf(" - \t\t");
}
}
printf("\nTotal Page Faults:\t%d\n", pageFaults);
return 0;
}
```

OUTPUT:

BHUMIKA			
Incoming	Frame 1	Frame 2	Frame 3
4	4	-	-
1	4	1	-
2	4	1	2
4	4	1	2
5	5	1	2
Total Page Faults: 4			



c. Optimal:

PROGRAM CODE:

```
#include <stdio.h>

int search(int key, int frame_items[], int frame_occupied)
{
    for (int i = 0; i < frame_occupied; i++)
        if (frame_items[i] == key)
            return 1;
    return 0;
}

void printOuterStructure(int max_frames){
    printf("_____BHUMIKA_____\\n");
    printf("Stream ");

    for(int i = 0; i < max_frames; i++)
        printf("Frame%d ", i+1);
}

void printCurrFrames(int item, int frame_items[], int frame_occupied, int
max_frames){
    printf("\\n%d \\t\\t", item);
    for(int i = 0; i < max_frames; i++){
        if(i < frame_occupied)
```




**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
printf("%d \t\t", frame_items[i]);  
  
else  
  
printf("- \t\t");  
  
}  
  
}  
  
int predict(int ref_str[], int frame_items[], int refStrLen, int index, int  
frame_occupied)  
{  
    int result = -1, farthest = index;  
    for (int i = 0; i < frame_occupied; i++) {  
        int j;  
        for (j = index; j < refStrLen; j++)  
        {  
            if (frame_items[i] == ref_str[j])  
            {  
                if (j > farthest) {  
                    farthest = j;  
                    result = i;  
                }  
                break;  
            }  
        }  
    }  
}
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
        if (j == refStrLen)
            return i;
    }

    return (result == -1) ? 0 : result;
}

void optimalPage(int ref_str[], int refStrLen, int frame_items[], int max_frames)
{

    int frame_occupied = 0;
    printOuterStructure(max_frames);

    int hits = 0;
    for (int i = 0; i < refStrLen; i++) {

        if (search(ref_str[i], frame_items, frame_occupied)) {
            hits++;
            printCurrFrames(ref_str[i], frame_items, frame_occupied, max_frames);
            continue;
        }
    }
}
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
if (frame_occupied < max_frames){
    frame_items[frame_occupied] = ref_str[i];
    frame_occupied++;
    printCurrFrames(ref_str[i], frame_items, frame_occupied, max_frames);
}

else {
    int pos = predict(ref_str, frame_items, refStrLen, i + 1, frame_occupied);
    frame_items[pos] = ref_str[i];
    printCurrFrames(ref_str[i], frame_items, frame_occupied, max_frames);
}

}

printf("\n\nHits: %d\n", hits);
printf("Misses: %d", refStrLen - hits);
}

int main()
{
    int ref_str[] = {7, 0, 1, 2, 0, 3, 0, 4, 2, 3, 0, 3, 2, 1, 2, 0, 1, 7, 0, 1};
    int refStrLen = sizeof(ref_str) / sizeof(ref_str[0]);
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
int max_frames = 3;
int frame_items[max_frames];

optimalPage(ref_str, refStrLen, frame_items, max_frames);
return 0;
}
```

OUTPUT:

BHUMIKA			
Stream	Frame1	Frame2	Frame3
7	7	-	-
0	7	0	-
1	7	0	1
2	2	0	1
0	2	0	1
3	2	0	3
0	2	0	3
4	2	4	3
2	2	4	3
3	2	4	3
0	2	0	3
3	2	0	3
2	2	0	3
1	2	0	1
2	2	0	1
0	2	0	1
1	2	0	1
7	7	0	1
0	7	0	1
1	7	0	1
Hits: 11			
Misses: 9			



EXPERIMENT-6

AIM: Write a program to implement first fit, best fit and worst fit algorithm for memory management.

➤ **First Fit:**

PROGRAM CODE:

```
#include<stdio.h>

void firstFit(int blockSize[], int m, int processSize[], int n)
{
    int i, j;
    int allocation[n];
    for(i = 0; i < n; i++)
    {
        allocation[i] = -1;
    }
    for (i = 0; i < n; i++)
    {
        for (j = 0; j < m; j++)
        {
            if (blockSize[j] >= processSize[i])
            {
                allocation[i] = j;
                blockSize[j] -= processSize[i];
            }
        }
    }
}
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
        break;
    }
}

printf("____BHUMIKA____\n");
printf("\nProcess No.\tProcess Size\tBlock no.\n");
for (int i = 0; i < n; i++)
{
    printf(" %i\t\t\t", i+1);
    printf("%i\t\t\t", processSize[i]);
    if (allocation[i] != -1)
        printf("%i", allocation[i] + 1);
    else
        printf("Not Allocated");
    printf("\n");
}
}

int main()
{
    int m;

    int n;

    int blockSize[] = {100, 500, 200, 300, 600};
    int processSize[] = {212, 417, 112, 426};
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
m = sizeof(blockSize) / sizeof(blockSize[0]);  
n = sizeof(processSize) / sizeof(processSize[0]);  
firstFit(blockSize, m, processSize, n);  
return 0 ;  
}
```

OUTPUT:

_____BHUMIKA_____		
Process No.	Process Size	Block no.
1	212	2
2	417	5
3	112	2
4	426	Not Allocated



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



➤ **Best Fit:**

PROGRAM CODE:

```
#include <stdio.h>

void implimentBestFit(int blockSize[], int blocks, int processSize[], int
processes)
{
    int allocation[processes];
    int occupied[blocks];
    for(int i = 0; i < processes; i++){
        allocation[i] = -1;
    }

    for(int i = 0; i < blocks; i++){
        occupied[i] = 0;
    }
    for (int i = 0; i < processes; i++)
    {
        int indexPlaced = -1;
        for (int j = 0; j < blocks; j++) {
            if (blockSize[j] >= processSize[i] && !occupied[j])
            {
                if (indexPlaced == -1)
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**

```
        indexPlaced = j;
    else if (blockSize[j] < blockSize[indexPlaced])
        indexPlaced = j;
    }
}
if (indexPlaced != -1)
{
    allocation[i] = indexPlaced;
    occupied[indexPlaced] = 1;
}
}
printf("_____BHUMIKA_____\n");
printf("\nProcess No.\tProcess Size\tBlock no.\n");
for (int i = 0; i < processes; i++)
{
    printf("%d \t\t\t %d \t\t\t", i+1, processSize[i]);
    if (allocation[i] != -1)
        printf("%d\n", allocation[i] + 1);
    else
        printf("Not Allocated\n");
}
}
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
int main()
{
    int blockSize[] = {100, 50, 30, 120, 35};
    int processSize[] = {40, 10, 30, 60};
    int blocks = sizeof(blockSize)/sizeof(blockSize[0]);
    int proccesses = sizeof(processSize)/sizeof(processSize[0]);

    implimentBestFit(blockSize, blocks, processSize, proccesses);

    return 0 ;
}
```

OUTPUT:

A screenshot of a terminal window with a dark background. At the top, the name "BHUMIKA" is underlined. Below it, there is a table with three columns: "Process No.", "Process Size", and "Block no.". The table contains four rows of data.

Process No.	Process Size	Block no.
1	40	2
2	10	3
3	30	5
4	60	1



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



➤ **Worst Fit:**

PROGRAM CODE:

```
#include <stdio.h>

void implimentWorstFit(int blockSize[], int blocks, int processSize[], int
processes)
{
    int allocation[processes];
    for(int i = 0; i < processes; i++){
        allocation[i] = -1;
    }
    for (int i=0; i<processes; i++)
    {

        int indexPlaced = -1;
        for (int j=0; j<blocks; j++)
        {
            if (blockSize[j] >= processSize[i])
            {
                if (indexPlaced == -1)
                    indexPlaced = j;
                else if (blockSize[indexPlaced] < blockSize[j])
                    indexPlaced = j;
            }
        }
    }
}
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
}  
if (indexPlaced != -1)  
{  
    allocation[i] = indexPlaced;  
    blockSize[indexPlaced] -= processSize[i];  
}  
}  
printf("_____BHUMIKA_____\n");  
printf("\nProcess No.\tProcess Size\tBlock no.\n");  
for (int i = 0; i < processes; i++)  
{  
    printf("%d \t\t\t %d \t\t\t", i+1, processSize[i]);  
    if (allocation[i] != -1)  
        printf("%d\n", allocation[i] + 1);  
    else  
        printf("Not Allocated\n");  
}  
}  
  
int main()  
{  
    int blockSize[] = {5, 4, 3, 6, 7};  
    int processSize[] = {1, 3, 5, 3};  
    int blocks = sizeof(blockSize)/sizeof(blockSize[0]);
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
int processes = sizeof(processSize)/sizeof(processSize[0]);

implimentWorstFit(blockSize, blocks, processSize, processes);

return 0 ;
}
```

OUTPUT:

_____BHUMIKA_____		
Process No.	Process Size	Block no.
1	1	5
2	3	4
3	5	5
4	3	1



EXPERIMENT-7

AIM: Write a program to implement reader/writer problem using semaphore.

PROGRAM CODE:

```
#include <stdio.h>

#include <pthread.h>

#include <semaphore.h>

#include <unistd.h>


#define NUM_READERS 3

#define NUM_WRITERS 2


sem_t mutex, writeBlock;

int readersCount = 0;

int sharedData = 0;


void *reader(void *arg) {
    int readerId = *(int *)arg;
    while (1) {
        sem_wait(&mutex);
        readersCount++;
        if (readersCount == 1) {
            sem_wait(&writeBlock);
        }
    }
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
sem_post(&mutex);

// Read the shared data
printf("Reader %d (Bhumika) read: %d\n", readerId, sharedData);

sem_wait(&mutex);
readersCount--;
if (readersCount == 0) {
    sem_post(&writeBlock);
}
sem_post(&mutex);

// Sleep to simulate processing
usleep(100000);
}
return NULL;
}

void *writer(void *arg) {
    int writerId = *(int *)arg;
    while (1) {
        sem_wait(&writeBlock);
```




**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
// Write to the shared data
sharedData++;
printf("Writer %d (Bhumika) wrote: %d\n", writerId, sharedData);

sem_post(&writeBlock);

// Sleep to simulate processing
usleep(200000);
}
return NULL;
}

int main() {
    pthread_t readers[NUM_READERS];
    pthread_t writers[NUM_WRITERS];

    sem_init(&mutex, 0, 1);
    sem_init(&writeBlock, 0, 1);

    int readerIds[NUM_READERS];
    int writerIds[NUM_WRITERS];

    for (int i = 0; i < NUM_READERS; i++) {
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
    readerIds[i] = i + 1;
    pthread_create(&readers[i], NULL, reader, &readerIds[i]);
}

for (int i = 0; i < NUM_WRITERS; i++) {
    writerIds[i] = i + 1;
    pthread_create(&writers[i], NULL, writer, &writerIds[i]);
}

for (int i = 0; i < NUM_READERS; i++) {
    pthread_join(readers[i], NULL);
}

for (int i = 0; i < NUM_WRITERS; i++) {
    pthread_join(writers[i], NULL);
}

sem_destroy(&mutex);
sem_destroy(&writeBlock);

return 0;
}
```

OUTPUT:

```
____BHUMIKA____  
Reader 1 (Bhumika) read: 0  
Reader 2 (Bhumika) read: 0  
Writer 1 (Bhumika) wrote: 1  
Reader 3 (Bhumika) read: 1  
... 
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



EXPERIMENT-8

AIM: Write a program to implement Producer-Consumer problem using semaphores.

PROGRAM CODE:

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
int mutex = 1;
```

```
int full = 0;
```

```
int empty = 10, x = 0;
```

```
void producer()
```

```
{
```

```
    --mutex;
```

```
    ++full;
```

```
    --empty;
```

```
    x++;
```

```
    printf("\nProducer produces"
```

```
        "item %d",
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
x);

++mutex;

}

void consumer()
{
    --mutex;
    --full;
    ++empty;
    printf("\nConsumer consumes "
           "item %d",
           x);
    x--;

    ++mutex;
}

int main()
{
    int n, i;
    printf("____BHUMIKA____\n");
    printf("\n1. Press 1 for Producer"
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
"\n2. Press 2 for Consumer"
```

```
"\n3. Press 3 for Exit");
```

```
#pragma omp critical
```

```
for (i = 1; i > 0; i++) {
```

```
    printf("\nEnter your choice:");
```

```
    scanf("%d", &n);
```

```
    // Switch Cases
```

```
    switch (n) {
```

```
        case 1:
```

```
            if ((mutex == 1)
```

```
                && (empty != 0)) {
```

```
                producer();
```

```
            }
```

```
        else {
```

```
            printf("Buffer is full!");
```

```
        }
```

```
        break;
```

```
    case 2:
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
if ((mutex == 1)
    && (full != 0)) {
    consumer();
}

else {
    printf("Buffer is empty!");
}

break;

case 3:
    exit(0);
    break;
}

}

}
```

OUTPUT:

BHUMIKA

1. Press 1 for Producer
2. Press 2 for Consumer
3. Press 3 for Exit

Enter your choice:1
Producer produces item 1

Enter your choice:1
Producer produces item 2

Enter your choice:2
Consumer consumes item 2

Enter your choice:2
Consumer consumes item 1

Enter your choice:2
Buffer is empty!

Enter your choice:3



EXPERIMENT-9

AIM: Write a program to implement Banker's algorithm for deadlock avoidance.

PROGRAM CODE:

```
#include<stdio.h>
```

```
int main() {
```

```
    int p, c, count = 0, i, j, alc[5][3], max[5][3], need[5][3], safe[5], available[3],  
    done[5], terminate = 0;
```

```
    printf("____BHUMIKA____\n");
```

```
    printf("Enter the number of process and resources");
```

```
    scanf("%d %d", & p, & c);
```

```
    printf("enter allocation of resource of all process %dx%d matrix", p, c);
```

```
    for (i = 0; i < p; i++) {
```

```
        for (j = 0; j < c; j++) {
```

```
            scanf("%d", & alc[i][j]);
```

```
        }
```

```
    }
```

```
    printf("enter the max resource process required %dx%d matrix", p, c);
```

```
    for (i = 0; i < p; i++) {
```

```
        for (j = 0; j < c; j++) {
```

```
            scanf("%d", & max[i][j]);
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
}  
  
}  
  
printf("enter the available resource");  
  
for (i = 0; i < c; i++)  
    scanf("%d", & available[i]);  
  
printf("\n need resources matrix are\n");  
for (i = 0; i < p; i++) {  
    for (j = 0; j < c; j++) {  
        need[i][j] = max[i][j] - alc[i][j];  
        printf("%d\t", need[i][j]);  
    }  
    printf("\n");  
}  
  
for (i = 0; i < p; i++) {  
    done[i] = 0;  
}  
  
while (count < p) {  
    for (i = 0; i < p; i++) {  
        if (done[i] == 0) {  
            for (j = 0; j < c; j++) {  
                if (need[i][j] > available[j])  
                    break;  
            }  
        }  
    }  
}
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
if (j == c) {  
    safe[count] = i;  
    done[i] = 1;  
  
    for (j = 0; j < c; j++) {  
        available[j] += alc[i][j];  
    }  
    count++;  
    terminate = 0;  
} else {  
    terminate++;  
}  
}  
}  
  
if (terminate == (p - 1)) {  
    printf("safe sequence does not exist");  
    break;  
}  
  
}  
  
if (terminate != (p - 1)) {  
    printf("\n available resource after completion\n");  
    for (i = 0; i < c; i++) {
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
printf("%d\t", available[i]);  
}  
printf("\n safe sequence are\n");  
for (i = 0; i < p; i++) {  
    printf("p%d\t", safe[i]);  
}  
}  
  
return 0;  
}
```

OUTPUT:

BHUMIKA

Enter the number of process and resources

5 3

enter allocation of resource of all process 5x3 matrix

0 1 0

2 0 0

3 0 2

0 0 2

2 1 1

enter the max resource process required 5x3 matrix

7 5 3

3 2 2

9 0 2

4 2 2

5 3 3

enter the available resource

3 3 2

need resources matrix are

7 4 3

1 2 2

6 0 0

4 2 0

3 2 2

available resource after completion

10 5 7

safe sequence are

p1 p3 p4 p0 p2



EXPERIMENT-10

AIM: Write C programs to implement the various File Organisation Techniques.

PROGRAM CODE:

➤ **SINGLE LEVEL DIRECTORY:**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <sys/stat.h>
```

```
#include <unistd.h>
```

```
#include <dirent.h>
```

```
#include <string.h>
```

```
void createDirectory(const char *directoryName) {
```

```
    int status = mkdir(directoryName, 0777);
```

```
    if (status == 0) {
```

```
        printf("Directory '%s' created successfully.\n", directoryName);
```

```
    } else {
```

```
        printf("Failed to create directory '%s'.\n", directoryName);
```

```
    }
```

```
}
```

```
void listDirectories() {
```

```
    DIR *dir;
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
struct dirent *entry;

if ((dir = opendir(".")) != NULL) {
    printf("Directories in the current location:\n");
    while ((entry = readdir(dir)) != NULL) {
        if (entry->d_type == DT_DIR) {
            printf("%s\n", entry->d_name);
        }
    }
    closedir(dir);
} else {
    printf("Error opening directory.\n");
}

void deleteDirectory(const char *directoryName) {
    if (rmdir(directoryName) == 0) {
        printf("Directory '%s' deleted successfully.\n", directoryName);
    } else {
        printf("Failed to delete directory '%s'.\n", directoryName);
    }
}
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
int main() {  
    int choice;  
    char dirName[100];  
  
    while (1) {  
        printf("\n1. Create Directory\n");  
        printf("2. List Directories\n");  
        printf("3. Delete Directory\n");  
        printf("4. Exit\n");  
        printf("Enter your choice: ");  
        scanf("%d", &choice);  
  
        switch (choice) {  
            case 1:  
                printf("Enter directory name: ");  
                scanf("%s", dirName);  
                createDirectory(dirName);  
                break;  
            case 2:  
                listDirectories();  
                break;  
            case 3:  
                printf("Enter directory name to delete: ");
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
scanf("%s", dirName);  
deleteDirectory(dirName);  
  
break;  
case 4:  
    exit(0);  
default:  
    printf("Invalid choice. Please enter a valid option.\n");  
}  
  
}  
  
return 0;  
}
```

OUTPUT:

```
1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 1
Enter directory name: Bhumika
Directory 'Bhumika' created successfully.
```

```
1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 2
Directories in the current location:
.
..
Bhumika
```

```
1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 3
Enter directory name to delete: Bhumika
Directory 'Bhumika' deleted successfully.
```

```
1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 4
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



➤ **Two Level Directory:**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <sys/stat.h>
```

```
#include <unistd.h>
```

```
#include <dirent.h>
```

```
#include <string.h>
```

```
void createDirectory(const char *directoryName) {  
    int status = mkdir(directoryName, 0777);  
  
    if (status == 0) {  
        printf("Directory '%s' created successfully.\n", directoryName);  
    } else {  
        printf("Failed to create directory '%s'.\n", directoryName);  
    }  
}
```

```
void listDirectories(const char *path) {  
    DIR *dir;  
    struct dirent *entry;  
  
    if ((dir = opendir(path)) != NULL) {
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
printf("Directories in '%s':\n", path);
while ((entry = readdir(dir)) != NULL) {
    if (entry->d_type == DT_DIR && strcmp(entry->d_name, ".") != 0 &&
        strcmp(entry->d_name, "..") != 0) {
        printf("%s\n", entry->d_name);
    }
}
closedir(dir);
} else {
    printf("Error opening directory '%s'.\n", path);
}
}
```

```
void deleteDirectory(const char *directoryName) {
    if (rmdir(directoryName) == 0) {
        printf("Directory '%s' deleted successfully.\n", directoryName);
    } else {
        printf("Failed to delete directory '%s'.\n", directoryName);
    }
}
```

```
Int main() {
    int choice;
    char dirName[100];
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
char subDirName[100];

char path[200];

while (1) {
    printf("\n1. Create Directory\n");
    printf("2. List Directories\n");
    printf("3. Delete Directory\n");
    printf("4. Exit\n");
    printf("Enter your choice: ");
    scanf("%d", &choice);

    switch (choice) {
        case 1:
            printf("Enter parent directory name: ");
            scanf("%s", dirName);
            createDirectory(dirName);

            printf("Enter subdirectory name: ");
            scanf("%s", subDirName);

            snprintf(path, sizeof(path), "%s/%s", dirName, subDirName);
            createDirectory(path);
            break;
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



case 2:

```
printf("Enter directory path to list: ");  
scanf("%s", path);  
listDirectories(path);  
break;
```

case 3:

```
printf("Enter directory name to delete: ");  
scanf("%s", dirName);  
deleteDirectory(dirName);  
break;
```

case 4:

```
exit(0);
```

default:

```
printf("Invalid choice. Please enter a valid option.\n");
```

```
}
```

```
}
```

```
return 0;
```

```
}
```

OUTPUT:

```
1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 1
Enter parent directory name: Piplani
Directory 'Piplani' created successfully.
Enter subdirectory name: Bhumika
Directory 'Piplani/Bhumika' created successfully.

1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 2
Enter directory path to list: Piplani
Directories in 'Piplani':
Bhumika

1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 3
Enter directory name to delete: Piplani/Bhumika
Directory 'Piplani/Bhumika' deleted successfully.

1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 4
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



➤ **Hierarchical Level Directory:**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <sys/stat.h>
```

```
#include <unistd.h>
```

```
#include <dirent.h>
```

```
#include <string.h>
```

```
void createDirectory(const char *directoryName) {  
    int status = mkdir(directoryName, 0777);  
  
    if (status == 0) {  
        printf("Directory '%s' created successfully.\n", directoryName);  
    } else {  
        printf("Failed to create directory '%s'.\n", directoryName);  
    }  
}
```

```
void listDirectories(const char *path) {  
    DIR *dir;  
    struct dirent *entry;  
  
    if ((dir = opendir(path)) != NULL) {
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**


```
printf("Directories in '%s':\n", path);  
while ((entry = readdir(dir)) != NULL) {  
    if (entry->d_type == DT_DIR && strcmp(entry->d_name, ".") != 0 &&  
        strcmp(entry->d_name, "..") != 0) {  
        printf("%s\n", entry->d_name);  
        char subpath[256];  
        snprintf(subpath, sizeof(subpath), "%s/%s", path, entry->d_name);  
        listDirectories(subpath);  
    }  
}  
closedir(dir);  
} else {  
    printf("Error opening directory '%s'.\n", path);  
}  
}  
  
void deleteDirectory(const char *directoryName) {  
    if (rmdir(directoryName) == 0) {  
        printf("Directory '%s' deleted successfully.\n", directoryName);  
    } else {  
        printf("Failed to delete directory '%s'.\n", directoryName);  
    }  
}
```



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
int main() {  
    int choice;  
    char dirName[100];  
    char path[200];  
  
    while (1) {  
        printf("\n1. Create Directory\n");  
        printf("2. List Directories\n");  
        printf("3. Delete Directory\n");  
        printf("4. Exit\n");  
        printf("Enter your choice: ");  
        scanf("%d", &choice);  
  
        switch (choice) {  
            case 1:  
                printf("Enter directory path to create: ");  
                scanf("%s", path);  
                createDirectory(path);  
                break;  
            case 2:  
                printf("Enter directory path to list: ");  
                scanf("%s", path);
```

**Department of Computer Science and Engineering
Delhi Technical Campus, Greater Noida**



**DELHI TECHNICAL CAMPUS
GREATER NOIDA**
Affiliated to GGSIPU and approved by AICTE & COA



```
listDirectories(path);

break;

case 3:

    printf("Enter directory name to delete: ");

    scanf("%s", dirName);

    deleteDirectory(dirName);

    break;

case 4:

    exit(0);

default:

    printf("Invalid choice. Please enter a valid option.\n");

}

}

return 0;

}
```

OUTPUT:

```
1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 1
Enter directory path to create: Bhumika/Piplani
Directory 'Bhumika/Piplani' created successfully.

1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 1
Enter directory path to create: Bhumika/Piplani/Btech
Directory 'Bhumika/Piplani/Btech' created successfully.

1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 2
Enter directory path to list: Bhumika
Directories in 'Bhumika':
Piplani
Directories in 'Bhumika/Piplani':
Btech
Directories in 'Bhumika/Piplani/Btech':

1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 3
Enter directory name to delete: Bhumika/Piplani/Btech
Directory 'Bhumika/Piplani/Btech' deleted successfully.

1. Create Directory
2. List Directories
3. Delete Directory
4. Exit
Enter your choice: 4
```