11 kW AC Wall Box Charger:



Product Overview:

11kW wall box AC Charger is composed of main control unit, charging interface, metering and charging unit. It's resistant to vibration and it covers a small area which can be installed in indoor and outdoor environments and provides AC power for electric vehicles with on board charger

Product Features:

- Protection against lightning protection, leakage, short circuit, over current.
- Wall or Pole mounted installation.
- Smart interface and easy usability.
- Monitor and control through Bijlify mobile app & 3rd party systems.
- Supports IEC 61851 standard charging sequence.

Applications:

- EV Charging stations in residential, commercial buildings.
- EV Charging stations for large, medium and small.
- EV fleet (private and public).
- EV dealers and service providers.

Specifications:

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East) Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

POWER INPUT	
Power Connection	3P + N + PE
Input Voltage	415VAC ± 10%
Frequency	50Hz ± 10%
POWER OUTPUT	
Rated Power	11kW
Rated Output Current	16A
No. of Output	1
Plug	AC Type-2
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	Over Current, Over Voltage, Under Voltage, Surge Protection, Short Circuit Protection, Ground Fault
USER INTERFACE	
Display	20x4 Character LCD display with blue backlight
Status Indicator	Multi colored LED indicator
User Authorization	QR Code
COMMUNICATION	
Network Connectivity	GSM/ GPRo 3G/4G Connectivity
Communication Protocol	OCPP v1.6j
ENVIRONMENT	
Operating Temperature	-20°C to 60°C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% without condensation
Altitude	≤2000m
Place of installation	Indoor and Outdoor
MECHANICAL DESIGN	
Shell Material	Hot-dip galvanized steel sheet IP-
Ingress Protection	IP 55
Cooling	Natural Cooling
Length of charging gun	5m
Dimensions (WxDxH)	310 mm X 140mm X 450mm
Installation	Wall or Pole Mounted
REGULATION	
Charging Mode Standard	IEC61851-1 Charging mode – 3

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East) Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

22 kW AC Wall Box Charger:



Product Overview:

22kW wall box AC Charger is composed of main control unit, charging interface, metering and charging unit. It's resistant to vibration and it covers a small area which can be installed in indoor and outdoor environments and provides AC power for electric vehicles with on board charger.

Product Features:

- Protection against lightning protection, leakage, short circuit,
- over current.
- Wall or Pole mounted installation.
- Smart interface and easy usability.
- Monitor and control through Bijlify mobile app & 3rd party systems.
- Supports IEC 61851 standard charging sequence.

Applications:

- EV Charging stations in buildings,
- Charge point operators, commercial buildings.
- EV Charging stations for large, medium and small operators.
- EV dealers and service providers

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East) Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

Specifications:

POWER INPUT	
Power Connection	3P + N + PE
Input Voltage	415VAC ± 10%
Frequency	50Hz ± 10%
POWER OUTPUT	
Rated Power	22kW
Rated Output Current	32A
No. of Output	1
Plug	AC Type-2
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	Over Current, Over Voltage, Under Voltage, Surge Protection, Short Circuit Protection, Ground Fault
USER INTERFACE	
Display	20x4 Character LCD display with blue backlight
Status Indicator	Multi colored LED indicator
User Authorization	App
COMMUNICATION	
Network Connectivity	GSM/ GPRo 3G/4G Connectivity
Communication Protocol	OCPP 1.6
ENVIRONMENT	
Operating Temperature	-20°C to 60°C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% without condensation
Altitude	≤2000m
Place of installation	Indoor and Outdoor
MECHANICAL DESIGN	
Shell Material	Hot-dip galvanized steel sheet
Ingress Protection	IP 55
Cooling	Natural Cooling
Length of charging gun	5m
Dimensions (WxDxH)	310 mm X 140mm X 450mm
Installation	Wall or Pole Mounted
REGULATION	
Charging Mode Standard	IEC 61851-1 Charging

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East) Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

30kW DC Charger



Product Overview:

DC Fast Charger has complete protection system which includes surge protection, residual current devices, short circuit, over/under voltage etc. It is suitable for indoor as well as outdoor installation where fast charging is convenient for users. The 30kW DC Charger also features network communication capability. It is able to connect with remote network systems and provide real-time information, such as the locations of charging stations, charging parameters and billing information. These Chargers can be used for EV infrastructure, operators, EV fleet (private and public), EV dealers and service providers, commercial parking spaces, highways, residential buildings.

Product Features:

- Charging protection such as input over/under voltage, connection abnormality, emergency stop.
- Protection against lightning, leakage, short circuit, over current, over temperature.
- Wall or Pole mounted installation, easy to install.
- Touch screen operation interface.
- Supports IEC 61851 standard charging.
- Display – 9” TFT touch screen interface.

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East) Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

- Flexible smart connectivity: Ethernet, SIM based, QR Code, OCPP 1.6.
- CCS2 and AC Type 2 Plug Combination available on request.

Specifications:

POWER INPUT	
Power Connection	3P + N + PE
Input Voltage	415VAC ± 10%
Frequency	50Hz ± 10%
Efficiency	≥94%
Power Factor	≥0.99
Total Harmonic Factor	THD <5%
POWER OUTPUT	
Output Voltage	150V-1000V
Rated Power	30kW
Rated Output Current	80A
No. of Output	1
Plug	CCS-2
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	Over Current, Over Voltage, Under Voltage, Surge Protection, Short Circuit Protection, Ground Fault, Over Temperature
USER INTERFACE	
Display	9” TFT Color Touch Screen
Status Indicator	LED Lamps for ON, Charging and Fault
User Authorization	App
COMMUNICATION	
Network Connectivity	SIM based
Communication Protocol	OCPP 1.6
ENVIRONMENT	
Operating Temperature	-20°C to 60 °C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% without condensation
Altitude	≤2000m
Place of installation	Indoor and Outdoor

MECHANICAL DESIGN	
Shell Material	Hot-dip galvanized steel sheet
Ingress Protection	IP 55
Cooling	Forced Cooling
Noise	≤55dB
Length of charging gun	5m
Dimensions (WxDxH)	600mm X 300mm X 650mm
Installation	Wall or Pole Mounted
REGULATION	
Charging Mode Standard	IEC61851-1 Charging mode – 4

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East) Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

60kW DC Charger



Product Overview:

30kW DC + 30kW DC Charger has complete protection system which includes surge protection, residual current devices, short circuit, over/under voltage etc. It is suitable for indoor as well as outdoor installation where fast charging is convenient for users. It also features network communication capability. It is able to connect with remote network systems and provide real-time information, such as the locations of charging stations, charging parameters and billing information. These Chargers can be used for EV infrastructure, operators, EV fleet (private and public), EV dealers and service providers, commercial parking spaces, highways, residential buildings.

Product Features:

- Charging protection such as input over/under voltage, connection abnormality, emergency stop.
- Protection against lightning, leakage, short circuit, over current, over temperature.
- Wall or Pole mounted installation, easy to install.

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East) Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

- Touch screen operation interface.
- Supports IEC 61851 standard charging.
- Display – 9” TFT touch screen interface.
- Flexible smart connectivity: Ethernet, SIM based, QR Code, OCPP 1.6.
- CCS2 Dual GUN Combination.

Specifications:

POWER INPUT	
Power Connection	3P + N + PE
Input Voltage	415VAC ± 10%
Frequency	50Hz ± 10%
Efficiency	≥94%
Power Factor	≥0.99
Total Harmonic Factor	THD <5%
POWER OUTPUT	
Output Voltage	DC - 150V-1000V
Rated Power	60kW (DC- 30kW; DC-30kW)
Rated Output Current	DC - 150A
No. of Output	2
Plug	CCS-2
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	Over Current, Over Voltage, Under Voltage, Surge Protection, Short Circuit Protection, Ground Fault, Over Temperature
USER INTERFACE	
Display	9” TFT Color Touch Screen
Status Indicator	LED Lamps for ON, Charging and Fault
User Authorization	App
COMMUNICATION	
Network Connectivity	SIM based
Communication Protocol	OCPP 1.6

ENVIRONMENT	
Operating Temperature	-20°C to 60 °C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% without condensation
Altitude	≤2000m
Place of installation	Indoor and Outdoor
MECHANICAL DESIGN	
Shell Material	Hot-dip galvanized steel sheet
Ingress Protection	IP 55
Cooling	Forced Cooling
Noise	≤55dB
Length of charging gun	5m
Dimensions (WxDxH)	
Installation	Floor Mounted
REGULATION	
Charging Mode Standard	IEC61851-1 Charging mode – 4

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East) Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

Annexure – II

EXCLUSIONS

- All Civil engineering, drawings and construction, fabrication of concrete, foundation for machinery.
- Site Management.
- Unloading of equipment.
- Any Statutory approvals.
- Electrical Engineering, drawings, installations other than mentioned in the scope of supply.
- Power supply, Distribution Panels, Cables & other infrastructure.
- Electrical protecting devices, wire duct, fastening piece and cable box.
- Safety equipment, platform that meet local plant safety rule.
- Additional items which are not mentioned in the proposal.

TERMS AND CONDITIONS

Schedule of Delivery:

Equipment as per the proposal shall be supplied within 4 to 6 weeks from the effective date of contract and receiving advance.
Supplier may dispatch the equipment well ahead of the above delivery time, based on the availability of raw materials.

App Integration

Charger shall be integrated on 'Bijlify' Platform. CMS is a part of offer solution.

Taxation

GST will be extra at actual, presently @5%

Payment Terms

50 % of the contract price as advance along with PO.
Balance 50% with 100% taxes shall be paid against Proforma Invoice prior to shipment.

Freight and Insurance will be extra.

Inspection

Inspection of equipment shall be done as per Standards unless otherwise agreed by supplier and in which case all costs and expenses for such inspection are to be borne by the buyer.

Warranty

We offer Lifetime Guarantee of the product, under Bijlify Zen Bundle package.

Validity

Proposal is valid for 30 days from date of offer.

Annexure – III

PRICE SCHEDULE

Sl. No.	Description	Qty.	Unit Rate	Amount (INR)
1	3.3kW AC 001 Univ. charger	1		
2	9.9kW AC (3x3.3) Charger	1		
3	7.4kW AC Type 2 Charger Single Gun	1		
4	11 kW AC Type 2 Charger	1		
5	22 kW AC Type 2 Charger	1		
6	30kW DC Fast Charger	1		
7	60kW DC Dual Gun Charger	1		

Zen Bundle:

Rs. 2 per unit consumed shall be charged on Pay per use basis, which includes: -

- ✓ Hardware Management –
  - **Charger Lifetime Guarantee Coverage** (Excluding external damages)
  - 24*7 Customer Care Support (Technical & End Customer issues)
  - Operational issues handling
  - Regular Charger performance checkup
- ✓ Software Management -
  - Server Maintenance
  - Cloud Space Charges
  - Payments refunds and settlement process charges through Payment gateway
- ✓ Bijlify Terminal: CPMS (Charge Point Monitoring Software) access